


SN10KHT5542, SN10KHT5543 OCTAL TTL-TO-ECL TRANSLATORS WITH OUTPUT ENABLE

SDZS001A – D3136, AUGUST 1988 – REVISED DECEMBER 1988

- 10KH Compatible
- ECL and TTL Control Inputs
- P-N-P Inputs Reduce DC Loading
- Flow-Through Architectures Optimizes PCB Layout
- Center Pin VCC, VEE and GND Configurations Minimize High-Speed Switching Noise
- ESD Protection Exceeds 2000 V Per MIL-STD-883C, Method 3015
- Package Options Include "Small Outline" Packages and Standard Plastic 300-mil DIPs

DW OR NT PACKAGE
(TOP VIEW)



description



These octal TTL-to-ECL translators are designed to provide efficient translation between a TTL signal environment and a 10KH ECL signal environment. The designer has a choice of inverting ('5542) or true ('5543) outputs. Two pins, $\overline{OE}1$ and $\overline{OE}2$, are provided for output enable control. These control inputs are negative ANDed together, with $\overline{OE}1$ being ECL compatible and $\overline{OE}2$ being TTL compatible. This offers the choice of controlling the outputs of the device from either a TTL or ECL signal environment. The outputs, when disabled, go to a normal ECL logic low level.

The SN10KHT5542 and SN10KHT5543 are characterized for operation from 0°C to 75°C.

FUNCTION TABLE

| OUTPUT CONTROL | | DATA INPUT | OUTPUT | |
|------------------|------------------|------------|--------|-------|
| $\overline{OE}1$ | $\overline{OE}2$ | A | '5542 | '5543 |
| H | X | X | L | L |
| X | H | X | L | L |
| L | L | L | H | L |
| L | L | H | L | H |

logic symbols†




†These symbols are in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

SN10KHT5542, SN10KHT5543
OCTAL TTL-TO-ECL TRANSLATORS WITH OUTPUT ENABLE

SDZS001A – D3136, AUGUST 1988 – REVISED DECEMBER 1988

logic diagrams (positive logic)



absolute maximum ratings over operating ambient temperature range (unless otherwise noted)[†]

| | |
|--|-----------------|
| Supply voltage range, V_{CC} | –0.5 V to 7 V |
| Supply voltage range, V_{EE} | –8 V to 0 V |
| Input voltage range (TTL) (See Note 1) | –1.2 V to 7 V |
| Input voltage range (ECL) | V_{EE} to 0 V |
| Input current range (TTL) | –30 mA to 5 mA |
| Operating ambient temperature range | 0°C to 75°C |
| Storage temperature range | –65°C to 150°C |

[†]Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: The input voltage ratings may be exceeded provided the input current ratings are observed.

recommended operating conditions (see Note 2)

| | | MIN | NOM | MAX | UNIT |
|----------|--|-------|-------|-------|------|
| V_{CC} | TTL supply voltage | 4.5 | 5.0 | 5.5 | V |
| V_{EE} | ECL supply voltage | –4.94 | –5.2 | –5.46 | V |
| V_{IH} | TTL high-level input voltage | 2 | | | V |
| V_{IH} | ECL high-level input voltage [‡] | 0°C | –1170 | –840 | mV |
| | | 25°C | –1130 | –810 | |
| | | 75°C | –1070 | –735 | |
| V_{IL} | TTL low-level input voltage | | | 0.8 | V |
| V_{IL} | ECL low-level input voltage [‡] | 0°C | –1950 | –1480 | mV |
| | | 25°C | –1950 | –1480 | |
| | | 75°C | –1950 | –1450 | |
| I_{IK} | TTL input clamp current | | | –18 | mA |
| T_A | Operating ambient temperature (see Note 3) | 0 | | 75 | °C |

[‡] The algebraic convention, in which the least positive (most negative) value is designated minimum, is used in this data sheet for logic voltage levels and temperature only.

NOTES: 2. If unused, OE1 should be tied directly to –2 V.

3. Each 10KH series circuit has been designed to meet the dc specifications shown in the electrical characteristics table after thermal equilibrium has been established. The circuit is in a test socket or mounted on a printed circuit board, and transverse air flow greater than 500 linear ft/min is maintained.

SN10KHT5542, SN10KHT5543

OCTAL TTL-TO-ECL TRANSLATORS WITH OUTPUT ENABLE

SDZS001A – D3136, AUGUST 1988 – REVISED DECEMBER 1988

electrical characteristics over recommended operating ambient temperature range (unless otherwise noted) (see Note 2)

| PARAMETER | | TEST CONDITIONS | | MIN | TYP† | MAX | UNIT |
|-------------------|-------------------------------|---|------|-------|------|-------|---------------|
| V_{IK} | A inputs and $\overline{OE}2$ | $V_{CC} = 4.5\text{ V}$, $V_{EE} = -4.94\text{ V}$, $I_I = -18\text{ mA}$ | | | | -1.2 | V |
| I_I | A inputs and $\overline{OE}2$ | $V_{CC} = 5.5\text{ V}$, $V_{EE} = -5.46\text{ V}$, $V_I = 7\text{ V}$ | | | | 0.1 | mA |
| I_{IH} | A inputs and $\overline{OE}2$ | $V_{CC} = 5.5\text{ V}$, $V_{EE} = -5.46\text{ V}$, $V_I = 2.7\text{ V}$ | | | | 20 | μA |
| | $\overline{OE}1$ only | $V_{CC} = 5.5\text{ V}$, $V_{EE} = -5.46\text{ V}$, $V_I = -840\text{ mV}$ | 0°C | | | 350 | |
| | | $V_{CC} = 5.5\text{ V}$, $V_{EE} = -5.46\text{ V}$, $V_I = -810\text{ mV}$ | 25°C | | | 350 | |
| | | $V_{CC} = 5.5\text{ V}$, $V_{EE} = -5.46\text{ V}$, $V_I = -735\text{ mV}$ | 75°C | | | 350 | |
| I_{IL} | A inputs and $\overline{OE}2$ | $V_{CC} = 5.5\text{ V}$, $V_{EE} = -5.46\text{ V}$, $V_I = 0.5\text{ V}$ | | | | -500 | μA |
| | $\overline{OE}1$ only | $V_{CC} = 5.5\text{ V}$, $V_{EE} = -5.46\text{ V}$, $V_I = -1950\text{ mV}$ | 0°C | | 0.5 | | |
| | | | 25°C | | 0.5 | | |
| | | | 75°C | | 0.5 | | |
| V_{OH}^\ddagger | | $V_{CC} = 4.5\text{ V}$, $V_{EE} = -5.2\text{ V}$, $\pm 5\%$, See Note 3 | 0°C | -1020 | | -840 | mV |
| | | | 25°C | -980 | | -810 | |
| | | | 75°C | -920 | | -735 | |
| V_{OL}^\ddagger | | $V_{CC} = 4.5\text{ V}$, $V_{EE} = -5.2\text{ V}$, $\pm 5\%$, See Note 3 | 0°C | -1950 | | -1630 | mV |
| | | | 25°C | -1950 | | -1630 | |
| | | | 75°C | -1950 | | -1600 | |
| I_{CCH} | | $V_{CC} = 5.5\text{ V}$, $V_{EE} = -5.46\text{ V}$ | | | 15 | 22 | mA |
| I_{CCL} | | $V_{CC} = 5.5\text{ V}$, $V_{EE} = -5.46\text{ V}$ | | | 17 | 25 | mA |
| I_{EE} | | $V_{CC} = 5.5\text{ V}$, $V_{EE} = -5.46\text{ V}$ | | | -78 | -111 | mA |
| C_i | | $V_{CC} = 5\text{ V}$, $V_{EE} = -5.2\text{ V}$, $f = 10\text{ MHz}$ | | | 5 | | pF |

switching characteristics over recommended ranges of operating ambient temperature and supply voltage (unless otherwise noted) (see Note 4)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | MIN | TYP† | MAX | UNIT |
|-----------|------------------------|-------------|-----|------|-----|------|
| t_{PLH} | Any A | Y | 0.1 | 1.7 | 3.7 | ns |
| t_{PHL} | | | 0.1 | 1.6 | 3.3 | |
| t_{PLH} | $\overline{OE}1$ (ECL) | Y | 0.8 | 2.8 | 5 | ns |
| t_{PHL} | | | 0.4 | 2.3 | 4.5 | |
| t_{PLH} | $\overline{OE}2$ (TTL) | Y | 0.8 | 3 | 5.3 | ns |
| t_{PHL} | | | 0.6 | 2.5 | 4.7 | |
| t_r | | Y | | 1.5 | | ns |
| t_f | | | | 1.5 | | |

† All typical values are at $V_{CC} = 5\text{ V}$, $V_{EE} = -5.2\text{ V}$, $T_A = 25^\circ\text{C}$.

‡ The algebraic convention, in which the least positive (most negative) value is designated minimum, is used in this data sheet for logic voltage levels and temperature only.

- NOTES: 2. Each 10KH series circuit has been designed to meet the dc specifications shown in the electrical characteristics table after thermal equilibrium has been established. The circuit is in a test socket or mounted on a printed circuit board and transverse air flow greater than 500 linear ft/min is maintained.
3. Outputs are terminated through a 50- Ω resistor to -2 V.
4. Load circuit and switching waveforms are shown in Section 1.

SN10KHT5542, SN10KHT5543

OCTAL TTL-TO-ECL TRANSLATORS WITH OUTPUT ENABLE

SDZS001A – D3136, AUGUST 1988 – REVISED DECEMBER 1988

electrical characteristics over recommended operating ambient temperature range (unless otherwise noted) (see Note 2)

| PARAMETER | | TEST CONDITIONS | | | | MIN | TYP [†] | MAX | UNIT |
|------------------------------|-------------------------------|---|--|------|-------|-------|------------------|------|------|
| V _{IK} | A inputs and $\overline{OE}2$ | V _{CC} = 4.5 V, V _{EE} = -4.94 V, I _I = -18 mA | | | | | | -1.2 | V |
| I _I | A inputs and $\overline{OE}2$ | V _{CC} = 5.5 V, V _{EE} = -5.46 V, V _I = 7 V | | | | | | 0.1 | mA |
| I _{IH} | A inputs and $\overline{OE}2$ | V _{CC} = 5.5 V, V _{EE} = -5.46 V, V _I = 2.7 V | | | | | | 20 | μA |
| | $\overline{OE}1$ only | V _{CC} = 5.5 V, V _{EE} = -5.46 V, V _I = -840 mV | | 0°C | | | 350 | | |
| | | V _{CC} = 5.5 V, V _{EE} = -5.46 V, V _I = -810 mV | | 25°C | | | 350 | | |
| | | V _{CC} = 5.5 V, V _{EE} = -5.46 V, V _I = -735 mV | | 75°C | | | 350 | | |
| I _{IL} | A inputs and $\overline{OE}2$ | V _{CC} = 5.5 V, V _{EE} = -5.46 V, V _I = 0.5 V | | | | | | -500 | μA |
| | $\overline{OE}1$ only | V _{CC} = 5.5 V, V _{EE} = -5.46 V, V _I = -1950 mV | | 0°C | | 0.5 | | | |
| | | | | 25°C | | 0.5 | | | |
| | | | | 75°C | | 0.5 | | | |
| V _{OH} [‡] | | V _{CC} = 4.5 V, V _{EE} = -5.2 V, ±5%, See Note 3 | | 0°C | -1020 | -840 | mV | | |
| | | | | 25°C | -980 | -810 | | | |
| | | | | 75°C | -920 | -735 | | | |
| V _{OL} [‡] | | V _{CC} = 4.5 V, V _{EE} = -5.2 V, ±5%, See Note 3 | | 0°C | -1950 | -1630 | mV | | |
| | | | | 25°C | -1950 | -1630 | | | |
| | | | | 75°C | -1950 | -1600 | | | |
| I _{CCH} | | V _{CC} = 5.5 V, V _{EE} = -5.46 V | | | | | 17 | 25 | mA |
| I _{CCL} | | V _{CC} = 5.5 V, V _{EE} = -5.46 V | | | | | 15 | 22 | mA |
| I _{EE} | | V _{CC} = 5.5 V, V _{EE} = -5.46 V | | | | | -77 | -111 | mA |
| C _i | | V _{CC} = 5 V, V _{EE} = -5.2 V, f = 10 MHz | | | | | 5 | | pF |

switching characteristics over recommended ranges of operating ambient temperature and supply voltage (unless otherwise noted) (see Note 4)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | MIN | TYP† | MAX | UNIT |
|-----------|------------------------|-------------|-----|------|-----|------|
| t_{PLH} | Any A | Y | 0.1 | 1.5 | 3 | ns |
| t_{PHL} | | | 0.1 | 1.5 | 3.3 | |
| t_{PLH} | $\overline{OE}1$ (ECL) | Y | 0.6 | 2.2 | 4.3 | ns |
| t_{PHL} | | | 0.5 | 2.4 | 4.3 | |
| t_{PLH} | $\overline{OE}2$ (TTL) | Y | 0.7 | 2.2 | 4.4 | ns |
| t_{PHL} | | | 0.5 | 2.6 | 4.7 | |
| t_r | | Y | | 1.5 | | ns |
| t_f | | | | 1.5 | | |

† All typical values are at $V_{CC} = 5\text{ V}$, $V_{EE} = -5.2\text{ V}$, $T_A = 25^\circ\text{C}$.

‡ The algebraic convention, in which the least positive (most negative) value is designated minimum, is used in this data sheet for logic voltage levels and temperature only.

- NOTES: 2. Each 10KH series circuit has been designed to meet the dc specifications shown in the electrical characteristics table after thermal equilibrium has been established. The circuit is in a test socket or mounted on a printed circuit board and transverse air flow greater than 500 linear ft/min is maintained.
3. Outputs are terminated through a 50- Ω resistor to -2 V.
4. Load circuit and voltage waveforms are shown in Section 1.

PACKAGING INFORMATION

| Orderable part number | Status (1) | Material type (2) | Package Pins | Package qty Carrier | RoHS (3) | Lead finish/ Ball material (4) | MSL rating/ Peak reflow (5) | Op temp (°C) | Part marking (6) |
|-------------------------------|---------------|----------------------|----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| SN10KHT5543DW | Active | Production | SOIC (DW) 24 | 25 TUBE | Yes | NIPDAU | Level-1-260C-UNLIM | 0 to 70 | 10KHT5543 |
| SN10KHT5543DW.A | Active | Production | SOIC (DW) 24 | 25 TUBE | Yes | NIPDAU | Level-1-260C-UNLIM | 0 to 70 | 10KHT5543 |

⁽¹⁾ **Status:** For more details on status, see our [product life cycle](#).

⁽²⁾ **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

⁽⁴⁾ **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

⁽⁵⁾ **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

⁽⁶⁾ **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer:The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TUBE




*All dimensions are nominal

| Device | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|-----------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| SN10KHT5543DW | DW | SOIC | 24 | 25 | 506.98 | 12.7 | 4826 | 6.6 |
| SN10KHT5543DW.A | DW | SOIC | 24 | 25 | 506.98 | 12.7 | 4826 | 6.6 |

DW (R-PDSO-G24)

PLASTIC SMALL OUTLINE



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2025, Texas Instruments Incorporated