

# EVM User's Guide: TPSM8287B30LAPEVM

## TPSM8287B30 Evaluation Module




### Description

The TPSM8287B30LAPEVM evaluation module (EVM) facilitates the evaluation of the TPSM8287B30. The device supports up to 30A load current in a pin-to-pin compatible, step-down power module with an I<sup>2</sup>C interface, remote sense, and frequency synchronization in a 3.75mm × 8mm MagPack™ package. The EVMs provide an I<sup>2</sup>C adjustable output voltage, with 0.8% accuracy, between 0.4V and 1.675V from input voltages from 2.7V to 6V.

### Features

- 30A output current power module with integrated inductor, input capacitors, and output capacitors in a MagPack package
- Excellent thermal performance ( $\theta_{JA} = 11.9^{\circ}\text{C/W}$ )
- 3.75mm × 8mm × 2mm power module provides 66mm<sup>2</sup> total design size
- Start-up output voltage adjustable through jumpers to 1 of 16 values
- Highly accurate output voltage with remote sense and adjustable control loop compensation



# 1 Evaluation Module Overview

## 1.1 Introduction

The TPSM8287B30LAPEVM enables evaluation of the TPSM8287B30LAPVCHR power module in a typical, standalone, step-down converter application. The TPSM8287Bxx are high-efficiency, high-accuracy, small and thin point-of-load (POL) power modules in applications such as the core supply for FPGAs, ASICs, DSPs, optical modules, storage, test and measurement, and other space-limited applications.

## 1.2 Kit Contents

The TPSM8287B30LAPEVM box (the kit) includes a PCB (SR087) to evaluate the TPSM8287B30 device in a typical, standalone (not paralleled) application. To evaluate the device using TI's TPSM8287B30 EVM GUI to operate the I<sup>2</sup>C bus, order the [USB2ANY adapter EVM](#) separately.

## 1.3 Specification

The following table provides a summary of the TPSM8287B30LAPEVM performance specifications.

**Table 1-1. Performance Specification Summary**

SPECIFICATION	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Input voltage		2.7	3.3 or 5	6	V
Output voltage	$V_{IN} > V_{OUT} + 1.5V$	0.4	0.6	1.675	V
Output current	TPSM8287B30LAPEVM (SR087-001)	0		30	A

## 1.4 Device Information

The TPSM8287B30 is a family of pin-to-pin compatible 15A, 20A, 25A, and 30A power modules, which integrate the inductor and input and output capacitors. The devices use an I<sup>2</sup>C interface to fine tune the output voltage to precisely match the needs of processor cores. The devices can be operated without the I<sup>2</sup>C interface to provide a high current, fixed-output-voltage power supply.

## 2 Hardware

### 2.1 Safety Instructions

**WARNING**



Hot surface. Contact can cause burns. Do not touch.

**WARNING**

High currents can be present on the input and output.

### 2.2 Header Information

<b>J1 – VIN/GND</b>	Input and return connections from the input supply to the EVM. This connector accepts up to 10 AWG wire.
<b>MH1/2 – VIN/GND</b>	Alternate input and return connections from the input supply to the EVM. These holes are sized for M4 or #8 bolts.
<b>J2 – VOUT/GND</b>	Input and return connections from the EVM to the load. This connector accepts up to 10 AWG wire.
<b>MH3/4 – VOUT/GND</b>	Alternate input and return connections from the EVM to the load. These holes are sized for M4 or #8 bolts.
<b>J3 – PG/GND</b>	The PG output appears on pin 2 of this header with ground on pin 1.
<b>J4 – SYNC_OUT/GND</b>	The SYNC_OUT signal appears on pin 1 of this header with ground on pin 2.
<b>J6 – VOUT/GND SMA</b>	Measure the output voltage waveform at this SMA connector.

### 2.3 Jumper Information

<b>JP1 – EN</b>	EN pin input jumper. Place the supplied jumper across ON and EN to turn on the module. Place the jumper across OFF and EN to turn off the module. With the jumper installed across ON and EN, users can create a precise turn-on voltage with R2 and R16. Keep the value of R2 above 15kΩ.
<b>JP2 – MODE/SYNC</b>	MODE/SYNC pin input jumper. Place the supplied jumper across PWM (Pulse Width Modulation) and MODE/SYNC to operate the IC in forced PWM mode. Place the jumper across PFM (Pulse Frequency Modulation)/PWM and MODE/SYNC to operate the IC in PFM/PWM mode. Remove the jumper to apply a synchronization signal on the MODE/SYNC pin.
<b>JP3 – PG Pullup</b>	PG pin pullup voltage jumper. Place the supplied jumper on JP3 to connect the PG pin pullup resistor to VIN. Alternatively, the jumper can be removed and a different voltage can be supplied on pin 1 to pull up the PG pin to a different level. This externally applied voltage must remain below 6.5V.
<b>JP4 and JP6 – VSET1</b>	VSET1 setting jumper. Place the supplied jumper on either JP4 and JP6 but not both.
<b>JP5 and JP7 – VSET2</b>	VSET2 setting jumper. Place the supplied jumper on either JP5 and JP7 but not both.

To properly set the start-up voltage, the two jumpers for VSETx must be set before VIN is applied. Changing the jumpers after VIN is applied has no effect.

**WARNING**

Before applying VIN, verify that both jumpers are installed: to JP4 or JP6 and to JP5 or JP7.

Do not leave the VSETx pins floating.

## 2.4 Interfaces

<b>J5 – I<sup>2</sup>C</b>	I <sup>2</sup> C adapter connection. Connect the 10-pin ribbon cable from the USB2ANY adapter EVM to this header to communicate with the device over the I <sup>2</sup> C bus through the TPSM8287B30 EVM GUI. This header is keyed to prevent backwards installation. The TPSM8287B30LAPEVM does not require the USB2ANY EVM to operate.
----------------------------	---

## 2.5 Test Points

<b>TP1/2 – VOSNS/GOSNS</b>	Regulated output voltage connections. Measure the output voltage regulation at this point.
<b>TP3/4 – VIN/GND S+/S–</b>	Input voltage sense connections. Measure the input voltage at this point.
<b>TP5/6 – VOUT/GND S+/S–</b>	Output voltage sense connections for efficiency measurements. Measure the output voltage at this point when calculating efficiency.
<b>TP7 – SW</b>	SW node test point. Measure the SW node at this point. This test point is not installed.

## 3 Software

The TPSM8287B30 EVM GUI is provided on the [TPSM8287B30LAPEVM](#) tool folder to communicate with the device over the I<sup>2</sup>C bus through the USB2ANY adapter EVM. A valid input voltage must be applied.

The GUI automatically connects to the EVM. If this connection does not happen, then click either the *Connect* button at the top right of the GUI or the *link* symbol at the very bottom left of the GUI.

## 4 Implementation Results

The TPSM8287B30LAPEVM is used to take all the data in the [TPSM8287Bxx 2.7V to 6V Input, 15A, 20A, 25A and 30A, Parallelable Step-Down Power Module with I<sup>2</sup>C Interface and Remote Sense](#) in a MagPack™ Package datasheet. See the device datasheet for the performance of this EVM.

### 4.1 Evaluation Setup

#### 4.1.1 Ripple Measurement Setup

The SMA connector, J6, is used to measure the output voltage ripple and transient response. Connect the SMA connector directly to the oscilloscope with a coaxial (coax) cable, instead of using a 10x oscilloscope probe, to achieve the best results. This action enables the use of the smallest V/div setting on the oscilloscope to view the ripple. The EVM contains a 49.9Ω resistor in series with the SMA connector to block reflections on the coax cable. Either the high-impedance or 50Ω terminated setting on the oscilloscope can be used.

#### 4.1.2 Loop Response Measurement


The loop response can be measured by replacing R5 with a 10Ω resistor and applying the injection signal across. [Figure 4-2](#) shows the loop response measurement results.

#### 4.1.3 Precise Turn-on Voltage

With the jumper on JP1 installed, R2 and R16 can be modified to create a precise turn-on voltage. See [Achieving a Clean Start-up by Using a DC/DC Converter With a Precise Enable-pin Threshold analog design journal](#) for details. Keep the value of R2 above 15kΩ.


## 4.2 Performance Data and Results

The following figure shows the thermal performance of the TPSM8287B30LAPEVM.



**Figure 4-1. Thermal Performance (TPSM8287B30LAPEVM,  $V_{IN} = 5V$ ,  $V_{OUT} = 0.6V$ ,  $I_{OUT} = 30A$ )**

The following figure shows the loop response measurement of the TPSM8287B30LAPEVM.



**Figure 4-2. Loop Response Measurement (TPSM8287B30LAPEVM,  $V_{IN} = 5V$ ,  $V_{OUT} = 0.6V$ ,  $I_{OUT} = 30A$ )**

## 5 Hardware Design Files

### 5.1 Schematics

The following figure shows the EVM schematics.




Figure 5-1. TPSM8287B30LAPEVM Schematic

## 5.2 PCB Layouts

This section provides the TPSM8287B30LAPEVM board layout (SR087). The Gerber files are available on the [TPSM8287B30LAPEVM](#) tool folder. All eight layers use 2-ounce copper.




Figure 5-2. Top Assembly




Figure 5-3. Top Layer




Figure 5-4. Internal Layer 1




Figure 5-5. Internal Layer 2




Figure 5-6. Internal Layer 3







Figure 5-7. Internal Layer 4




**Figure 5-8. Internal Layer 5**



**Figure 5-9. Internal Layer 6**



**Figure 5-10. Bottom Layer**



**Figure 5-11. Bottom Assembly (Mirrored)**

TPS8287BxL I2C				TPS8287BxH I2C			
Uout	USET1	USET2	Address	Uout	USET1	USET2	Address
0.4V	GND	GND	0x45	0.8V	GND	GND	0x45
0.45V	GND	OUTL_R	0x47	0.85V	GND	OUT_R	0x47
0.5V	GND	OUTL_R	0x47	0.9V	GND	OUT_R	0x47
0.55V	GND	OUT_R	0x44	1.05V	GND	OUT_R	0x44
0.55V	GND	OUT_R	0x44	1.1V	GND	OUTL_R	0x47
0.575V	GND	OUT_R	0x44	1.15V	GND	OUT_R	0x44
0.6V	GND	OUTL_R	0x47	1.2V	GND	OUT_R	0x47
0.65V	VIN_R	GND	0x45	1.25V	GND	OUT_R	0x44
0.65V	VIN_R	OUT_R	0x47	1.3V	VIN_R	VIN_R	0x47
0.675V	VIN_R	GND	0x44	1.35V	VIN_R	OUT_R	0x44
0.7V	VIN	GND	0x45	1.4V	VIN	GND	0x45
0.725V	VIN	GND	0x44	1.45V	VIN	GND	0x44
0.75V	VIN	OUT_R	0x47	1.5V	VIN	OUT_R	0x47
0.75V	VIN	OUT_R	0x44	1.55V	VIN	OUT_R	0x44

### 5.3 Bill of Materials (BOM)

The following table lists the BOM for this EVM.

**Table 5-1. TPSM8287B30LAPEVM (SR087) Bill of Materials**

QUANTITY -001	REF DES	VALUE	DESCRIPTION	SIZE	PART NUMBER	MANUFACTURER
1	C1	0.015 $\mu$ F	Ceramic Capacitor, 50V, X7R	0402	Std	Std
4	C3, C4, C12, C13	22 $\mu$ F	Ceramic Capacitor, 6.3V, X6S	0603	GRM188C80J226ME01D	Murata
4	C5, C6, C7, C8	22 $\mu$ F	Ceramic Capacitor, 10V, X6S	0603	GRM188C81A226ME01D	Murata
2	C9, C10	220 $\mu$ F	Tantalum Capacitor, 10V, 50m $\Omega$ ESR	7343	TPSD227M010R0050	AVX
1	C11	47 $\mu$ F	Ceramic Capacitor, 4V, X6S	0603	GRM188C80G476ME01D	Murata
2	C14, C15	10 $\mu$ F	Ceramic Capacitor, 4V, X6S	0402	GRM155C80G106ME18D	Murata
1	R1	301 $\Omega$	Resistor 1%, 0.063 W	0402	Std	Std
5	R2, R9, R10, R11, R12	47k $\Omega$	Resistor 5%, 0.1 W	0603	Std	Std
1	R3	10k $\Omega$	Resistor 5%, 0.1 W	0603	Std	Std
1	R4	49.9 $\Omega$	Resistor 1%, 0.1 W	0603	Std	Std
2	R5, R6	0 $\Omega$	Resistor 5%, 0.1 W	0603	Std	Std
2	R7, R8	1.0M $\Omega$	Resistor 5%, 0.1 W	0603	Std	Std
1	U1 <sup>(1)</sup>		2.7V to 6V Input, 30A parallelable step-down power module with I <sup>2</sup> C interface and remote sense in a MagPack package	3.75mm x 8mm	TPSM8287B30LAPVCHR	Texas Instruments

(1) These U1 devices can not contain the correct top side markings and are still fully tested and functional devices.

## 6 Additional Information

### 6.1 Trademarks

MagPack™ is a trademark of Texas Instruments.  
All trademarks are the property of their respective owners.

## 7 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

<b>Changes from Revision * (March 2025) to Revision A (February 2026)</b>	<b>Page</b>
• Changed $\theta_{JA}$ value from 8.8°C/W to 11.9°C/W in the <i>Features</i> .....	<a href="#">1</a>
• Updated the thermal image in <i>Performance Data and Results</i> .....	<a href="#">5</a>

---

## STANDARD TERMS FOR EVALUATION MODULES

1. *Delivery:* TI delivers TI evaluation boards, kits, or modules, including any accompanying demonstration software, components, and/or documentation which may be provided together or separately (collectively, an "EVM" or "EVMs") to the User ("User") in accordance with the terms set forth herein. User's acceptance of the EVM is expressly subject to the following terms.
  - 1.1 EVMs are intended solely for product or software developers for use in a research and development setting to facilitate feasibility evaluation, experimentation, or scientific analysis of TI semiconductors products. EVMs have no direct function and are not finished products. EVMs shall not be directly or indirectly assembled as a part or subassembly in any finished product. For clarification, any software or software tools provided with the EVM ("Software") shall not be subject to the terms and conditions set forth herein but rather shall be subject to the applicable terms that accompany such Software
  - 1.2 EVMs are not intended for consumer or household use. EVMs may not be sold, sublicensed, leased, rented, loaned, assigned, or otherwise distributed for commercial purposes by Users, in whole or in part, or used in any finished product or production system.
2. *Limited Warranty and Related Remedies/Disclaimers:*
  - 2.1 These terms do not apply to Software. The warranty, if any, for Software is covered in the applicable Software License Agreement.
  - 2.2 TI warrants that the TI EVM will conform to TI's published specifications for ninety (90) days after the date TI delivers such EVM to User. Notwithstanding the foregoing, TI shall not be liable for a nonconforming EVM if (a) the nonconformity was caused by neglect, misuse or mistreatment by an entity other than TI, including improper installation or testing, or for any EVMs that have been altered or modified in any way by an entity other than TI, (b) the nonconformity resulted from User's design, specifications or instructions for such EVMs or improper system design, or (c) User has not paid on time. Testing and other quality control techniques are used to the extent TI deems necessary. TI does not test all parameters of each EVM. User's claims against TI under this Section 2 are void if User fails to notify TI of any apparent defects in the EVMs within ten (10) business days after delivery, or of any hidden defects with ten (10) business days after the defect has been detected.
  - 2.3 TI's sole liability shall be at its option to repair or replace EVMs that fail to conform to the warranty set forth above, or credit User's account for such EVM. TI's liability under this warranty shall be limited to EVMs that are returned during the warranty period to the address designated by TI and that are determined by TI not to conform to such warranty. If TI elects to repair or replace such EVM, TI shall have a reasonable time to repair such EVM or provide replacements. Repaired EVMs shall be warranted for the remainder of the original warranty period. Replaced EVMs shall be warranted for a new full ninety (90) day warranty period.

### **WARNING**

**Evaluation Kits are intended solely for use by technically qualified, professional electronics experts who are familiar with the dangers and application risks associated with handling electrical mechanical components, systems, and subsystems.**

**User shall operate the Evaluation Kit within TI's recommended guidelines and any applicable legal or environmental requirements as well as reasonable and customary safeguards. Failure to set up and/or operate the Evaluation Kit within TI's recommended guidelines may result in personal injury or death or property damage. Proper set up entails following TI's instructions for electrical ratings of interface circuits such as input, output and electrical loads.**

**NOTE:**

**EXPOSURE TO ELECTROSTATIC DISCHARGE (ESD) MAY CAUSE DEGRADATION OR FAILURE OF THE EVALUATION KIT; TI RECOMMENDS STORAGE OF THE EVALUATION KIT IN A PROTECTIVE ESD BAG.**

### 3 Regulatory Notices:

#### 3.1 United States

##### 3.1.1 Notice applicable to EVMs not FCC-Approved:

**FCC NOTICE:** This kit is designed to allow product developers to evaluate electronic components, circuitry, or software associated with the kit to determine whether to incorporate such items in a finished product and software developers to write software applications for use with the end product. This kit is not a finished product and when assembled may not be resold or otherwise marketed unless all required FCC equipment authorizations are first obtained. Operation is subject to the condition that this product not cause harmful interference to licensed radio stations and that this product accept harmful interference. Unless the assembled kit is designed to operate under part 15, part 18 or part 95 of this chapter, the operator of the kit must operate under the authority of an FCC license holder or must secure an experimental authorization under part 5 of this chapter.

##### 3.1.2 For EVMs annotated as FCC – FEDERAL COMMUNICATIONS COMMISSION Part 15 Compliant:

#### **CAUTION**

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

#### **FCC Interference Statement for Class A EVM devices**

*NOTE: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.*

#### **FCC Interference Statement for Class B EVM devices**

*NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:*

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

#### 3.2 Canada

##### 3.2.1 For EVMs issued with an Industry Canada Certificate of Conformance to RSS-210 or RSS-247

#### **Concerning EVMs Including Radio Transmitters:**

This device complies with Industry Canada license-exempt RSSs. Operation is subject to the following two conditions:

(1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

#### **Concernant les EVMs avec appareils radio:**

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes: (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

#### **Concerning EVMs Including Detachable Antennas:**

Under Industry Canada regulations, this radio transmitter may only operate using an antenna of a type and maximum (or lesser) gain approved for the transmitter by Industry Canada. To reduce potential radio interference to other users, the antenna type and its gain should be so chosen that the equivalent isotropically radiated power (e.i.r.p.) is not more than that necessary for successful communication. This radio transmitter has been approved by Industry Canada to operate with the antenna types listed in the user guide with the maximum permissible gain and required antenna impedance for each antenna type indicated. Antenna types not included in this list, having a gain greater than the maximum gain indicated for that type, are strictly prohibited for use with this device.

### Concernant les EVMs avec antennes détachables

Conformément à la réglementation d'Industrie Canada, le présent émetteur radio peut fonctionner avec une antenne d'un type et d'un gain maximal (ou inférieur) approuvé pour l'émetteur par Industrie Canada. Dans le but de réduire les risques de brouillage radioélectrique à l'intention des autres utilisateurs, il faut choisir le type d'antenne et son gain de sorte que la puissance isotrope rayonnée équivalente (p.i.r.e.) ne dépasse pas l'intensité nécessaire à l'établissement d'une communication satisfaisante. Le présent émetteur radio a été approuvé par Industrie Canada pour fonctionner avec les types d'antenne énumérés dans le manuel d'usage et ayant un gain admissible maximal et l'impédance requise pour chaque type d'antenne. Les types d'antenne non inclus dans cette liste, ou dont le gain est supérieur au gain maximal indiqué, sont strictement interdits pour l'exploitation de l'émetteur.

#### 3.3 Japan

3.3.1 *Notice for EVMs delivered in Japan:* Please see [http://www.tij.co.jp/lstds/ti\\_ja/general/eStore/notice\\_01.page](http://www.tij.co.jp/lstds/ti_ja/general/eStore/notice_01.page) 日本国内に輸入される評価用キット、ボードについては、次のところをご覧ください。

<https://www.ti.com/ja-jp/legal/notice-for-evaluation-kits-delivered-in-japan.html>

3.3.2 *Notice for Users of EVMs Considered "Radio Frequency Products" in Japan:* EVMs entering Japan may not be certified by TI as conforming to Technical Regulations of Radio Law of Japan.

If User uses EVMs in Japan, not certified to Technical Regulations of Radio Law of Japan, User is required to follow the instructions set forth by Radio Law of Japan, which includes, but is not limited to, the instructions below with respect to EVMs (which for the avoidance of doubt are stated strictly for convenience and should be verified by User):

1. Use EVMs in a shielded room or any other test facility as defined in the notification #173 issued by Ministry of Internal Affairs and Communications on March 28, 2006, based on Sub-section 1.1 of Article 6 of the Ministry's Rule for Enforcement of Radio Law of Japan,
2. Use EVMs only after User obtains the license of Test Radio Station as provided in Radio Law of Japan with respect to EVMs, or
3. Use of EVMs only after User obtains the Technical Regulations Conformity Certification as provided in Radio Law of Japan with respect to EVMs. Also, do not transfer EVMs, unless User gives the same notice above to the transferee. Please note that if User does not follow the instructions above, User will be subject to penalties of Radio Law of Japan.

【無線電波を送信する製品の開発キットをお使いになる際の注意事項】 開発キットの中には技術基準適合証明を受けていないものがあります。技術適合証明を受けていないものご使用に際しては、電波法遵守のため、以下のいずれかの措置を取っていただく必要がありますのでご注意ください。

1. 電波法施行規則第6条第1項第1号に基づく平成18年3月28日総務省告示第173号で定められた電波暗室等の試験設備でご使用いただく。
2. 実験局の免許を取得後ご使用いただく。
3. 技術基準適合証明を取得後ご使用いただく。

なお、本製品は、上記の「ご使用にあたっての注意」を譲渡先、移転先に通知しない限り、譲渡、移転できないものとします。

上記を遵守頂けない場合は、電波法の罰則が適用される可能性があることをご留意ください。日本テキサス・イ

ンスツルメンツ株式会社

東京都新宿区西新宿 6 丁目 2 4 番 1 号

西新宿三井ビル

3.3.3 *Notice for EVMs for Power Line Communication:* Please see [http://www.tij.co.jp/lstds/ti\\_ja/general/eStore/notice\\_02.page](http://www.tij.co.jp/lstds/ti_ja/general/eStore/notice_02.page)

電力線搬送波通信についての開発キットをお使いになる際の注意事項については、次のところをご覧ください。 <https://www.ti.com/ja-jp/legal/notice-for-evaluation-kits-for-power-line-communication.html>

#### 3.4 European Union

3.4.1 *For EVMs subject to EU Directive 2014/30/EU (Electromagnetic Compatibility Directive):*

This is a class A product intended for use in environments other than domestic environments that are connected to a low-voltage power-supply network that supplies buildings used for domestic purposes. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

- 
- 4 *EVM Use Restrictions and Warnings:*
    - 4.1 EVMS ARE NOT FOR USE IN FUNCTIONAL SAFETY AND/OR SAFETY CRITICAL EVALUATIONS, INCLUDING BUT NOT LIMITED TO EVALUATIONS OF LIFE SUPPORT APPLICATIONS.
    - 4.2 User must read and apply the user guide and other available documentation provided by TI regarding the EVM prior to handling or using the EVM, including without limitation any warning or restriction notices. The notices contain important safety information related to, for example, temperatures and voltages.
    - 4.3 *Safety-Related Warnings and Restrictions:*
      - 4.3.1 User shall operate the EVM within TI's recommended specifications and environmental considerations stated in the user guide, other available documentation provided by TI, and any other applicable requirements and employ reasonable and customary safeguards. Exceeding the specified performance ratings and specifications (including but not limited to input and output voltage, current, power, and environmental ranges) for the EVM may cause personal injury or death, or property damage. If there are questions concerning performance ratings and specifications, User should contact a TI field representative prior to connecting interface electronics including input power and intended loads. Any loads applied outside of the specified output range may also result in unintended and/or inaccurate operation and/or possible permanent damage to the EVM and/or interface electronics. Please consult the EVM user guide prior to connecting any load to the EVM output. If there is uncertainty as to the load specification, please contact a TI field representative. During normal operation, even with the inputs and outputs kept within the specified allowable ranges, some circuit components may have elevated case temperatures. These components include but are not limited to linear regulators, switching transistors, pass transistors, current sense resistors, and heat sinks, which can be identified using the information in the associated documentation. When working with the EVM, please be aware that the EVM may become very warm.
      - 4.3.2 EVMs are intended solely for use by technically qualified, professional electronics experts who are familiar with the dangers and application risks associated with handling electrical mechanical components, systems, and subsystems. User assumes all responsibility and liability for proper and safe handling and use of the EVM by User or its employees, affiliates, contractors or designees. User assumes all responsibility and liability to ensure that any interfaces (electronic and/or mechanical) between the EVM and any human body are designed with suitable isolation and means to safely limit accessible leakage currents to minimize the risk of electrical shock hazard. User assumes all responsibility and liability for any improper or unsafe handling or use of the EVM by User or its employees, affiliates, contractors or designees.
    - 4.4 User assumes all responsibility and liability to determine whether the EVM is subject to any applicable international, federal, state, or local laws and regulations related to User's handling and use of the EVM and, if applicable, User assumes all responsibility and liability for compliance in all respects with such laws and regulations. User assumes all responsibility and liability for proper disposal and recycling of the EVM consistent with all applicable international, federal, state, and local requirements.
  5. *Accuracy of Information:* To the extent TI provides information on the availability and function of EVMs, TI attempts to be as accurate as possible. However, TI does not warrant the accuracy of EVM descriptions, EVM availability or other information on its websites as accurate, complete, reliable, current, or error-free.
  6. *Disclaimers:*
    - 6.1 EXCEPT AS SET FORTH ABOVE, EVMS AND ANY MATERIALS PROVIDED WITH THE EVM (INCLUDING, BUT NOT LIMITED TO, REFERENCE DESIGNS AND THE DESIGN OF THE EVM ITSELF) ARE PROVIDED "AS IS" AND "WITH ALL FAULTS." TI DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, REGARDING SUCH ITEMS, INCLUDING BUT NOT LIMITED TO ANY EPIDEMIC FAILURE WARRANTY OR IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADE SECRETS OR OTHER INTELLECTUAL PROPERTY RIGHTS.
    - 6.2 EXCEPT FOR THE LIMITED RIGHT TO USE THE EVM SET FORTH HEREIN, NOTHING IN THESE TERMS SHALL BE CONSTRUED AS GRANTING OR CONFERRING ANY RIGHTS BY LICENSE, PATENT, OR ANY OTHER INDUSTRIAL OR INTELLECTUAL PROPERTY RIGHT OF TI, ITS SUPPLIERS/LICENSORS OR ANY OTHER THIRD PARTY, TO USE THE EVM IN ANY FINISHED END-USER OR READY-TO-USE FINAL PRODUCT, OR FOR ANY INVENTION, DISCOVERY OR IMPROVEMENT, REGARDLESS OF WHEN MADE, CONCEIVED OR ACQUIRED.
  7. *USER'S INDEMNITY OBLIGATIONS AND REPRESENTATIONS.* USER WILL DEFEND, INDEMNIFY AND HOLD TI, ITS LICENSORS AND THEIR REPRESENTATIVES HARMLESS FROM AND AGAINST ANY AND ALL CLAIMS, DAMAGES, LOSSES, EXPENSES, COSTS AND LIABILITIES (COLLECTIVELY, "CLAIMS") ARISING OUT OF OR IN CONNECTION WITH ANY HANDLING OR USE OF THE EVM THAT IS NOT IN ACCORDANCE WITH THESE TERMS. THIS OBLIGATION SHALL APPLY WHETHER CLAIMS ARISE UNDER STATUTE, REGULATION, OR THE LAW OF TORT, CONTRACT OR ANY OTHER LEGAL THEORY, AND EVEN IF THE EVM FAILS TO PERFORM AS DESCRIBED OR EXPECTED.

8. *Limitations on Damages and Liability:*

8.1 *General Limitations.* IN NO EVENT SHALL TI BE LIABLE FOR ANY SPECIAL, COLLATERAL, INDIRECT, PUNITIVE, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES IN CONNECTION WITH OR ARISING OUT OF THESE TERMS OR THE USE OF THE EVMS , REGARDLESS OF WHETHER TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. EXCLUDED DAMAGES INCLUDE, BUT ARE NOT LIMITED TO, COST OF REMOVAL OR REINSTALLATION, ANCILLARY COSTS TO THE PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES, RETESTING, OUTSIDE COMPUTER TIME, LABOR COSTS, LOSS OF GOODWILL, LOSS OF PROFITS, LOSS OF SAVINGS, LOSS OF USE, LOSS OF DATA, OR BUSINESS INTERRUPTION. NO CLAIM, SUIT OR ACTION SHALL BE BROUGHT AGAINST TI MORE THAN TWELVE (12) MONTHS AFTER THE EVENT THAT GAVE RISE TO THE CAUSE OF ACTION HAS OCCURRED.

8.2 *Specific Limitations.* IN NO EVENT SHALL TI'S AGGREGATE LIABILITY FROM ANY USE OF AN EVM PROVIDED HEREUNDER, INCLUDING FROM ANY WARRANTY, INDEMNITY OR OTHER OBLIGATION ARISING OUT OF OR IN CONNECTION WITH THESE TERMS, , EXCEED THE TOTAL AMOUNT PAID TO TI BY USER FOR THE PARTICULAR EVM(S) AT ISSUE DURING THE PRIOR TWELVE (12) MONTHS WITH RESPECT TO WHICH LOSSES OR DAMAGES ARE CLAIMED. THE EXISTENCE OF MORE THAN ONE CLAIM SHALL NOT ENLARGE OR EXTEND THIS LIMIT.

9. *Return Policy.* Except as otherwise provided, TI does not offer any refunds, returns, or exchanges. Furthermore, no return of EVM(s) will be accepted if the package has been opened and no return of the EVM(s) will be accepted if they are damaged or otherwise not in a resalable condition. If User feels it has been incorrectly charged for the EVM(s) it ordered or that delivery violates the applicable order, User should contact TI. All refunds will be made in full within thirty (30) working days from the return of the components(s), excluding any postage or packaging costs.

10. *Governing Law:* These terms and conditions shall be governed by and interpreted in accordance with the laws of the State of Texas, without reference to conflict-of-laws principles. User agrees that non-exclusive jurisdiction for any dispute arising out of or relating to these terms and conditions lies within courts located in the State of Texas and consents to venue in Dallas County, Texas. Notwithstanding the foregoing, any judgment may be enforced in any United States or foreign court, and TI may seek injunctive relief in any United States or foreign court.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2023, Texas Instruments Incorporated

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#), [TI's General Quality Guidelines](#), or other applicable terms available either on [ti.com](http://ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2026, Texas Instruments Incorporated

Last updated 10/2025