

LMP7704-SP Neutron Displacement Damage Characterization



ABSTRACT

The LMP7704-SP was subjected to a one-time characterization to determine the effects of Neutron Displacement Damage (NDD) to the device parameters. A sample size of twelve units was exposed to radiation testing per MIL-STD-883 (Method 1017 for Neutron Irradiation). The samples were dosed to exposure levels of 1×10^{12} n/cm², 5×10^{12} n/cm², and 1×10^{13} n/cm², with three samples evaluated per exposure level. Electrical testing was performed at Texas Instruments before and after neutron irradiation using the production test program for the device. All tested parameters remained within the data sheet specified limits. Degradation of input offset voltage on some samples was observed and is discussed herein.

Table of Contents

| | |
|--|---|
| 1 Overview..... | 2 |
| 2 Test Procedures..... | 3 |
| 3 Facility..... | 4 |
| 4 Results..... | 5 |
| 4.1 Input Offset Voltage Parametric Shift..... | 5 |
| 5 Summary of Results..... | 6 |
| A Test Results..... | 7 |

Trademarks

All trademarks are the property of their respective owners.

1 Overview

The LMP7704-SP is a precision amplifier with low input bias, low offset voltage, 2.5MHz gain bandwidth, and a wide supply voltage. The device is radiation-hardened and operates in the military temperature range of -55°C to $+125^{\circ}\text{C}$. The high dc precision of this amplifier, specifically the low offset voltage of $\pm 60\mu\text{V}$ and ultra-low input bias of $\pm 500\text{fA}$, make this device an excellent choice for interfacing with precision sensors with high-output impedances. This amplifier can be configured for transducer, bridge, strain gauge, and trans-impedance amplification.

Table 1-1. Overview Information

| TI Part Number | LMP7704-SP |
|------------------------------------|---|
| Device Name | 5962R1920601VXC |
| SMD Number | 5962-19206 |
| Device Function | Radiation Hardness Assured (RHA), Precision, Low Input Bias, RRIO, Wide Supply Range Amplifiers |
| Technology | VIP050 |
| Device Package | 14-pin CFP (HBH) |
| Unbiased Quantity Tested | 12 |
| Exposure Facility | VPT Rad, Chelmsford, MA |
| Neutron Fluence (1-MeV Equivalent) | 1.0×10^{12} , 5.0×10^{12} , $1.0 \times 10^{13} \text{ n/cm}^2$ |
| Irradiation Temperature | 25°C |

TI may provide technical, applications or design advice, quality characterization, and reliability data or service providing these items shall not expand or otherwise affect TI's warranties as set forth in the Texas Instruments Incorporated Standard Terms and Conditions of Sale for Semiconductor Products and no obligation or liability shall arise from Semiconductor Products and no obligation or liability shall arise from TI's provision of such items.

2 Test Procedures

The LMP7704-SP samples were electrically pre-tested using the production automated test equipment program. General test procedures were per MIL-STD-883, Method 1017. The exposed devices were then re-tested on the same ATE hardware. An additional control unit (serial number 13) that was not exposed to the neutron source was measured alongside the exposed samples, for both pre- and post-exposure ATE testing. The specified limits at $T_A = 25^\circ\text{C}$ are listed below.

Table 2-1. LMP7704-SP Specification Compliance Matrix

| Parameter | Test Condition | LMP7704-SP Data Sheet (SNOSDB6) | | | | Test # |
|--------------------------------|--|------------------------------------|-----------|-----------|------------------|---------------------------------------|
| | | MIN | TYP | MAX | Unit | |
| Input offset voltage | | | ± 60 | ± 260 | μV | 104.4 to 104.11 |
| Power-supply rejection ratio | $2.7\text{V} < V_S < 12\text{V}$ | 86 | 100 | | dB | 104.16 to 104.19 |
| | $2.7\text{V} < V_S < 12\text{V}$, Flight model post-HDR exposure | 82 | | | | |
| Input bias current | $V_S = 5\text{V}$ | | ± 0.5 | ± 10 | pA | 120.0–120.3 |
| | $V_S = 5\text{V}$, Flight model post-TID exposure | | | ± 400 | | |
| | $V_S = 10\text{V}$ | | ± 1 | ± 10 | pA | 120.12 to 120.15 |
| | $V_S = 10\text{V}$, Flight model post-TID exposure | | | ± 400 | | |
| Input offset current | | | ± 40 | | fA | 120.8 to 120.11, 120.20 to 120.23 |
| Common-mode rejection ratio | $V_S = 5\text{V}, (V-) < V_{CM} < (V+)$ | 85 | 130 | | dB | 105.0 to 105.3 |
| | $V_S = 5\text{V}, (V-) < V_{CM} < (V+)$, Flight model post-HDR exposure | 76 | | | | |
| | $V_S = 10\text{V}, (V-) < V_{CM} < (V+)$ | 90 | 130 | | dB | 105.4 to 105.7 |
| | $V_S = 10\text{V}, (V-) < V_{CM} < (V+)$, Flight model post-HDR exposure | 83 | | | | |
| Open-loop voltage gain | $V_S = 5\text{V}, (V-) + 0.3\text{V} < V_{OUT} < (V+) - 0.3\text{V}, R_L = 2\text{k}\Omega$ | 100 | 119 | | dB | 106.0 to 106.3 |
| | $V_S = 5\text{V}, (V-) + 0.3\text{V} < V_{OUT} < (V+) - 0.3\text{V}, R_L = 2\text{k}\Omega$, Flight model post-HDR exposure | 84 | | | | |
| | $V_S = 5\text{V}, (V-) + 0.2\text{V} < V_{OUT} < (V+) - 0.2\text{V}, R_L = 10\text{k}\Omega$ | 100 | 130 | | dB | 106.4 to 106.7 |
| | $V_S = 10\text{V}, (V-) + 0.3\text{V} < V_{OUT} < (V+) - 0.3\text{V}, R_L = 2\text{k}\Omega$ | 100 | 121 | | dB | 106.8 to 106.11 |
| | $V_S = 10\text{V}, (V-) + 0.2\text{V} < V_{OUT} < (V+) - 0.2\text{V}, R_L = 10\text{k}\Omega$ | 100 | 134 | | dB | 106.12 to 106.15 |
| Gain bandwidth | | | 2.5 | | MHz | 116.x |
| Slew rate | $V_S = 10\text{V}, G = 1$, 9V step, 10% to 90% rising | | 0.8 | | V/ μs | 109.x |
| Voltage output swing from rail | Positive rail, $R_L = 2\text{k}\Omega$ to $V_S / 2$ | | 60 | 120 | mV | 110.0 to 110.3, 110.16 to 110.19 |
| | Positive rail, $R_L = 10\text{k}\Omega$ to $V_S / 2$ | | 40 | 60 | | 110.8 to 110.11, 110.24 to 110.27 |
| | Negative rail, $R_L = 2\text{k}\Omega$ to $V_S / 2$ | | 50 | 120 | mV | 110.4 to 110.7, 110.20 to 110.23 |
| | Negative rail, $R_L = 10\text{k}\Omega$ to $V_S / 2$ | | 30 | 50 | | 110.12 to 110.15, 110.28 to 110.31 |
| Short-circuit current | $V_S = 5\text{V}, V_{OUT} = V_S / 2, V_{IN} = \pm 100\text{mV}$ | | +66, -76 | | mA | 111.x |
| Total quiescent current | $V_S = 5\text{V}, I_O = 0\text{A}$ | | 2.9 | 3.7 | mA | 101.2, 101.3, 112.2, 112.3 |
| | $V_S = 10\text{V}, I_O = 0\text{A}$ | | 3.2 | 4.2 | mA | 101.4, 101.5, 112.4, 112.5 |

Table 2-2. Neutron Irradiation Conditions

| Serial Numbers | Sample Qty | Neutron Fluence (n/cm ²) | Bias |
|----------------|------------|--------------------------------------|----------|
| 1, 2, 3, 4 | 4 | 1.0×10^{12} | Unbiased |
| 5, 6, 7, 8 | 4 | 5.0×10^{12} | Unbiased |
| 9, 10, 11, 12 | 4 | 1.0×10^{13} | Unbiased |

3 Facility

VPT Rad performed neutron displacement damage irradiations in a low-enriched, open-pool, water moderated, thermal neutron reactor at the University of Massachusetts Lowell. The reactor uses flat-plate type fuel and has a maximum thermal energy output of up to 1MW. The Fast Neutron Irradiator (FNI) faces one side of the reactor core. The experimental facility replaces three beam ports that originally existed on the left side of the research reactor. The FNI is designed to give a fast flux level $\geq 10^{11}$ n/cm²-s, with relatively low thermal fluence and gamma dose rates. Samples with a cross-sectional area as large as 30cm (12in) \times 30cm (12in) and up to 15cm (6in) thick can be irradiated. The fast neutron flux is designed to be nearly uniform over the 30cm (12in) \times 30cm (12in) area facing the core, and the fast fluence variation through the sample thickness is minimized through a single 180° rotation of the sample canister at the midpoint of the irradiation period. The fluences are calculated based on 1MeV equivalences.

The neutron fluence rate is determined using the previously-measured neutron radiation field for the FNI, performed in accordance with ASTM standards (ASTM F1190), and correlated to the measured reactor power level. The neutron dose is timed to meet the fluence specified for the irradiation. Neutron dosimetry meeting ASTM standards (ASTM E265) is used to track and make sure that irradiations meet the required minimum. The facility retains source design with the Defense Logistics Agency (DLA) Laboratory Suitability Program for ASTM Test Method 1017.

4 Results

There were no functional failures at any irradiation level. All tested parameters remained within the data sheet specifications for all devices, with dosage up to 1×10^{13} n/cm². Noticeable shifts in input offset voltage were recorded for some units dosed to 5×10^{12} n/cm² and to 1×10^{13} n/cm². All other tested parameters were observed to be within the test limits of the ATE program for the device, and as a result, within the data sheet specifications. While the gain-bandwidth product appeared to shift for some units, this particular test serves as a functional screen for gross outliers rather than a precise parametric measurement, and thus these results are not of significant concern.

4.1 Input Offset Voltage Parametric Shift

Input offset voltage (V_{OS}) for the LMP7704-SP is specified as $\pm 60\mu V$ typical and $\pm 260\mu V$ maximum at $T_A = 25^\circ C$. The input offset voltage was measured at multiple supply voltages, with test limits of $\pm 185\mu V$ for guardbanding purposes.

Three of the twelve devices exposed to neutron irradiation were found to have a measured input offset voltage outside of the guardbanded test limits, on one or more of the four device amplifier channels, for at least one of the V_{OS} tests performed on the ATE. All measured values remained within the data sheet specified limits, for all devices. The values reported below represent the magnitude and directionality of the shift from the pre-exposure measurement, expressed in μV , for each device and condition. Full pre- and post-exposure data for all ATE tests performed are included in the report appendix. As a crude index, the data for each dose level are used to calculate the Bessel-corrected sample standard deviation (s) of the offset shift; s is found to increase as the cumulative dose increases.

Table 4-1. Offset Voltage Parametric Shifts (μV), Dosing to 1×10^{12} n/cm²


| Unit | Supply | Channel A | Channel B | Channel C | Channel D | s |
|------|-------------|-----------|-----------|-----------|-----------|--------|
| 1 | $V_S = 5V$ | +88.432 | +24.036 | +50.195 | -4.177 | 35.044 |
| | $V_S = 10V$ | +79.624 | +18.513 | +38.832 | -5.127 | |
| 2 | $V_S = 5V$ | +27.634 | +39.601 | -41.485 | +60.676 | 35.044 |
| | $V_S = 10V$ | +22.145 | +34.311 | -35.087 | +57.200 | |
| 3 | $V_S = 5V$ | -61.277 | -14.743 | +16.797 | +3.580 | 35.044 |
| | $V_S = 10V$ | -52.567 | -14.465 | +11.481 | +2.171 | |
| 4 | $V_S = 5V$ | -7.876 | -12.891 | +8.308 | -8.516 | 35.044 |
| | $V_S = 10V$ | -6.592 | -9.093 | +6.550 | -8.083 | |

Table 4-2. Offset Voltage Parametric Shifts, Dosing to 5×10^{12} n/cm²

| Unit | Supply | Channel A | Channel B | Channel C | Channel D | s |
|------|-------------|-----------|-----------|-----------|-----------|--------|
| 5 | $V_S = 5V$ | -25.547 | -118.428 | -38.656 | +3.755 | 66.673 |
| | $V_S = 10V$ | -26.434 | -105.461 | -36.588 | +4.632 | |
| 6 | $V_S = 5V$ | -19.562 | -4.832 | +13.177 | -7.609 | 66.673 |
| | $V_S = 10V$ | -18.817 | -0.652 | +13.181 | -4.783 | |
| 7 | $V_S = 5V$ | -36.408 | +38.063 | -32.699 | +113.456 | 66.673 |
| | $V_S = 10V$ | -29.418 | +25.783 | -26.348 | +107.052 | |
| 8 | $V_S = 5V$ | -26.330 | -72.764 | -8.161 | +185.890 | 66.673 |
| | $V_S = 10V$ | -25.182 | -69.251 | -4.635 | +175.764 | |

Table 4-3. Offset Voltage Parametric Shifts, Dosing to $1 \times 10^{13} \text{ n/cm}^2$

| Unit | Supply | Channel A | Channel B | Channel C | Channel D | s |
|------|----------------------|-----------|-----------|-----------|-----------|--------|
| 9 | V _S = 5V | +172.272 | -124.878 | -94.899 | +40.835 | 84.223 |
| | V _S = 10V | +160.339 | -114.584 | -87.128 | +31.696 | |
| 10 | V _S = 5V | +64.434 | +102.370 | -31.398 | +53.751 | 84.223 |
| | V _S = 10V | +70.216 | +94.933 | -30.141 | +63.028 | |
| 11 | V _S = 5V | -75.925 | -142.616 | -12.038 | -83.020 | 84.223 |
| | V _S = 10V | -71.388 | -137.099 | -13.083 | -72.343 | |
| 12 | V _S = 5V | -64.779 | +29.720 | +70.216 | -7.914 | 84.223 |
| | V _S = 10V | -57.925 | +22.536 | +61.959 | -13.460 | |


Figure 4-1. Sample Input Offset Voltage NDD Graph

5 Summary of Results

Some devices experienced parametric drift to levels in excess of the guardbanded test limits for input offset voltage. However, all measurements remained within the data sheet specifications. The data suggest that circuit designers seeking to use the LMP7704-SP must consider the possible effects of parametric drift of the V_{OS} specifications when assessing circuits for fault-planning purposes.

A Test Results


This appendix contains the detailed test results.

NDD Report
LMP7704-SP


NDD Report

LMP7704-SP

| 101.0_Iq_init_Vcc_2p7V | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | mA | mA | |
| Max Limit | 3.33 | 3.33 | Min Limit | 1.1 | 1.1 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 2.662 | 2.667 | 0.005 | 0.18% | 0.22% |
| 1 | 1 | 2.683 | 2.686 | 0.002 | 0.09% | 0.10% |
| 1 | 2 | 2.668 | 2.673 | 0.005 | 0.19% | 0.23% |
| 1 | 3 | 2.623 | 2.625 | 0.001 | 0.06% | 0.07% |
| 1 | 4 | 2.623 | 2.628 | 0.005 | 0.18% | 0.22% |
| 5 | 5 | 2.678 | 2.659 | -0.018 | -0.68% | 0.82% |
| 5 | 6 | 2.658 | 2.651 | -0.007 | -0.28% | 0.34% |
| 5 | 7 | 2.626 | 2.608 | -0.018 | -0.70% | 0.82% |
| 5 | 8 | 2.641 | 2.616 | -0.024 | -0.92% | 1.09% |
| 10 | 9 | 2.667 | 2.616 | -0.050 | -1.89% | 2.26% |
| 10 | 10 | 2.621 | 2.581 | -0.040 | -1.54% | 1.81% |
| 10 | 11 | 2.633 | 2.597 | -0.036 | -1.36% | 1.61% |
| 10 | 12 | 2.613 | 2.572 | -0.041 | -1.58% | 1.85% |
| Max | | 2.683 | 2.686 | 0.005 | 0.19% | 2.26% |
| Average | | 2.646 | 2.629 | -0.017 | -0.63% | 0.88% |
| Min | | 2.613 | 2.572 | -0.050 | -1.89% | 0.07% |
| Std Dev | | 0.024 | 0.036 | 0.020 | 0.77% | 0.77% |




| 101.0_Iq_init_Vcc_2p7V | | | | |
|-----------------------------------|-----------|-----------|--------|-------|
| Test Site | TI Dallas | Tester | ETS364 | |
| Test Number | EB4632 | Unit | mA | |
| Max Limit | 3.33 | Min Limit | 1.1 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 1.100 | 1.100 | 1.100 | 1.100 |
| Min | 2.667 | 2.625 | 2.608 | 2.572 |
| Average | 2.667 | 2.653 | 2.634 | 2.592 |
| Max | 2.667 | 2.686 | 2.659 | 2.617 |
| UL | 3.330 | 3.330 | 3.330 | 3.330 |




NDD Report

LMP7704-SP

| 101.1_Iq_init_Vee_2p7V | | | | | | |
|------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Delta | Delta % |
| Tester | ETS364 | ETS364 | Max Limit | -1.1 | | % of Limit Range |
| Test Number | EB4632 | EB4632 | Min Limit | -3.33 | | |
| | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 1*10^12 n/cm^2 | 0 | -2.664 | -2.668 | -0.004 | 0.17% | 0.20% |
| 1 | 1 | -2.684 | -2.686 | -0.002 | 0.06% | 0.08% |
| 1 | 2 | -2.669 | -2.674 | -0.004 | 0.17% | 0.20% |
| 1 | 3 | -2.624 | -2.625 | -0.001 | 0.03% | 0.04% |
| 1 | 4 | -2.624 | -2.628 | -0.004 | 0.16% | 0.19% |
| 5 | 5 | -2.678 | -2.660 | 0.019 | -0.71% | 0.85% |
| 5 | 6 | -2.659 | -2.651 | 0.008 | -0.31% | 0.37% |
| 5 | 7 | -2.627 | -2.608 | 0.019 | -0.72% | 0.85% |
| 5 | 8 | -2.642 | -2.617 | 0.025 | -0.93% | 1.10% |
| 10 | 9 | -2.668 | -2.617 | 0.051 | -1.91% | 2.28% |
| 10 | 10 | -2.622 | -2.581 | 0.041 | -1.57% | 1.84% |
| 10 | 11 | -2.634 | -2.598 | 0.036 | -1.38% | 1.63% |
| 10 | 12 | -2.614 | -2.572 | 0.042 | -1.61% | 1.89% |
| Max | | -2.614 | -2.572 | 0.051 | 0.17% | 2.28% |
| Average | | -2.647 | -2.630 | 0.017 | -0.66% | 0.89% |
| Min | | -2.684 | -2.686 | -0.004 | -1.91% | 0.04% |
| Std Dev | | 0.024 | 0.036 | 0.020 | 0.77% | 0.79% |




| 101.1_Iq_init_Vee_2p7V | | | | | | |
|------------------------|----------------|-----------|-----------|--------|--------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Delta | Delta % |
| Tester | ETS364 | ETS364 | Max Limit | -1.1 | | % of Limit Range |
| Test Number | EB4632 | EB4632 | Min Limit | -3.33 | | |
| | 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | |
| LL | | -3.330 | -3.330 | -3.330 | -3.330 | |
| Min | | -2.668 | -2.686 | -2.660 | -2.617 | |
| Average | | -2.668 | -2.653 | -2.634 | -2.592 | |
| Max | | -2.668 | -2.625 | -2.608 | -2.572 | |
| UL | | -1.100 | -1.100 | -1.100 | -1.100 | |




NDD Report

LMP7704-SP

| 101.2_Iq_init_Vcc_5V | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | 3.33 |
| Tester | ETS364 | ETS364 | Min Limit | mA | Max Limit | 1.1 |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 2.886 | 2.892 | 0.006 | 0.20% | 0.26% |
| 1 | 1 | 2.909 | 2.914 | 0.004 | 0.15% | 0.20% |
| 1 | 2 | 2.890 | 2.897 | 0.007 | 0.24% | 0.31% |
| 1 | 3 | 2.843 | 2.845 | 0.002 | 0.08% | 0.10% |
| 1 | 4 | 2.842 | 2.849 | 0.006 | 0.23% | 0.29% |
| 5 | 5 | 2.903 | 2.886 | -0.017 | -0.59% | 0.77% |
| 5 | 6 | 2.881 | 2.882 | 0.001 | 0.03% | 0.04% |
| 5 | 7 | 2.845 | 2.829 | -0.016 | -0.56% | 0.71% |
| 5 | 8 | 2.860 | 2.839 | -0.021 | -0.75% | 0.96% |
| 10 | 9 | 2.891 | 2.844 | -0.047 | -1.63% | 2.12% |
| 10 | 10 | 2.840 | 2.801 | -0.039 | -1.36% | 1.73% |
| 10 | 11 | 2.854 | 2.821 | -0.033 | -1.17% | 1.50% |
| 10 | 12 | 2.834 | 2.795 | -0.039 | -1.38% | 1.75% |
| Max | | 2.909 | 2.914 | 0.007 | 0.24% | 2.12% |
| Average | | 2.868 | 2.853 | -0.014 | -0.50% | 0.83% |
| Min | | 2.834 | 2.795 | -0.047 | -1.63% | 0.04% |
| Std Dev | | 0.027 | 0.038 | 0.020 | 0.70% | 0.72% |




| 101.2_Iq_init_Vcc_5V | | | | | | |
|-----------------------------------|-----------|-----------|-----------|-------|-----------|------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | 3.33 |
| Tester | ETS364 | ETS364 | Min Limit | mA | Max Limit | 1.1 |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 1.100 | 1.100 | 1.100 | 1.100 | | |
| Min | 2.892 | 2.845 | 2.829 | 2.795 | | |
| Average | 2.892 | 2.876 | 2.859 | 2.815 | | |
| Max | 2.892 | 2.914 | 2.886 | 2.844 | | |
| UL | 3.330 | 3.330 | 3.330 | 3.330 | | |




NDD Report

LMP7704-SP

| 101.3_Iq_init_Vee_5V | | | | | | |
|----------------------|-----------|---|------------------|--------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | -1.1 |
| Tester | ETS364 | ETS364 | Min Limit | -3.33 | Delta | -0.005 |
| Test Number | EB4632 | EB4632 <th>% of Limit Range</th> <td>0.23%</td> <th>Delta %</th> <td>0.18%</td> | % of Limit Range | 0.23% | Delta % | 0.18% |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -2.887 | -2.892 | -0.005 | 0.18% | 0.23% |
| 1 | 1 | -2.911 | -2.914 | -0.004 | 0.13% | 0.17% |
| 1 | 2 | -2.891 | -2.898 | -0.006 | 0.22% | 0.29% |
| 1 | 3 | -2.844 | -2.846 | -0.002 | 0.06% | 0.08% |
| 1 | 4 | -2.843 | -2.849 | -0.006 | 0.20% | 0.26% |
| 5 | 5 | -2.904 | -2.886 | 0.018 | -0.61% | 0.80% |
| 5 | 6 | -2.882 | -2.882 | 0.000 | 0.01% | 0.01% |
| 5 | 7 | -2.846 | -2.830 | 0.017 | -0.58% | 0.74% |
| 5 | 8 | -2.861 | -2.839 | 0.022 | -0.77% | 0.99% |
| 10 | 9 | -2.892 | -2.844 | 0.048 | -1.66% | 2.16% |
| 10 | 10 | -2.841 | -2.802 | 0.039 | -1.38% | 1.76% |
| 10 | 11 | -2.855 | -2.821 | 0.034 | -1.19% | 1.52% |
| 10 | 12 | -2.835 | -2.795 | 0.040 | -1.40% | 1.78% |
| Max | | -2.835 | -2.795 | 0.048 | 0.22% | 2.16% |
| Average | | -2.869 | -2.854 | 0.015 | -0.52% | 0.83% |
| Min | | -2.911 | -2.914 | -0.006 | -1.66% | 0.01% |
| Std Dev | | 0.027 | 0.038 | 0.020 | 0.70% | 0.75% |




| 101.3_Iq_init_Vee_5V | | | | | | |
|----------------------|-----------|-----------|------------------|--------|-----------|--------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | -1.1 |
| Tester | ETS364 | ETS364 | Min Limit | -3.33 | Delta | -0.005 |
| Test Number | EB4632 | EB4632 | % of Limit Range | 0.23% | Delta % | 0.18% |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -3.330 | -3.330 | -3.330 | -3.330 | | |
| Min | -2.892 | -2.914 | -2.886 | -2.844 | | |
| Average | -2.892 | -2.877 | -2.859 | -2.815 | | |
| Max | -2.892 | -2.846 | -2.830 | -2.795 | | |
| UL | -1.100 | -1.100 | -1.100 | -1.100 | | |




NDD Report

LMP7704-SP

| 101.4_Iq_init_Vcc_10V | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | 3.78 |
| Tester | ETS364 | ETS364 | Min Limit | mA | Max Limit | 1.1 |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 3.199 | 3.205 | 0.007 | 0.21% | 0.25% |
| 1 | 1 | 3.216 | 3.223 | 0.007 | 0.21% | 0.26% |
| 1 | 2 | 3.195 | 3.204 | 0.009 | 0.28% | 0.34% |
| 1 | 3 | 3.152 | 3.156 | 0.004 | 0.14% | 0.16% |
| 1 | 4 | 3.150 | 3.158 | 0.008 | 0.26% | 0.31% |
| 5 | 5 | 3.215 | 3.201 | -0.014 | -0.44% | 0.53% |
| 5 | 6 | 3.190 | 3.202 | 0.012 | 0.37% | 0.44% |
| 5 | 7 | 3.154 | 3.143 | -0.011 | -0.36% | 0.43% |
| 5 | 8 | 3.168 | 3.150 | -0.019 | -0.58% | 0.69% |
| 10 | 9 | 3.203 | 3.163 | -0.040 | -1.25% | 1.49% |
| 10 | 10 | 3.149 | 3.115 | -0.034 | -1.08% | 1.27% |
| 10 | 11 | 3.166 | 3.137 | -0.029 | -0.91% | 1.08% |
| 10 | 12 | 3.148 | 3.115 | -0.033 | -1.06% | 1.25% |
| Max | | 3.216 | 3.223 | 0.012 | 0.37% | 1.49% |
| Average | | 3.177 | 3.167 | -0.010 | -0.32% | 0.65% |
| Min | | 3.148 | 3.115 | -0.040 | -1.25% | 0.16% |
| Std Dev | | 0.026 | 0.036 | 0.019 | 0.60% | 0.46% |




| 101.4_Iq_init_Vcc_10V | | | | | | |
|-----------------------------------|-----------|-----------|-----------|-------|-----------|------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | 3.78 |
| Tester | ETS364 | ETS364 | Min Limit | mA | Max Limit | 1.1 |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 1.100 | 1.100 | 1.100 | 1.100 | | |
| Min | 3.205 | 3.156 | 3.143 | 3.115 | | |
| Average | 3.205 | 3.185 | 3.174 | 3.132 | | |
| Max | 3.205 | 3.223 | 3.202 | 3.163 | | |
| UL | 3.780 | 3.780 | 3.780 | 3.780 | | |




NDD Report

LMP7704-SP

| 101.5_Iq_init_Vee_10V | | | | | | |
|-----------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | -1.1 | -1.1 | | | | |
| Min Limit | -3.78 | -3.78 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -3.200 | -3.206 | -0.006 | 0.19% | 0.23% |
| 1 | 1 | -3.217 | -3.223 | -0.006 | 0.19% | 0.23% |
| 1 | 2 | -3.196 | -3.205 | -0.008 | 0.26% | 0.31% |
| 1 | 3 | -3.153 | -3.157 | -0.004 | 0.11% | 0.13% |
| 1 | 4 | -3.151 | -3.159 | -0.008 | 0.24% | 0.28% |
| 5 | 5 | -3.216 | -3.201 | 0.015 | -0.46% | 0.55% |
| 5 | 6 | -3.191 | -3.202 | -0.011 | 0.35% | 0.42% |
| 5 | 7 | -3.155 | -3.143 | 0.012 | -0.38% | 0.45% |
| 5 | 8 | -3.170 | -3.150 | 0.019 | -0.60% | 0.71% |
| 10 | 9 | -3.204 | -3.164 | 0.040 | -1.25% | 1.50% |
| 10 | 10 | -3.150 | -3.115 | 0.035 | -1.10% | 1.30% |
| 10 | 11 | -3.167 | -3.138 | 0.029 | -0.93% | 1.09% |
| 10 | 12 | -3.149 | -3.115 | 0.034 | -1.09% | 1.28% |
| Max | | -3.149 | -3.115 | 0.040 | 0.35% | 1.50% |
| Average | | -3.178 | -3.168 | 0.011 | -0.34% | 0.65% |
| Min | | -3.217 | -3.223 | -0.011 | -1.25% | 0.13% |
| Std Dev | | 0.026 | 0.036 | 0.019 | 0.60% | 0.47% |




| 101.5_Iq_init_Vee_10V | | | | | | |
|-----------------------|-----------|--------|--------|--------|--|--|
| Test Site | TI Dallas | | | | | |
| Tester | ETS364 | | | | | |
| Test Number | EB4632 | | | | | |
| Max Limit | -1.1 | mA | | | | |
| Min Limit | -3.78 | mA | | | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -3.780 | -3.780 | -3.780 | -3.780 | | |
| Min | -3.206 | -3.223 | -3.202 | -3.164 | | |
| Average | -3.206 | -3.186 | -3.174 | -3.133 | | |
| Max | -3.206 | -3.157 | -3.143 | -3.115 | | |
| UL | -1.100 | -1.100 | -1.100 | -1.100 | | |




NDD Report

LMP7704-SP

| 101.6_Iq_init_Vcc_12V | | | | | | |
|-----------------------|-----------|-----------|-----------|--------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | 3.78 |
| Tester | ETS364 | ETS364 | Min Limit | mA | Max Limit | 1.1 |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 3.328 | 3.335 | 0.007 | 0.21% | 0.26% |
| 1 | 1 | 3.342 | 3.349 | 0.007 | 0.22% | 0.28% |
| 1 | 2 | 3.320 | 3.330 | 0.010 | 0.30% | 0.37% |
| 1 | 3 | 3.280 | 3.284 | 0.004 | 0.14% | 0.17% |
| 1 | 4 | 3.277 | 3.286 | 0.009 | 0.27% | 0.33% |
| 5 | 5 | 3.344 | 3.330 | -0.014 | -0.42% | 0.52% |
| 5 | 6 | 3.317 | 3.332 | 0.014 | 0.43% | 0.54% |
| 5 | 7 | 3.282 | 3.272 | -0.011 | -0.32% | 0.39% |
| 5 | 8 | 3.296 | 3.278 | -0.018 | -0.54% | 0.66% |
| 10 | 9 | 3.332 | 3.293 | -0.039 | -1.17% | 1.46% |
| 10 | 10 | 3.277 | 3.243 | -0.033 | -1.02% | 1.25% |
| 10 | 11 | 3.295 | 3.266 | -0.028 | -0.85% | 1.04% |
| 10 | 12 | 3.278 | 3.246 | -0.033 | -0.99% | 1.21% |
| Max | | 3.344 | 3.349 | 0.014 | 0.43% | 1.46% |
| Average | | 3.305 | 3.296 | -0.009 | -0.29% | 0.65% |
| Min | | 3.277 | 3.243 | -0.039 | -1.17% | 0.17% |
| Std Dev | | 0.026 | 0.036 | 0.019 | 0.58% | 0.44% |




| 101.6_Iq_init_Vcc_12V | | | | | | |
|-----------------------|-----------|-----------|-----------|-------|-----------|------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | 3.78 |
| Tester | ETS364 | ETS364 | Min Limit | mA | Max Limit | 1.1 |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | 1.100 | 1.100 | 1.100 | 1.100 | | |
| Min | 3.335 | 3.284 | 3.272 | 3.243 | | |
| Average | 3.335 | 3.313 | 3.303 | 3.262 | | |
| Max | 3.335 | 3.349 | 3.332 | 3.293 | | |
| UL | 3.780 | 3.780 | 3.780 | 3.780 | | |




NDD Report

LMP7704-SP

| 101.7_Iq_init_Vee_12V | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | mA | |
| Tester | ETS364 | ETS364 | Max Limit | -1.1 | -1.1 | |
| Test Number | EB4632 | EB4632 | Min Limit | -3.78 | -3.78 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -3.329 | -3.335 | -0.006 | 0.19% | 0.23% |
| 1 | 1 | -3.343 | -3.349 | -0.007 | 0.20% | 0.25% |
| 1 | 2 | -3.322 | -3.331 | -0.009 | 0.28% | 0.34% |
| 1 | 3 | -3.281 | -3.285 | -0.004 | 0.11% | 0.14% |
| 1 | 4 | -3.278 | -3.286 | -0.008 | 0.25% | 0.30% |
| 5 | 5 | -3.345 | -3.330 | 0.015 | -0.44% | 0.54% |
| 5 | 6 | -3.318 | -3.332 | -0.014 | 0.41% | 0.51% |
| 5 | 7 | -3.283 | -3.272 | 0.011 | -0.34% | 0.41% |
| 5 | 8 | -3.297 | -3.278 | 0.019 | -0.56% | 0.69% |
| 10 | 9 | -3.333 | -3.293 | 0.040 | -1.19% | 1.49% |
| 10 | 10 | -3.278 | -3.243 | 0.034 | -1.05% | 1.28% |
| 10 | 11 | -3.296 | -3.267 | 0.029 | -0.87% | 1.07% |
| 10 | 12 | -3.279 | -3.246 | 0.033 | -1.01% | 1.24% |
| Max | | -3.278 | -3.243 | 0.040 | 0.41% | 1.49% |
| Average | | -3.306 | -3.296 | 0.010 | -0.31% | 0.65% |
| Min | | -3.345 | -3.349 | -0.014 | -1.19% | 0.14% |
| Std Dev | | 0.026 | 0.036 | 0.019 | 0.58% | 0.46% |




| 101.7_Iq_init_Vee_12V | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|-------|--|
| Test Site | TI Dallas | TI Dallas | Unit | mA | mA | |
| Tester | ETS364 | ETS364 | Max Limit | -1.1 | -1.1 | |
| Test Number | EB4632 | EB4632 | Min Limit | -3.78 | -3.78 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -3.780 | -3.780 | -3.780 | -3.780 | | |
| Min | -3.335 | -3.350 | -3.332 | -3.293 | | |
| Average | -3.335 | -3.313 | -3.303 | -3.262 | | |
| Max | -3.335 | -3.285 | -3.272 | -3.244 | | |
| UL | -1.100 | -1.100 | -1.100 | -1.100 | | |




NDD Report

LMP7704-SP

| 101.8_Iq_init_Vcc_MinMax | | | | | | |
|-----------------------------------|-----------|-----------|----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | 1 | 1 | | | | |
| Min Limit | -1 | -1 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 0.665 | 0.667 | 0.002 | 0.29% | 0.10% |
| 1 | 1 | 0.658 | 0.663 | 0.005 | 0.76% | 0.25% |
| 1 | 2 | 0.652 | 0.657 | 0.005 | 0.72% | 0.24% |
| 1 | 3 | 0.657 | 0.660 | 0.003 | 0.47% | 0.15% |
| 1 | 4 | 0.654 | 0.658 | 0.004 | 0.61% | 0.20% |
| 5 | 5 | 0.666 | 0.670 | 0.004 | 0.60% | 0.20% |
| 5 | 6 | 0.659 | 0.681 | 0.022 | 3.34% | 1.10% |
| 5 | 7 | 0.656 | 0.664 | 0.008 | 1.22% | 0.40% |
| 5 | 8 | 0.655 | 0.661 | 0.006 | 0.98% | 0.32% |
| 10 | 9 | 0.665 | 0.676 | 0.011 | 1.70% | 0.57% |
| 10 | 10 | 0.655 | 0.662 | 0.007 | 1.05% | 0.35% |
| 10 | 11 | 0.662 | 0.669 | 0.008 | 1.16% | 0.39% |
| 10 | 12 | 0.665 | 0.674 | 0.009 | 1.31% | 0.44% |
| Max | | 0.666 | 0.681 | 0.022 | 3.34% | 1.10% |
| Average | | 0.659 | 0.666 | 0.007 | 1.09% | 0.36% |
| Min | | 0.652 | 0.657 | 0.002 | 0.29% | 0.10% |
| Std Dev | | 0.005 | 0.007 | 0.005 | 0.78% | 0.26% |




| 101.8_Iq_init_Vcc_MinMax | | | | |
|-----------------------------------|-----------|--------|--------|--------|
| Test Site | TI Dallas | | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 1 | mA | | |
| Min Limit | -1 | mA | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | -1.000 | -1.000 | -1.000 | -1.000 |
| Min | 0.667 | 0.657 | 0.661 | 0.662 |
| Average | 0.667 | 0.660 | 0.669 | 0.670 |
| Max | 0.667 | 0.663 | 0.681 | 0.676 |
| UL | 1.000 | 1.000 | 1.000 | 1.000 |




NDD Report

LMP7704-SP

| 101.9_Iq_init_Vee_MinMax | | | | | | |
|-----------------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | 1 | 1 | | | | |
| Min Limit | -1 | -1 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.665 | -0.667 | -0.002 | 0.27% | 0.09% |
| 1 | 1 | -0.658 | -0.663 | -0.005 | 0.76% | 0.25% |
| 1 | 2 | -0.652 | -0.657 | -0.005 | 0.74% | 0.24% |
| 1 | 3 | -0.657 | -0.660 | -0.003 | 0.44% | 0.15% |
| 1 | 4 | -0.654 | -0.658 | -0.004 | 0.58% | 0.19% |
| 5 | 5 | -0.666 | -0.671 | -0.004 | 0.65% | 0.21% |
| 5 | 6 | -0.659 | -0.681 | -0.022 | 3.34% | 1.10% |
| 5 | 7 | -0.656 | -0.664 | -0.008 | 1.19% | 0.39% |
| 5 | 8 | -0.655 | -0.661 | -0.006 | 0.95% | 0.31% |
| 10 | 9 | -0.665 | -0.676 | -0.011 | 1.67% | 0.55% |
| 10 | 10 | -0.655 | -0.662 | -0.007 | 1.02% | 0.33% |
| 10 | 11 | -0.662 | -0.669 | -0.008 | 1.15% | 0.38% |
| 10 | 12 | -0.665 | -0.674 | -0.009 | 1.34% | 0.44% |
| Max | | -0.652 | -0.657 | -0.002 | 3.34% | 1.10% |
| Average | | -0.659 | -0.666 | -0.007 | 1.08% | 0.36% |
| Min | | -0.666 | -0.681 | -0.022 | 0.27% | 0.09% |
| Std Dev | | 0.005 | 0.007 | 0.005 | 0.78% | 0.26% |




| 101.9_Iq_init_Vee_MinMax | | | | |
|-----------------------------------|-----------|--------|--------|--------|
| Test Site | TI Dallas | | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 1 | mA | | |
| Min Limit | -1 | mA | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | -1.000 | -1.000 | -1.000 | -1.000 |
| Min | -0.667 | -0.663 | -0.681 | -0.676 |
| Average | -0.667 | -0.660 | -0.669 | -0.670 |
| Max | -0.667 | -0.657 | -0.661 | -0.662 |
| UL | 1.000 | 1.000 | 1.000 | 1.000 |




NDD Report

LMP7704-SP

| 104.4_Vios_5V_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV | uV | |
| Max Limit | 185 | 185 | Min Limit | -185 | -185 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 65.171 | 67.872 | 2.700 | 4.14% | 0.73% |
| 1 | 1 | 41.948 | 130.380 | 88.432 | 210.82% | 23.90% |
| 1 | 2 | -101.046 | -73.412 | 27.634 | -27.35% | 7.47% |
| 1 | 3 | -66.712 | -127.990 | -61.277 | 91.85% | 16.56% |
| 1 | 4 | 16.871 | 8.995 | -7.876 | -46.69% | 2.13% |
| 5 | 5 | 44.286 | 18.739 | -25.547 | -57.69% | 6.90% |
| 5 | 6 | -39.474 | -59.036 | -19.562 | 49.56% | 5.29% |
| 5 | 7 | 19.497 | -16.911 | -36.408 | -186.74% | 9.84% |
| 5 | 8 | -47.578 | -73.908 | -26.330 | 55.34% | 7.12% |
| 10 | 9 | 18.473 | 190.745 | 172.272 | 932.56% | 46.56% |
| 10 | 10 | -56.852 | 7.583 | 64.434 | -113.34% | 17.41% |
| 10 | 11 | -66.326 | -142.251 | -75.925 | 114.47% | 20.52% |
| 10 | 12 | -34.186 | -98.965 | -64.779 | 189.49% | 17.51% |
| Max | | 65.171 | 190.745 | 172.272 | 932.56% | 46.56% |
| Average | | -15.841 | -12.935 | 2.905 | 93.57% | 14.00% |
| Min | | -101.046 | -142.251 | -75.925 | -186.74% | 0.73% |
| Std Dev | | 52.436 | 98.884 | 70.204 | 276.47% | 12.19% |




| 104.4_Vios_5V_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|----------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV | uV | |
| Max Limit | 185 | 185 | Min Limit | -185 | -185 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -185.000 | -185.000 | -185.000 | -185.000 | | |
| Min | 67.872 | -127.990 | -73.908 | -142.251 | | |
| Average | 67.872 | -15.507 | -32.779 | -10.722 | | |
| Max | 67.872 | 130.380 | 18.739 | 190.745 | | |
| UL | 185.000 | 185.000 | 185.000 | 185.000 | | |




NDD Report

LMP7704-SP

| 104.5_Vios_5V_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|----------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV | uV | |
| Max Limit | 185 | 185 | Min Limit | -185 | -185 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 3.955 | 5.109 | 1.155 | 29.20% | 0.31% |
| 1 | 1 | 15.302 | 39.338 | 24.036 | 157.08% | 6.50% |
| 1 | 2 | 67.951 | 107.553 | 39.601 | 58.28% | 10.70% |
| 1 | 3 | -66.117 | -80.860 | -14.743 | 22.30% | 3.98% |
| 1 | 4 | -49.663 | -62.554 | -12.891 | 25.96% | 3.48% |
| 5 | 5 | -37.896 | -156.324 | -118.428 | 312.51% | 32.01% |
| 5 | 6 | 3.636 | -1.206 | -4.842 | -133.17% | 1.31% |
| 5 | 7 | 21.009 | 59.072 | 38.063 | 181.17% | 10.29% |
| 5 | 8 | -34.182 | -106.945 | -72.764 | 212.87% | 19.67% |
| 10 | 9 | -87.370 | -212.249 | -124.878 | 142.93% | 33.75% |
| 10 | 10 | 6.433 | 108.803 | 102.370 | 1591.35% | 27.67% |
| 10 | 11 | -81.329 | -223.945 | -142.616 | 175.36% | 38.54% |
| 10 | 12 | -11.586 | 18.134 | 29.720 | -256.52% | 8.03% |
| Max | | 67.951 | 108.803 | 102.370 | 1591.35% | 38.54% |
| Average | | -19.220 | -38.929 | -19.709 | 193.79% | 15.10% |
| Min | | -87.370 | -223.945 | -142.616 | -256.52% | 0.31% |
| Std Dev | | 45.079 | 112.036 | 73.920 | 445.79% | 13.53% |




| 104.5_Vios_5V_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|----------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV | uV | |
| Max Limit | 185 | 185 | Min Limit | -185 | -185 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -185.000 | -185.000 | -185.000 | -185.000 | | |
| Min | 5.110 | -80.860 | -156.324 | -223.945 | | |
| Average | 5.110 | 0.869 | -51.351 | -77.314 | | |
| Max | 5.110 | 107.553 | 59.072 | 108.803 | | |
| UL | 185.000 | 185.000 | 185.000 | 185.000 | | |




NDD Report

LMP7704-SP

| 104.6_Vios_5V_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV | uV | |
| Max Limit | 185 | 185 | Min Limit | -185 | -185 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -2.537 | -3.097 | -0.560 | 22.07% | 0.15% |
| 1 | 1 | -42.049 | 8.146 | 50.195 | -119.37% | 13.57% |
| 1 | 2 | 73.832 | 32.347 | -41.485 | -56.19% | 11.21% |
| 1 | 3 | -38.375 | -21.579 | 16.797 | -43.77% | 4.54% |
| 1 | 4 | -57.902 | -49.594 | 8.308 | -14.35% | 2.25% |
| 5 | 5 | -44.256 | -82.912 | -38.656 | 87.35% | 10.45% |
| 5 | 6 | 65.433 | 78.609 | 13.177 | 20.14% | 3.56% |
| 5 | 7 | 57.180 | 24.481 | -32.699 | -57.19% | 8.84% |
| 5 | 8 | -5.404 | -13.565 | -8.161 | 151.04% | 2.21% |
| 10 | 9 | -13.704 | -108.603 | -94.899 | 692.48% | 25.65% |
| 10 | 10 | -59.956 | -91.354 | -31.398 | 52.37% | 8.49% |
| 10 | 11 | 14.679 | 2.641 | -12.038 | -82.01% | 3.25% |
| 10 | 12 | 8.270 | 78.486 | 70.216 | 849.04% | 18.98% |
| Max | | 73.832 | 78.609 | 70.216 | 849.04% | 25.65% |
| Average | | -3.445 | -11.230 | -7.785 | 115.51% | 8.70% |
| Min | | -59.956 | -108.603 | -94.899 | -119.37% | 0.15% |
| Std Dev | | 46.099 | 59.548 | 42.500 | 301.46% | 7.40% |




| 104.6_Vios_5V_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|----------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV | uV | |
| Max Limit | 185 | 185 | Min Limit | -185 | -185 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -185.000 | -185.000 | -185.000 | -185.000 | | |
| Min | -3.097 | -49.594 | -82.912 | -108.603 | | |
| Average | -3.097 | -7.670 | 1.653 | -29.708 | | |
| Max | -3.097 | 32.347 | 78.609 | 78.486 | | |
| UL | 185.000 | 185.000 | 185.000 | 185.000 | | |




NDD Report

LMP7704-SP

| 104.7_Vios_5V_D | | | | | | |
|-----------------|-----------|-----------|----------|---------|------------------|------------------|
| Test Site | TI Dallas | TI Dallas | Delta | Delta % | % of Limit Range | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | uV | uV | | | | |
| Max Limit | 185 | 185 | | | | |
| Min Limit | -185 | -185 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -91.736 | -94.299 | -2.563 | 2.79% | 0.69% |
| 1 | 1 | -72.569 | -76.747 | -4.177 | 5.76% | 1.13% |
| 1 | 2 | -103.660 | -42.984 | 60.676 | -58.53% | 16.40% |
| 1 | 3 | -45.624 | -42.043 | 3.580 | -7.85% | 0.97% |
| 1 | 4 | 38.279 | 29.763 | -8.516 | -22.25% | 2.30% |
| 5 | 5 | 10.229 | 13.984 | 3.755 | 36.71% | 1.01% |
| 5 | 6 | 35.435 | 27.826 | -7.609 | -21.47% | 2.06% |
| 5 | 7 | -70.658 | 42.798 | 113.456 | -160.57% | 30.66% |
| 5 | 8 | 18.775 | 204.665 | 185.890 | 990.11% | 50.24% |
| 10 | 9 | -15.821 | 25.014 | 40.835 | -258.10% | 11.04% |
| 10 | 10 | -65.643 | -11.892 | 53.751 | -81.88% | 14.53% |
| 10 | 11 | -62.194 | -145.214 | -83.020 | 133.49% | 22.44% |
| 10 | 12 | -8.783 | -16.697 | -7.914 | 90.11% | 2.14% |
| Max | | 38.279 | 204.665 | 185.890 | 990.11% | 50.24% |
| Average | | -33.382 | -6.602 | 26.780 | 49.87% | 11.97% |
| Min | | -103.660 | -145.214 | -83.020 | -258.10% | 0.69% |
| Std Dev | | 48.902 | 84.429 | 66.757 | 299.84% | 15.07% |




| 104.7_Vios_5V_D | | | | | |
|-----------------|-----------|----------|----------|----------|--|
| Test Site | TI Dallas | ETS364 | | | |
| Tester | ETS364 | | | | |
| Test Number | EB4632 | | | | |
| Max Limit | 185 | uV | | | |
| Min Limit | -185 | uV | | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | |
| LL | -185.000 | -185.000 | -185.000 | -185.000 | |
| Min | -94.299 | -76.747 | 13.985 | -145.214 | |
| Average | -94.299 | -33.003 | 72.319 | -37.198 | |
| Max | -94.299 | 29.763 | 204.665 | 25.014 | |
| UL | 185.000 | 185.000 | 185.000 | 185.000 | |




NDD Report

LMP7704-SP

| 104.8_Vios_10V_A | | | | | | |
|------------------|-----------|---|-----------|---------|------------------|----------|
| Test Site | TI Dallas | TI Dallas | Unit | uV | Max Limit | 185 |
| Tester | ETS364 | ETS364 | Min Limit | -185 | Delta | 2.264 |
| Test Number | EB4632 | EB4632 <th>Delta %</th> <td>3.07%</td> <th>% of Limit Range</th> <td>0.61%</td> | Delta % | 3.07% | % of Limit Range | 0.61% |
| Serial # | PRE NDD | POST NDD | | | | |
| 0 | 73.619 | 75.883 | Delta | 2.264 | Delta % | 3.07% |
| 1 | 45.238 | 124.862 | Delta | 79.624 | Delta % | 176.01% |
| 1 | -107.405 | -85.261 | Delta | 22.145 | Delta % | -20.62% |
| 1 | -53.531 | -106.098 | Delta | -52.567 | Delta % | 98.20% |
| 1 | 8.233 | 1.641 | Delta | -6.592 | Delta % | -80.07% |
| 5 | 47.759 | 21.325 | Delta | -26.434 | Delta % | -55.35% |
| 5 | -7.426 | -26.243 | Delta | -18.817 | Delta % | 253.40% |
| 5 | 14.655 | -14.763 | Delta | -29.418 | Delta % | -200.74% |
| 5 | -42.373 | -67.555 | Delta | -25.182 | Delta % | 59.43% |
| 10 | 25.568 | 185.907 | Delta | 160.339 | Delta % | 627.10% |
| 10 | -53.120 | 17.096 | Delta | 70.216 | Delta % | -132.18% |
| 10 | -75.785 | -147.172 | Delta | -71.388 | Delta % | 94.20% |
| 10 | -37.329 | -95.254 | Delta | -57.925 | Delta % | 155.17% |
| Max | 73.619 | 185.907 | Delta | 160.339 | Delta % | 627.10% |
| Average | -12.454 | -8.895 | Delta | 3.559 | Delta % | 75.20% |
| Min | -107.405 | -147.172 | Delta | -71.388 | Delta % | -200.74% |
| Std Dev | 53.912 | 95.900 | Delta | 65.269 | Delta % | 209.91% |
| | | | | | | 11.42% |




| 104.8_Vios_10V_A | | | | | | |
|------------------|-----------|-----------|-----------|----------|------------------|----------|
| Test Site | TI Dallas | TI Dallas | Unit | uV | Max Limit | 185 |
| Tester | ETS364 | ETS364 | Min Limit | -185 | Delta | 2.264 |
| Test Number | EB4632 | EB4632 | Delta % | 3.07% | % of Limit Range | 0.61% |
| Serial # | PRE NDD | POST NDD | Delta | 2.264 | Delta % | 3.07% |
| LL | -185.000 | -185.000 | Delta | -185.000 | Delta % | -185.000 |
| Min | 75.883 | -106.098 | Delta | -67.555 | Delta % | -147.172 |
| Average | 75.883 | -16.214 | Delta | -21.809 | Delta % | -9.856 |
| Max | 75.883 | 124.862 | Delta | 21.325 | Delta % | 185.907 |
| UL | 185.000 | 185.000 | Delta | 185.000 | Delta % | 185.000 |




NDD Report

LMP7704-SP

| 104.9_Vios_10V_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|----------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV | uV | |
| Max Limit | 185 | 185 | Min Limit | -185 | -185 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 2.846 | 3.783 | 0.937 | 32.92% | 0.25% |
| 1 | 1 | 22.402 | 40.915 | 18.513 | 82.64% | 5.00% |
| 1 | 2 | 71.076 | 105.386 | 34.311 | 48.27% | 9.27% |
| 1 | 3 | -53.604 | -68.069 | -14.465 | 26.99% | 3.91% |
| 1 | 4 | -29.634 | -38.727 | -9.093 | 30.68% | 2.46% |
| 5 | 5 | -33.576 | -139.038 | -105.461 | 314.09% | 28.50% |
| 5 | 6 | -27.545 | -28.197 | -0.652 | 2.37% | 0.18% |
| 5 | 7 | 26.381 | 52.164 | 25.783 | 97.73% | 6.97% |
| 5 | 8 | -23.160 | -92.411 | -69.251 | 299.01% | 18.72% |
| 10 | 9 | -83.968 | -198.552 | -114.584 | 136.46% | 30.97% |
| 10 | 10 | -22.772 | 72.161 | 94.933 | -416.89% | 25.66% |
| 10 | 11 | -75.801 | -212.900 | -137.099 | 180.87% | 37.05% |
| 10 | 12 | -22.606 | -0.070 | 22.536 | -99.69% | 6.09% |
| Max | | 71.076 | 105.386 | 94.933 | 314.09% | 37.05% |
| Average | | -19.228 | -38.735 | -19.507 | 56.57% | 13.46% |
| Min | | -83.968 | -212.900 | -137.099 | -416.89% | 0.18% |
| Std Dev | | 42.280 | 100.319 | 67.635 | 183.26% | 12.96% |




| 104.9_Vios_10V_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|----------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV | uV | |
| Max Limit | 185 | 185 | Min Limit | -185 | -185 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -185.000 | -185.000 | -185.000 | -185.000 | | |
| Min | 3.783 | -68.069 | -139.038 | -212.900 | | |
| Average | 3.783 | 9.876 | -51.870 | -84.840 | | |
| Max | 3.783 | 105.386 | 52.164 | 72.161 | | |
| UL | 185.000 | 185.000 | 185.000 | 185.000 | | |




NDD Report

LMP7704-SP

| 104.10_Vios_10V_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV | uV | |
| Max Limit | 185 | 185 | Min Limit | -185 | -185 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 6.940 | 6.127 | -0.814 | -11.73% | 0.22% |
| 1 | 1 | -33.776 | 5.057 | 38.832 | -114.97% | 10.50% |
| 1 | 2 | 72.548 | 37.461 | -35.087 | -48.36% | 9.48% |
| 1 | 3 | -41.969 | -30.489 | 11.481 | -27.35% | 3.10% |
| 1 | 4 | -39.968 | -33.418 | 6.550 | -16.39% | 1.77% |
| 5 | 5 | -23.358 | -59.947 | -36.588 | 156.64% | 9.89% |
| 5 | 6 | 72.889 | 86.070 | 13.181 | 18.08% | 3.56% |
| 5 | 7 | 42.734 | 16.386 | -26.348 | -61.66% | 7.12% |
| 5 | 8 | 1.545 | -3.090 | -4.635 | -300.01% | 1.25% |
| 10 | 9 | 1.498 | -85.631 | -87.128 | -5817.88% | 23.55% |
| 10 | 10 | -64.770 | -94.911 | -30.141 | 46.54% | 8.15% |
| 10 | 11 | 22.047 | 8.964 | -13.083 | -59.34% | 3.54% |
| 10 | 12 | 3.270 | 65.229 | 61.959 | 1894.77% | 16.75% |
| Max | | 72.889 | 86.070 | 61.959 | 1894.77% | 23.55% |
| Average | | 1.510 | -6.322 | -7.832 | -333.97% | 7.61% |
| Min | | -64.770 | -94.911 | -87.128 | -5817.88% | 0.22% |
| Std Dev | | 42.975 | 53.967 | 37.478 | 1735.15% | 6.69% |




| 104.10_Vios_10V_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|----------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV | uV | |
| Max Limit | 185 | 185 | Min Limit | -185 | -185 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -185.000 | -185.000 | -185.000 | -185.000 | | |
| Min | 6.127 | -33.418 | -59.947 | -94.911 | | |
| Average | 6.127 | -5.347 | 9.855 | -26.587 | | |
| Max | 6.127 | 37.461 | 86.070 | 65.229 | | |
| UL | 185.000 | 185.000 | 185.000 | 185.000 | | |




NDD Report

LMP7704-SP

| 104.11_Vios_10V_D | | | | | | |
|-------------------|-----------|-----------|-----------|---------|------------------|---------|
| Test Site | TI Dallas | TI Dallas | Unit | uV | Max Limit | 185 |
| Tester | ETS364 | ETS364 | Min Limit | -185 | Delta | Delta % |
| Test Number | EB4632 | EB4632 | Delta | Delta % | % of Limit Range | |
| Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 13 | -74.450 | -76.002 | -1.553 | 2.09% | 0.42% |
| 1 | 1 | -62.511 | -67.638 | -5.127 | 8.20% | 1.39% |
| 1 | 2 | -92.161 | -34.961 | 57.200 | -62.07% | 15.46% |
| 1 | 3 | -37.346 | -35.175 | 2.171 | -5.81% | 0.59% |
| 1 | 4 | 40.932 | 32.849 | -8.083 | -19.75% | 2.18% |
| 5 | 5 | 7.837 | 12.469 | 4.632 | 59.10% | 1.25% |
| 5 | 6 | 50.461 | 45.678 | -4.783 | -9.48% | 1.29% |
| 5 | 7 | -55.651 | 51.401 | 107.052 | -192.36% | 28.93% |
| 5 | 8 | 51.699 | 227.463 | 175.764 | 339.98% | 47.50% |
| 10 | 9 | -16.837 | 14.859 | 31.696 | -188.25% | 8.57% |
| 10 | 10 | -48.311 | 14.717 | 63.028 | -130.46% | 17.03% |
| 10 | 11 | -70.262 | -142.605 | -72.343 | 102.96% | 19.55% |
| 10 | 12 | -17.832 | -31.292 | -13.460 | 75.48% | 3.64% |
| Max | | 51.699 | 227.463 | 175.764 | 339.98% | 47.50% |
| Average | | -24.956 | 0.905 | 25.861 | -1.57% | 11.37% |
| Min | | -92.161 | -142.605 | -72.343 | -192.36% | 0.42% |
| Std Dev | | 49.301 | 87.681 | 62.893 | 138.22% | 14.21% |




| 104.11_Vios_10V_D | | | | | | |
|-------------------|-----------|----------|-----------|----------|------------------|----------|
| Test Site | TI Dallas | ETS364 | Unit | uV | Max Limit | 185 |
| Tester | ETS364 | EB4632 | Min Limit | -185 | Delta | Delta % |
| Test Number | EB4632 | | Delta | Delta % | % of Limit Range | |
| LL | -185.000 | -185.000 | -185.000 | -185.000 | -185.000 | -185.000 |
| Min | -76.002 | -67.639 | 12.469 | 14.859 | 227.463 | 14.859 |
| Average | -76.002 | -26.231 | 84.253 | -36.080 | 227.463 | 14.859 |
| Max | -76.002 | 32.849 | 227.463 | 14.859 | 185.000 | 185.000 |
| UL | 185.000 | 185.000 | 185.000 | 185.000 | 185.000 | 185.000 |




NDD Report

LMP7704-SP

| 104.16_PSRR_A | | | | | | |
|----------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 45.1 | 45.1 | Min Limit | -45.1 | -45.1 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 11.557 | 11.548 | -0.009 | -0.07% | 0.01% |
| 1 | 1 | 4.640 | 1.341 | -3.298 | -71.09% | 3.66% |
| 1 | 2 | -6.340 | -6.682 | -0.342 | 5.39% | 0.38% |
| 1 | 3 | 2.402 | 6.085 | 3.683 | 153.31% | 4.08% |
| 1 | 4 | 8.576 | 8.563 | -0.013 | -0.15% | 0.01% |
| 5 | 5 | 5.688 | 3.462 | -2.226 | -39.13% | 2.47% |
| 5 | 6 | 3.284 | 1.810 | -1.474 | -44.89% | 1.63% |
| 5 | 7 | 2.616 | 5.148 | 2.531 | 96.76% | 2.81% |
| 5 | 8 | 5.743 | 3.596 | -2.147 | -37.39% | 2.38% |
| 10 | 9 | 7.796 | 5.128 | -2.668 | -34.23% | 2.96% |
| 10 | 10 | 0.621 | 6.065 | 5.444 | 876.26% | 6.04% |
| 10 | 11 | -5.889 | -11.118 | -5.230 | 88.81% | 5.80% |
| 10 | 12 | -1.214 | -1.263 | -0.049 | 4.06% | 0.05% |
| Max | | 11.557 | 11.548 | 5.444 | 876.26% | 6.04% |
| Average | | 3.037 | 2.591 | -0.446 | 76.74% | 2.48% |
| Min | | -6.340 | -11.118 | -5.230 | -71.09% | 0.01% |
| Std Dev | | 5.283 | 6.096 | 2.947 | 248.87% | 2.06% |




| 104.16_PSRR_A | | | | |
|----------------|-----------|---------|-----------|---------|
| Test Site | TI Dallas | ETS364 | Tester | ETS364 |
| Test Number | EB4632 | EB4632 | Unit | uV_V |
| Max Limit | 45.1 | 45.1 | Min Limit | -45.1 |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 |
| LL | -45.100 | -45.100 | -45.100 | -45.100 |
| Min | 11.548 | -6.682 | 1.810 | -11.118 |
| Average | 11.548 | 2.327 | 3.504 | -0.297 |
| Max | 11.548 | 8.563 | 5.148 | 6.066 |
| UL | 45.100 | 45.100 | 45.100 | 45.100 |




NDD Report

LMP7704-SP

| 104.17_PSRR_B | | | | | | |
|----------------|-----------|-----------|-----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 45.1 | 45.1 | Min Limit | -45.1 | -45.1 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 2.699 | 2.842 | 0.143 | 5.29% | 0.16% |
| 1 | 1 | 6.646 | 5.055 | -1.591 | -23.93% | 1.76% |
| 1 | 2 | 2.714 | 1.551 | -1.163 | -42.86% | 1.29% |
| 1 | 3 | -0.212 | 0.773 | 0.985 | -464.58% | 1.09% |
| 1 | 4 | 6.270 | 6.663 | 0.393 | 6.27% | 0.44% |
| 5 | 5 | 2.333 | 3.602 | 1.270 | 54.43% | 1.41% |
| 5 | 6 | -5.673 | -6.815 | -1.142 | 20.13% | 1.27% |
| 5 | 7 | 3.387 | 1.765 | -1.622 | -47.89% | 1.80% |
| 5 | 8 | 11.479 | 12.498 | 1.020 | 8.88% | 1.13% |
| 10 | 9 | 0.410 | -0.538 | -0.947 | -231.22% | 1.05% |
| 10 | 10 | -0.132 | -3.413 | -3.281 | 2489.68% | 3.64% |
| 10 | 11 | 6.701 | 6.657 | -0.044 | -0.65% | 0.05% |
| 10 | 12 | -1.863 | -4.281 | -2.418 | 129.80% | 2.68% |
| Max | | 11.479 | 12.498 | 1.270 | 2489.68% | 3.64% |
| Average | | 2.674 | 2.028 | -0.646 | 146.41% | 1.37% |
| Min | | -5.673 | -6.815 | -3.281 | -464.58% | 0.05% |
| Std Dev | | 4.422 | 5.171 | 1.405 | 719.62% | 0.98% |




| 104.17_PSRR_B | | | | |
|----------------|-----------|---------|---------|---------|
| Test Site | TI Dallas | ETS364 | EB4632 | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 45.1 | uV_V | | |
| Min Limit | -45.1 | uV_V | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 |
| LL | -45.100 | -45.100 | -45.100 | -45.100 |
| Min | 2.842 | 0.773 | -6.816 | -4.281 |
| Average | 2.842 | 3.510 | 2.763 | -0.394 |
| Max | 2.842 | 6.663 | 12.498 | 6.657 |
| UL | 45.100 | 45.100 | 45.100 | 45.100 |




NDD Report

LMP7704-SP

| 104.18_PSRR_C | | | | | | |
|----------------|-----------|-----------|-----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 45.1 | 45.1 | Min Limit | -45.1 | -45.1 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 7.189 | 7.203 | 0.014 | 0.19% | 0.02% |
| 1 | 1 | 4.359 | 1.560 | -2.800 | -64.22% | 3.10% |
| 1 | 2 | 3.397 | 4.589 | 1.193 | 35.11% | 1.32% |
| 1 | 3 | 0.671 | 0.352 | -0.319 | -47.56% | 0.35% |
| 1 | 4 | 5.183 | 3.263 | -1.921 | -37.05% | 2.13% |
| 5 | 5 | 1.558 | -0.038 | -1.595 | -102.41% | 1.77% |
| 5 | 6 | 12.903 | 12.557 | -0.347 | -2.69% | 0.38% |
| 5 | 7 | 0.539 | 2.567 | 2.028 | 376.18% | 2.25% |
| 5 | 8 | 5.404 | 5.276 | -0.128 | -2.36% | 0.14% |
| 10 | 9 | 3.273 | 4.753 | 1.480 | 45.22% | 1.64% |
| 10 | 10 | 0.932 | 3.776 | 2.844 | 305.02% | 3.15% |
| 10 | 11 | 3.358 | 2.187 | -1.171 | -34.87% | 1.30% |
| 10 | 12 | 1.135 | -2.130 | -3.266 | -287.58% | 3.62% |
| Max | | 12.903 | 12.557 | 2.844 | 376.18% | 3.62% |
| Average | | 3.839 | 3.532 | -0.307 | 14.08% | 1.63% |
| Min | | 0.539 | -2.130 | -3.266 | -287.58% | 0.02% |
| Std Dev | | 3.422 | 3.677 | 1.847 | 167.69% | 1.20% |




| 104.18_PSRR_C | | | | | | |
|----------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 45.1 | 45.1 | Min Limit | -45.1 | -45.1 | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -45.100 | -45.100 | -45.100 | -45.100 | | |
| Min | 7.203 | 0.352 | -0.038 | -2.130 | | |
| Average | 7.203 | 2.441 | 5.091 | 2.147 | | |
| Max | 7.203 | 4.590 | 12.557 | 4.753 | | |
| UL | 45.100 | 45.100 | 45.100 | 45.100 | | |




NDD Report

LMP7704-SP

| 104.19_PSRR_D | | | | | | |
|----------------|-----------|-----------|-----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 45.1 | 45.1 | Min Limit | -45.1 | -45.1 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 8.154 | 8.005 | -0.149 | -1.83% | 0.17% |
| 1 | 1 | -0.515 | -0.453 | 0.062 | -12.01% | 0.07% |
| 1 | 2 | 9.382 | 8.104 | -1.278 | -13.62% | 1.42% |
| 1 | 3 | 0.324 | 0.228 | -0.096 | -29.68% | 0.11% |
| 1 | 4 | 0.382 | -0.112 | -0.494 | -129.35% | 0.55% |
| 5 | 5 | -3.437 | -3.213 | 0.224 | -6.53% | 0.25% |
| 5 | 6 | 11.607 | 4.699 | -6.907 | -59.51% | 7.66% |
| 5 | 7 | 5.582 | 8.553 | 2.972 | 53.24% | 3.29% |
| 5 | 8 | 11.753 | 7.193 | -4.560 | -38.80% | 5.05% |
| 10 | 9 | 4.060 | 1.502 | -2.558 | -63.00% | 2.84% |
| 10 | 10 | 6.538 | 9.732 | 3.195 | 48.86% | 3.54% |
| 10 | 11 | 0.928 | 3.352 | 2.424 | 261.19% | 2.69% |
| 10 | 12 | -2.221 | -2.069 | 0.151 | -6.82% | 0.17% |
| Max | | 11.753 | 9.732 | 3.195 | 261.19% | 7.66% |
| Average | | 4.041 | 3.502 | -0.540 | 0.17% | 2.14% |
| Min | | -3.437 | -3.213 | -6.907 | -129.35% | 0.07% |
| Std Dev | | 5.192 | 4.476 | 2.860 | 91.51% | 2.34% |




| 104.19_PSRR_D | | | | | | |
|----------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 45.1 | 45.1 | Min Limit | -45.1 | -45.1 | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -45.100 | -45.100 | -45.100 | -45.100 | | |
| Min | 8.005 | -0.453 | -3.213 | -2.069 | | |
| Average | 8.005 | 1.942 | 4.308 | 3.129 | | |
| Max | 8.005 | 8.104 | 8.553 | 9.732 | | |
| UL | 45.100 | 45.100 | 45.100 | 45.100 | | |




NDD Report

LMP7704-SP

| 105.0_CMRR_5V_A | | | | | | |
|-----------------|-----------|-----------|-----------|---------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number |
| Unit | uV_V | uV_V | Max Limit | 158.5 | 158.5 | Min Limit |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -9.468 | -9.443 | 0.025 | -0.26% | 0.01% |
| 1 | 1 | 0.098 | -0.982 | -1.080 | -1103.37% | 0.34% |
| 1 | 2 | 18.474 | 16.615 | -1.858 | -10.06% | 0.59% |
| 1 | 3 | 5.336 | -4.132 | -9.468 | -177.42% | 2.99% |
| 1 | 4 | -1.936 | 0.074 | 2.010 | -103.82% | 0.63% |
| 5 | 5 | -9.040 | -15.681 | -6.641 | 73.46% | 2.09% |
| 5 | 6 | 10.887 | 11.050 | 0.163 | 1.50% | 0.05% |
| 5 | 7 | 0.562 | 9.257 | 8.695 | 1546.53% | 2.74% |
| 5 | 8 | 3.080 | 11.672 | 8.592 | 278.93% | 2.71% |
| 10 | 9 | -15.814 | -27.429 | -11.615 | 73.45% | 3.66% |
| 10 | 10 | 17.523 | 6.125 | -11.398 | -65.05% | 3.60% |
| 10 | 11 | 20.740 | 28.450 | 7.710 | 37.17% | 2.43% |
| 10 | 12 | 14.023 | 17.615 | 3.593 | 25.62% | 1.13% |
| Max | | 20.740 | 28.450 | 8.695 | 1546.53% | 3.66% |
| Average | | 4.190 | 3.322 | -0.867 | 44.36% | 1.77% |
| Min | | -15.814 | -27.429 | -11.615 | -1103.37% | 0.01% |
| Std Dev | | 11.651 | 15.109 | 7.184 | 556.84% | 1.35% |




| 105.0_CMRR_5V_A | | | | | | |
|-----------------|-----------|-----------|-----------|----------|--------|-------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number |
| Unit | uV_V | uV_V | Max Limit | 158.5 | 158.5 | Min Limit |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -158.500 | -158.500 | -158.500 | -158.500 | | |
| Min | -9.443 | -4.132 | -15.681 | -27.429 | | |
| Average | -9.443 | 2.894 | 4.075 | 6.190 | | |
| Max | -9.443 | 16.615 | 11.672 | 28.450 | | |
| UL | 158.500 | 158.500 | 158.500 | 158.500 | | |




NDD Report

LMP7704-SP

| 105.1_CMRR_5V_B | | | | | | |
|-----------------|-----------|-----------|-----------|---------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number |
| Unit | uV_V | uV_V | Max Limit | 158.5 | 158.5 | Min Limit |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 6.444 | 6.708 | 0.264 | 4.09% | 0.08% |
| 1 | 1 | 9.485 | 17.788 | 8.303 | 87.53% | 2.62% |
| 1 | 2 | -2.901 | -0.703 | 2.198 | -75.77% | 0.69% |
| 1 | 3 | 17.778 | 13.558 | -4.219 | -23.73% | 1.33% |
| 1 | 4 | 4.717 | 6.028 | 1.310 | 27.78% | 0.41% |
| 5 | 5 | 7.452 | 2.889 | -4.563 | -61.23% | 1.44% |
| 5 | 6 | 9.335 | 11.512 | 2.178 | 23.33% | 0.69% |
| 5 | 7 | 9.248 | -1.433 | -10.681 | -115.50% | 3.37% |
| 5 | 8 | -10.158 | -7.405 | 2.753 | -27.10% | 0.87% |
| 10 | 9 | 7.408 | 15.496 | 8.087 | 109.16% | 2.55% |
| 10 | 10 | -2.687 | -6.581 | -3.894 | 144.94% | 1.23% |
| 10 | 11 | 1.306 | 14.267 | 12.961 | 992.75% | 4.09% |
| 10 | 12 | 2.971 | -3.747 | -6.717 | -226.12% | 2.12% |
| Max | | 17.778 | 17.788 | 12.961 | 992.75% | 4.09% |
| Average | | 4.646 | 5.260 | 0.614 | 66.16% | 1.65% |
| Min | | -10.158 | -7.405 | -10.681 | -226.12% | 0.08% |
| Std Dev | | 7.081 | 8.762 | 6.642 | 295.22% | 1.21% |




| 105.1_CMRR_5V_B | | | | | | |
|-----------------|-----------|-----------|-----------|----------|--------|-------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number |
| Unit | uV_V | uV_V | Max Limit | 158.5 | uV_V | Min Limit |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -158.500 | -158.500 | -158.500 | -158.500 | | |
| Min | -6.708 | -0.703 | -7.405 | -6.581 | | |
| Average | 6.708 | 9.168 | 1.391 | 4.859 | | |
| Max | 6.708 | 17.788 | 11.512 | 15.496 | | |
| UL | 158.500 | 158.500 | 158.500 | 158.500 | | |




NDD Report

LMP7704-SP

| 105.2_CMRR_5V_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 158.5 | 158.5 | Min Limit | -158.5 | -158.5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -8.746 | -8.431 | 0.315 | -3.60% | 0.10% |
| 1 | 1 | -2.889 | 0.691 | 3.579 | -123.91% | 1.13% |
| 1 | 2 | -6.500 | -7.500 | -1.001 | 15.39% | 0.32% |
| 1 | 3 | 12.134 | 2.749 | -9.385 | -77.34% | 2.96% |
| 1 | 4 | 2.039 | 5.493 | 3.454 | 169.42% | 1.09% |
| 5 | 5 | 6.963 | 11.033 | 4.069 | 58.44% | 1.28% |
| 5 | 6 | -5.998 | 12.221 | 18.219 | -303.74% | 5.75% |
| 5 | 7 | -5.513 | -8.962 | -3.449 | 62.57% | 1.09% |
| 5 | 8 | -8.208 | -17.306 | -9.098 | 110.85% | 2.87% |
| 10 | 9 | -1.421 | -8.779 | -7.358 | 517.88% | 2.32% |
| 10 | 10 | 7.416 | -14.121 | -21.537 | -290.41% | 6.79% |
| 10 | 11 | 2.560 | -6.640 | -9.200 | -359.43% | 2.90% |
| 10 | 12 | 12.146 | 17.362 | 5.216 | 42.94% | 1.65% |
| Max | | 12.146 | 17.362 | 18.219 | 517.88% | 6.79% |
| Average | | 0.307 | -1.707 | -2.014 | -13.92% | 2.33% |
| Min | | -8.746 | -17.306 | -21.537 | -359.43% | 0.10% |
| Std Dev | | 7.475 | 10.803 | 9.722 | 231.52% | 1.99% |




| 105.2_CMRR_5V_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|----------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 158.5 | 158.5 | Min Limit | -158.5 | -158.5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -158.500 | -158.500 | -158.500 | -158.500 | | |
| Min | -8.431 | -7.500 | -17.306 | -14.121 | | |
| Average | -8.431 | 0.358 | -0.754 | -3.045 | | |
| Max | -8.431 | 5.493 | 12.221 | 17.362 | | |
| UL | 158.500 | 158.500 | 158.500 | 158.500 | | |




NDD Report

LMP7704-SP

| 105.3_CMRR_5V_D | | | | | | |
|-----------------------------------|-----------|-----------|----------|---------|------------------|------------------|
| Test Site | TI Dallas | TI Dallas | Delta | Delta % | % of Limit Range | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | uV_V | uV_V | | | | |
| Max Limit | 158.5 | 158.5 | | | | |
| Min Limit | -158.5 | -158.5 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 1.482 | 1.713 | 0.231 | 15.62% | 0.07% |
| 1 | 1 | 3.461 | 3.962 | 0.502 | 14.49% | 0.16% |
| 1 | 2 | 0.033 | 2.809 | 2.776 | 8438.60% | 0.88% |
| 1 | 3 | -2.579 | -1.367 | 1.211 | -46.98% | 0.38% |
| 1 | 4 | -4.181 | -2.236 | 1.945 | -46.51% | 0.61% |
| 5 | 5 | -5.951 | -8.593 | -2.642 | 44.40% | 0.83% |
| 5 | 6 | -14.374 | 10.266 | 24.639 | -171.42% | 7.77% |
| 5 | 7 | 0.211 | -18.523 | -18.734 | -8870.27% | 5.91% |
| 5 | 8 | -11.715 | -4.073 | 7.642 | -65.23% | 2.41% |
| 10 | 9 | -10.393 | -5.975 | 4.418 | -42.51% | 1.39% |
| 10 | 10 | -1.751 | -18.806 | -17.055 | 973.90% | 5.38% |
| 10 | 11 | 5.886 | 5.213 | -0.673 | -11.44% | 0.21% |
| 10 | 12 | 16.346 | 8.234 | -8.111 | -49.62% | 2.56% |
| Max | | 16.346 | 10.266 | 24.639 | 8438.60% | 7.77% |
| Average | | -1.810 | -2.106 | -0.296 | 14.08% | 2.20% |
| Min | | -14.374 | -18.806 | -18.734 | -8870.27% | 0.07% |
| Std Dev | | 8.103 | 9.124 | 10.848 | 3545.92% | 2.55% |




| 105.3_CMRR_5V_D | | | | | | |
|-----------------------------------|-----------|-----------|----------|----------|------------------|--|
| Test Site | TI Dallas | TI Dallas | Delta | Delta % | % of Limit Range | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Max Limit | 158.5 | uV_V | | | | |
| Min Limit | -158.5 | uV_V | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -158.500 | -158.500 | -158.500 | -158.500 | | |
| Min | -1.713 | -2.236 | -18.523 | -18.806 | | |
| Average | 1.713 | 0.792 | -5.231 | -2.834 | | |
| Max | 1.713 | 3.962 | 10.266 | 8.235 | | |
| UL | 158.500 | 158.500 | 158.500 | 158.500 | | |




NDD Report

LMP7704-SP

| 105.4_CMRR_10V_A | | | | | | |
|------------------|-----------|-----------|-----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number |
| Unit | uV_V | uV_V | Max Limit | 70.8 | 70.8 | Min Limit |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -4.631 | -4.804 | -0.173 | 3.72% | 0.12% |
| 1 | 1 | -0.291 | 0.634 | 0.925 | -317.58% | 0.65% |
| 1 | 2 | 9.223 | 8.167 | -1.057 | -11.46% | 0.75% |
| 1 | 3 | 0.766 | -3.627 | -4.393 | -573.31% | 3.10% |
| 1 | 4 | -2.311 | -1.857 | 0.454 | -19.64% | 0.32% |
| 5 | 5 | -5.271 | -6.274 | -1.003 | 19.04% | 0.71% |
| 5 | 6 | 2.617 | 3.158 | 0.540 | 20.64% | 0.38% |
| 5 | 7 | -0.331 | 1.157 | 1.488 | -449.46% | 1.05% |
| 5 | 8 | 0.630 | 5.321 | 4.691 | 745.14% | 3.31% |
| 10 | 9 | -10.073 | -12.642 | -2.570 | 25.51% | 1.81% |
| 10 | 10 | 7.078 | 1.798 | -5.279 | -74.59% | 3.73% |
| 10 | 11 | 9.472 | 16.321 | 6.849 | 72.31% | 4.84% |
| 10 | 12 | 5.291 | 5.168 | -0.123 | -2.32% | 0.09% |
| Max | | 9.472 | 16.321 | 6.849 | 745.14% | 4.84% |
| Average | | 0.936 | 0.963 | 0.027 | -43.23% | 1.61% |
| Min | | -10.073 | -12.642 | -5.279 | -573.31% | 0.09% |
| Std Dev | | 5.813 | 7.245 | 3.271 | 312.95% | 1.60% |




| 105.4_CMRR_10V_A | | | | |
|------------------|-----------|---------|------------|----------------|
| Test Site | TI Dallas | ETS364 | Tester | EB4632 |
| Test Number | 16.321 | 5.321 | Max Limit | uV_V |
| Max Limit | 70.8 | 70.8 | Min Limit | uV_V |
| Min Limit | -70.8 | -70.8 | Pass Range | 1*10^12 n/cm^2 |
| LL | -70.800 | -70.800 | -70.800 | 0 |
| Min | -4.804 | -3.627 | -6.274 | 1 |
| Average | -4.804 | 0.829 | 0.840 | 5 |
| Max | -4.804 | 8.167 | 5.321 | 10 |
| UL | 70.800 | 70.800 | 70.800 | 16.321 |




NDD Report

LMP7704-SP

| 105.5_CMRR_10V_B | | | | | | | |
|------------------|-----------|-----------|-----------|--------|----------|------------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | uV_V | uV_V | Max Limit | 70.8 | 70.8 | Min Limit | -70.8 |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 13 | 2.260 | 2.324 | 0.064 | 2.85% | 0.05% | |
| 1 | 1 | 2.598 | 5.579 | 2.981 | 114.74% | 2.11% | |
| 1 | 2 | -2.709 | -1.498 | 1.211 | -44.69% | 0.85% | |
| 1 | 3 | 8.856 | 6.947 | -1.908 | -21.55% | 1.35% | |
| 1 | 4 | 1.292 | 2.074 | 0.782 | 60.49% | 0.55% | |
| 5 | 5 | 3.285 | 2.640 | -0.645 | -19.64% | 0.46% | |
| 5 | 6 | 3.303 | 2.444 | -0.860 | -26.02% | 0.61% | |
| 5 | 7 | 4.094 | 0.231 | -3.862 | -94.35% | 2.73% | |
| 5 | 8 | -6.202 | -5.228 | 0.974 | -15.71% | 0.69% | |
| 10 | 9 | 2.850 | 7.319 | 4.469 | 156.82% | 3.16% | |
| 10 | 10 | -2.935 | -2.070 | 0.865 | -29.49% | 0.61% | |
| 10 | 11 | -1.675 | 3.123 | 4.799 | -286.45% | 3.39% | |
| 10 | 12 | 1.120 | 0.570 | -0.550 | -49.11% | 0.39% | |
| Max | | 8.856 | 7.319 | 4.799 | 156.82% | 3.39% | |
| Average | | 1.241 | 1.881 | 0.640 | -19.39% | 1.30% | |
| Min | | -6.202 | -5.228 | -3.862 | -286.45% | 0.05% | |
| Std Dev | | 3.840 | 3.578 | 2.421 | 105.89% | 1.14% | |




| 105.5_CMRR_10V_B | | | | |
|------------------|-----------|---------|-----------|---------|
| Test Site | TI Dallas | ETS364 | Tester | ETS364 |
| Test Number | EB4632 | EB4632 | Max Limit | 70.8 |
| Min Limit | -70.8 | uV_V | Max Limit | 70.8 |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 |
| LL | -70.800 | -70.800 | -70.800 | -70.800 |
| Min | 2.324 | -1.498 | -5.228 | -2.070 |
| Average | 2.324 | 3.275 | 0.022 | 2.236 |
| Max | 2.324 | 6.947 | 2.640 | 7.319 |
| UL | 70.800 | 70.800 | 70.800 | 70.800 |




NDD Report

LMP7704-SP

| 105.6_CMRR_10V_C | | | | | | | |
|------------------|-----------|-----------|-----------|--------|----------|------------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | uV_V | uV_V | Max Limit | 70.8 | 70.8 | Min Limit | -70.8 |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 13 | -5.021 | -5.003 | 0.018 | -0.35% | 0.01% | |
| 1 | 1 | -2.784 | -1.349 | 1.434 | -51.53% | 1.01% | |
| 1 | 2 | -4.765 | -4.755 | 0.010 | -0.21% | 0.01% | |
| 1 | 3 | 5.212 | 2.048 | -3.163 | -60.69% | 2.23% | |
| 1 | 4 | -1.364 | 0.893 | 2.257 | -165.50% | 1.59% | |
| 5 | 5 | 1.695 | 3.683 | 1.988 | 117.33% | 1.40% | |
| 5 | 6 | -4.399 | 2.282 | 6.681 | -151.88% | 4.72% | |
| 5 | 7 | -3.362 | -5.075 | -1.713 | 50.96% | 1.21% | |
| 5 | 8 | -4.732 | -6.988 | -2.256 | 47.68% | 1.59% | |
| 10 | 9 | -4.340 | -7.005 | -2.666 | 61.42% | 1.88% | |
| 10 | 10 | 2.239 | -6.613 | -8.852 | -395.41% | 6.25% | |
| 10 | 11 | -0.480 | -4.019 | -3.539 | 737.93% | 2.50% | |
| 10 | 12 | 5.157 | 8.185 | 3.028 | 58.71% | 2.14% | |
| Max | | 5.212 | 8.185 | 6.681 | 737.93% | 6.25% | |
| Average | | -1.303 | -1.824 | -0.521 | 19.11% | 2.04% | |
| Min | | -5.021 | -7.005 | -8.852 | -395.41% | 0.01% | |
| Std Dev | | 3.755 | 4.835 | 3.845 | 254.75% | 1.73% | |




| 105.6_CMRR_10V_C | | | | | | | |
|------------------|-----------|-----------|-----------|---------|--------|-------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | uV_V | uV_V | Max Limit | 70.8 | 70.8 | Min Limit | -70.8 |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | | |
| LL | -70.800 | -70.800 | -70.800 | -70.800 | | | |
| Min | -5.003 | -4.755 | -6.988 | -7.005 | | | |
| Average | -5.003 | -0.791 | -1.525 | -2.363 | | | |
| Max | -5.003 | 2.048 | 3.683 | 8.185 | | | |
| UL | 70.800 | 70.800 | 70.800 | 70.800 | | | |




NDD Report

LMP7704-SP

| 105.7_CMRR_10V_D | | | | | | | |
|------------------|-----------|-----------|-----------|--------|----------|------------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | uV_V | uV_V | Max Limit | 70.8 | 70.8 | Min Limit | -70.8 |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 13 | -0.790 | -0.764 | 0.027 | -3.37% | 0.02% | |
| 1 | 1 | -0.646 | -0.598 | 0.048 | -7.47% | 0.03% | |
| 1 | 2 | -2.146 | -0.862 | 1.284 | -59.86% | 0.91% | |
| 1 | 3 | -2.485 | -2.126 | 0.359 | -14.44% | 0.25% | |
| 1 | 4 | -2.986 | -2.146 | 0.840 | -28.12% | 0.59% | |
| 5 | 5 | -3.553 | -4.092 | -0.539 | 15.17% | 0.38% | |
| 5 | 6 | -9.238 | 2.505 | 11.743 | -127.11% | 8.29% | |
| 5 | 7 | -0.997 | -10.384 | -9.388 | 941.67% | 6.63% | |
| 5 | 8 | -7.471 | -2.950 | 4.521 | -60.52% | 3.19% | |
| 10 | 9 | -6.508 | -4.552 | 1.956 | -30.05% | 1.38% | |
| 10 | 10 | -2.560 | -8.773 | -6.213 | 242.73% | 4.39% | |
| 10 | 11 | 2.139 | 1.202 | -0.938 | -43.83% | 0.66% | |
| 10 | 12 | 6.823 | 4.565 | -2.258 | -33.09% | 1.59% | |
| Max | | 6.823 | 4.565 | 11.743 | 941.67% | 8.29% | |
| Average | | -2.340 | -2.229 | 0.111 | 60.90% | 2.18% | |
| Min | | -9.238 | -10.384 | -9.388 | -127.11% | 0.02% | |
| Std Dev | | 4.127 | 4.141 | 4.979 | 277.80% | 2.69% | |




| 105.7_CMRR_10V_D | | | | | | | |
|------------------|-----------|-----------|-----------|---------|--------|-------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | uV_V | uV_V | Max Limit | 70.8 | 70.8 | Min Limit | -70.8 |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | | |
| LL | -70.800 | -70.800 | -70.800 | -70.800 | | | |
| Min | -0.764 | -2.146 | -10.384 | -8.773 | | | |
| Average | -0.764 | -1.433 | -3.730 | -1.890 | | | |
| Max | -0.764 | -0.598 | 2.505 | 4.565 | | | |
| UL | 70.800 | 70.800 | 70.800 | 70.800 | | | |




NDD Report

LMP7704-SP

| 106.0_Aol_300mV_5V_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 9 | 63.1 | Min Limit | -9 | -63.1 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -1.012 | -1.076 | -0.064 | 6.28% | 0.35% |
| 1 | 1 | -0.860 | -0.431 | 0.429 | -49.91% | 2.39% |
| 1 | 2 | -0.916 | -0.867 | 0.049 | -5.30% | 0.27% |
| 1 | 3 | -0.975 | -0.978 | -0.002 | 0.26% | 0.01% |
| 1 | 4 | -0.792 | -1.299 | -0.507 | 64.02% | 2.82% |
| 5 | 5 | -0.919 | -1.586 | -0.667 | 72.65% | 3.71% |
| 5 | 6 | -0.975 | -1.048 | -0.073 | 7.51% | 0.41% |
| 5 | 7 | -0.975 | -1.684 | -0.709 | 72.68% | 3.94% |
| 5 | 8 | -1.186 | -0.576 | 0.610 | -51.44% | 3.39% |
| 10 | 9 | -0.988 | -1.548 | -0.561 | 56.75% | 3.11% |
| 10 | 10 | -1.057 | -1.347 | -0.290 | 27.39% | 1.61% |
| 10 | 11 | -1.054 | -1.434 | -0.380 | 36.09% | 2.11% |
| 10 | 12 | -1.048 | -1.001 | 0.047 | -4.45% | 0.26% |
| Max | | -0.792 | -0.431 | 0.610 | 72.68% | 3.94% |
| Average | | -0.981 | -1.144 | -0.163 | 17.89% | 1.87% |
| Min | | -1.186 | -1.684 | -0.709 | -51.44% | 0.01% |
| Std Dev | | 0.099 | 0.384 | 0.405 | 41.89% | 1.47% |




| 106.0_Aol_300mV_5V_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 63.1 | 63.1 | Min Limit | -63.1 | -63.1 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -63.100 | -63.100 | -63.100 | -63.100 | | |
| Min | -1.076 | -1.299 | -1.684 | -1.548 | | |
| Average | -1.076 | -0.894 | -1.223 | -1.333 | | |
| Max | -1.076 | -0.431 | -0.576 | -1.001 | | |
| UL | 63.100 | 63.100 | 63.100 | 63.100 | | |




NDD Report

LMP7704-SP

| 106.1_Aol_300mV_5V_B | | | | | | |
|----------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 9 | 63.1 | Min Limit | -9 | -63.1 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -1.171 | -1.197 | -0.027 | 2.28% | 0.15% |
| 1 | 1 | -1.126 | -0.842 | 0.284 | -25.22% | 1.58% |
| 1 | 2 | -0.895 | -1.098 | -0.203 | 22.65% | 1.13% |
| 1 | 3 | -1.095 | -1.395 | -0.301 | 27.45% | 1.67% |
| 1 | 4 | -1.255 | -1.197 | 0.059 | -4.66% | 0.33% |
| 5 | 5 | -0.878 | -1.563 | -0.685 | 77.99% | 3.81% |
| 5 | 6 | -1.278 | -1.281 | -0.003 | 0.20% | 0.01% |
| 5 | 7 | -1.030 | -1.618 | -0.587 | 57.01% | 3.26% |
| 5 | 8 | -1.192 | -1.131 | 0.061 | -5.09% | 0.34% |
| 10 | 9 | -0.854 | -1.716 | -0.861 | 100.82% | 4.79% |
| 10 | 10 | -1.018 | -1.818 | -0.800 | 78.57% | 4.44% |
| 10 | 11 | -1.099 | -1.183 | -0.084 | 7.62% | 0.47% |
| 10 | 12 | -1.198 | -1.028 | 0.171 | -14.25% | 0.95% |
| Max | | -0.854 | -0.842 | 0.284 | 100.82% | 4.79% |
| Average | | -1.084 | -1.313 | -0.229 | 25.03% | 1.76% |
| Min | | -1.278 | -1.818 | -0.861 | -25.22% | 0.01% |
| Std Dev | | 0.141 | 0.290 | 0.384 | 40.56% | 1.72% |




| 106.1_Aol_300mV_5V_B | | | | | | |
|----------------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 63.1 | uV_V | Min Limit | -63.1 | uV_V | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -63.100 | -63.100 | -63.100 | -63.100 | | |
| Min | -1.197 | -1.395 | -1.618 | -1.818 | | |
| Average | -1.197 | -1.133 | -1.398 | -1.436 | | |
| Max | -1.197 | -0.842 | -1.131 | -1.028 | | |
| UL | 63.100 | 63.100 | 63.100 | 63.100 | | |




NDD Report

LMP7704-SP

| 106.2_Aol_300mV_5V_C | | | | | | |
|----------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 9 | 63.1 | Min Limit | -9 | -63.1 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -1.119 | -0.939 | 0.180 | -16.09% | 1.00% |
| 1 | 1 | -1.180 | -0.862 | 0.319 | -27.01% | 1.77% |
| 1 | 2 | -0.903 | -1.052 | -0.149 | 16.48% | 0.83% |
| 1 | 3 | -1.255 | -1.151 | 0.104 | -8.29% | 0.58% |
| 1 | 4 | -1.251 | -1.006 | 0.245 | -19.60% | 1.36% |
| 5 | 5 | -1.011 | -1.123 | -0.111 | 11.01% | 0.62% |
| 5 | 6 | -0.932 | -1.277 | -0.345 | 37.00% | 1.92% |
| 5 | 7 | -0.951 | -1.518 | -0.567 | 59.65% | 3.15% |
| 5 | 8 | -0.966 | -1.096 | -0.131 | 13.51% | 0.73% |
| 10 | 9 | -1.049 | -0.846 | 0.203 | -19.32% | 1.13% |
| 10 | 10 | -1.149 | -1.319 | -0.170 | 14.83% | 0.95% |
| 10 | 11 | -1.221 | -1.309 | -0.087 | 7.16% | 0.49% |
| 10 | 12 | -1.088 | -1.246 | -0.159 | 14.59% | 0.88% |
| Max | | -0.903 | -0.846 | 0.319 | 59.65% | 3.15% |
| Average | | -1.083 | -1.134 | -0.051 | 6.46% | 1.18% |
| Min | | -1.255 | -1.518 | -0.567 | -27.01% | 0.49% |
| Std Dev | | 0.124 | 0.197 | 0.253 | 24.60% | 0.73% |




| 106.2_Aol_300mV_5V_C | | | | | | |
|----------------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 63.1 | uV_V | Min Limit | -63.1 | uV_V | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -63.100 | -63.100 | -63.100 | -63.100 | | |
| Min | -0.939 | -1.151 | -1.518 | -1.319 | | |
| Average | -0.939 | -1.018 | -1.254 | -1.180 | | |
| Max | -0.939 | -0.862 | -1.096 | -0.846 | | |
| UL | 63.100 | 63.100 | 63.100 | 63.100 | | |




NDD Report

LMP7704-SP

| 106.3_Aol_300mV_5V_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 9 | 63.1 | Min Limit | -9 | -63.1 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -1.110 | -1.047 | 0.063 | -5.65% | 0.35% |
| 1 | 1 | -1.045 | -1.137 | -0.092 | 8.85% | 0.51% |
| 1 | 2 | -1.049 | -0.976 | 0.073 | -6.96% | 0.41% |
| 1 | 3 | -1.274 | -1.138 | 0.136 | -10.66% | 0.75% |
| 1 | 4 | -1.034 | -1.105 | -0.071 | 6.91% | 0.40% |
| 5 | 5 | -0.963 | -0.857 | 0.106 | -10.98% | 0.59% |
| 5 | 6 | -0.971 | -1.557 | -0.585 | 60.24% | 3.25% |
| 5 | 7 | -0.989 | -1.139 | -0.151 | 15.24% | 0.84% |
| 5 | 8 | -0.960 | -1.374 | -0.414 | 43.16% | 2.30% |
| 10 | 9 | -1.143 | -1.303 | -0.159 | 13.91% | 0.88% |
| 10 | 10 | -1.222 | -1.468 | -0.246 | 20.10% | 1.36% |
| 10 | 11 | -1.108 | -1.719 | -0.612 | 55.19% | 3.40% |
| 10 | 12 | -0.999 | -1.317 | -0.317 | 31.78% | 1.76% |
| Max | | -0.960 | -0.857 | 0.136 | 60.24% | 3.40% |
| Average | | -1.067 | -1.241 | -0.175 | 17.01% | 1.29% |
| Min | | -1.274 | -1.719 | -0.612 | -10.98% | 0.35% |
| Std Dev | | 0.100 | 0.244 | 0.251 | 24.25% | 1.07% |




| 106.3_Aol_300mV_5V_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|---------|---------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Max Limit | 63.1 | uV_V | |
| Min Limit | -63.1 | -63.1 | uV_V | -63.100 | -63.100 | -63.100 |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -63.100 | -63.100 | -63.100 | -63.100 | | |
| Min | -1.047 | -1.139 | -1.557 | -1.719 | | |
| Average | -1.047 | -1.089 | -1.232 | -1.452 | | |
| Max | -1.047 | -0.976 | -0.857 | -1.303 | | |
| UL | 63.100 | 63.100 | 63.100 | 63.100 | | |




NDD Report

LMP7704-SP

| 106.4_Aol_200mV_5V_A | | | | | | | |
|----------------------|-----------|-----------|-----------|--------|----------|------------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | uV_V | uV_V | Max Limit | 9 | 9 | Min Limit | -9 |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 13 | -0.290 | -0.333 | -0.042 | 14.65% | 0.24% | |
| 1 | 1 | -0.333 | -0.508 | -0.175 | 52.57% | 0.97% | |
| 1 | 2 | -0.014 | -0.109 | -0.096 | 699.27% | 0.53% | |
| 1 | 3 | -0.391 | -0.545 | -0.155 | 39.58% | 0.86% | |
| 1 | 4 | -0.304 | -0.286 | 0.018 | -5.76% | 0.10% | |
| 5 | 5 | -0.160 | -0.527 | -0.367 | 229.72% | 2.04% | |
| 5 | 6 | -0.393 | -0.315 | 0.078 | -19.85% | 0.43% | |
| 5 | 7 | -0.303 | -0.408 | -0.106 | 34.92% | 0.59% | |
| 5 | 8 | -0.352 | -0.120 | 0.232 | -65.82% | 1.29% | |
| 10 | 9 | -0.223 | -0.991 | -0.768 | 344.57% | 4.27% | |
| 10 | 10 | -0.243 | -0.493 | -0.250 | 102.96% | 1.39% | |
| 10 | 11 | -0.219 | -0.784 | -0.565 | 258.30% | 3.14% | |
| 10 | 12 | -0.363 | 0.488 | 0.851 | -234.65% | 4.73% | |
| Max | | -0.014 | 0.488 | 0.851 | 699.27% | 4.73% | |
| Average | | -0.276 | -0.379 | -0.104 | 111.57% | 1.58% | |
| Min | | -0.393 | -0.991 | -0.768 | -234.65% | 0.10% | |
| Std Dev | | 0.106 | 0.357 | 0.390 | 231.22% | 1.53% | |




| 106.4_Aol_200mV_5V_A | | | | | | | |
|----------------------|-----------|-----------|-----------|--------|--------|-------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | uV_V | uV_V | Max Limit | 9 | uV_V | Min Limit | -9 |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | | |
| LL | -9.000 | -9.000 | -9.000 | -9.000 | | | |
| Min | -0.333 | -0.545 | -0.527 | -0.991 | | | |
| Average | -0.333 | -0.362 | -0.343 | -0.445 | | | |
| Max | -0.333 | -0.110 | -0.120 | 0.489 | | | |
| UL | 9.000 | 9.000 | 9.000 | 9.000 | | | |




NDD Report

LMP7704-SP

| 106.5_Aol_200mV_5V_B | | | | | | |
|----------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 9 | 9 | Min Limit | -9 | -9 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.056 | -0.362 | -0.306 | 546.79% | 1.70% |
| 1 | 1 | -0.154 | -0.173 | -0.019 | 12.01% | 0.10% |
| 1 | 2 | -0.044 | -0.054 | -0.009 | 20.72% | 0.05% |
| 1 | 3 | -0.333 | -0.293 | 0.040 | -11.95% | 0.22% |
| 1 | 4 | -0.321 | -0.334 | -0.013 | 4.08% | 0.07% |
| 5 | 5 | -0.263 | -0.670 | -0.407 | 154.56% | 2.26% |
| 5 | 6 | -0.245 | -0.491 | -0.246 | 100.49% | 1.37% |
| 5 | 7 | -0.126 | -0.556 | -0.430 | 340.81% | 2.39% |
| 5 | 8 | -0.273 | -0.233 | 0.041 | -14.86% | 0.23% |
| 10 | 9 | -0.308 | -0.577 | -0.269 | 87.55% | 1.50% |
| 10 | 10 | -0.146 | -0.549 | -0.404 | 277.66% | 2.24% |
| 10 | 11 | -0.349 | -0.943 | -0.594 | 170.11% | 3.30% |
| 10 | 12 | -0.385 | -0.322 | 0.063 | -16.48% | 0.35% |
| Max | | -0.044 | -0.054 | 0.063 | 546.79% | 3.30% |
| Average | | -0.231 | -0.427 | -0.196 | 128.58% | 1.21% |
| Min | | -0.385 | -0.943 | -0.594 | -16.48% | 0.05% |
| Std Dev | | 0.114 | 0.236 | 0.224 | 170.57% | 1.11% |




| 106.5_Aol_200mV_5V_B | | | | |
|----------------------|-----------|--------|-----------|--------|
| Test Site | TI Dallas | ETS364 | Tester | ETS364 |
| Test Number | EB4632 | EB4632 | Unit | uV_V |
| Max Limit | 9 | 9 | Min Limit | -9 |
| Std Dev | 0.114 | 0.236 | Std Dev | 0.224 |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 |
| LL | -9.000 | -9.000 | -9.000 | -9.000 |
| Min | -0.362 | -0.334 | -0.670 | -0.944 |
| Average | -0.362 | -0.213 | -0.488 | -0.598 |
| Max | -0.362 | -0.054 | -0.233 | -0.322 |
| UL | 9.000 | 9.000 | 9.000 | 9.000 |




NDD Report

LMP7704-SP

| 106.6_Aol_200mV_5V_C | | | | | | | |
|----------------------|-----------|-----------|-----------|--------|----------|------------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | uV_V | uV_V | Max Limit | 9 | 9 | Min Limit | -9 |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 13 | -0.490 | -0.177 | 0.312 | -63.77% | 1.74% | |
| 1 | 1 | -0.316 | -0.289 | 0.027 | -8.40% | 0.15% | |
| 1 | 2 | -0.171 | -0.319 | -0.148 | 86.06% | 0.82% | |
| 1 | 3 | -0.301 | 0.189 | 0.490 | -162.82% | 2.72% | |
| 1 | 4 | -0.425 | -0.297 | 0.128 | -30.10% | 0.71% | |
| 5 | 5 | -0.389 | 0.504 | 0.893 | -229.72% | 4.96% | |
| 5 | 6 | -0.345 | -0.579 | -0.234 | 67.91% | 1.30% | |
| 5 | 7 | -0.186 | 0.020 | 0.207 | -110.90% | 1.15% | |
| 5 | 8 | -0.263 | -0.384 | -0.121 | 46.10% | 0.67% | |
| 10 | 9 | -0.290 | -0.468 | -0.177 | 61.09% | 0.99% | |
| 10 | 10 | -0.176 | -0.737 | -0.562 | 319.58% | 3.12% | |
| 10 | 11 | -0.262 | -0.308 | -0.046 | 17.49% | 0.25% | |
| 10 | 12 | -0.322 | -0.253 | 0.069 | -21.53% | 0.38% | |
| Max | | -0.171 | 0.504 | 0.893 | 319.58% | 4.96% | |
| Average | | -0.303 | -0.238 | 0.065 | -2.23% | 1.46% | |
| Min | | -0.490 | -0.737 | -0.562 | -229.72% | 0.15% | |
| Std Dev | | 0.096 | 0.324 | 0.364 | 134.58% | 1.38% | |




| 106.6_Aol_200mV_5V_C | | | | | | | |
|----------------------|-----------|-----------|-----------|--------|--------|-------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | uV_V | uV_V | Max Limit | 9 | uV_V | Min Limit | -9 |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | | |
| LL | -9.000 | -9.000 | -9.000 | -9.000 | | | |
| Min | -0.178 | -0.319 | -0.579 | -0.737 | | | |
| Average | -0.178 | -0.179 | -0.110 | -0.441 | | | |
| Max | -0.178 | 0.189 | 0.505 | -0.253 | | | |
| UL | 9.000 | 9.000 | 9.000 | 9.000 | | | |




NDD Report

LMP7704-SP

| 106.7_Aol_200mV_5V_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 9 | 9 | Min Limit | -9 | -9 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.208 | -0.173 | 0.035 | -16.83% | 0.19% |
| 1 | 1 | -0.168 | -0.481 | -0.314 | 187.28% | 1.74% |
| 1 | 2 | -0.344 | -0.378 | -0.035 | 10.04% | 0.19% |
| 1 | 3 | -0.192 | -0.294 | -0.102 | 53.12% | 0.57% |
| 1 | 4 | -0.086 | -0.260 | -0.174 | 202.68% | 0.97% |
| 5 | 5 | -0.208 | -0.587 | -0.379 | 181.67% | 2.10% |
| 5 | 6 | -0.190 | -0.294 | -0.104 | 54.52% | 0.58% |
| 5 | 7 | -0.230 | -1.104 | -0.874 | 380.34% | 4.86% |
| 5 | 8 | -0.185 | -0.398 | -0.213 | 114.66% | 1.18% |
| 10 | 9 | -0.299 | -0.846 | -0.547 | 183.26% | 3.04% |
| 10 | 10 | -0.280 | 0.387 | 0.667 | -238.52% | 3.71% |
| 10 | 11 | -0.055 | -0.944 | -0.889 | 1615.64% | 4.94% |
| 10 | 12 | -0.382 | -0.195 | 0.187 | -48.97% | 1.04% |
| Max | | -0.055 | 0.387 | 0.667 | 1615.64% | 4.94% |
| Average | | -0.217 | -0.428 | -0.211 | 206.07% | 1.93% |
| Min | | -0.382 | -1.104 | -0.889 | -238.52% | 0.19% |
| Std Dev | | 0.092 | 0.385 | 0.418 | 449.47% | 1.68% |




| 106.7_Aol_200mV_5V_D | | | | |
|-----------------------------------|-----------|--------|-----------|--------|
| Test Site | TI Dallas | ETS364 | Tester | ETS364 |
| Test Number | EB4632 | EB4632 | Unit | uV_V |
| Max Limit | 9 | 9 | Min Limit | -9 |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | -9.000 | -9.000 | -9.000 | -9.000 |
| Min | -0.173 | -0.481 | -1.104 | -0.944 |
| Average | -0.173 | -0.353 | -0.596 | -0.399 |
| Max | -0.173 | -0.260 | -0.294 | 0.387 |
| UL | 9.000 | 9.000 | 9.000 | 9.000 |




NDD Report

LMP7704-SP

| 106.8_Aol_300mV_10V_A | | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | uV_V | uV_V | Max Limit | 9 | 9 | Min Limit | -9 |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 13 | -0.783 | -0.811 | -0.029 | 3.68% | 0.16% | |
| 1 | 1 | -0.835 | -0.869 | -0.034 | 4.07% | 0.19% | |
| 1 | 2 | -0.853 | -0.845 | 0.008 | -0.95% | 0.05% | |
| 1 | 3 | -0.851 | -0.979 | -0.128 | 15.07% | 0.71% | |
| 1 | 4 | -0.878 | -0.861 | 0.017 | -1.90% | 0.09% | |
| 5 | 5 | -0.778 | -0.775 | 0.002 | -0.28% | 0.01% | |
| 5 | 6 | -0.815 | -0.817 | -0.002 | 0.22% | 0.01% | |
| 5 | 7 | -0.915 | -0.892 | 0.023 | -2.55% | 0.13% | |
| 5 | 8 | -0.937 | -1.090 | -0.153 | 16.29% | 0.85% | |
| 10 | 9 | -0.816 | -0.696 | 0.120 | -14.65% | 0.66% | |
| 10 | 10 | -0.947 | -1.046 | -0.098 | 10.37% | 0.55% | |
| 10 | 11 | -0.947 | -1.259 | -0.313 | 33.03% | 1.74% | |
| 10 | 12 | -0.889 | -1.188 | -0.299 | 33.58% | 1.66% | |
| Max | | -0.778 | -0.696 | 0.120 | 33.58% | 1.74% | |
| Average | | -0.865 | -0.933 | -0.068 | 7.38% | 0.52% | |
| Min | | -0.947 | -1.259 | -0.313 | -14.65% | 0.01% | |
| Std Dev | | 0.060 | 0.168 | 0.127 | 14.04% | 0.60% | |




| 106.8_Aol_300mV_10V_A | | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|--------|-------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | uV_V | uV_V | Max Limit | 9 | uV_V | Min Limit | -9 |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | | |
| LL | -9.000 | -9.000 | -9.000 | -9.000 | | | |
| Min | -0.811 | -0.979 | -1.090 | -1.259 | | | |
| Average | -0.811 | -0.889 | -0.893 | -1.047 | | | |
| Max | -0.811 | -0.845 | -0.775 | -0.696 | | | |
| UL | 9.000 | 9.000 | 9.000 | 9.000 | | | |




NDD Report

LMP7704-SP

| 106.9_Aol_300mV_10V_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 9 | 9 | Min Limit | -9 | -9 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.860 | -0.856 | 0.004 | -0.46% | 0.02% |
| 1 | 1 | -0.740 | -0.778 | -0.037 | 5.04% | 0.21% |
| 1 | 2 | -0.872 | -0.936 | -0.064 | 7.36% | 0.36% |
| 1 | 3 | -0.878 | -0.703 | 0.176 | -19.99% | 0.98% |
| 1 | 4 | -0.890 | -0.813 | 0.077 | -8.64% | 0.43% |
| 5 | 5 | -0.789 | -1.061 | -0.271 | 34.33% | 1.51% |
| 5 | 6 | -0.793 | -0.992 | -0.200 | 25.18% | 1.11% |
| 5 | 7 | -0.914 | -0.915 | -0.001 | 0.14% | 0.01% |
| 5 | 8 | -0.899 | -1.008 | -0.109 | 12.12% | 0.61% |
| 10 | 9 | -0.784 | -0.988 | -0.204 | 26.04% | 1.13% |
| 10 | 10 | -0.939 | -1.053 | -0.113 | 12.05% | 0.63% |
| 10 | 11 | -0.817 | -0.922 | -0.104 | 12.78% | 0.58% |
| 10 | 12 | -0.844 | -0.978 | -0.135 | 15.97% | 0.75% |
| Max | | -0.740 | -0.703 | 0.176 | 34.33% | 1.51% |
| Average | | -0.848 | -0.923 | -0.076 | 9.38% | 0.64% |
| Min | | -0.939 | -1.061 | -0.271 | -19.99% | 0.01% |
| Std Dev | | 0.059 | 0.109 | 0.121 | 14.75% | 0.45% |




| 106.9_Aol_300mV_10V_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | uV_V | uV_V | |
| Max Limit | 9 | 9 | Min Limit | -9 | -9 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -9.000 | -9.000 | -9.000 | -9.000 | | |
| Min | -0.856 | -0.936 | -1.061 | -1.053 | | |
| Average | -0.856 | -0.808 | -0.994 | -0.985 | | |
| Max | -0.856 | -0.703 | -0.915 | -0.922 | | |
| UL | 9.000 | 9.000 | 9.000 | 9.000 | | |




NDD Report

LMP7704-SP

| 106.10_Aol_300mV_10V_C | | | | | | |
|------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | uV_V | uV_V | | | | |
| Max Limit | 9 | 9 | | | | |
| Min Limit | -9 | -9 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.770 | -0.805 | -0.034 | 4.45% | 0.19% |
| 1 | 1 | -0.824 | -0.799 | 0.024 | -2.95% | 0.14% |
| 1 | 2 | -0.803 | -0.869 | -0.067 | 8.31% | 0.37% |
| 1 | 3 | -0.882 | -0.849 | 0.033 | -3.79% | 0.19% |
| 1 | 4 | -0.784 | -0.903 | -0.119 | 15.21% | 0.66% |
| 5 | 5 | -0.852 | -0.767 | 0.085 | -9.95% | 0.47% |
| 5 | 6 | -0.872 | -0.839 | 0.033 | -3.76% | 0.18% |
| 5 | 7 | -0.848 | -1.138 | -0.290 | 34.16% | 1.61% |
| 5 | 8 | -0.876 | -0.901 | -0.025 | 2.83% | 0.14% |
| 10 | 9 | -0.787 | -0.978 | -0.191 | 24.21% | 1.06% |
| 10 | 10 | -0.780 | -0.789 | -0.009 | 1.13% | 0.05% |
| 10 | 11 | -0.832 | -0.920 | -0.088 | 10.53% | 0.49% |
| 10 | 12 | -0.853 | -0.923 | -0.070 | 8.17% | 0.39% |
| Max | | -0.770 | -0.767 | 0.085 | 34.16% | 1.61% |
| Average | | -0.828 | -0.883 | -0.055 | 6.81% | 0.46% |
| Min | | -0.882 | -1.138 | -0.290 | -9.95% | 0.05% |
| Std Dev | | 0.039 | 0.098 | 0.102 | 12.22% | 0.44% |




| 106.10_Aol_300mV_10V_C | | | | | | |
|------------------------|-----------|-----------|--------|--------|--|--|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Max Limit | 9 | uV_V | | | | |
| Min Limit | -9 | uV_V | | | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -9.000 | -9.000 | -9.000 | -9.000 | | |
| Min | -0.805 | -0.903 | -1.138 | -0.978 | | |
| Average | -0.805 | -0.855 | -0.911 | -0.902 | | |
| Max | -0.805 | -0.800 | -0.767 | -0.789 | | |
| UL | 9.000 | 9.000 | 9.000 | 9.000 | | |




NDD Report

LMP7704-SP

| 106.11_Aol_300mV_10V_D | | | | | | |
|------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | uV_V | uV_V | | | | |
| Max Limit | 9 | 9 | | | | |
| Min Limit | -9 | -9 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.776 | -0.795 | -0.020 | 2.55% | 0.11% |
| 1 | 1 | -0.799 | -0.822 | -0.024 | 2.98% | 0.13% |
| 1 | 2 | -0.801 | -0.800 | 0.001 | -0.07% | 0.00% |
| 1 | 3 | -0.851 | -0.888 | -0.037 | 4.35% | 0.21% |
| 1 | 4 | -0.884 | -0.881 | 0.002 | -0.26% | 0.01% |
| 5 | 5 | -0.838 | -0.994 | -0.156 | 18.59% | 0.87% |
| 5 | 6 | -0.826 | -1.038 | -0.212 | 25.71% | 1.18% |
| 5 | 7 | -0.856 | -0.850 | 0.006 | -0.72% | 0.03% |
| 5 | 8 | -0.787 | -0.896 | -0.109 | 13.91% | 0.61% |
| 10 | 9 | -0.841 | -0.879 | -0.037 | 4.43% | 0.21% |
| 10 | 10 | -0.862 | -1.435 | -0.573 | 66.48% | 3.18% |
| 10 | 11 | -0.883 | -1.369 | -0.486 | 54.97% | 2.70% |
| 10 | 12 | -0.897 | -0.916 | -0.018 | 2.05% | 0.10% |
| Max | | -0.776 | -0.795 | 0.006 | 66.48% | 3.18% |
| Average | | -0.838 | -0.966 | -0.128 | 15.00% | 0.72% |
| Min | | -0.897 | -1.435 | -0.573 | -0.72% | 0.00% |
| Std Dev | | 0.039 | 0.206 | 0.191 | 21.94% | 1.05% |




| 106.11_Aol_300mV_10V_D | | | | | | |
|------------------------|-----------|-----------|--------|--------|--|--|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Max Limit | 9 | uV_V | | | | |
| Min Limit | -9 | uV_V | | | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -9.000 | -9.000 | -9.000 | -9.000 | | |
| Min | -0.795 | -0.888 | -1.038 | -1.435 | | |
| Average | -0.795 | -0.848 | -0.945 | -1.150 | | |
| Max | -0.795 | -0.800 | -0.850 | -0.879 | | |
| UL | 9.000 | 9.000 | 9.000 | 9.000 | | |




NDD Report

LMP7704-SP

| 106.12_Aol_200mV_10V_A | | | | | | |
|------------------------|-----------|-----------|----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | uV_V | uV_V | | | | |
| Max Limit | 9 | 9 | | | | |
| Min Limit | -9 | -9 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.183 | -0.193 | -0.010 | 5.23% | 0.05% |
| 1 | 1 | -0.288 | -0.323 | -0.036 | 12.38% | 0.20% |
| 1 | 2 | -0.230 | -0.289 | -0.059 | 25.72% | 0.33% |
| 1 | 3 | -0.278 | -0.889 | -0.611 | 220.09% | 3.40% |
| 1 | 4 | -0.279 | -0.336 | -0.056 | 20.19% | 0.31% |
| 5 | 5 | -0.174 | 0.098 | 0.273 | -156.54% | 1.51% |
| 5 | 6 | -0.191 | -0.271 | -0.080 | 42.06% | 0.45% |
| 5 | 7 | -0.255 | -0.246 | 0.008 | -3.26% | 0.05% |
| 5 | 8 | -0.249 | -0.266 | -0.018 | 7.08% | 0.10% |
| 10 | 9 | -0.237 | -0.109 | 0.128 | -54.12% | 0.71% |
| 10 | 10 | -0.213 | -0.350 | -0.137 | 64.15% | 0.76% |
| 10 | 11 | -0.268 | -0.418 | -0.150 | 55.95% | 0.83% |
| 10 | 12 | -0.304 | -0.077 | 0.227 | -74.63% | 1.26% |
| Max | | -0.174 | 0.098 | 0.273 | 220.09% | 3.40% |
| Average | | -0.242 | -0.282 | -0.040 | 12.64% | 0.77% |
| Min | | -0.304 | -0.889 | -0.611 | -156.54% | 0.05% |
| Std Dev | | 0.042 | 0.228 | 0.214 | 86.45% | 0.91% |




| 106.12_Aol_200mV_10V_A | | | | | | |
|------------------------|-----------|-----------|--------|--------|--|--|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Max Limit | 9 | uV_V | | | | |
| Min Limit | -9 | uV_V | | | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -9.000 | -9.000 | -9.000 | -9.000 | | |
| Min | -0.193 | -0.889 | -0.271 | -0.418 | | |
| Average | -0.193 | -0.459 | -0.171 | -0.238 | | |
| Max | -0.193 | -0.289 | 0.099 | -0.077 | | |
| UL | 9.000 | 9.000 | 9.000 | 9.000 | | |




NDD Report

LMP7704-SP

| 106.13_Aol_200mV_10V_B | | | | | | |
|------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | uV_V | uV_V | | | | |
| Max Limit | 9 | 9 | | | | |
| Min Limit | -9 | -9 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.264 | -0.200 | 0.064 | -24.13% | 0.35% |
| 1 | 1 | -0.262 | -0.203 | 0.059 | -22.41% | 0.33% |
| 1 | 2 | -0.239 | -0.260 | -0.021 | 8.87% | 0.12% |
| 1 | 3 | -0.188 | -0.304 | -0.117 | 62.21% | 0.65% |
| 1 | 4 | -0.241 | -0.306 | -0.066 | 27.28% | 0.36% |
| 5 | 5 | -0.252 | -0.607 | -0.355 | 140.97% | 1.97% |
| 5 | 6 | -0.169 | -0.448 | -0.279 | 165.70% | 1.55% |
| 5 | 7 | -0.160 | -0.382 | -0.221 | 138.18% | 1.23% |
| 5 | 8 | -0.223 | -0.398 | -0.175 | 78.41% | 0.97% |
| 10 | 9 | -0.229 | -0.484 | -0.254 | 110.86% | 1.41% |
| 10 | 10 | -0.294 | -0.198 | 0.096 | -32.60% | 0.53% |
| 10 | 11 | -0.256 | -0.234 | 0.022 | -8.59% | 0.12% |
| 10 | 12 | -0.217 | -0.277 | -0.060 | 27.49% | 0.33% |
| Max | | -0.160 | -0.198 | 0.096 | 165.70% | 1.97% |
| Average | | -0.230 | -0.331 | -0.101 | 51.71% | 0.76% |
| Min | | -0.294 | -0.607 | -0.355 | -32.60% | 0.12% |
| Std Dev | | 0.039 | 0.126 | 0.146 | 69.38% | 0.60% |




| 106.13_Aol_200mV_10V_B | | | | | | |
|------------------------|-----------|-----------|--------|--------|--|--|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Max Limit | 9 | uV_V | | | | |
| Min Limit | -9 | uV_V | | | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -9.000 | -9.000 | -9.000 | -9.000 | | |
| Min | -0.200 | -0.306 | -0.607 | -0.484 | | |
| Average | -0.200 | -0.268 | -0.459 | -0.298 | | |
| Max | -0.200 | -0.203 | -0.382 | -0.198 | | |
| UL | 9.000 | 9.000 | 9.000 | 9.000 | | |




NDD Report

LMP7704-SP

| 106.14_Aol_200mV_10V_C | | | | | | |
|------------------------|-----------|-----------|----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | uV_V | uV_V | | | | |
| Max Limit | 9 | 9 | | | | |
| Min Limit | -9 | -9 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.206 | -0.263 | -0.057 | 27.53% | 0.32% |
| 1 | 1 | -0.173 | -0.162 | 0.011 | -6.48% | 0.06% |
| 1 | 2 | -0.188 | -0.307 | -0.119 | 63.35% | 0.66% |
| 1 | 3 | -0.295 | -0.264 | 0.031 | -10.62% | 0.17% |
| 1 | 4 | -0.291 | -0.314 | -0.023 | 7.89% | 0.13% |
| 5 | 5 | -0.200 | -0.088 | 0.112 | -55.78% | 0.62% |
| 5 | 6 | -0.216 | 0.470 | 0.686 | -317.01% | 3.81% |
| 5 | 7 | -0.243 | -0.398 | -0.156 | 64.22% | 0.87% |
| 5 | 8 | -0.268 | -0.182 | 0.086 | -32.06% | 0.48% |
| 10 | 9 | -0.224 | -0.353 | -0.129 | 57.82% | 0.72% |
| 10 | 10 | -0.131 | -0.713 | -0.582 | 442.85% | 3.23% |
| 10 | 11 | -0.148 | -0.318 | -0.171 | 115.36% | 0.95% |
| 10 | 12 | -0.243 | -0.554 | -0.311 | 127.91% | 1.73% |
| Max | | -0.131 | 0.470 | 0.686 | 442.85% | 3.81% |
| Average | | -0.217 | -0.265 | -0.048 | 37.31% | 1.06% |
| Min | | -0.295 | -0.713 | -0.582 | -317.01% | 0.06% |
| Std Dev | | 0.051 | 0.275 | 0.286 | 164.51% | 1.18% |




| 106.14_Aol_200mV_10V_C | | | | |
|------------------------|-----------|--------|--------|--------|
| Test Site | TI Dallas | | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 9 | uV_V | | |
| Min Limit | -9 | uV_V | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 |
| LL | -9.000 | -9.000 | -9.000 | -9.000 |
| Min | -0.263 | -0.314 | -0.398 | -0.713 |
| Average | -0.263 | -0.262 | -0.050 | -0.485 |
| Max | -0.263 | -0.162 | 0.470 | -0.318 |
| UL | 9.000 | 9.000 | 9.000 | 9.000 |




NDD Report

LMP7704-SP

| 106.15_Aol_200mV_10V_D | | | | | | |
|------------------------|-----------|-----------|----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | uV_V | uV_V | | | | |
| Max Limit | 9 | 9 | | | | |
| Min Limit | -9 | -9 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.207 | -0.262 | -0.054 | 26.23% | 0.30% |
| 1 | 1 | -0.185 | -0.245 | -0.060 | 32.08% | 0.33% |
| 1 | 2 | -0.250 | -0.184 | 0.065 | -26.21% | 0.36% |
| 1 | 3 | -0.211 | -0.252 | -0.041 | 19.52% | 0.23% |
| 1 | 4 | -0.209 | -0.233 | -0.024 | 11.60% | 0.13% |
| 5 | 5 | -0.283 | -0.254 | 0.029 | -10.12% | 0.16% |
| 5 | 6 | -0.267 | 0.153 | 0.420 | -157.40% | 2.33% |
| 5 | 7 | -0.213 | -0.049 | 0.164 | -77.20% | 0.91% |
| 5 | 8 | -0.230 | -0.189 | 0.041 | -17.96% | 0.23% |
| 10 | 9 | -0.128 | -0.331 | -0.203 | 158.39% | 1.13% |
| 10 | 10 | -0.241 | -0.430 | -0.189 | 78.59% | 1.05% |
| 10 | 11 | -0.243 | -0.379 | -0.136 | 55.87% | 0.75% |
| 10 | 12 | -0.215 | -0.446 | -0.231 | 107.64% | 1.28% |
| Max | | -0.128 | 0.153 | 0.420 | 158.39% | 2.33% |
| Average | | -0.222 | -0.238 | -0.017 | 15.46% | 0.71% |
| Min | | -0.283 | -0.446 | -0.231 | -157.40% | 0.13% |
| Std Dev | | 0.039 | 0.159 | 0.174 | 80.07% | 0.63% |




| 106.15_Aol_200mV_10V_D | | | | |
|------------------------|-----------|--------|--------|--------|
| Test Site | TI Dallas | | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 9 | uV_V | | |
| Min Limit | -9 | uV_V | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 |
| LL | -9.000 | -9.000 | -9.000 | -9.000 |
| Min | -0.262 | -0.252 | -0.254 | -0.446 |
| Average | -0.262 | -0.228 | -0.085 | -0.396 |
| Max | -0.262 | -0.184 | 0.153 | -0.331 |
| UL | 9.000 | 9.000 | 9.000 | 9.000 |




NDD Report

LMP7704-SP

| 107.0_Ib_res_pos_A | | | | | | |
|--------------------|-----------|-----------|-----------|--------|------------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | nA | nA | |
| Max Limit | 5 | 5 | Min Limit | -5 | -5 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.005 | -0.038 | -0.033 | 624.53% | 0.33% |
| 1 | 1 | 0.005 | -0.009 | -0.015 | -269.09% | 0.15% |
| 1 | 2 | 0.007 | 0.048 | 0.040 | 536.00% | 0.40% |
| 1 | 3 | 0.005 | -0.075 | -0.080 | -1732.61% | 0.80% |
| 1 | 4 | -0.009 | 0.049 | 0.058 | -648.31% | 0.58% |
| 5 | 5 | 0.004 | -0.025 | -0.028 | -786.11% | 0.28% |
| 5 | 6 | 0.004 | -0.003 | -0.007 | -183.33% | 0.07% |
| 5 | 7 | -0.018 | 0.011 | 0.029 | -162.15% | 0.29% |
| 5 | 8 | -0.003 | -0.025 | -0.022 | 651.52% | 0.22% |
| 10 | 9 | -0.007 | 0.021 | 0.027 | -410.61% | 0.27% |
| 10 | 10 | 0.001 | -0.058 | -0.058 | -11640.00% | 0.58% |
| 10 | 11 | -0.005 | -0.015 | -0.010 | 200.00% | 0.10% |
| 10 | 12 | -0.007 | -0.019 | -0.013 | 192.42% | 0.13% |
| Max | | 0.007 | 0.049 | 0.058 | 651.52% | 0.80% |
| Average | | -0.002 | -0.011 | -0.009 | -1048.29% | 0.32% |
| Min | | -0.018 | -0.075 | -0.080 | -11640.00% | 0.07% |
| Std Dev | | 0.007 | 0.037 | 0.039 | 3249.66% | 0.22% |




| 107.0_Ib_res_pos_A | | | | | | |
|--------------------|-----------|-----------|-----------|--------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | nA | nA | |
| Max Limit | 5 | nA | Min Limit | -5 | nA | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -5.000 | -5.000 | -5.000 | -5.000 | | |
| Min | -0.038 | -0.075 | -0.025 | -0.058 | | |
| Average | -0.038 | 0.003 | -0.010 | -0.018 | | |
| Max | -0.038 | 0.049 | 0.011 | 0.021 | | |
| UL | 5.000 | 5.000 | 5.000 | 5.000 | | |




NDD Report

LMP7704-SP

| 107.1_Ib_res_pos_B | | | | | | |
|--------------------|-----------|-----------|-----------|--------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | nA | nA | |
| Max Limit | 5 | 5 | Min Limit | -5 | -5 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 0.008 | -0.021 | -0.029 | -354.22% | 0.29% |
| 1 | 1 | -0.007 | 0.001 | 0.008 | -118.84% | 0.08% |
| 1 | 2 | -0.007 | 0.042 | 0.050 | -688.89% | 0.50% |
| 1 | 3 | -0.006 | -0.071 | -0.064 | 1037.10% | 0.64% |
| 1 | 4 | 0.000 | 0.067 | 0.067 | 16750.00% | 0.67% |
| 5 | 5 | 0.007 | -0.026 | -0.033 | -471.83% | 0.33% |
| 5 | 6 | -0.005 | 0.015 | 0.020 | -408.33% | 0.20% |
| 5 | 7 | -0.003 | 0.015 | 0.018 | -674.07% | 0.18% |
| 5 | 8 | 0.002 | -0.004 | -0.005 | -331.25% | 0.05% |
| 10 | 9 | 0.001 | 0.006 | 0.005 | 416.67% | 0.05% |
| 10 | 10 | 0.004 | -0.068 | -0.072 | -1751.22% | 0.72% |
| 10 | 11 | -0.016 | 0.000 | 0.016 | -98.11% | 0.16% |
| 10 | 12 | 0.013 | -0.040 | -0.053 | -411.63% | 0.53% |
| Max | | 0.013 | 0.067 | 0.067 | 16750.00% | 0.72% |
| Average | | -0.001 | -0.006 | -0.006 | 991.95% | 0.34% |
| Min | | -0.016 | -0.071 | -0.072 | -1751.22% | 0.05% |
| Std Dev | | 0.008 | 0.039 | 0.043 | 4776.97% | 0.24% |




| 107.1_Ib_res_pos_B | | | | | | |
|--------------------|-----------|-----------|-----------|--------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | nA | nA | |
| Max Limit | 5 | nA | Min Limit | -5 | nA | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -5.000 | -5.000 | -5.000 | -5.000 | | |
| Min | -0.021 | -0.071 | -0.026 | -0.068 | | |
| Average | -0.021 | 0.010 | 0.000 | -0.026 | | |
| Max | -0.021 | 0.067 | 0.016 | 0.006 | | |
| UL | 5.000 | 5.000 | 5.000 | 5.000 | | |




NDD Report

LMP7704-SP

| 107.2_Ib_res_pos_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | nA | nA | |
| Max Limit | 5 | 5 | Min Limit | -5 | -5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 0.002 | -0.002 | -0.005 | -200.00% | 0.05% |
| 1 | 1 | -0.015 | 0.005 | 0.021 | -133.77% | 0.21% |
| 1 | 2 | -0.009 | 0.036 | 0.045 | -494.44% | 0.45% |
| 1 | 3 | 0.005 | -0.053 | -0.058 | -1121.15% | 0.58% |
| 1 | 4 | -0.004 | 0.036 | 0.040 | -1108.33% | 0.40% |
| 5 | 5 | -0.012 | 0.020 | 0.032 | -270.00% | 0.32% |
| 5 | 6 | -0.003 | -0.017 | -0.014 | 480.00% | 0.14% |
| 5 | 7 | -0.002 | -0.001 | 0.000 | -20.00% | 0.00% |
| 5 | 8 | -0.010 | -0.003 | 0.007 | -66.00% | 0.07% |
| 10 | 9 | -0.001 | -0.033 | -0.032 | 5333.33% | 0.32% |
| 10 | 10 | 0.002 | -0.042 | -0.044 | -2718.75% | 0.44% |
| 10 | 11 | -0.005 | -0.014 | -0.010 | 195.92% | 0.10% |
| 10 | 12 | -0.003 | -0.035 | -0.032 | 972.73% | 0.32% |
| Max | | 0.005 | 0.036 | 0.045 | 5333.33% | 0.58% |
| Average | | -0.004 | -0.008 | -0.004 | 65.35% | 0.26% |
| Min | | -0.015 | -0.053 | -0.058 | -2718.75% | 0.00% |
| Std Dev | | 0.006 | 0.028 | 0.032 | 1822.57% | 0.18% |




| 107.2_Ib_res_pos_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | nA | nA | |
| Max Limit | 5 | nA | Min Limit | -5 | nA | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -5.000 | -5.000 | -5.000 | -5.000 | | |
| Min | -0.003 | -0.053 | -0.017 | -0.042 | | |
| Average | -0.003 | 0.006 | 0.000 | -0.031 | | |
| Max | -0.003 | 0.036 | 0.020 | -0.015 | | |
| UL | 5.000 | 5.000 | 5.000 | 5.000 | | |




NDD Report

LMP7704-SP

| 107.3 Ib_res_pos_D | | | | | | |
|--------------------|-----------|-----------|-----------|--------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | nA | nA | |
| Tester | ETS364 | ETS364 | Max Limit | 5 | 5 | |
| Test Number | EB4632 | EB4632 | Min Limit | -5 | -5 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.007 | 0.007 | 0.014 | -197.10% | 0.14% |
| 1 | 1 | 0.011 | 0.005 | -0.006 | -57.66% | 0.06% |
| 1 | 2 | -0.004 | -0.006 | -0.002 | 48.72% | 0.02% |
| 1 | 3 | -0.001 | -0.036 | -0.035 | 4971.43% | 0.35% |
| 1 | 4 | -0.001 | 0.032 | 0.033 | -6600.00% | 0.33% |
| 5 | 5 | -0.008 | 0.003 | 0.011 | -133.73% | 0.11% |
| 5 | 6 | -0.006 | -0.018 | -0.012 | 193.55% | 0.12% |
| 5 | 7 | 0.011 | 0.014 | 0.003 | 26.17% | 0.03% |
| 5 | 8 | -0.021 | -0.004 | 0.017 | -79.34% | 0.17% |
| 10 | 9 | -0.014 | -0.024 | -0.010 | 76.09% | 0.10% |
| 10 | 10 | -0.010 | -0.032 | -0.022 | 218.00% | 0.22% |
| 10 | 11 | 0.006 | -0.011 | -0.016 | -294.64% | 0.16% |
| 10 | 12 | 0.004 | -0.018 | -0.022 | -516.28% | 0.22% |
| Max | | 0.011 | 0.032 | 0.033 | 4971.43% | 0.35% |
| Average | | -0.003 | -0.007 | -0.004 | -180.37% | 0.16% |
| Min | | -0.021 | -0.036 | -0.035 | -6600.00% | 0.02% |
| Std Dev | | 0.009 | 0.019 | 0.019 | 2386.87% | 0.10% |




| 107.3 Ib_res_pos_D | | | | | | |
|--------------------|-----------|-----------|-----------|--------|----|--|
| Test Site | TI Dallas | TI Dallas | Unit | nA | nA | |
| Tester | ETS364 | ETS364 | Max Limit | 5 | 5 | |
| Test Number | EB4632 | EB4632 | Min Limit | -5 | -5 | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -5.000 | -5.000 | -5.000 | -5.000 | | |
| Min | 0.007 | -0.036 | -0.018 | -0.032 | | |
| Average | 0.007 | -0.001 | -0.002 | -0.021 | | |
| Max | 0.007 | 0.033 | 0.014 | -0.011 | | |
| UL | 5.000 | 5.000 | 5.000 | 5.000 | | |




NDD Report

LMP7704-SP

| 107.4 Ib_res_neg_A | | | | | | |
|--------------------|-----------|-----------|-----------|----------|------------------|----|
| Test Site | TI Dallas | TI Dallas | Unit | nA | Max Limit | 5 |
| Tester | ETS364 | ETS364 | Min Limit | -5 | Max Limit | -5 |
| Test Number | EB4632 | EB4632 | Max Limit | 5 | Min Limit | -5 |
| Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 0.680 | 0.701 | 0.021 | 3.07% | 0.21% | |
| 1 | 0.418 | 1.152 | 0.734 | 175.62% | 7.34% | |
| 1 | -0.967 | -0.759 | 0.208 | -21.49% | 2.08% | |
| 1 | -0.477 | -0.917 | -0.440 | 92.33% | 4.40% | |
| 1 | 0.090 | 0.031 | -0.059 | -65.70% | 0.59% | |
| 5 | 0.438 | 0.255 | -0.184 | -41.89% | 1.84% | |
| 5 | -0.064 | -0.186 | -0.123 | 192.62% | 1.23% | |
| 5 | 0.139 | -0.105 | -0.244 | -175.36% | 2.44% | |
| 5 | -0.364 | -0.631 | -0.267 | 73.27% | 2.67% | |
| 10 | 0.242 | 1.684 | 1.443 | 596.94% | 14.43% | |
| 10 | -0.465 | 0.189 | 0.654 | -140.77% | 6.54% | |
| 10 | -0.686 | -1.250 | -0.564 | 82.20% | 5.64% | |
| 10 | -0.330 | -0.883 | -0.553 | 167.64% | 5.53% | |
| Max | 0.680 | 1.684 | 1.443 | 596.94% | 14.43% | |
| Average | -0.103 | -0.055 | 0.048 | 72.19% | 4.23% | |
| Min | -0.967 | -1.250 | -0.564 | -175.36% | 0.21% | |
| Std Dev | 0.489 | 0.862 | 0.582 | 196.30% | 3.84% | |




| 107.4 Ib_res_neg_A | | | | | | |
|--------------------|-----------|-----------|-----------|--------|-----------|----|
| Test Site | TI Dallas | TI Dallas | Unit | nA | Max Limit | 5 |
| Tester | ETS364 | ETS364 | Min Limit | -5 | Max Limit | -5 |
| Test Number | EB4632 | EB4632 | Max Limit | 5 | Min Limit | -5 |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -5.000 | -5.000 | -5.000 | -5.000 | | |
| Min | -0.701 | -0.917 | -0.631 | -1.250 | | |
| Average | 0.701 | -0.123 | -0.167 | -0.065 | | |
| Max | 0.701 | 1.152 | 0.255 | 1.685 | | |
| UL | 5.000 | 5.000 | 5.000 | 5.000 | | |




NDD Report

LMP7704-SP

| 107.5 Ib_res_neg_B | | | | | | |
|--------------------|-----------|---|-----------|----------|------------------|--|
| Test Site | TI Dallas | TI Dallas | Unit | nA | nA | |
| Tester | ETS364 | ETS364 | Max Limit | 5 | 5 | |
| Test Number | EB4632 | EB4632 <th>Min Limit</th> <td>-5</td> <td>-5</td> <th></th> | Min Limit | -5 | -5 | |
| Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 0.036 | 0.044 | 0.008 | 21.67% | 0.08% | |
| 1 | 0.217 | 0.374 | 0.158 | 72.77% | 1.58% | |
| 1 | 0.655 | 0.966 | 0.311 | 47.47% | 3.11% | |
| 1 | -0.482 | -0.617 | -0.136 | 28.20% | 1.36% | |
| 1 | -0.259 | -0.339 | -0.080 | 30.66% | 0.80% | |
| 5 | -0.288 | -1.262 | -0.973 | 337.48% | 9.73% | |
| 5 | -0.247 | -0.251 | -0.004 | 1.66% | 0.04% | |
| 5 | 0.254 | 0.525 | 0.270 | 106.33% | 2.70% | |
| 5 | -0.201 | -0.828 | -0.626 | 311.02% | 6.26% | |
| 10 | -0.751 | -1.788 | -1.037 | 138.01% | 10.37% | |
| 10 | -0.189 | 0.681 | 0.869 | -460.98% | 8.69% | |
| 10 | -0.678 | -1.919 | -1.242 | 183.20% | 12.42% | |
| 10 | -0.195 | 0.005 | 0.200 | -102.77% | 2.00% | |
| Max | 0.655 | 0.966 | 0.869 | 337.48% | 12.42% | |
| Average | -0.164 | -0.339 | -0.175 | 54.98% | 4.55% | |
| Min | -0.751 | -1.919 | -1.242 | -460.98% | 0.04% | |
| Std Dev | 0.385 | 0.915 | 0.617 | 197.50% | 4.36% | |




| 107.5 Ib_res_neg_B | | | | | | |
|--------------------------------------|-----------|-----------|-----------|--------|----|--|
| Test Site | TI Dallas | TI Dallas | Unit | nA | nA | |
| Tester | ETS364 | ETS364 | Max Limit | 5 | 5 | |
| Test Number | EB4632 | EB4632 | Min Limit | nA | nA | |
| 1*10 ¹² n/cm ² | 0 | 1 | 5 | 10 | | |
| LL | -5.000 | -5.000 | -5.000 | -5.000 | | |
| Min | 0.044 | -0.617 | -1.262 | -1.920 | | |
| Average | 0.044 | 0.096 | -0.454 | -0.755 | | |
| Max | 0.044 | 0.966 | 0.525 | 0.681 | | |
| UL | 5.000 | 5.000 | 5.000 | 5.000 | | |




NDD Report

LMP7704-SP

| 107.6 Ib_res_neg_C | | | | | | |
|--------------------|-----------|-----------|-----------|--------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | nA | nA | |
| Max Limit | 5 | 5 | Min Limit | -5 | -5 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 0.071 | 0.066 | -0.005 | -6.78% | 0.05% |
| 1 | 1 | -0.299 | 0.066 | 0.365 | -122.10% | 3.65% |
| 1 | 2 | 0.659 | 0.345 | -0.314 | -47.68% | 3.14% |
| 1 | 3 | -0.371 | -0.261 | 0.110 | -29.55% | 1.10% |
| 1 | 4 | -0.356 | -0.298 | 0.057 | -16.15% | 0.57% |
| 5 | 5 | -0.199 | -0.565 | -0.366 | 183.98% | 3.66% |
| 5 | 6 | 0.669 | 0.767 | 0.097 | 14.53% | 0.97% |
| 5 | 7 | 0.405 | 0.156 | -0.249 | -61.46% | 2.49% |
| 5 | 8 | 0.028 | -0.006 | -0.035 | -122.54% | 0.35% |
| 10 | 9 | 0.026 | -0.778 | -0.804 | -3114.34% | 8.04% |
| 10 | 10 | -0.582 | -0.832 | -0.250 | 42.97% | 2.50% |
| 10 | 11 | 0.211 | 0.081 | -0.130 | -61.79% | 1.30% |
| 10 | 12 | 0.045 | 0.584 | 0.539 | 1208.30% | 5.39% |
| Max | | 0.669 | 0.767 | 0.539 | 1208.30% | 8.04% |
| Average | | 0.024 | -0.052 | -0.076 | -164.05% | 2.55% |
| Min | | -0.582 | -0.832 | -0.804 | -3114.34% | 0.05% |
| Std Dev | | 0.390 | 0.485 | 0.341 | 952.46% | 2.28% |




| 107.6 Ib_res_neg_C | | | | |
|--------------------|-----------|--------|--------|--------|
| Test Site | TI Dallas | ETS364 | EB4632 | |
| Tester | | | | |
| Test Number | | | | |
| Max Limit | 5 | nA | | |
| Min Limit | -5 | nA | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 |
| LL | -5.000 | -5.000 | -5.000 | -5.000 |
| Min | 0.066 | -0.298 | -0.565 | -0.832 |
| Average | 0.066 | -0.037 | 0.088 | -0.236 |
| Max | 0.066 | 0.345 | 0.767 | 0.584 |
| UL | 5.000 | 5.000 | 5.000 | 5.000 |




NDD Report

LMP7704-SP

| 107.7_Ib_res_neg_D | | | | | | |
|--------------------|-----------|-----------|-----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | nA | nA | |
| Max Limit | 5 | 5 | Min Limit | -5 | -5 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.670 | -0.680 | -0.009 | 1.37% | 0.09% |
| 1 | 1 | -0.559 | -0.591 | -0.032 | 5.82% | 0.32% |
| 1 | 2 | -0.825 | -0.293 | 0.533 | -64.55% | 5.33% |
| 1 | 3 | -0.332 | -0.285 | 0.047 | -14.22% | 0.47% |
| 1 | 4 | 0.385 | 0.317 | -0.069 | -17.83% | 0.69% |
| 5 | 5 | 0.077 | 0.119 | 0.041 | 53.56% | 0.41% |
| 5 | 6 | 0.461 | 0.443 | -0.018 | -3.95% | 0.18% |
| 5 | 7 | -0.491 | 0.426 | 0.916 | -186.79% | 9.16% |
| 5 | 8 | 0.477 | 2.075 | 1.598 | 335.31% | 15.98% |
| 10 | 9 | -0.144 | 0.133 | 0.278 | -192.31% | 2.78% |
| 10 | 10 | -0.424 | 0.152 | 0.576 | -135.92% | 5.76% |
| 10 | 11 | -0.621 | -1.260 | -0.639 | 102.85% | 6.39% |
| 10 | 12 | -0.155 | -0.300 | -0.145 | 93.92% | 1.45% |
| Max | | 0.477 | 2.075 | 1.598 | 335.31% | 15.98% |
| Average | | -0.217 | 0.020 | 0.237 | -1.75% | 3.77% |
| Min | | -0.825 | -1.260 | -0.639 | -192.31% | 0.09% |
| Std Dev | | 0.446 | 0.790 | 0.563 | 138.37% | 4.72% |




| 107.7_Ib_res_neg_D | | | | |
|--------------------|-----------|--------|--------|--------|
| Test Site | TI Dallas | ETS364 | EB4632 | |
| Test Number | | | | |
| Max Limit | 5 | nA | | |
| Min Limit | -5 | nA | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 |
| LL | -5.000 | -5.000 | -5.000 | -5.000 |
| Min | -0.680 | -0.591 | 0.119 | -1.260 |
| Average | -0.680 | -0.213 | 0.766 | -0.319 |
| Max | -0.680 | 0.317 | 2.075 | 0.152 |
| UL | 5.000 | 5.000 | 5.000 | 5.000 |




NDD Report

LMP7704-SP

| 120.0_Ibp_cap_5V_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 0.053 | -0.262 | -0.315 | -595.84% | 1.58% |
| 1 | 1 | 0.007 | -0.070 | -0.078 | -1048.65% | 0.39% |
| 1 | 2 | 0.001 | -0.047 | -0.048 | -4840.00% | 0.24% |
| 1 | 3 | 0.113 | -0.077 | -0.190 | -167.99% | 0.95% |
| 1 | 4 | 0.003 | -0.017 | -0.020 | -654.84% | 0.10% |
| 5 | 5 | 0.081 | -0.410 | -0.491 | -608.56% | 2.45% |
| 5 | 6 | 0.025 | -0.375 | -0.400 | -1592.43% | 2.00% |
| 5 | 7 | 0.073 | -0.478 | -0.551 | -750.20% | 2.76% |
| 5 | 8 | 0.040 | -0.368 | -0.408 | -1016.96% | 2.04% |
| 10 | 9 | 0.103 | -0.653 | -0.756 | -735.93% | 3.78% |
| 10 | 10 | 0.037 | -0.606 | -0.643 | -1751.77% | 3.21% |
| 10 | 11 | 0.088 | -0.583 | -0.671 | -759.91% | 3.36% |
| 10 | 12 | 0.013 | -0.620 | -0.632 | -5058.40% | 3.16% |
| Max | | 0.113 | -0.017 | -0.020 | -167.99% | 3.78% |
| Average | | 0.049 | -0.351 | -0.400 | -1506.27% | 2.00% |
| Min | | 0.001 | -0.653 | -0.756 | -5058.40% | 0.10% |
| Std Dev | | 0.039 | 0.236 | 0.253 | 1584.32% | 1.26% |




| 120.0_Ibp_cap_5V_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | -0.262 | -0.077 | -0.478 | -0.653 | | |
| Average | -0.262 | -0.053 | -0.408 | -0.615 | | |
| Max | -0.262 | -0.017 | -0.368 | -0.583 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 120.1_Ibp_cap_5V_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 0.103 | -0.121 | -0.224 | -218.01% | 1.12% |
| 1 | 1 | 0.051 | 0.093 | 0.042 | 81.52% | 0.21% |
| 1 | 2 | 0.084 | -0.026 | -0.110 | -130.57% | 0.55% |
| 1 | 3 | 0.046 | 0.008 | -0.038 | -82.61% | 0.19% |
| 1 | 4 | 0.017 | 0.058 | 0.041 | 243.45% | 0.20% |
| 5 | 5 | 0.090 | -0.322 | -0.412 | -455.58% | 2.06% |
| 5 | 6 | 0.146 | -0.452 | -0.598 | -408.89% | 2.99% |
| 5 | 7 | 0.149 | -0.225 | -0.374 | -250.47% | 1.87% |
| 5 | 8 | 0.083 | -0.327 | -0.410 | -493.73% | 2.05% |
| 10 | 9 | 0.131 | -0.540 | -0.670 | -512.85% | 3.35% |
| 10 | 10 | 0.178 | -0.669 | -0.847 | -475.79% | 4.23% |
| 10 | 11 | 0.586 | -0.563 | -1.148 | -196.01% | 5.74% |
| 10 | 12 | 0.184 | -0.644 | -0.828 | -450.19% | 4.14% |
| Max | | 0.586 | 0.093 | 0.042 | 243.45% | 5.74% |
| Average | | 0.142 | -0.287 | -0.429 | -257.67% | 2.21% |
| Min | | 0.017 | -0.669 | -1.148 | -512.85% | 0.19% |
| Std Dev | | 0.143 | 0.273 | 0.374 | 239.08% | 1.79% |




| 120.1_Ibp_cap_5V_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | -0.121 | -0.026 | -0.452 | -0.669 | | |
| Average | -0.121 | 0.033 | -0.331 | -0.604 | | |
| Max | -0.121 | 0.093 | -0.225 | -0.540 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 120.2_Ibp_cap_5V_C | | | | | | |
|--------------------|-----------|-----------|-----------|-----------|------------------|---------|
| Test Site | TI Dallas | TI Dallas | Unit | pA | Max Limit | 10 |
| Tester | ETS364 | ETS364 | Min Limit | -10 | Delta | Delta % |
| Test Number | EB4632 | EB4632 | Delta % | | % of Limit Range | |
| Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 0.101 | -0.128 | -0.229 | -226.76% | 1.14% | |
| 1 | 0.012 | -0.063 | -0.075 | -641.88% | 0.38% | |
| 1 | 2 | -0.037 | -0.069 | 87.50% | 0.16% | |
| 1 | 3 | 0.140 | 0.012 | -91.25% | 0.64% | |
| 1 | 4 | 0.026 | 0.084 | 218.56% | 0.29% | |
| 5 | 5 | 0.078 | -0.449 | -678.38% | 2.64% | |
| 5 | 6 | 0.118 | -0.407 | -445.16% | 2.62% | |
| 5 | 7 | 0.101 | -0.433 | -526.73% | 2.67% | |
| 5 | 8 | 0.059 | -0.343 | -680.85% | 2.01% | |
| 10 | 9 | 0.111 | -0.678 | -709.81% | 3.94% | |
| 10 | 10 | 0.045 | -0.723 | -1719.96% | 3.84% | |
| 10 | 11 | 0.126 | -0.561 | -546.97% | 3.43% | |
| 10 | 12 | 0.064 | -0.690 | -1184.59% | 3.77% | |
| Max | 0.140 | 0.084 | 0.058 | 218.56% | 3.94% | |
| Average | 0.073 | -0.342 | -0.415 | -549.71% | 2.12% | |
| Min | -0.037 | -0.723 | -0.789 | -1719.96% | 0.16% | |
| Std Dev | 0.051 | 0.282 | 0.302 | 513.38% | 1.44% | |




| 120.2_Ibp_cap_5V_C | | | | | | |
|--------------------|-----------|---------|-----------|---------|------------------|---------|
| Test Site | TI Dallas | ETS364 | Unit | pA | Max Limit | 10 |
| Tester | ETS364 | ETS364 | Min Limit | -10 | Delta | Delta % |
| Test Number | EB4632 | EB4632 | Delta % | | % of Limit Range | |
| Serial # | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | -0.128 | -0.069 | -0.449 | -0.723 | | |
| Average | -0.128 | -0.009 | -0.408 | -0.663 | | |
| Max | -0.128 | 0.084 | -0.343 | -0.561 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 120.3_Ibp_cap_5V_D | | | | | | | |
|--------------------|-----------|-----------|-----------|--------|----------|------------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | pA | pA | Max Limit | 10 | 10 | Min Limit | -10 |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 13 | 0.103 | -0.303 | -0.406 | -393.60% | 2.03% | |
| 1 | 1 | 0.047 | 0.003 | -0.044 | -92.75% | 0.22% | |
| 1 | 2 | 0.062 | -0.021 | -0.083 | -133.55% | 0.42% | |
| 1 | 3 | 0.114 | -0.043 | -0.156 | -137.52% | 0.78% | |
| 1 | 4 | -0.035 | -0.050 | -0.014 | 40.68% | 0.07% | |
| 5 | 5 | 0.082 | -0.492 | -0.574 | -698.05% | 2.87% | |
| 5 | 6 | 0.049 | -0.401 | -0.450 | -924.44% | 2.25% | |
| 5 | 7 | 0.156 | -0.353 | -0.509 | -326.33% | 2.55% | |
| 5 | 8 | 0.193 | -0.383 | -0.576 | -298.19% | 2.88% | |
| 10 | 9 | 0.143 | -0.506 | -0.648 | -453.99% | 3.24% | |
| 10 | 10 | -0.065 | -0.701 | -0.637 | 985.91% | 3.18% | |
| 10 | 11 | 0.166 | -0.661 | -0.827 | -497.89% | 4.13% | |
| 10 | 12 | 0.106 | -0.774 | -0.880 | -829.72% | 4.40% | |
| Max | | 0.193 | 0.003 | -0.014 | 985.91% | 4.40% | |
| Average | | 0.086 | -0.360 | -0.447 | -289.19% | 2.23% | |
| Min | | -0.065 | -0.774 | -0.880 | -924.44% | 0.07% | |
| Std Dev | | 0.076 | 0.269 | 0.291 | 480.15% | 1.45% | |




| 120.3_Ibp_cap_5V_D | | | | | | | |
|--------------------|-----------|-----------|-----------|---------|--------|-------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | pA | pA | Max Limit | 10 | pA | Min Limit | -10 |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | | |
| Min | -0.303 | -0.050 | -0.492 | -0.774 | | | |
| Average | -0.303 | -0.028 | -0.407 | -0.660 | | | |
| Max | -0.303 | 0.003 | -0.353 | -0.506 | | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | | |




NDD Report

LMP7704-SP

| 120.4 Ibn_cap_5V_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.310 | -0.398 | -0.088 | 28.26% | 0.44% |
| 1 | 1 | -0.251 | -0.319 | -0.068 | 26.94% | 0.34% |
| 1 | 2 | -0.299 | -0.396 | -0.096 | 32.18% | 0.48% |
| 1 | 3 | -0.196 | -0.317 | -0.121 | 61.55% | 0.60% |
| 1 | 4 | -0.293 | -0.323 | -0.030 | 10.25% | 0.15% |
| 5 | 5 | 0.123 | -0.559 | -0.682 | -555.25% | 3.41% |
| 5 | 6 | -0.318 | -0.687 | -0.369 | 115.95% | 1.84% |
| 5 | 7 | -0.233 | -0.621 | -0.388 | 167.10% | 1.94% |
| 5 | 8 | -0.254 | -0.498 | -0.244 | 95.91% | 1.22% |
| 10 | 9 | -0.820 | -0.806 | 0.014 | -1.68% | 0.07% |
| 10 | 10 | -0.349 | -0.693 | -0.344 | 98.82% | 1.72% |
| 10 | 11 | -0.623 | -0.823 | -0.201 | 32.19% | 1.00% |
| 10 | 12 | -0.364 | -0.746 | -0.382 | 104.95% | 1.91% |
| Max | | 0.123 | -0.317 | 0.014 | 167.10% | 3.41% |
| Average | | -0.322 | -0.553 | -0.231 | 16.70% | 1.16% |
| Min | | -0.820 | -0.823 | -0.682 | -555.25% | 0.07% |
| Std Dev | | 0.219 | 0.190 | 0.196 | 178.77% | 0.97% |




| 120.4 Ibn_cap_5V_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | -0.398 | -0.396 | -0.687 | -0.823 | | |
| Average | -0.398 | -0.338 | -0.591 | -0.767 | | |
| Max | -0.398 | -0.317 | -0.498 | -0.693 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 120.8_Ios_cap_5V_A | | | | | | |
|--------------------|-----------|-----------|-----------|--------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | pA | Max Limit | 10 |
| Tester | ETS364 | ETS364 | Min Limit | -10 | Max Limit | -10 |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 0.363 | 0.135 | -0.228 | -62.72% | 1.14% |
| 1 | 1 | 0.258 | 0.248 | -0.010 | -3.87% | 0.05% |
| 1 | 2 | 0.300 | 0.348 | 0.048 | 15.98% | 0.24% |
| 1 | 3 | 0.309 | 0.240 | -0.069 | -22.44% | 0.35% |
| 1 | 4 | 0.296 | 0.306 | 0.010 | 3.28% | 0.05% |
| 5 | 5 | -0.042 | 0.150 | 0.192 | -452.83% | 0.96% |
| 5 | 6 | 0.343 | 0.312 | -0.031 | -9.04% | 0.16% |
| 5 | 7 | 0.306 | 0.143 | -0.163 | -53.24% | 0.81% |
| 5 | 8 | 0.294 | 0.130 | -0.164 | -55.73% | 0.82% |
| 10 | 9 | 0.923 | 0.153 | -0.770 | -83.41% | 3.85% |
| 10 | 10 | 0.385 | 0.087 | -0.298 | -77.45% | 1.49% |
| 10 | 11 | 0.711 | 0.241 | -0.470 | -66.15% | 2.35% |
| 10 | 12 | 0.377 | 0.126 | -0.251 | -66.53% | 1.25% |
| Max | | 0.923 | 0.348 | 0.192 | 15.98% | 3.85% |
| Average | | 0.371 | 0.201 | -0.170 | -71.86% | 1.04% |
| Min | | -0.042 | 0.087 | -0.770 | -452.83% | 0.05% |
| Std Dev | | 0.229 | 0.085 | 0.249 | 119.17% | 1.07% |




| 120.8_Ios_cap_5V_A | | | | | | |
|--------------------|-----------|---------|-----------|---------|-----------|-----|
| Test Site | TI Dallas | ETS364 | Unit | pA | Max Limit | 10 |
| Tester | ETS364 | ETS364 | Min Limit | -10 | Max Limit | -10 |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | 0.135 | 0.240 | 0.130 | 0.087 | | |
| Average | 0.135 | 0.286 | 0.184 | 0.152 | | |
| Max | 0.135 | 0.348 | 0.312 | 0.241 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 120.5 Ibn_cap_5V_B | | | | | | |
|--------------------|-----------|---|-----------|----------|------------------|----|
| Test Site | TI Dallas | TI Dallas | Unit | pA | Max Limit | 10 |
| Tester | ETS364 | ETS364 | Min Limit | -10 | Delta | |
| Test Number | EB4632 | EB4632 <th>Delta %</th> <td></td> <th>% of Limit Range</th> <td></td> | Delta % | | % of Limit Range | |
| Serial # | PRE NDD | POST NDD | | | | |
| 0 | 0.218 | -0.181 | -0.399 | -183.32% | 1.99% | |
| 1 | -0.217 | -0.293 | -0.075 | 34.71% | 0.38% | |
| 1 | -0.200 | -0.471 | -0.271 | 135.40% | 1.35% | |
| 1 | -0.099 | -0.177 | -0.078 | 78.55% | 0.39% | |
| 1 | -0.330 | -0.267 | 0.063 | -19.02% | 0.31% | |
| 5 | 0.161 | -0.432 | -0.593 | -369.24% | 2.96% | |
| 5 | -0.214 | -0.663 | -0.449 | 209.28% | 2.24% | |
| 5 | -0.151 | -0.224 | -0.073 | 48.47% | 0.37% | |
| 5 | -0.183 | -0.437 | -0.254 | 138.82% | 1.27% | |
| 10 | -0.858 | -0.656 | 0.202 | -23.52% | 1.01% | |
| 10 | -0.389 | -0.651 | -0.261 | 67.13% | 1.31% | |
| 10 | -0.498 | -0.559 | -0.060 | 12.14% | 0.30% | |
| 10 | -0.296 | -0.562 | -0.266 | 89.95% | 1.33% | |
| Max | 0.218 | -0.177 | 0.202 | 209.28% | 2.96% | |
| Average | -0.235 | -0.429 | -0.193 | 16.87% | 1.17% | |
| Min | -0.858 | -0.663 | -0.593 | -369.24% | 0.30% | |
| Std Dev | 0.272 | 0.183 | 0.218 | 150.29% | 0.84% | |




| 120.5 Ibn_cap_5V_B | | | | | | |
|--------------------|-----------|---------|-----------|---------|------------------|----|
| Test Site | TI Dallas | ETS364 | Unit | pA | Max Limit | 10 |
| Tester | ETS364 | ETS364 | Min Limit | -10 | Delta | |
| Test Number | EB4632 | EB4632 | Delta % | | % of Limit Range | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | -0.181 | -0.471 | -0.663 | -0.656 | | |
| Average | -0.181 | -0.302 | -0.439 | -0.607 | | |
| Max | -0.181 | -0.177 | -0.224 | -0.559 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 120.9_Ios_cap_5V_B | | | | | | |
|--------------------|-----------|-----------|-----------|----------|------------------|----|
| Test Site | TI Dallas | TI Dallas | Unit | pA | Max Limit | 10 |
| Tester | ETS364 | ETS364 | Min Limit | -10 | Delta | |
| Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 0.115 | 0.060 | 0.175 | -152.31% | 0.88% | |
| 1 | 0.269 | 0.386 | 0.117 | 43.67% | 0.59% | |
| 1 | 0.285 | 0.445 | 0.160 | 56.41% | 0.80% | |
| 1 | 0.145 | 0.185 | 0.040 | 27.53% | 0.20% | |
| 1 | 0.347 | 0.325 | -0.022 | -6.32% | 0.11% | |
| 5 | 0.070 | 0.111 | 0.181 | -257.77% | 0.90% | |
| 5 | 0.361 | 0.212 | -0.149 | -41.38% | 0.75% | |
| 5 | 0.300 | -0.001 | -0.301 | -100.30% | 1.51% | |
| 5 | 0.266 | 0.110 | -0.156 | -58.63% | 0.78% | |
| 10 | 0.988 | 0.116 | -0.872 | -88.22% | 4.36% | |
| 10 | 0.567 | -0.018 | -0.585 | -103.19% | 2.93% | |
| 10 | 1.084 | -0.004 | -1.088 | -100.35% | 5.44% | |
| 10 | 0.479 | -0.083 | -0.562 | -117.21% | 2.81% | |
| Max | 1.084 | 0.445 | 0.181 | 56.41% | 5.44% | |
| Average | 0.377 | 0.142 | -0.236 | -69.08% | 1.70% | |
| Min | -0.115 | -0.083 | -1.088 | -257.77% | 0.11% | |
| Std Dev | 0.348 | 0.163 | 0.421 | 87.05% | 1.68% | |




| 120.9_Ios_cap_5V_B | | | | | | |
|--------------------|-----------|----------|-----------|---------|------------------|----|
| Test Site | TI Dallas | ETS364 | Unit | pA | Max Limit | 10 |
| Tester | ETS364 | ETS364 | Min Limit | -10 | Delta | |
| Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | -10.000 | |
| Min | 0.060 | 0.185 | -0.001 | -0.083 | -0.083 | |
| Average | 0.060 | 0.335 | 0.108 | 0.003 | 0.003 | |
| Max | 0.060 | 0.445 | 0.212 | 0.116 | 0.116 | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | 10.000 | |




NDD Report

LMP7704-SP

| 120.6 Ibn_cap_5V_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.285 | -0.230 | 0.055 | -19.34% | 0.28% |
| 1 | 1 | -0.395 | -0.425 | -0.030 | 7.70% | 0.15% |
| 1 | 2 | -0.318 | -0.361 | -0.043 | 13.64% | 0.22% |
| 1 | 3 | -0.225 | -0.213 | 0.011 | -5.07% | 0.06% |
| 1 | 4 | -0.420 | -0.302 | 0.119 | -28.22% | 0.59% |
| 5 | 5 | -0.011 | -0.541 | -0.530 | 4772.97% | 2.65% |
| 5 | 6 | -0.263 | -0.626 | -0.363 | 138.19% | 1.82% |
| 5 | 7 | -0.225 | -0.470 | -0.246 | 109.40% | 1.23% |
| 5 | 8 | -0.349 | -0.490 | -0.141 | 40.44% | 0.71% |
| 10 | 9 | -0.688 | -0.795 | -0.107 | 15.60% | 0.54% |
| 10 | 10 | -0.349 | -0.665 | -0.316 | 90.38% | 1.58% |
| 10 | 11 | -0.528 | -0.674 | -0.146 | 27.71% | 0.73% |
| 10 | 12 | -0.294 | -0.722 | -0.428 | 145.56% | 2.14% |
| Max | | -0.011 | -0.213 | 0.119 | 4772.97% | 2.65% |
| Average | | -0.335 | -0.501 | -0.167 | 408.38% | 0.98% |
| Min | | -0.688 | -0.795 | -0.530 | -28.22% | 0.06% |
| Std Dev | | 0.161 | 0.190 | 0.197 | 1312.68% | 0.83% |






| 120.6 Ibn_cap_5V_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | -0.230 | -0.425 | -0.626 | -0.795 | | |
| Average | -0.230 | -0.325 | -0.532 | -0.714 | | |
| Max | -0.230 | -0.213 | -0.470 | -0.665 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |



NDD Report

LMP7704-SP


| 120.10_Ios_cap_5V_C | | | | | | |
|---------------------|-----------|---|-----------|----------|------------------|----|
| Test Site | TI Dallas | TI Dallas | Unit | pA | Max Limit | 10 |
| Tester | ETS364 | ETS364 | Min Limit | -10 | Delta | |
| Test Number | EB4632 | EB4632 <th>Delta %</th> <td></td> <th>% of Limit Range</th> <td></td> | Delta % | | % of Limit Range | |
| Serial # | PRE NDD | POST NDD | | | | |
| 0 | 0.386 | 0.102 | -0.284 | -73.52% | 1.42% | |
| 1 | 0.407 | 0.362 | -0.045 | -10.99% | 0.22% | |
| 1 | 0.281 | 0.293 | 0.011 | 4.02% | 0.06% | |
| 1 | 0.364 | 0.226 | -0.139 | -38.07% | 0.69% | |
| 1 | 0.447 | 0.386 | -0.061 | -13.61% | 0.30% | |
| 5 | 0.089 | 0.091 | 0.003 | 3.04% | 0.01% | |
| 5 | 0.381 | 0.220 | -0.161 | -42.36% | 0.81% | |
| 5 | 0.326 | 0.037 | -0.288 | -88.52% | 1.44% | |
| 5 | 0.408 | 0.148 | -0.260 | -63.82% | 1.30% | |
| 10 | 0.799 | 0.118 | -0.681 | -85.26% | 3.41% | |
| 10 | 0.394 | -0.058 | -0.452 | -114.71% | 2.26% | |
| 10 | 0.654 | 0.113 | -0.541 | -82.74% | 2.70% | |
| 10 | 0.358 | 0.032 | -0.325 | -90.97% | 1.63% | |
| Max | 0.799 | 0.386 | 0.011 | 4.02% | 3.41% | |
| Average | 0.407 | 0.159 | -0.248 | -53.65% | 1.25% | |
| Min | 0.089 | -0.058 | -0.681 | -114.71% | 0.01% | |
| Std Dev | 0.170 | 0.132 | 0.214 | 39.80% | 1.06% | |




NDD Report

LMP7704-SP

| 120.7_Ibn_cap_5V_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.334 | -0.526 | -0.192 | 57.53% | 0.96% |
| 1 | 1 | -0.227 | -0.444 | -0.217 | 95.59% | 1.08% |
| 1 | 2 | -0.106 | -0.448 | -0.342 | 323.25% | 1.71% |
| 1 | 3 | -0.307 | -0.445 | -0.138 | 44.95% | 0.69% |
| 1 | 4 | -0.314 | -0.513 | -0.199 | 63.44% | 1.00% |
| 5 | 5 | 0.052 | -0.603 | -0.655 | -1259.04% | 3.27% |
| 5 | 6 | -0.298 | -0.706 | -0.408 | 136.82% | 2.04% |
| 5 | 7 | -0.245 | -0.638 | -0.393 | 160.40% | 1.97% |
| 5 | 8 | -0.087 | -0.545 | -0.459 | 529.56% | 2.29% |
| 10 | 9 | -0.839 | -0.872 | -0.032 | 3.87% | 0.16% |
| 10 | 10 | -0.310 | -0.673 | -0.363 | 116.82% | 1.81% |
| 10 | 11 | -0.530 | -0.813 | -0.283 | 53.30% | 1.41% |
| 10 | 12 | -0.327 | -0.925 | -0.599 | 183.31% | 2.99% |
| Max | | 0.052 | -0.444 | -0.032 | 529.56% | 3.27% |
| Average | | -0.298 | -0.627 | -0.329 | 39.22% | 1.65% |
| Min | | -0.839 | -0.925 | -0.655 | -1259.04% | 0.16% |
| Std Dev | | 0.216 | 0.164 | 0.178 | 414.64% | 0.89% |




| 120.7_Ibn_cap_5V_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | -0.526 | -0.513 | -0.706 | -0.925 | | |
| Average | -0.526 | -0.462 | -0.623 | -0.821 | | |
| Max | -0.526 | -0.444 | -0.545 | -0.673 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 120.11_Ios_cap_5V_D | | | | | | |
|---------------------|-----------|-----------|-----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | pA | pA | |
| Tester | ETS364 | ETS364 | Max Limit | 10 | 10 | |
| Test Number | EB4632 | EB4632 | Min Limit | -10 | -10 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 0.437 | 0.223 | -0.214 | -48.96% | 1.07% |
| 1 | 1 | 0.274 | 0.447 | 0.173 | 63.32% | 0.87% |
| 1 | 2 | 0.168 | 0.427 | 0.259 | 153.96% | 1.29% |
| 1 | 3 | 0.421 | 0.403 | -0.018 | -4.37% | 0.09% |
| 1 | 4 | 0.278 | 0.463 | 0.185 | 66.33% | 0.92% |
| 5 | 5 | 0.030 | 0.111 | 0.081 | 267.88% | 0.40% |
| 5 | 6 | 0.347 | 0.304 | -0.043 | -12.29% | 0.21% |
| 5 | 7 | 0.401 | 0.285 | -0.116 | -28.96% | 0.58% |
| 5 | 8 | 0.280 | 0.162 | -0.118 | -42.12% | 0.59% |
| 10 | 9 | 0.982 | 0.366 | -0.616 | -62.70% | 3.08% |
| 10 | 10 | 0.246 | -0.029 | -0.274 | -111.68% | 1.37% |
| 10 | 11 | 0.696 | 0.152 | -0.544 | -78.18% | 2.72% |
| 10 | 12 | 0.433 | 0.152 | -0.281 | -64.91% | 1.40% |
| Max | | 0.982 | 0.463 | 0.259 | 267.88% | 3.08% |
| Average | | 0.384 | 0.267 | -0.117 | 7.49% | 1.12% |
| Min | | 0.030 | -0.029 | -0.616 | -111.68% | 0.09% |
| Std Dev | | 0.239 | 0.152 | 0.268 | 106.09% | 0.90% |




| 120.11_Ios_cap_5V_D | | | | | | |
|---------------------|-----------|-----------|-----------|---------|-----|--|
| Test Site | TI Dallas | TI Dallas | Unit | pA | pA | |
| Tester | ETS364 | ETS364 | Max Limit | 10 | 10 | |
| Test Number | EB4632 | EB4632 | Min Limit | -10 | -10 | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | 0.223 | 0.403 | 0.111 | -0.029 | | |
| Average | 0.223 | 0.435 | 0.216 | 0.160 | | |
| Max | 0.223 | 0.463 | 0.304 | 0.366 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 120.12_Ibp_cap_10V_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.723 | -0.990 | -0.267 | 36.97% | 1.34% |
| 1 | 1 | -0.705 | -0.951 | -0.247 | 34.98% | 1.23% |
| 1 | 2 | -0.717 | -0.786 | -0.069 | 9.69% | 0.35% |
| 1 | 3 | -0.657 | -0.834 | -0.177 | 26.88% | 0.88% |
| 1 | 4 | -0.710 | -0.731 | -0.021 | 2.89% | 0.10% |
| 5 | 5 | 0.488 | -1.129 | -1.617 | -331.23% | 8.09% |
| 5 | 6 | -0.743 | -1.034 | -0.291 | 39.13% | 1.45% |
| 5 | 7 | -0.691 | -0.964 | -0.273 | 39.51% | 1.36% |
| 5 | 8 | -0.676 | -1.024 | -0.348 | 51.57% | 1.74% |
| 10 | 9 | -0.630 | -1.269 | -0.640 | 101.56% | 3.20% |
| 10 | 10 | -0.638 | -1.168 | -0.530 | 83.04% | 2.65% |
| 10 | 11 | -0.652 | -1.280 | -0.628 | 96.35% | 3.14% |
| 10 | 12 | -0.738 | -1.181 | -0.444 | 60.12% | 2.22% |
| Max | | 0.488 | -0.731 | -0.021 | 101.56% | 8.09% |
| Average | | -0.599 | -1.026 | -0.427 | 19.34% | 2.14% |
| Min | | -0.743 | -1.280 | -1.617 | -331.23% | 0.10% |
| Std Dev | | 0.329 | 0.176 | 0.406 | 109.59% | 2.03% |




| 120.12_Ibp_cap_10V_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | pA | Min Limit | -10 | pA | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | -0.990 | -0.952 | -1.129 | -1.280 | | |
| Average | -0.990 | -0.826 | -1.038 | -1.225 | | |
| Max | -0.990 | -0.731 | -0.964 | -1.168 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 120.13_Ibp_cap_10V_B | | | | | | |
|----------------------|-----------|-----------|-----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -1.219 | -1.389 | -0.171 | 14.03% | 0.85% |
| 1 | 1 | -1.240 | -1.349 | -0.110 | 8.86% | 0.55% |
| 1 | 2 | -1.235 | -1.313 | -0.077 | 6.27% | 0.39% |
| 1 | 3 | -1.261 | -1.257 | 0.004 | -0.36% | 0.02% |
| 1 | 4 | -1.279 | -1.264 | 0.015 | -1.17% | 0.07% |
| 5 | 5 | -0.070 | -1.594 | -1.524 | 2177.57% | 7.62% |
| 5 | 6 | -1.256 | -1.644 | -0.388 | 30.88% | 1.94% |
| 5 | 7 | -1.178 | -1.392 | -0.214 | 18.14% | 1.07% |
| 5 | 8 | -1.206 | -1.481 | -0.275 | 22.82% | 1.38% |
| 10 | 9 | -1.164 | -1.660 | -0.496 | 42.60% | 2.48% |
| 10 | 10 | -1.131 | -1.840 | -0.709 | 62.65% | 3.54% |
| 10 | 11 | -0.814 | -1.744 | -0.930 | 114.29% | 4.65% |
| 10 | 12 | -1.135 | -1.658 | -0.523 | 46.09% | 2.62% |
| Max | | -0.070 | -1.257 | 0.015 | 2177.57% | 7.62% |
| Average | | -1.091 | -1.507 | -0.415 | 195.59% | 2.09% |
| Min | | -1.279 | -1.840 | -1.524 | -1.17% | 0.02% |
| Std Dev | | 0.329 | 0.194 | 0.437 | 596.35% | 2.17% |




| 120.13_Ibp_cap_10V_B | | | | | | |
|----------------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | -1.389 | -1.349 | -1.644 | -1.840 | | |
| Average | -1.389 | -1.296 | -1.528 | -1.726 | | |
| Max | -1.389 | -1.257 | -1.392 | -1.658 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 120.14_Ibp_cap_10V_C | | | | | | |
|----------------------|-----------|-----------|-----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.768 | -0.908 | -0.139 | 18.16% | 0.70% |
| 1 | 1 | -0.768 | -0.994 | -0.226 | 29.38% | 1.13% |
| 1 | 2 | -0.812 | -0.859 | -0.047 | 5.83% | 0.24% |
| 1 | 3 | -0.764 | -0.772 | -0.008 | 0.99% | 0.04% |
| 1 | 4 | -0.766 | -0.702 | 0.064 | -8.38% | 0.32% |
| 5 | 5 | 0.300 | -1.123 | -1.423 | -474.87% | 7.12% |
| 5 | 6 | -0.762 | -1.098 | -0.336 | 44.05% | 1.68% |
| 5 | 7 | -0.733 | -1.054 | -0.321 | 43.73% | 1.60% |
| 5 | 8 | -0.766 | -1.030 | -0.263 | 34.37% | 1.32% |
| 10 | 9 | -0.715 | -1.435 | -0.719 | 100.55% | 3.60% |
| 10 | 10 | -0.761 | -1.287 | -0.526 | 69.08% | 2.63% |
| 10 | 11 | -0.730 | -1.255 | -0.525 | 71.87% | 2.62% |
| 10 | 12 | -0.777 | -1.292 | -0.515 | 66.29% | 2.57% |
| Max | | 0.300 | -0.702 | 0.064 | 100.55% | 7.12% |
| Average | | -0.679 | -1.062 | -0.383 | 0.08% | 1.97% |
| Min | | -0.812 | -1.435 | -1.423 | -474.87% | 0.04% |
| Std Dev | | 0.295 | 0.218 | 0.389 | 146.14% | 1.89% |




| 120.14_Ibp_cap_10V_C | | | | | | |
|----------------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | -0.908 | -0.994 | -1.124 | -1.435 | | |
| Average | -0.908 | -0.832 | -1.076 | -1.317 | | |
| Max | -0.908 | -0.702 | -1.030 | -1.256 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 120.15_Ibp_cap_10V_D | | | | | | |
|----------------------|-----------|-----------|-----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -1.185 | -1.363 | -0.178 | 15.05% | 0.89% |
| 1 | 1 | -1.194 | -1.331 | -0.137 | 11.43% | 0.68% |
| 1 | 2 | -1.092 | -1.214 | -0.122 | 11.12% | 0.61% |
| 1 | 3 | -1.105 | -1.270 | -0.165 | 14.97% | 0.83% |
| 1 | 4 | -1.178 | -1.216 | -0.038 | 3.20% | 0.19% |
| 5 | 5 | -0.031 | -1.555 | -1.524 | 4869.33% | 7.62% |
| 5 | 6 | -1.169 | -1.518 | -0.349 | 29.85% | 1.74% |
| 5 | 7 | -1.132 | -1.399 | -0.267 | 23.55% | 1.33% |
| 5 | 8 | -1.072 | -1.443 | -0.371 | 34.61% | 1.85% |
| 10 | 9 | -1.077 | -1.574 | -0.497 | 46.16% | 2.49% |
| 10 | 10 | -1.250 | -1.714 | -0.464 | 37.11% | 2.32% |
| 10 | 11 | -1.086 | -1.809 | -0.724 | 66.64% | 3.62% |
| 10 | 12 | -1.157 | -1.760 | -0.603 | 52.13% | 3.01% |
| Max | | -0.031 | -1.214 | -0.038 | 4869.33% | 7.62% |
| Average | | -1.056 | -1.474 | -0.418 | 401.16% | 2.09% |
| Min | | -1.250 | -1.809 | -1.524 | 3.20% | 0.19% |
| Std Dev | | 0.313 | 0.201 | 0.390 | 1342.64% | 1.95% |




| 120.15_Ibp_cap_10V_D | | | | | | |
|----------------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | -1.363 | -1.331 | -1.555 | -1.810 | | |
| Average | -1.363 | -1.258 | -1.479 | -1.714 | | |
| Max | -1.363 | -1.214 | -1.399 | -1.574 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 120.16_Ibn_cap_10V_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -1.455 | -1.604 | -0.149 | 10.24% | 0.75% |
| 1 | 1 | -1.322 | -1.423 | -0.102 | 7.69% | 0.51% |
| 1 | 2 | -1.370 | -1.510 | -0.140 | 10.18% | 0.70% |
| 1 | 3 | -1.296 | -1.556 | -0.260 | 20.07% | 1.30% |
| 1 | 4 | -1.362 | -1.529 | -0.167 | 12.27% | 0.84% |
| 5 | 5 | -2.673 | -1.863 | 0.810 | -30.30% | 4.05% |
| 5 | 6 | -1.426 | -1.636 | -0.211 | 14.77% | 1.05% |
| 5 | 7 | -1.341 | -1.899 | -0.558 | 41.61% | 2.79% |
| 5 | 8 | -1.411 | -1.778 | -0.368 | 26.05% | 1.84% |
| 10 | 9 | -1.622 | -2.086 | -0.464 | 28.58% | 2.32% |
| 10 | 10 | -1.442 | -2.119 | -0.677 | 46.98% | 3.39% |
| 10 | 11 | -0.326 | -2.089 | -1.763 | 540.10% | 8.81% |
| 10 | 12 | -1.454 | -2.196 | -0.743 | 51.09% | 3.71% |
| Max | | -0.326 | -1.423 | 0.810 | 540.10% | 8.81% |
| Average | | -1.423 | -1.792 | -0.368 | 59.95% | 2.47% |
| Min | | -2.673 | -2.196 | -1.763 | -30.30% | 0.51% |
| Std Dev | | 0.487 | 0.268 | 0.567 | 145.77% | 2.27% |




| 120.16_Ibn_cap_10V_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | -1.604 | -1.556 | -1.899 | -2.196 | | |
| Average | -1.604 | -1.505 | -1.794 | -2.123 | | |
| Max | -1.604 | -1.423 | -1.636 | -2.086 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 120.20_Ios_cap_10V_A | | | | | | |
|----------------------|-----------|---|-----------|----------|------------------|----|
| Test Site | TI Dallas | TI Dallas | Unit | pA | Max Limit | 10 |
| Tester | ETS364 | ETS364 | Min Limit | -10 | Delta | |
| Test Number | EB4632 | EB4632 <th>Delta %</th> <td></td> <th>% of Limit Range</th> <td></td> | Delta % | | % of Limit Range | |
| Serial # | PRE NDD | POST NDD | | | | |
| 0 | 0.732 | 0.614 | -0.118 | -16.13% | 0.59% | |
| 1 | 0.617 | 0.472 | -0.145 | -23.52% | 0.73% | |
| 1 | 0.654 | 0.724 | 0.070 | 10.69% | 0.35% | |
| 1 | 0.639 | 0.723 | 0.084 | 13.08% | 0.42% | |
| 1 | 0.652 | 0.799 | 0.147 | 22.51% | 0.73% | |
| 5 | 3.161 | 0.734 | -2.427 | -76.78% | 12.14% | |
| 5 | 0.682 | 0.602 | -0.080 | -11.77% | 0.40% | |
| 5 | 0.650 | 0.935 | 0.285 | 43.83% | 1.42% | |
| 5 | 0.735 | 0.754 | 0.019 | 2.60% | 0.10% | |
| 10 | 0.993 | 0.817 | -0.176 | -17.73% | 0.88% | |
| 10 | 0.804 | 0.951 | 0.148 | 18.38% | 0.74% | |
| 10 | -0.326 | 0.809 | 1.135 | -348.60% | 5.67% | |
| 10 | 0.716 | 1.015 | 0.299 | 41.78% | 1.50% | |
| Max | 3.161 | 1.015 | 1.135 | 43.83% | 12.14% | |
| Average | 0.824 | 0.765 | -0.059 | -26.28% | 1.97% | |
| Min | -0.326 | 0.472 | -2.427 | -348.60% | 0.10% | |
| Std Dev | 0.765 | 0.151 | 0.787 | 101.86% | 3.37% | |




| 120.20_Ios_cap_10V_A | | | | | | |
|----------------------|-----------|---------|-----------|---------|------------------|----|
| Test Site | TI Dallas | ETS364 | Unit | pA | Max Limit | 10 |
| Tester | ETS364 | ETS364 | Min Limit | -10 | Delta | |
| Test Number | EB4632 | EB4632 | Delta % | | % of Limit Range | |
| Serial # | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | 0.614 | 0.472 | 0.602 | 0.809 | | |
| Average | 0.614 | 0.679 | 0.756 | 0.898 | | |
| Max | 0.614 | 0.799 | 0.935 | 1.015 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 120.17_Ibn_cap_10V_B | | | | | | |
|----------------------|-----------|-----------|------------------|-----------|-----------|---------|
| Test Site | TI Dallas | TI Dallas | Unit | pA | Max Limit | 10 |
| Tester | ETS364 | ETS364 | Min Limit | -10 | Delta | Delta % |
| Test Number | EB4632 | EB4632 | % of Limit Range | | | |
| Serial # | PRE NDD | POST NDD | | | | |
| 0 | 13 | -0.941 | -1.347 | -0.406 | 43.13% | 2.03% |
| 1 | 1 | -1.224 | -1.361 | -0.137 | 11.22% | 0.69% |
| 1 | 2 | -1.286 | -1.532 | -0.246 | 19.13% | 1.23% |
| 1 | 3 | -1.182 | -1.453 | -0.271 | 22.95% | 1.36% |
| 1 | 4 | -1.328 | -1.456 | -0.128 | 9.63% | 0.64% |
| 5 | 5 | -2.762 | -1.720 | 1.041 | -37.71% | 5.21% |
| 5 | 6 | -1.276 | -1.526 | -0.251 | 19.68% | 1.25% |
| 5 | 7 | -1.253 | -1.523 | -0.271 | 21.59% | 1.35% |
| 5 | 8 | -1.334 | -1.790 | -0.455 | 34.10% | 2.28% |
| 10 | 9 | -1.585 | -1.933 | -0.349 | 21.99% | 1.74% |
| 10 | 10 | -1.481 | -2.116 | -0.634 | 42.83% | 3.17% |
| 10 | 11 | -0.019 | -1.886 | -1.867 | 10092.43% | 9.34% |
| 10 | 12 | -1.316 | -1.954 | -0.639 | 48.53% | 3.19% |
| Max | -0.019 | -1.347 | 1.041 | 10092.43% | 9.34% | |
| Average | -1.307 | -1.661 | -0.355 | 796.12% | 2.58% | |
| Min | -2.762 | -2.116 | -1.867 | -37.71% | 0.64% | |
| Std Dev | 0.581 | 0.253 | 0.615 | 2793.28% | 2.39% | |






| 120.17_Ibn_cap_10V_B | | | | | | |
|----------------------|-----------|-----------|------------------|-----------|-----------|---------|
| Test Site | TI Dallas | TI Dallas | Unit | pA | Max Limit | 10 |
| Tester | ETS364 | ETS364 | Min Limit | -10 | Delta | Delta % |
| Test Number | EB4632 | EB4632 | % of Limit Range | | | |
| Serial # | PRE NDD | POST NDD | | | | |
| 0 | 13 | -0.941 | -1.347 | -0.406 | 43.13% | 2.03% |
| 1 | 1 | -1.224 | -1.361 | -0.137 | 11.22% | 0.69% |
| 1 | 2 | -1.286 | -1.532 | -0.246 | 19.13% | 1.23% |
| 1 | 3 | -1.182 | -1.453 | -0.271 | 22.95% | 1.36% |
| 1 | 4 | -1.328 | -1.456 | -0.128 | 9.63% | 0.64% |
| 5 | 5 | -2.762 | -1.720 | 1.041 | -37.71% | 5.21% |
| 5 | 6 | -1.276 | -1.526 | -0.251 | 19.68% | 1.25% |
| 5 | 7 | -1.253 | -1.523 | -0.271 | 21.59% | 1.35% |
| 5 | 8 | -1.334 | -1.790 | -0.455 | 34.10% | 2.28% |
| 10 | 9 | -1.585 | -1.933 | -0.349 | 21.99% | 1.74% |
| 10 | 10 | -1.481 | -2.116 | -0.634 | 42.83% | 3.17% |
| 10 | 11 | -0.019 | -1.886 | -1.867 | 10092.43% | 9.34% |
| 10 | 12 | -1.316 | -1.954 | -0.639 | 48.53% | 3.19% |
| Max | -0.019 | -1.347 | 1.041 | 10092.43% | 9.34% | |
| Average | -1.307 | -1.661 | -0.355 | 796.12% | 2.58% | |
| Min | -2.762 | -2.116 | -1.867 | -37.71% | 0.64% | |
| Std Dev | 0.581 | 0.253 | 0.615 | 2793.28% | 2.39% | |



NDD Report

LMP7704-SP


| 120.21_Ios_cap_10V_B | | | | | | |
|----------------------|-----------|-----------|-----------|----------|------------------|--------|
| Test Site | TI Dallas | TI Dallas | Unit | pA | Max Limit | 10 |
| Tester | ETS364 | ETS364 | Min Limit | -10 | Max Limit | -10 |
| Test Number | EB4632 | EB4632 | Max Limit | 10 | Min Limit | -10 |
| Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | -0.277 | -0.043 | 0.235 | -84.64% | 1.17% | |
| 1 | 1 | -0.016 | 0.012 | 0.027 | -172.33% | 0.14% |
| 1 | 2 | 0.051 | 0.220 | 0.169 | 332.94% | 0.84% |
| 1 | 3 | -0.079 | 0.196 | 0.276 | -346.92% | 1.38% |
| 1 | 4 | 0.049 | 0.192 | 0.143 | 291.04% | 0.71% |
| 5 | 5 | 2.692 | 0.126 | -2.566 | -95.31% | 12.83% |
| 5 | 6 | 0.019 | -0.118 | -0.137 | -709.33% | 0.68% |
| 5 | 7 | 0.075 | 0.132 | 0.057 | 76.27% | 0.28% |
| 5 | 8 | 0.129 | 0.309 | 0.180 | 139.78% | 0.90% |
| 10 | 9 | 0.421 | 0.273 | -0.148 | -35.08% | 0.74% |
| 10 | 10 | 0.350 | 0.276 | -0.074 | -21.21% | 0.37% |
| 10 | 11 | -0.795 | 0.141 | 0.937 | -117.79% | 4.68% |
| 10 | 12 | 0.181 | 0.296 | 0.115 | 63.86% | 0.58% |
| Max | 2.692 | 0.309 | 0.937 | 332.94% | 12.83% | |
| Average | 0.215 | 0.155 | -0.060 | -52.21% | 1.95% | |
| Min | -0.795 | -0.118 | -2.566 | -709.33% | 0.14% | |
| Std Dev | 0.802 | 0.134 | 0.800 | 269.96% | 3.47% | |




NDD Report

LMP7704-SP

| 120.18_Ibn_cap_10V_C | | | | | | |
|----------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -1.298 | -1.240 | 0.057 | -4.41% | 0.29% |
| 1 | 1 | -1.177 | -1.329 | -0.152 | 12.90% | 0.76% |
| 1 | 2 | -1.234 | -1.283 | -0.049 | 3.99% | 0.25% |
| 1 | 3 | -1.206 | -1.350 | -0.145 | 12.02% | 0.72% |
| 1 | 4 | -1.293 | -1.352 | -0.059 | 4.53% | 0.29% |
| 5 | 5 | -2.262 | -1.680 | 0.582 | -25.72% | 2.91% |
| 5 | 6 | -1.242 | -1.440 | -0.198 | 15.96% | 0.99% |
| 5 | 7 | -1.208 | -1.568 | -0.360 | 29.83% | 1.80% |
| 5 | 8 | -1.341 | -1.564 | -0.224 | 16.68% | 1.12% |
| 10 | 9 | -1.411 | -1.901 | -0.489 | 34.64% | 2.45% |
| 10 | 10 | -1.300 | -1.885 | -0.585 | 44.97% | 2.92% |
| 10 | 11 | -0.394 | -1.842 | -1.448 | 367.98% | 7.24% |
| 10 | 12 | -1.260 | -1.991 | -0.731 | 58.00% | 3.65% |
| Max | | -0.394 | -1.240 | 0.582 | 367.98% | 7.24% |
| Average | | -1.279 | -1.571 | -0.292 | 43.95% | 1.95% |
| Min | | -2.262 | -1.991 | -1.448 | -25.72% | 0.25% |
| Std Dev | | 0.387 | 0.263 | 0.475 | 99.72% | 1.96% |




| 120.18_Ibn_cap_10V_C | | | | | | |
|----------------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | -1.240 | -1.352 | -1.680 | -1.991 | | |
| Average | -1.240 | -1.329 | -1.563 | -1.904 | | |
| Max | -1.240 | -1.283 | -1.440 | -1.842 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 120.22_Ios_cap_10V_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 0.530 | 0.333 | -0.197 | -37.17% | 0.98% |
| 1 | 1 | 0.409 | 0.335 | -0.074 | -18.02% | 0.37% |
| 1 | 2 | 0.422 | 0.424 | 0.002 | 0.47% | 0.01% |
| 1 | 3 | 0.441 | 0.579 | 0.137 | 31.14% | 0.69% |
| 1 | 4 | 0.527 | 0.650 | 0.123 | 23.33% | 0.61% |
| 5 | 5 | 2.562 | 0.557 | -2.005 | -78.26% | 10.02% |
| 5 | 6 | 0.480 | 0.342 | -0.138 | -28.69% | 0.69% |
| 5 | 7 | 0.474 | 0.514 | 0.040 | 8.35% | 0.20% |
| 5 | 8 | 0.574 | 0.535 | -0.040 | -6.91% | 0.20% |
| 10 | 9 | 0.696 | 0.466 | -0.230 | -33.10% | 1.15% |
| 10 | 10 | 0.539 | 0.598 | 0.059 | 10.93% | 0.29% |
| 10 | 11 | -0.337 | 0.586 | 0.923 | -273.89% | 4.62% |
| 10 | 12 | 0.483 | 0.699 | 0.216 | 44.67% | 1.08% |
| Max | | 2.562 | 0.699 | 0.923 | 44.67% | 10.02% |
| Average | | 0.600 | 0.509 | -0.091 | -27.47% | 1.61% |
| Min | | -0.337 | 0.333 | -2.005 | -273.89% | 0.01% |
| Std Dev | | 0.638 | 0.121 | 0.643 | 80.98% | 2.79% |




| 120.22_Ios_cap_10V_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | 0.333 | 0.335 | 0.342 | 0.466 | | |
| Average | 0.333 | 0.497 | 0.487 | 0.587 | | |
| Max | 0.333 | 0.650 | 0.557 | 0.699 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 120.19_Ibn_cap_10V_D | | | | | | |
|----------------------|-----------|---|-----------|---------|------------------|-------|
| Test Site | TI Dallas | TI Dallas | Unit | pA | Max Limit | 10 |
| Tester | ETS364 | ETS364 | Min Limit | -10 | Delta | |
| Test Number | EB4632 | EB4632 <th>Delta %</th> <td></td> <th>% of Limit Range</th> <td></td> | Delta % | | % of Limit Range | |
| Serial # | PRE NDD | POST NDD | | | | |
| 0 | 13 | -1.413 | -0.218 | 15.46% | 1.09% | |
| 1 | 1 | -1.268 | -0.550 | 22.31% | 1.41% | |
| 1 | 2 | -1.171 | -1.444 | 23.26% | 1.36% | |
| 1 | 3 | -1.347 | -1.729 | 28.36% | 1.91% | |
| 1 | 4 | -1.367 | -1.640 | 19.94% | 1.36% | |
| 5 | 5 | -2.405 | -1.885 | 0.519 | -21.60% | 2.60% |
| 5 | 6 | -1.377 | -1.643 | -0.267 | 19.37% | 1.33% |
| 5 | 7 | -1.328 | -1.896 | -0.568 | 42.80% | 2.84% |
| 5 | 8 | -1.204 | -1.760 | -0.556 | 46.19% | 2.78% |
| 10 | 9 | -1.598 | -2.136 | -0.538 | 33.66% | 2.69% |
| 10 | 10 | -1.394 | -2.040 | -0.647 | 46.39% | 3.23% |
| 10 | 11 | -0.468 | -2.089 | -1.621 | 346.38% | 8.10% |
| 10 | 12 | -1.425 | -2.230 | -0.806 | 56.54% | 4.03% |
| Max | -0.468 | -1.444 | 0.519 | 346.38% | 8.10% | |
| Average | -1.366 | -1.821 | -0.455 | 52.23% | 2.67% | |
| Min | -2.405 | -2.230 | -1.621 | -21.60% | 1.09% | |
| Std Dev | 0.410 | 0.246 | 0.474 | 90.50% | 1.86% | |




| 120.19_Ibn_cap_10V_D | | | | | | |
|----------------------|-----------|---|-----------|---------|------------------|----|
| Test Site | TI Dallas | ETS364 | Unit | pA | Max Limit | 10 |
| Tester | ETS364 | ETS364 | Min Limit | -10 | Delta | |
| Test Number | EB4632 | EB4632 <th>Delta %</th> <td></td> <th>% of Limit Range</th> <td></td> | Delta % | | % of Limit Range | |
| Serial # | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | -1.632 | -1.729 | -1.897 | -2.230 | | |
| Average | -1.632 | -1.591 | -1.796 | -2.124 | | |
| Max | -1.632 | -1.444 | -1.643 | -2.041 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 120.23_Ios_cap_10V_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|----------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 0.228 | 0.269 | 0.040 | 17.60% | 0.20% |
| 1 | 1 | 0.073 | 0.220 | 0.146 | 199.05% | 0.73% |
| 1 | 2 | 0.079 | 0.230 | 0.151 | 190.42% | 0.75% |
| 1 | 3 | 0.242 | 0.458 | 0.217 | 89.54% | 1.08% |
| 1 | 4 | 0.189 | 0.424 | 0.235 | 124.42% | 1.17% |
| 5 | 5 | 2.374 | 0.330 | -2.044 | -86.10% | 10.22% |
| 5 | 6 | 0.208 | 0.126 | -0.082 | -39.62% | 0.41% |
| 5 | 7 | 0.196 | 0.498 | 0.302 | 154.06% | 1.51% |
| 5 | 8 | 0.132 | 0.317 | 0.185 | 140.33% | 0.93% |
| 10 | 9 | 0.521 | 0.562 | 0.041 | 7.85% | 0.20% |
| 10 | 10 | 0.144 | 0.326 | 0.183 | 127.16% | 0.91% |
| 10 | 11 | -0.618 | 0.279 | 0.897 | -145.16% | 4.49% |
| 10 | 12 | 0.268 | 0.471 | 0.202 | 75.50% | 1.01% |
| Max | | 2.374 | 0.562 | 0.897 | 199.05% | 10.22% |
| Average | | 0.310 | 0.347 | 0.036 | 65.77% | 1.82% |
| Min | | -0.618 | 0.126 | -2.044 | -145.16% | 0.20% |
| Std Dev | | 0.670 | 0.127 | 0.666 | 107.57% | 2.75% |




| 120.23_Ios_cap_10V_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | pA | pA | |
| Max Limit | 10 | 10 | Min Limit | -10 | -10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -10.000 | -10.000 | -10.000 | -10.000 | | |
| Min | 0.269 | 0.220 | 0.126 | 0.279 | | |
| Average | 0.269 | 0.333 | 0.318 | 0.409 | | |
| Max | 0.269 | 0.459 | 0.498 | 0.562 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 109.8_SR_Rise_10V_A | | | | | | |
|---------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | V_us | V_us | |
| Max Limit | 10 | 10 | Min Limit | 0.01 | 0.01 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 0.802 | 0.810 | 0.008 | 0.93% | 0.08% |
| 1 | 1 | 0.818 | 0.823 | 0.006 | 0.70% | 0.06% |
| 1 | 2 | 0.812 | 0.817 | 0.006 | 0.68% | 0.06% |
| 1 | 3 | 0.795 | 0.793 | -0.003 | -0.33% | 0.03% |
| 1 | 4 | 0.795 | 0.799 | 0.004 | 0.53% | 0.04% |
| 5 | 5 | 0.812 | 0.801 | -0.011 | -1.39% | 0.11% |
| 5 | 6 | 0.813 | 0.814 | 0.001 | 0.14% | 0.01% |
| 5 | 7 | 0.789 | 0.780 | -0.010 | -1.22% | 0.10% |
| 5 | 8 | 0.809 | 0.801 | -0.008 | -1.05% | 0.09% |
| 10 | 9 | 0.811 | 0.786 | -0.025 | -3.02% | 0.25% |
| 10 | 10 | 0.791 | 0.769 | -0.022 | -2.76% | 0.22% |
| 10 | 11 | 0.798 | 0.779 | -0.019 | -2.39% | 0.19% |
| 10 | 12 | 0.794 | 0.768 | -0.026 | -3.32% | 0.26% |
| Max | | 0.818 | 0.823 | 0.008 | 0.93% | 0.26% |
| Average | | 0.803 | 0.795 | -0.008 | -0.96% | 0.11% |
| Min | | 0.789 | 0.768 | -0.026 | -3.32% | 0.01% |
| Std Dev | | 0.010 | 0.018 | 0.012 | 1.53% | 0.09% |




| 109.8_SR_Rise_10V_A | | | | | | |
|---------------------|-----------|-----------|-----------|--------|--------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | V_us | V_us | |
| Max Limit | 10 | V_us | Min Limit | 0.01 | V_us | |
| 1*10^12 n/cm^2 | 0 | 0.010 | 1 | 0.010 | 0.010 | 0.010 |
| LL | 0.010 | 0.010 | Min | 0.793 | 0.780 | 0.768 |
| Average | 0.810 | 0.808 | Max | 0.799 | 0.799 | 0.775 |
| UL | 10.000 | 10.000 | UL | 0.824 | 0.814 | 0.786 |
| | | | | 10.000 | 10.000 | 10.000 |




NDD Report

LMP7704-SP

| 109.9_SR_Rise_10V_B | | | | | | | |
|---------------------|-----------|-----------|-----------|--------|---------|------------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | V_us | V_us | Max Limit | 10 | 10 | Min Limit | 0.01 |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 13 | 0.804 | 0.805 | 0.001 | 0.16% | 0.01% | |
| 1 | 1 | 0.824 | 0.823 | -0.001 | -0.13% | 0.01% | |
| 1 | 2 | 0.819 | 0.822 | 0.003 | 0.33% | 0.03% | |
| 1 | 3 | 0.798 | 0.795 | -0.002 | -0.31% | 0.03% | |
| 1 | 4 | 0.794 | 0.793 | -0.001 | -0.10% | 0.01% | |
| 5 | 5 | 0.815 | 0.796 | -0.019 | -2.34% | 0.19% | |
| 5 | 6 | 0.811 | 0.804 | -0.007 | -0.86% | 0.07% | |
| 5 | 7 | 0.789 | 0.771 | -0.018 | -2.31% | 0.18% | |
| 5 | 8 | 0.806 | 0.789 | -0.017 | -2.10% | 0.17% | |
| 10 | 9 | 0.811 | 0.781 | -0.030 | -3.76% | 0.31% | |
| 10 | 10 | 0.801 | 0.768 | -0.033 | -4.16% | 0.33% | |
| 10 | 11 | 0.798 | 0.767 | -0.031 | -3.92% | 0.31% | |
| 10 | 12 | 0.789 | 0.757 | -0.032 | -4.01% | 0.32% | |
| Max | | 0.824 | 0.823 | 0.003 | 0.33% | 0.33% | |
| Average | | 0.805 | 0.790 | -0.014 | -1.81% | 0.15% | |
| Min | | 0.789 | 0.757 | -0.033 | -4.16% | 0.01% | |
| Std Dev | | 0.011 | 0.021 | 0.014 | 1.74% | 0.13% | |




| 109.9_SR_Rise_10V_B | | | | | | | |
|---------------------|-----------|-----------------|-----------|--------|-----------------|-------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Max Limit | 10 | V _{us} | Min Limit | 0.01 | V _{us} | Average | 0.805 |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | | |
| LL | 0.010 | 0.010 | 0.010 | 0.010 | | | |
| Min | 0.805 | 0.793 | 0.771 | 0.757 | | | |
| Average | 0.805 | 0.808 | 0.790 | 0.768 | | | |
| Max | 0.805 | 0.823 | 0.804 | 0.781 | | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | | |




NDD Report

LMP7704-SP

| 109.10_SR_Rise_10V_C | | | | | | | |
|----------------------|-----------|-----------|-----------|--------|---------|------------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | V_us | V_us | Max Limit | 10 | 10 | Min Limit | 0.01 |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 13 | 0.798 | 0.804 | 0.006 | 0.73% | 0.06% | |
| 1 | 1 | 0.813 | 0.820 | 0.007 | 0.86% | 0.07% | |
| 1 | 2 | 0.818 | 0.825 | 0.007 | 0.82% | 0.07% | |
| 1 | 3 | 0.798 | 0.802 | 0.004 | 0.50% | 0.04% | |
| 1 | 4 | 0.797 | 0.801 | 0.004 | 0.46% | 0.04% | |
| 5 | 5 | 0.808 | 0.795 | -0.013 | -1.62% | 0.13% | |
| 5 | 6 | 0.809 | 0.807 | -0.002 | -0.21% | 0.02% | |
| 5 | 7 | 0.790 | 0.783 | -0.007 | -0.90% | 0.07% | |
| 5 | 8 | 0.808 | 0.798 | -0.010 | -1.27% | 0.10% | |
| 10 | 9 | 0.808 | 0.781 | -0.026 | -3.26% | 0.26% | |
| 10 | 10 | 0.799 | 0.780 | -0.020 | -2.48% | 0.20% | |
| 10 | 11 | 0.801 | 0.779 | -0.022 | -2.72% | 0.22% | |
| 10 | 12 | 0.792 | 0.771 | -0.021 | -2.68% | 0.21% | |
| Max | | 0.818 | 0.825 | 0.007 | 0.86% | 0.26% | |
| Average | | 0.803 | 0.796 | -0.007 | -0.90% | 0.11% | |
| Min | | 0.790 | 0.771 | -0.026 | -3.26% | 0.02% | |
| Std Dev | | 0.008 | 0.016 | 0.012 | 1.53% | 0.08% | |




| 109.10_SR_Rise_10V_C | | | | | | | |
|----------------------|-----------|-----------|-----------|--------|--------|-------------|-----------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | V_us | V_us | Max Limit | 10 | V_us | Min Limit | 0.01 V_us |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | | |
| LL | 0.010 | 0.010 | 0.010 | 0.010 | | | |
| Min | 0.804 | 0.801 | 0.783 | 0.771 | | | |
| Average | 0.804 | 0.812 | 0.796 | 0.778 | | | |
| Max | 0.804 | 0.825 | 0.807 | 0.781 | | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | | |




NDD Report

LMP7704-SP

| 109.11_SR_Rise_10V_D | | | | | | |
|----------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | V_us | V_us | |
| Tester | ETS364 | ETS364 | Max Limit | 10 | 10 | |
| Test Number | EB4632 | EB4632 | Min Limit | 0.01 | 0.01 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 0.802 | 0.802 | 0.000 | 0.02% | 0.00% |
| 1 | 1 | 0.817 | 0.819 | 0.003 | 0.33% | 0.03% |
| 1 | 2 | 0.820 | 0.818 | -0.002 | -0.20% | 0.02% |
| 1 | 3 | 0.795 | 0.793 | -0.003 | -0.33% | 0.03% |
| 1 | 4 | 0.798 | 0.796 | -0.002 | -0.24% | 0.02% |
| 5 | 5 | 0.809 | 0.796 | -0.013 | -1.57% | 0.13% |
| 5 | 6 | 0.808 | 0.798 | -0.011 | -1.34% | 0.11% |
| 5 | 7 | 0.787 | 0.771 | -0.017 | -2.15% | 0.17% |
| 5 | 8 | 0.812 | 0.793 | -0.020 | -2.40% | 0.20% |
| 10 | 9 | 0.801 | 0.771 | -0.030 | -3.74% | 0.30% |
| 10 | 10 | 0.798 | 0.772 | -0.025 | -3.20% | 0.26% |
| 10 | 11 | 0.796 | 0.769 | -0.027 | -3.43% | 0.27% |
| 10 | 12 | 0.789 | 0.760 | -0.030 | -3.75% | 0.30% |
| Max | | 0.820 | 0.819 | 0.003 | 0.33% | 0.30% |
| Average | | 0.803 | 0.789 | -0.014 | -1.69% | 0.14% |
| Min | | 0.787 | 0.760 | -0.030 | -3.75% | 0.00% |
| Std Dev | | 0.010 | 0.019 | 0.012 | 1.52% | 0.12% |




| 109.11_SR_Rise_10V_D | | | | | | |
|----------------------|-----------|-----------|-----------|--------|------|--|
| Test Site | TI Dallas | TI Dallas | Unit | V_us | V_us | |
| Tester | ETS364 | ETS364 | Max Limit | 10 | 10 | |
| Test Number | EB4632 | EB4632 | Min Limit | 0.01 | 0.01 | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | 0.010 | 0.010 | 0.010 | 0.010 | | |
| Min | 0.802 | 0.793 | 0.771 | 0.760 | | |
| Average | 0.802 | 0.807 | 0.789 | 0.768 | | |
| Max | 0.802 | 0.819 | 0.798 | 0.772 | | |
| UL | 10.000 | 10.000 | 10.000 | 10.000 | | |




NDD Report

LMP7704-SP

| 116.0_GBW_5V_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | MHz | MHz | |
| Tester | ETS364 | ETS364 | Max Limit | 20 | 20 | |
| Test Number | EB4632 | EB4632 | Min Limit | 0.1 | 0.1 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 4.081 | 4.275 | 0.194 | 4.76% | 0.98% |
| 1 | 1 | 3.218 | 6.819 | 3.602 | 111.92% | 18.10% |
| 1 | 2 | 5.749 | 4.530 | -1.219 | -21.20% | 6.12% |
| 1 | 3 | 4.254 | 6.701 | 2.448 | 57.54% | 12.30% |
| 1 | 4 | 2.360 | 2.227 | -0.133 | -5.64% | 0.67% |
| 5 | 5 | 3.202 | 2.423 | -0.779 | -24.34% | 3.92% |
| 5 | 6 | 3.185 | 3.705 | 0.520 | 16.33% | 2.61% |
| 5 | 7 | 2.404 | 2.411 | 0.007 | 0.30% | 0.04% |
| 5 | 8 | 3.472 | 4.785 | 1.313 | 37.80% | 6.60% |
| 10 | 9 | 2.432 | 8.744 | 6.312 | 259.53% | 31.72% |
| 10 | 10 | 3.807 | 2.359 | -1.448 | -38.02% | 7.27% |
| 10 | 11 | 4.242 | 7.013 | 2.771 | 65.32% | 13.92% |
| 10 | 12 | 2.913 | 6.008 | 3.095 | 106.26% | 15.55% |
| Max | | 5.749 | 8.744 | 6.312 | 259.53% | 31.72% |
| Average | | 3.486 | 4.769 | 1.283 | 43.89% | 9.22% |
| Min | | 2.360 | 2.227 | -1.448 | -38.02% | 0.04% |
| Std Dev | | 0.951 | 2.142 | 2.253 | 80.59% | 9.01% |




| 116.0_GBW_5V_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|-----|--|
| Test Site | TI Dallas | TI Dallas | Unit | MHz | MHz | |
| Tester | ETS364 | ETS364 | Max Limit | 20 | 20 | |
| Test Number | EB4632 | EB4632 | Min Limit | 0.1 | 0.1 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 0.100 | 0.100 | 0.100 | 0.100 | | |
| Min | 0.4275 | 2.227 | 2.411 | 2.360 | | |
| Average | 4.275 | 5.069 | 3.331 | 6.031 | | |
| Max | 4.275 | 6.819 | 4.785 | 8.744 | | |
| UL | 20.000 | 20.000 | 20.000 | 20.000 | | |




NDD Report

LMP7704-SP

| 116.1_GBW_5V_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | MHz | MHz | |
| Tester | ETS364 | ETS364 | Max Limit | 20 | 20 | |
| Test Number | EB4632 | EB4632 | Min Limit | 0.1 | 0.1 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 2.206 | 2.198 | -0.008 | -0.38% | 0.04% |
| 1 | 1 | 2.413 | 3.043 | 0.630 | 26.13% | 3.17% |
| 1 | 2 | 4.294 | 5.939 | 1.645 | 38.31% | 8.27% |
| 1 | 3 | 4.209 | 5.050 | 0.841 | 19.98% | 4.23% |
| 1 | 4 | 3.551 | 4.045 | 0.494 | 13.92% | 2.48% |
| 5 | 5 | 3.109 | 7.526 | 4.417 | 142.05% | 22.20% |
| 5 | 6 | 2.226 | 2.262 | 0.035 | 1.59% | 0.18% |
| 5 | 7 | 2.478 | 3.575 | 1.097 | 44.25% | 5.51% |
| 5 | 8 | 2.947 | 5.922 | 2.975 | 100.95% | 14.95% |
| 10 | 9 | 5.234 | 9.643 | 4.408 | 84.22% | 22.15% |
| 10 | 10 | 2.217 | 5.729 | 3.513 | 158.48% | 17.65% |
| 10 | 11 | 4.971 | 10.000 | 5.029 | 101.17% | 25.27% |
| 10 | 12 | 2.249 | 2.223 | -0.026 | -1.15% | 0.13% |
| Max | | 5.234 | 10.000 | 5.029 | 158.48% | 25.27% |
| Average | | 3.239 | 5.166 | 1.927 | 56.12% | 9.71% |
| Min | | 2.206 | 2.198 | -0.026 | -1.15% | 0.04% |
| Std Dev | | 1.104 | 2.656 | 1.880 | 55.21% | 9.42% |




| 116.1_GBW_5V_B | | | | |
|-----------------------------------|-----------|--------|--------|--------|
| Test Site | TI Dallas | ETS364 | EB4632 | |
| Tester | | | | |
| Test Number | | | | |
| Max Limit | 20 | MHz | | |
| Min Limit | 0.1 | MHz | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 0.100 | 0.100 | 0.100 | 0.100 |
| Min | 0.2198 | 3.044 | 2.262 | 2.223 |
| Average | 2.198 | 4.519 | 4.821 | 6.899 |
| Max | 2.198 | 5.939 | 7.526 | 10.000 |
| UL | 20.000 | 20.000 | 20.000 | 20.000 |




NDD Report

LMP7704-SP

| 116.2_GBW_5V_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | MHz | MHz | |
| Tester | ETS364 | ETS364 | Max Limit | 20 | 20 | |
| Test Number | EB4632 | EB4632 | Min Limit | 0.1 | 0.1 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 2.220 | 2.205 | -0.015 | -0.66% | 0.07% |
| 1 | 1 | 3.268 | 2.269 | -0.999 | -30.57% | 5.02% |
| 1 | 2 | 4.482 | 2.763 | -1.719 | -38.36% | 8.64% |
| 1 | 3 | 3.078 | 2.500 | -0.578 | -18.77% | 2.90% |
| 1 | 4 | 3.940 | 3.520 | -0.421 | -10.68% | 2.11% |
| 5 | 5 | 3.314 | 5.444 | 2.130 | 64.27% | 10.70% |
| 5 | 6 | 4.132 | 4.678 | 0.546 | 13.21% | 2.74% |
| 5 | 7 | 3.811 | 2.615 | -1.196 | -31.38% | 6.01% |
| 5 | 8 | 2.241 | 2.386 | 0.145 | 6.47% | 0.73% |
| 10 | 9 | 2.365 | 5.803 | 3.438 | 145.35% | 17.28% |
| 10 | 10 | 4.018 | 5.170 | 1.152 | 28.68% | 5.79% |
| 10 | 11 | 2.319 | 2.143 | -0.176 | -7.61% | 0.89% |
| 10 | 12 | 2.207 | 4.780 | 2.573 | 116.57% | 12.93% |
| Max | | 4.482 | 5.803 | 3.438 | 145.35% | 17.28% |
| Average | | 3.184 | 3.560 | 0.375 | 18.20% | 5.83% |
| Min | | 2.207 | 2.143 | -1.719 | -38.36% | 0.07% |
| Std Dev | | 0.840 | 1.398 | 1.547 | 57.37% | 5.24% |




| 116.2_GBW_5V_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|-----|--|
| Test Site | TI Dallas | TI Dallas | Unit | MHz | MHz | |
| Tester | ETS364 | ETS364 | Max Limit | 20 | MHz | |
| Test Number | EB4632 | EB4632 | Min Limit | 0.1 | MHz | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 0.100 | 0.100 | 0.100 | 0.100 | | |
| Min | 0.205 | 2.269 | 2.386 | 2.143 | | |
| Average | 2.205 | 2.763 | 3.781 | 4.474 | | |
| Max | 2.205 | 3.520 | 5.445 | 5.803 | | |
| UL | 20.000 | 20.000 | 20.000 | 20.000 | | |




NDD Report

LMP7704-SP

| 116.3 GBW_5V_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | MHz | MHz | |
| Tester | ETS364 | ETS364 | Max Limit | 20 | 20 | |
| Test Number | EB4632 | EB4632 | Min Limit | 0.1 | 0.1 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 5.480 | 5.473 | -0.007 | -0.12% | 0.03% |
| 1 | 1 | 4.577 | 4.737 | 0.160 | 3.50% | 0.81% |
| 1 | 2 | 5.959 | 3.169 | -2.789 | -46.81% | 14.02% |
| 1 | 3 | 3.377 | 3.146 | -0.230 | -6.82% | 1.16% |
| 1 | 4 | 3.082 | 2.768 | -0.315 | -10.21% | 1.58% |
| 5 | 5 | 2.292 | 2.290 | -0.002 | -0.07% | 0.01% |
| 5 | 6 | 3.027 | 3.069 | 0.042 | 1.39% | 0.21% |
| 5 | 7 | 4.471 | 2.919 | -1.552 | -34.71% | 7.80% |
| 5 | 8 | 2.469 | 9.368 | 6.899 | 279.45% | 34.67% |
| 10 | 9 | 2.350 | 2.473 | 0.123 | 5.24% | 0.62% |
| 10 | 10 | 4.229 | 2.424 | -1.805 | -42.69% | 9.07% |
| 10 | 11 | 4.032 | 7.287 | 3.255 | 80.72% | 16.36% |
| 10 | 12 | 2.209 | 2.495 | 0.286 | 12.97% | 1.44% |
| Max | | 5.959 | 9.368 | 6.899 | 279.45% | 34.67% |
| Average | | 3.658 | 3.971 | 0.313 | 18.60% | 6.75% |
| Min | | 2.209 | 2.290 | -2.789 | -46.81% | 0.01% |
| Std Dev | | 1.241 | 2.185 | 2.426 | 84.50% | 10.10% |




| 116.3 GBW_5V_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|-----|--|
| Test Site | TI Dallas | TI Dallas | Unit | MHz | MHz | |
| Tester | ETS364 | ETS364 | Max Limit | 20 | 20 | |
| Test Number | EB4632 | EB4632 | Min Limit | 0.1 | 0.1 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 0.100 | 0.100 | 0.100 | 0.100 | | |
| Min | 5.473 | 2.768 | 2.291 | 2.424 | | |
| Average | 5.473 | 3.455 | 4.412 | 3.670 | | |
| Max | 5.473 | 4.737 | 9.368 | 7.287 | | |
| UL | 20.000 | 20.000 | 20.000 | 20.000 | | |




NDD Report

LMP7704-SP

| 116.4 GBW_10V_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | MHz | MHz | |
| Tester | ETS364 | ETS364 | Max Limit | 20 | 20 | |
| Test Number | EB4632 | EB4632 | Min Limit | 0.1 | 0.1 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 4.525 | 4.709 | 0.184 | 4.06% | 0.92% |
| 1 | 1 | 3.483 | 6.740 | 3.257 | 93.49% | 16.36% |
| 1 | 2 | 6.127 | 5.148 | -0.979 | -15.98% | 4.92% |
| 1 | 3 | 3.818 | 5.737 | 1.919 | 50.26% | 9.64% |
| 1 | 4 | 2.412 | 2.360 | -0.051 | -2.14% | 0.26% |
| 5 | 5 | 3.493 | 2.635 | -0.858 | -24.57% | 4.31% |
| 5 | 6 | 2.465 | 2.670 | 0.206 | 8.34% | 1.03% |
| 5 | 7 | 2.484 | 2.518 | 0.034 | 1.38% | 0.17% |
| 5 | 8 | 3.352 | 4.570 | 1.218 | 36.36% | 6.12% |
| 10 | 9 | 2.767 | 8.613 | 5.846 | 211.26% | 29.38% |
| 10 | 10 | 3.740 | 2.688 | -1.052 | -28.13% | 5.29% |
| 10 | 11 | 4.706 | 7.301 | 2.595 | 55.15% | 13.04% |
| 10 | 12 | 3.159 | 5.882 | 2.723 | 86.21% | 13.69% |
| Max | | 6.127 | 8.613 | 5.846 | 211.26% | 29.38% |
| Average | | 3.579 | 4.736 | 1.157 | 36.59% | 8.09% |
| Min | | 2.412 | 2.360 | -1.052 | -28.13% | 0.17% |
| Std Dev | | 1.059 | 2.073 | 2.033 | 65.85% | 8.37% |




| 116.4 GBW_10V_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|-----|--|
| Test Site | TI Dallas | TI Dallas | Unit | MHz | MHz | |
| Tester | ETS364 | ETS364 | Max Limit | 20 | 20 | |
| Test Number | EB4632 | EB4632 | Min Limit | 0.1 | 0.1 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 0.100 | 0.100 | 0.100 | 0.100 | | |
| Min | 4.709 | 2.360 | 2.518 | 2.688 | | |
| Average | 4.709 | 4.996 | 3.098 | 6.121 | | |
| Max | 4.709 | 6.740 | 4.570 | 8.613 | | |
| UL | 20.000 | 20.000 | 20.000 | 20.000 | | |




NDD Report

LMP7704-SP

| 116.5 GBW_10V_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | MHz | MHz | |
| Tester | ETS364 | ETS364 | Max Limit | 20 | 20 | |
| Test Number | EB4632 | EB4632 | Min Limit | 0.1 | 0.1 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 2.378 | 2.367 | -0.011 | -0.48% | 0.06% |
| 1 | 1 | 2.774 | 3.226 | 0.451 | 16.27% | 2.27% |
| 1 | 2 | 4.511 | 5.871 | 1.360 | 30.14% | 6.83% |
| 1 | 3 | 3.812 | 4.454 | 0.642 | 16.84% | 3.23% |
| 1 | 4 | 2.918 | 3.184 | 0.266 | 9.11% | 1.34% |
| 5 | 5 | 3.069 | 6.998 | 3.929 | 127.99% | 19.74% |
| 5 | 6 | 2.881 | 3.277 | 0.395 | 13.73% | 1.99% |
| 5 | 7 | 2.792 | 3.619 | 0.827 | 29.63% | 4.16% |
| 5 | 8 | 2.733 | 5.373 | 2.640 | 96.59% | 13.27% |
| 10 | 9 | 5.152 | 9.293 | 4.140 | 80.36% | 20.81% |
| 10 | 10 | 2.665 | 4.305 | 1.640 | 61.53% | 8.24% |
| 10 | 11 | 4.754 | 9.802 | 5.047 | 106.15% | 25.36% |
| 10 | 12 | 2.681 | 2.261 | -0.420 | -15.65% | 2.11% |
| Max | | 5.152 | 9.802 | 5.047 | 127.99% | 25.36% |
| Average | | 3.317 | 4.925 | 1.608 | 44.02% | 8.41% |
| Min | | 2.378 | 2.261 | -0.420 | -15.65% | 0.06% |
| Std Dev | | 0.919 | 2.464 | 1.771 | 45.54% | 8.56% |




| 116.5 GBW_10V_B | | | | | | | |
|-----------------------------------|-----------|--------|---|-------------|--------|-----|--|
| Test Site | TI Dallas | Tester | ETS364 <th>Test Number</th> <td>EB4632</td> | Test Number | EB4632 | | |
| Max Limit | 20 | MHz | | Min Limit | 0.1 | MHz | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | | |
| LL | 0.100 | 0.100 | 0.100 | 0.100 | | | |
| Min | 0.2367 | 3.184 | 3.277 | 2.261 | | | |
| Average | 2.367 | 4.184 | 4.817 | 6.415 | | | |
| Max | 2.367 | 5.871 | 6.998 | 9.802 | | | |
| UL | 20.000 | 20.000 | 20.000 | 20.000 | | | |




NDD Report

LMP7704-SP

| 116.6 GBW_10V_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | MHz | MHz | |
| Tester | ETS364 | ETS364 | Max Limit | 20 | 20 | |
| Test Number | EB4632 | EB4632 | Min Limit | 0.1 | 0.1 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 2.384 | 2.395 | 0.012 | 0.50% | 0.06% |
| 1 | 1 | 3.081 | 2.433 | -0.648 | -21.04% | 3.26% |
| 1 | 2 | 4.524 | 3.057 | -1.467 | -32.42% | 7.37% |
| 1 | 3 | 3.327 | 2.876 | -0.451 | -13.56% | 2.27% |
| 1 | 4 | 3.319 | 2.984 | -0.335 | -10.09% | 1.68% |
| 5 | 5 | 2.751 | 4.427 | 1.676 | 60.93% | 8.42% |
| 5 | 6 | 4.553 | 5.012 | 0.459 | 10.09% | 2.31% |
| 5 | 7 | 3.360 | 2.541 | -0.819 | -24.39% | 4.12% |
| 5 | 8 | 2.398 | 2.394 | -0.004 | -0.18% | 0.02% |
| 10 | 9 | 2.389 | 4.909 | 2.520 | 105.49% | 12.66% |
| 10 | 10 | 4.293 | 5.615 | 1.322 | 30.80% | 6.64% |
| 10 | 11 | 2.666 | 2.358 | -0.309 | -11.57% | 1.55% |
| 10 | 12 | 2.359 | 4.332 | 1.973 | 83.65% | 9.92% |
| Max | | 4.553 | 5.615 | 2.520 | 105.49% | 12.66% |
| Average | | 3.185 | 3.487 | 0.302 | 13.71% | 4.64% |
| Min | | 2.359 | 2.358 | -1.467 | -32.42% | 0.02% |
| Std Dev | | 0.817 | 1.189 | 1.207 | 43.74% | 4.00% |




| 116.6 GBW_10V_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|-----|--|
| Test Site | TI Dallas | TI Dallas | Unit | MHz | MHz | |
| Tester | ETS364 | ETS364 | Max Limit | 20 | MHz | |
| Test Number | EB4632 | EB4632 | Min Limit | 0.1 | MHz | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 0.100 | 0.100 | 0.100 | 0.100 | | |
| Min | 2.395 | 2.433 | 2.394 | 2.358 | | |
| Average | 2.395 | 2.838 | 3.593 | 4.303 | | |
| Max | 2.395 | 3.058 | 5.012 | 5.615 | | |
| UL | 20.000 | 20.000 | 20.000 | 20.000 | | |




NDD Report

LMP7704-SP

| 116.7_GBW_10V_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | MHz | MHz | |
| Tester | ETS364 | ETS364 | Max Limit | 20 | 20 | |
| Test Number | EB4632 | EB4632 | Min Limit | 0.1 | 0.1 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 4.749 | 4.769 | 0.020 | 0.43% | 0.10% |
| 1 | 1 | 4.278 | 4.473 | 0.194 | 4.54% | 0.98% |
| 1 | 2 | 5.517 | 3.015 | -2.503 | -45.36% | 12.58% |
| 1 | 3 | 3.165 | 3.002 | -0.163 | -5.15% | 0.82% |
| 1 | 4 | 3.305 | 3.001 | -0.303 | -9.18% | 1.52% |
| 5 | 5 | 2.444 | 2.437 | -0.007 | -0.31% | 0.04% |
| 5 | 6 | 3.722 | 3.697 | -0.025 | -0.68% | 0.13% |
| 5 | 7 | 3.858 | 3.257 | -0.601 | -15.57% | 3.02% |
| 5 | 8 | 3.759 | 9.757 | 5.999 | 159.60% | 30.14% |
| 10 | 9 | 2.552 | 2.407 | -0.145 | -5.69% | 0.73% |
| 10 | 10 | 3.589 | 2.317 | -1.271 | -35.43% | 6.39% |
| 10 | 11 | 4.509 | 7.355 | 2.846 | 63.10% | 14.30% |
| 10 | 12 | 2.530 | 3.146 | 0.617 | 24.38% | 3.10% |
| Max | | 5.517 | 9.757 | 5.999 | 159.60% | 30.14% |
| Average | | 3.690 | 4.049 | 0.358 | 10.36% | 5.68% |
| Min | | 2.444 | 2.317 | -2.503 | -45.36% | 0.04% |
| Std Dev | | 0.919 | 2.186 | 2.066 | 51.94% | 8.74% |




| 116.7_GBW_10V_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|-----|--|
| Test Site | TI Dallas | TI Dallas | Unit | MHz | MHz | |
| Tester | ETS364 | ETS364 | Max Limit | 20 | 20 | |
| Test Number | EB4632 | EB4632 | Min Limit | 0.1 | 0.1 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 0.100 | 0.100 | 0.100 | 0.100 | | |
| Min | 4.769 | 3.001 | 2.437 | 2.317 | | |
| Average | 4.769 | 3.373 | 4.787 | 3.806 | | |
| Max | 4.769 | 4.473 | 9.757 | 7.355 | | |
| UL | 20.000 | 20.000 | 20.000 | 20.000 | | |




NDD Report

LMP7704-SP

| 110.0_Vout_Vcc_5V_2k_A | | | | | | |
|-----------------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mV | mV | | | | |
| Max Limit | 108 | 108 | | | | |
| Min Limit | 5 | 5 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 45.790 | 45.957 | 0.167 | 0.37% | 0.16% |
| 1 | 1 | 46.116 | 46.517 | 0.402 | 0.87% | 0.39% |
| 1 | 2 | 46.404 | 46.283 | -0.121 | -0.26% | 0.12% |
| 1 | 3 | 45.145 | 46.120 | 0.975 | 2.16% | 0.95% |
| 1 | 4 | 45.240 | 45.706 | 0.466 | 1.03% | 0.45% |
| 5 | 5 | 45.539 | 47.786 | 2.248 | 4.94% | 2.18% |
| 5 | 6 | 46.601 | 48.133 | 1.532 | 3.29% | 1.49% |
| 5 | 7 | 45.416 | 47.284 | 1.868 | 4.11% | 1.81% |
| 5 | 8 | 45.946 | 47.549 | 1.603 | 3.49% | 1.56% |
| 10 | 9 | 45.858 | 48.709 | 2.852 | 6.22% | 2.77% |
| 10 | 10 | 45.474 | 48.190 | 2.716 | 5.97% | 2.64% |
| 10 | 11 | 45.858 | 48.262 | 2.404 | 5.24% | 2.33% |
| 10 | 12 | 45.528 | 48.465 | 2.937 | 6.45% | 2.85% |
| Max | | 46.601 | 48.709 | 2.937 | 6.45% | 2.85% |
| Average | | 45.763 | 47.305 | 1.542 | 3.38% | 1.52% |
| Min | | 45.145 | 45.706 | -0.121 | -0.26% | 0.12% |
| Std Dev | | 0.433 | 1.058 | 1.073 | 2.35% | 1.01% |




| 110.0_Vout_Vcc_5V_2k_A | | | | |
|-----------------------------------|-----------|---------|---------|---------|
| Test Site | TI Dallas | | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 108 | mV | | |
| Min Limit | 5 | mV | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 45.957 | 45.706 | 47.284 | 48.190 |
| Average | 45.957 | 46.157 | 47.688 | 48.407 |
| Max | 45.957 | 46.517 | 48.133 | 48.710 |
| UL | 108.000 | 108.000 | 108.000 | 108.000 |




NDD Report

LMP7704-SP

| 110.1_Vout_Vcc_5V_2k_B | | | | | | |
|-----------------------------------|-----------|-----------|----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mV | mV | | | | |
| Max Limit | 108 | 108 | | | | |
| Min Limit | 5 | 5 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 45.735 | 46.508 | 0.772 | 1.69% | 0.75% |
| 1 | 1 | 46.095 | 47.102 | 1.007 | 2.18% | 0.98% |
| 1 | 2 | 45.769 | 46.851 | 1.082 | 2.36% | 1.05% |
| 1 | 3 | 45.165 | 45.917 | 0.752 | 1.66% | 0.73% |
| 1 | 4 | 45.474 | 46.592 | 1.119 | 2.46% | 1.09% |
| 5 | 5 | 46.163 | 48.627 | 2.464 | 5.34% | 2.39% |
| 5 | 6 | 46.339 | 48.695 | 2.355 | 5.08% | 2.29% |
| 5 | 7 | 45.725 | 47.771 | 2.046 | 4.47% | 1.99% |
| 5 | 8 | 45.715 | 48.236 | 2.521 | 5.52% | 2.45% |
| 10 | 9 | 45.895 | 49.513 | 3.619 | 7.88% | 3.51% |
| 10 | 10 | 45.565 | 49.194 | 3.629 | 7.96% | 3.52% |
| 10 | 11 | 45.735 | 49.483 | 3.748 | 8.19% | 3.64% |
| 10 | 12 | 45.752 | 49.004 | 3.252 | 7.11% | 3.16% |
| Max | | 46.339 | 49.513 | 3.748 | 8.19% | 3.64% |
| Average | | 45.779 | 47.961 | 2.182 | 4.76% | 2.12% |
| Min | | 45.165 | 45.917 | 0.752 | 1.66% | 0.73% |
| Std Dev | | 0.303 | 1.244 | 1.146 | 2.50% | 1.11% |




| 110.1_Vout_Vcc_5V_2k_B | | | | |
|-----------------------------------|-----------|---------|---------|---------|
| Test Site | TI Dallas | | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 108 | mV | | |
| Min Limit | 5 | mV | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 46.508 | 45.917 | 47.771 | 49.004 |
| Average | 46.508 | 46.615 | 48.332 | 49.298 |
| Max | 46.508 | 47.102 | 48.695 | 49.513 |
| UL | 108.000 | 108.000 | 108.000 | 108.000 |




NDD Report

LMP7704-SP

| 110.2_Vout_Vcc_5V_2k_C | | | | | | |
|------------------------|-----------|-----------|----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mV | mV | | | | |
| Max Limit | 108 | 108 | | | | |
| Min Limit | 5 | 5 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 45.563 | 45.588 | 0.024 | 0.05% | 0.02% |
| 1 | 1 | 46.015 | 46.681 | 0.666 | 1.45% | 0.65% |
| 1 | 2 | 45.791 | 46.368 | 0.577 | 1.26% | 0.56% |
| 1 | 3 | 45.689 | 46.307 | 0.618 | 1.35% | 0.60% |
| 1 | 4 | 45.621 | 46.195 | 0.574 | 1.26% | 0.56% |
| 5 | 5 | 45.791 | 47.838 | 2.047 | 4.47% | 1.99% |
| 5 | 6 | 45.621 | 47.617 | 1.996 | 4.38% | 1.94% |
| 5 | 7 | 45.553 | 47.526 | 1.972 | 4.33% | 1.91% |
| 5 | 8 | 45.842 | 47.780 | 1.938 | 4.23% | 1.88% |
| 10 | 9 | 45.679 | 48.893 | 3.215 | 7.04% | 3.12% |
| 10 | 10 | 45.808 | 48.540 | 2.733 | 5.97% | 2.65% |
| 10 | 11 | 45.726 | 48.557 | 2.831 | 6.19% | 2.75% |
| 10 | 12 | 45.893 | 48.754 | 2.861 | 6.24% | 2.78% |
| Max | | 46.015 | 48.893 | 3.215 | 7.04% | 3.12% |
| Average | | 45.738 | 47.434 | 1.696 | 3.71% | 1.65% |
| Min | | 45.553 | 45.588 | 0.024 | 0.05% | 0.02% |
| Std Dev | | 0.135 | 1.103 | 1.076 | 2.35% | 1.05% |




| 110.2_Vout_Vcc_5V_2k_C | | | | |
|------------------------|-----------|---------|---------|---------|
| Test Site | TI Dallas | | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 108 | mV | | |
| Min Limit | 5 | mV | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 45.588 | 46.195 | 47.526 | 48.540 |
| Average | 45.588 | 46.388 | 47.690 | 48.686 |
| Max | 45.588 | 46.681 | 47.838 | 48.893 |
| UL | 108.000 | 108.000 | 108.000 | 108.000 |




NDD Report

LMP7704-SP

| 110.3_Vout_Vcc_5V_2k_D | | | | | | |
|-----------------------------------|-----------|-----------|----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mV | mV | | | | |
| Max Limit | 108 | 108 | | | | |
| Min Limit | 5 | 5 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 45.886 | 45.967 | 0.080 | 0.17% | 0.08% |
| 1 | 1 | 46.121 | 46.493 | 0.372 | 0.81% | 0.36% |
| 1 | 2 | 46.531 | 46.849 | 0.318 | 0.68% | 0.31% |
| 1 | 3 | 46.043 | 46.469 | 0.426 | 0.93% | 0.41% |
| 1 | 4 | 45.917 | 46.248 | 0.331 | 0.72% | 0.32% |
| 5 | 5 | 46.097 | 47.691 | 1.594 | 3.46% | 1.55% |
| 5 | 6 | 46.413 | 48.085 | 1.672 | 3.60% | 1.62% |
| 5 | 7 | 46.134 | 47.823 | 1.689 | 3.66% | 1.64% |
| 5 | 8 | 46.409 | 47.980 | 1.570 | 3.38% | 1.52% |
| 10 | 9 | 46.389 | 49.361 | 2.972 | 6.41% | 2.89% |
| 10 | 10 | 46.436 | 49.113 | 2.677 | 5.76% | 2.60% |
| 10 | 11 | 46.083 | 48.825 | 2.741 | 5.95% | 2.66% |
| 10 | 12 | 46.671 | 49.473 | 2.803 | 6.01% | 2.72% |
| Max | | 46.671 | 49.473 | 2.972 | 6.41% | 2.89% |
| Average | | 46.241 | 47.721 | 1.481 | 3.20% | 1.44% |
| Min | | 45.886 | 45.967 | 0.080 | 0.17% | 0.08% |
| Std Dev | | 0.246 | 1.232 | 1.083 | 2.33% | 1.05% |




| 110.3_Vout_Vcc_5V_2k_D | | | | |
|-----------------------------------|-----------|---------|---------|---------|
| Test Site | TI Dallas | | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 108 | mV | | |
| Min Limit | 5 | mV | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 45.967 | 46.248 | 47.691 | 48.825 |
| Average | 45.967 | 46.515 | 47.895 | 49.193 |
| Max | 45.967 | 46.849 | 48.085 | 49.473 |
| UL | 108.000 | 108.000 | 108.000 | 108.000 |




NDD Report

LMP7704-SP

| 110.4_Vout_Vee_5V_2k_A | | | | | | |
|-----------------------------------|-----------|-----------|----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mV | mV | | | | |
| Max Limit | 108 | 108 | | | | |
| Min Limit | 5 | 5 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 53.776 | 53.946 | 0.169 | 0.32% | 0.16% |
| 1 | 1 | 54.303 | 55.066 | 0.763 | 1.41% | 0.74% |
| 1 | 2 | 53.817 | 54.607 | 0.790 | 1.47% | 0.77% |
| 1 | 3 | 53.756 | 54.003 | 0.247 | 0.46% | 0.24% |
| 1 | 4 | 53.227 | 53.993 | 0.767 | 1.44% | 0.74% |
| 5 | 5 | 54.374 | 57.390 | 3.016 | 5.55% | 2.93% |
| 5 | 6 | 54.479 | 58.198 | 3.719 | 6.83% | 3.61% |
| 5 | 7 | 53.522 | 56.437 | 2.915 | 5.45% | 2.83% |
| 5 | 8 | 53.705 | 56.525 | 2.820 | 5.25% | 2.74% |
| 10 | 9 | 54.459 | 59.406 | 4.947 | 9.08% | 4.80% |
| 10 | 10 | 53.328 | 58.011 | 4.683 | 8.78% | 4.55% |
| 10 | 11 | 53.552 | 58.042 | 4.489 | 8.38% | 4.36% |
| 10 | 12 | 53.206 | 58.055 | 4.849 | 9.11% | 4.71% |
| Max | | 54.479 | 59.406 | 4.947 | 9.11% | 4.80% |
| Average | | 53.808 | 56.437 | 2.629 | 4.89% | 2.55% |
| Min | | 53.206 | 53.946 | 0.169 | 0.32% | 0.16% |
| Std Dev | | 0.459 | 1.911 | 1.859 | 3.46% | 1.81% |




| 110.4_Vout_Vee_5V_2k_A | | | | | | |
|-----------------------------------|-----------|---------|---------|---------|--|--|
| Test Site | TI Dallas | | | | | |
| Tester | ETS364 | | | | | |
| Test Number | EB4632 | | | | | |
| Max Limit | 108 | mV | | | | |
| Min Limit | 5 | mV | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 5.000 | 5.000 | 5.000 | 5.000 | | |
| Min | 53.946 | 53.993 | 56.437 | 58.011 | | |
| Average | 53.946 | 54.417 | 57.137 | 58.379 | | |
| Max | 53.946 | 55.066 | 58.198 | 59.406 | | |
| UL | 108.000 | 108.000 | 108.000 | 108.000 | | |




NDD Report

LMP7704-SP

| 110.5_Vout_Vee_5V_2k_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | mV | mV | |
| Max Limit | 108 | 108 | Min Limit | 5 | 5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 53.374 | 53.575 | 0.201 | 0.38% | 0.20% |
| 1 | 1 | 54.120 | 54.923 | 0.803 | 1.48% | 0.78% |
| 1 | 2 | 53.615 | 54.312 | 0.697 | 1.30% | 0.68% |
| 1 | 3 | 53.323 | 53.758 | 0.436 | 0.82% | 0.42% |
| 1 | 4 | 53.204 | 53.735 | 0.531 | 1.00% | 0.52% |
| 5 | 5 | 54.059 | 56.761 | 2.701 | 5.00% | 2.62% |
| 5 | 6 | 54.181 | 57.467 | 3.286 | 6.06% | 3.19% |
| 5 | 7 | 53.187 | 55.952 | 2.765 | 5.20% | 2.68% |
| 5 | 8 | 53.414 | 56.092 | 2.677 | 5.01% | 2.60% |
| 10 | 9 | 53.700 | 58.425 | 4.725 | 8.80% | 4.59% |
| 10 | 10 | 53.177 | 57.487 | 4.311 | 8.11% | 4.18% |
| 10 | 11 | 53.133 | 57.603 | 4.470 | 8.41% | 4.34% |
| 10 | 12 | 53.224 | 57.705 | 4.480 | 8.42% | 4.35% |
| Max | | 54.181 | 58.425 | 4.725 | 8.80% | 4.59% |
| Average | | 53.516 | 55.984 | 2.468 | 4.61% | 2.40% |
| Min | | 53.133 | 53.575 | 0.201 | 0.38% | 0.20% |
| Std Dev | | 0.384 | 1.740 | 1.740 | 3.26% | 1.69% |




| 110.5_Vout_Vee_5V_2k_B | | | | |
|-----------------------------------|-----------|---------|-----------|---------|
| Test Site | TI Dallas | ETS364 | Tester | ETS364 |
| Test Number | EB4632 | EB4632 | Unit | mV |
| Max Limit | 108 | mV | Min Limit | 5 mV |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 5 | 10 | |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 53.575 | 53.735 | 55.952 | 57.487 |
| Average | 53.575 | 54.182 | 56.568 | 57.805 |
| Max | 53.575 | 54.923 | 57.467 | 58.425 |
| UL | 108.000 | 108.000 | 108.000 | 108.000 |




NDD Report

LMP7704-SP

| 110.6_Vout_Vee_5V_2k_C | | | | | | |
|-----------------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mV | mV | | | | |
| Max Limit | 108 | 108 | | | | |
| Min Limit | 5 | 5 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 53.658 | 53.336 | -0.322 | -0.60% | 0.31% |
| 1 | 1 | 54.276 | 54.649 | 0.373 | 0.69% | 0.36% |
| 1 | 2 | 53.658 | 53.798 | 0.139 | 0.26% | 0.14% |
| 1 | 3 | 53.437 | 53.641 | 0.204 | 0.38% | 0.20% |
| 1 | 4 | 53.332 | 53.445 | 0.112 | 0.21% | 0.11% |
| 5 | 5 | 54.205 | 57.025 | 2.820 | 5.20% | 2.74% |
| 5 | 6 | 54.521 | 57.324 | 2.803 | 5.14% | 2.72% |
| 5 | 7 | 53.417 | 55.980 | 2.563 | 4.80% | 2.49% |
| 5 | 8 | 53.549 | 55.898 | 2.349 | 4.39% | 2.28% |
| 10 | 9 | 54.015 | 58.844 | 4.830 | 8.94% | 4.69% |
| 10 | 10 | 53.393 | 57.626 | 4.233 | 7.93% | 4.11% |
| 10 | 11 | 53.322 | 57.623 | 4.301 | 8.07% | 4.18% |
| 10 | 12 | 53.441 | 57.806 | 4.365 | 8.17% | 4.24% |
| Max | | 54.521 | 58.844 | 4.830 | 8.94% | 4.69% |
| Average | | 53.710 | 55.923 | 2.213 | 4.12% | 2.20% |
| Min | | 53.322 | 53.336 | -0.322 | -0.60% | 0.11% |
| Std Dev | | 0.405 | 1.941 | 1.900 | 3.54% | 1.78% |




| 110.6_Vout_Vee_5V_2k_C | | | | |
|-----------------------------------|-----------|---------|---------|---------|
| Test Site | TI Dallas | | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 108 | mV | | |
| Min Limit | 5 | mV | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 53.336 | 53.445 | 55.898 | 57.623 |
| Average | 53.336 | 53.883 | 56.557 | 57.975 |
| Max | 53.336 | 54.649 | 57.324 | 58.844 |
| UL | 108.000 | 108.000 | 108.000 | 108.000 |




NDD Report

LMP7704-SP

| 110.7_Vout_Vee_5V_2k_D | | | | | | |
|-----------------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mV | mV | | | | |
| Max Limit | 108 | 108 | | | | |
| Min Limit | 5 | 5 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 53.541 | 53.502 | -0.038 | -0.07% | 0.04% |
| 1 | 1 | 54.132 | 54.918 | 0.786 | 1.45% | 0.76% |
| 1 | 2 | 53.673 | 54.127 | 0.454 | 0.85% | 0.44% |
| 1 | 3 | 53.137 | 53.747 | 0.610 | 1.15% | 0.59% |
| 1 | 4 | 53.137 | 53.727 | 0.590 | 1.11% | 0.57% |
| 5 | 5 | 53.836 | 57.056 | 3.220 | 5.98% | 3.13% |
| 5 | 6 | 54.281 | 57.498 | 3.217 | 5.93% | 3.12% |
| 5 | 7 | 53.086 | 56.262 | 3.176 | 5.98% | 3.08% |
| 5 | 8 | 53.249 | 56.299 | 3.051 | 5.73% | 2.96% |
| 10 | 9 | 53.782 | 58.961 | 5.179 | 9.63% | 5.03% |
| 10 | 10 | 53.208 | 57.864 | 4.656 | 8.75% | 4.52% |
| 10 | 11 | 53.235 | 57.909 | 4.673 | 8.78% | 4.54% |
| 10 | 12 | 53.470 | 58.262 | 4.792 | 8.96% | 4.65% |
| Max | | 54.281 | 58.961 | 5.179 | 9.63% | 5.03% |
| Average | | 53.520 | 56.164 | 2.644 | 4.94% | 2.57% |
| Min | | 53.086 | 53.502 | -0.038 | -0.07% | 0.04% |
| Std Dev | | 0.396 | 1.944 | 1.917 | 3.59% | 1.85% |




| 110.7_Vout_Vee_5V_2k_D | | | | |
|-----------------------------------|-----------|---------|---------|---------|
| Test Site | TI Dallas | | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 108 | mV | | |
| Min Limit | 5 | mV | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 53.502 | 53.727 | 56.262 | 57.864 |
| Average | 53.502 | 54.130 | 56.779 | 58.249 |
| Max | 53.502 | 54.918 | 57.498 | 58.961 |
| UL | 108.000 | 108.000 | 108.000 | 108.000 |




NDD Report

LMP7704-SP

| 110.8_Vout_Vcc_5V_10k_A | | | | | | |
|-----------------------------------|-----------|-----------|----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mV | mV | | | | |
| Max Limit | 54 | 54 | | | | |
| Min Limit | 5 | 5 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 21.582 | 21.792 | 0.210 | 0.97% | 0.43% |
| 1 | 1 | 21.728 | 21.982 | 0.254 | 1.17% | 0.52% |
| 1 | 2 | 21.826 | 22.165 | 0.339 | 1.55% | 0.69% |
| 1 | 3 | 21.538 | 21.873 | 0.335 | 1.56% | 0.68% |
| 1 | 4 | 21.341 | 21.945 | 0.603 | 2.83% | 1.23% |
| 5 | 5 | 21.470 | 23.041 | 1.571 | 7.32% | 3.21% |
| 5 | 6 | 21.928 | 23.601 | 1.672 | 7.63% | 3.41% |
| 5 | 7 | 21.579 | 23.193 | 1.615 | 7.48% | 3.30% |
| 5 | 8 | 21.728 | 23.319 | 1.591 | 7.32% | 3.25% |
| 10 | 9 | 21.188 | 24.473 | 3.284 | 15.50% | 6.70% |
| 10 | 10 | 21.725 | 23.713 | 1.988 | 9.15% | 4.06% |
| 10 | 11 | 21.365 | 24.150 | 2.785 | 13.04% | 5.68% |
| 10 | 12 | 21.762 | 23.835 | 2.073 | 9.52% | 4.23% |
| Max | | 21.928 | 24.473 | 3.284 | 15.50% | 6.70% |
| Average | | 21.597 | 23.006 | 1.409 | 6.54% | 2.88% |
| Min | | 21.188 | 21.792 | 0.210 | 0.97% | 0.43% |
| Std Dev | | 0.213 | 0.948 | 1.003 | 4.70% | 2.05% |




| 110.8_Vout_Vcc_5V_10k_A | | | | |
|-----------------------------------|-----------|--------|--------|--------|
| Test Site | TI Dallas | | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 54 | mV | | |
| Min Limit | 5 | mV | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 21.792 | 21.873 | 23.041 | 23.713 |
| Average | 21.792 | 21.991 | 23.288 | 24.043 |
| Max | 21.792 | 22.165 | 23.601 | 24.473 |
| UL | 54.000 | 54.000 | 54.000 | 54.000 |




NDD Report

LMP7704-SP

| 110.9_Vout_Vcc_5V_10k_B | | | | | | |
|-----------------------------------|-----------|-----------|----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mV | mV | | | | |
| Max Limit | 54 | 54 | | | | |
| Min Limit | 5 | 5 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 21.547 | 21.896 | 0.349 | 1.62% | 0.71% |
| 1 | 1 | 21.655 | 22.537 | 0.882 | 4.07% | 1.80% |
| 1 | 2 | 21.479 | 22.575 | 1.096 | 5.10% | 2.24% |
| 1 | 3 | 21.163 | 22.076 | 0.912 | 4.31% | 1.86% |
| 1 | 4 | 21.414 | 22.133 | 0.719 | 3.36% | 1.47% |
| 5 | 5 | 21.706 | 24.120 | 2.414 | 11.12% | 4.93% |
| 5 | 6 | 21.689 | 23.862 | 2.173 | 10.02% | 4.43% |
| 5 | 7 | 21.530 | 23.631 | 2.101 | 9.76% | 4.29% |
| 5 | 8 | 21.486 | 23.774 | 2.288 | 10.65% | 4.67% |
| 10 | 9 | 21.581 | 25.067 | 3.487 | 16.16% | 7.12% |
| 10 | 10 | 21.442 | 24.470 | 3.028 | 14.12% | 6.18% |
| 10 | 11 | 21.540 | 24.813 | 3.273 | 15.19% | 6.68% |
| 10 | 12 | 21.455 | 24.650 | 3.195 | 14.89% | 6.52% |
| Max | | 21.706 | 25.067 | 3.487 | 16.16% | 7.12% |
| Average | | 21.514 | 23.508 | 1.993 | 9.26% | 4.07% |
| Min | | 21.163 | 21.896 | 0.349 | 1.62% | 0.71% |
| Std Dev | | 0.141 | 1.129 | 1.089 | 5.05% | 2.22% |




| 110.9_Vout_Vcc_5V_10k_B | | | | |
|-----------------------------------|-----------|--------|--------|--------|
| Test Site | TI Dallas | | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 54 | mV | | |
| Min Limit | 5 | mV | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 21.896 | 22.076 | 23.631 | 24.470 |
| Average | 21.896 | 22.330 | 23.847 | 24.750 |
| Max | 21.896 | 22.575 | 24.120 | 25.068 |
| UL | 54.000 | 54.000 | 54.000 | 54.000 |




NDD Report

LMP7704-SP

| 110.10_Vout_Vcc_5V_10k_C | | | | | | |
|-----------------------------------|-----------|-----------|----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mV | mV | | | | |
| Max Limit | 54 | 54 | | | | |
| Min Limit | 5 | 5 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 21.306 | 21.915 | 0.609 | 2.86% | 1.24% |
| 1 | 1 | 21.507 | 22.357 | 0.850 | 3.95% | 1.73% |
| 1 | 2 | 21.337 | 22.102 | 0.765 | 3.59% | 1.56% |
| 1 | 3 | 21.378 | 22.177 | 0.799 | 3.74% | 1.63% |
| 1 | 4 | 21.354 | 22.146 | 0.792 | 3.71% | 1.62% |
| 5 | 5 | 21.350 | 23.371 | 2.021 | 9.46% | 4.12% |
| 5 | 6 | 21.123 | 23.181 | 2.058 | 9.74% | 4.20% |
| 5 | 7 | 21.313 | 23.249 | 1.936 | 9.08% | 3.95% |
| 5 | 8 | 21.449 | 23.378 | 1.929 | 8.99% | 3.94% |
| 10 | 9 | 21.361 | 24.685 | 3.324 | 15.56% | 6.78% |
| 10 | 10 | 21.401 | 24.162 | 2.761 | 12.90% | 5.63% |
| 10 | 11 | 21.408 | 24.335 | 2.927 | 13.67% | 5.97% |
| 10 | 12 | 21.459 | 24.484 | 3.025 | 14.10% | 6.17% |
| Max | | 21.507 | 24.685 | 3.324 | 15.56% | 6.78% |
| Average | | 21.365 | 23.196 | 1.831 | 8.57% | 3.74% |
| Min | | 21.123 | 21.915 | 0.609 | 2.86% | 1.24% |
| Std Dev | | 0.094 | 0.994 | 0.982 | 4.59% | 2.00% |




| 110.10_Vout_Vcc_5V_10k_C | | | | |
|-----------------------------------|-----------|--------|--------|--------|
| Test Site | TI Dallas | | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 54 | mV | | |
| Min Limit | 5 | mV | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 21.915 | 22.102 | 23.181 | 24.162 |
| Average | 21.915 | 22.195 | 23.295 | 24.417 |
| Max | 21.915 | 22.357 | 23.378 | 24.685 |
| UL | 54.000 | 54.000 | 54.000 | 54.000 |




NDD Report

LMP7704-SP

| 110.11_Vout_Vcc_5V_10k_D | | | | | | |
|--------------------------|-----------|-----------|----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mV | mV | | | | |
| Max Limit | 54 | 54 | | | | |
| Min Limit | 5 | 5 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 21.705 | 21.757 | 0.052 | 0.24% | 0.11% |
| 1 | 1 | 21.647 | 22.012 | 0.365 | 1.69% | 0.74% |
| 1 | 2 | 22.003 | 22.222 | 0.219 | 0.99% | 0.45% |
| 1 | 3 | 21.745 | 22.086 | 0.341 | 1.57% | 0.70% |
| 1 | 4 | 21.616 | 21.968 | 0.351 | 1.62% | 0.72% |
| 5 | 5 | 21.756 | 23.081 | 1.325 | 6.09% | 2.70% |
| 5 | 6 | 21.810 | 23.213 | 1.403 | 6.43% | 2.86% |
| 5 | 7 | 21.800 | 23.176 | 1.376 | 6.31% | 2.81% |
| 5 | 8 | 21.973 | 23.183 | 1.210 | 5.51% | 2.47% |
| 10 | 9 | 21.912 | 24.625 | 2.714 | 12.39% | 5.54% |
| 10 | 10 | 21.973 | 24.473 | 2.500 | 11.38% | 5.10% |
| 10 | 11 | 21.783 | 24.259 | 2.476 | 11.37% | 5.05% |
| 10 | 12 | 22.108 | 24.707 | 2.598 | 11.75% | 5.30% |
| Max | | 22.108 | 24.707 | 2.714 | 12.39% | 5.54% |
| Average | | 21.833 | 23.135 | 1.302 | 5.95% | 2.66% |
| Min | | 21.616 | 21.757 | 0.052 | 0.24% | 0.11% |
| Std Dev | | 0.149 | 1.088 | 0.998 | 4.54% | 2.04% |




| 110.11_Vout_Vcc_5V_10k_D | | | | | | |
|--------------------------|-----------|--------|--------|--------|--|--|
| Test Site | TI Dallas | | | | | |
| Tester | ETS364 | | | | | |
| Test Number | EB4632 | | | | | |
| Max Limit | 54 | mV | | | | |
| Min Limit | 5 | mV | | | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | 5.000 | 5.000 | 5.000 | 5.000 | | |
| Min | 21.757 | 21.968 | 23.081 | 24.259 | | |
| Average | 21.757 | 22.072 | 23.163 | 24.516 | | |
| Max | 21.757 | 22.222 | 23.213 | 24.707 | | |
| UL | 54.000 | 54.000 | 54.000 | 54.000 | | |




NDD Report

LMP7704-SP

| 110.12_Vout_Vee_5V_10k_A | | | | | | | |
|--------------------------|-----------|-----------|-----------|--------|---------|------------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | mV | mV | Max Limit | 45 | 45 | Min Limit | 5 |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 13 | 26.416 | 26.594 | 0.178 | 0.67% | 0.45% | |
| 1 | 1 | 27.125 | 27.574 | 0.450 | 1.66% | 1.12% | |
| 1 | 2 | 26.785 | 26.937 | 0.151 | 0.56% | 0.38% | |
| 1 | 3 | 26.531 | 26.729 | 0.199 | 0.75% | 0.50% | |
| 1 | 4 | 26.510 | 26.746 | 0.236 | 0.89% | 0.59% | |
| 5 | 5 | 26.538 | 29.529 | 2.991 | 11.27% | 7.48% | |
| 5 | 6 | 27.081 | 30.473 | 3.392 | 12.52% | 8.48% | |
| 5 | 7 | 26.551 | 29.108 | 2.557 | 9.63% | 6.39% | |
| 5 | 8 | 26.622 | 29.030 | 2.408 | 9.04% | 6.02% | |
| 10 | 9 | 26.772 | 31.799 | 5.028 | 18.78% | 12.57% | |
| 10 | 10 | 26.399 | 30.384 | 3.986 | 15.10% | 9.96% | |
| 10 | 11 | 26.253 | 30.530 | 4.278 | 16.29% | 10.69% | |
| 10 | 12 | 26.419 | 30.771 | 4.352 | 16.47% | 10.88% | |
| Max | | 27.125 | 31.799 | 5.028 | 18.78% | 12.57% | |
| Average | | 26.615 | 28.939 | 2.323 | 8.74% | 5.81% | |
| Min | | 26.253 | 26.594 | 0.151 | 0.56% | 0.38% | |
| Std Dev | | 0.261 | 1.825 | 1.857 | 7.00% | 4.64% | |




| 110.12_Vout_Vee_5V_10k_A | | | | | | | |
|--------------------------|-----------|-----------|-----------|--------|--------|-------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | mV | mV | Max Limit | 45 | mV | Min Limit | 5 |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | | |
| LL | 5.000 | 5.000 | 5.000 | 5.000 | | | |
| Min | 26.594 | 26.730 | 29.030 | 30.384 | | | |
| Average | 26.594 | 26.997 | 29.535 | 30.871 | | | |
| Max | 26.594 | 27.575 | 30.473 | 31.799 | | | |
| UL | 45.000 | 45.000 | 45.000 | 45.000 | | | |




NDD Report

LMP7704-SP

| 110.13_Vout_Vee_5V_10k_B | | | | | | |
|--------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mV | mV | |
| Tester | ETS364 | ETS364 | Max Limit | 45 | 45 | |
| Test Number | EB4632 | EB4632 | Min Limit | 5 | 5 | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 26.203 | 25.838 | -0.364 | -1.39% | 0.91% |
| 1 | 1 | 26.637 | 27.357 | 0.720 | 2.70% | 1.80% |
| 1 | 2 | 26.274 | 26.881 | 0.607 | 2.31% | 1.52% |
| 1 | 3 | 26.067 | 26.460 | 0.393 | 1.51% | 0.98% |
| 1 | 4 | 26.101 | 26.575 | 0.475 | 1.82% | 1.19% |
| 5 | 5 | 26.878 | 29.584 | 2.707 | 10.07% | 6.77% |
| 5 | 6 | 26.667 | 29.547 | 2.880 | 10.80% | 7.20% |
| 5 | 7 | 26.060 | 28.667 | 2.608 | 10.01% | 6.52% |
| 5 | 8 | 26.152 | 28.365 | 2.214 | 8.46% | 5.53% |
| 10 | 9 | 26.386 | 31.143 | 4.757 | 18.03% | 11.89% |
| 10 | 10 | 26.043 | 30.053 | 4.010 | 15.40% | 10.03% |
| 10 | 11 | 26.023 | 30.518 | 4.496 | 17.28% | 11.24% |
| 10 | 12 | 26.114 | 30.780 | 4.666 | 17.87% | 11.66% |
| Max | | 26.878 | 31.143 | 4.757 | 18.03% | 11.89% |
| Average | | 26.277 | 28.598 | 2.320 | 8.84% | 5.94% |
| Min | | 26.023 | 25.838 | -0.364 | -1.39% | 0.91% |
| Std Dev | | 0.281 | 1.820 | 1.812 | 6.92% | 4.33% |




| 110.13_Vout_Vee_5V_10k_B | | | | |
|--------------------------|-----------|-----------|-----------|-----------|
| Test Site | TI Dallas | TI Dallas | TI Dallas | TI Dallas |
| Tester | ETS364 | ETS364 | ETS364 | ETS364 |
| Test Number | EB4632 | EB4632 | EB4632 | EB4632 |
| Max Limit | 45 | mV | mV | mV |
| Min Limit | 5 | mV | mV | mV |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 25.838 | 26.460 | 28.365 | 30.053 |
| Average | 25.838 | 26.818 | 29.041 | 30.624 |
| Max | 25.838 | 27.357 | 29.584 | 31.143 |
| UL | 45.000 | 45.000 | 45.000 | 45.000 |




NDD Report

LMP7704-SP

| 110.14_Vout_Vee_5V_10k_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | mV | mV | |
| Max Limit | 45 | 45 | Min Limit | 5 | 5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 26.471 | 26.012 | -0.459 | -1.73% | 1.15% |
| 1 | 1 | 26.820 | 26.948 | 0.128 | 0.48% | 0.32% |
| 1 | 2 | 26.454 | 26.416 | -0.038 | -0.14% | 0.10% |
| 1 | 3 | 26.291 | 26.266 | -0.025 | -0.09% | 0.06% |
| 1 | 4 | 26.240 | 26.239 | -0.001 | 0.00% | 0.00% |
| 5 | 5 | 26.787 | 29.212 | 2.426 | 9.06% | 6.06% |
| 5 | 6 | 26.885 | 29.473 | 2.588 | 9.63% | 6.47% |
| 5 | 7 | 26.264 | 28.469 | 2.205 | 8.40% | 5.51% |
| 5 | 8 | 26.450 | 28.398 | 1.947 | 7.36% | 4.87% |
| 10 | 9 | 26.702 | 31.140 | 4.438 | 16.62% | 11.10% |
| 10 | 10 | 26.206 | 30.050 | 3.844 | 14.67% | 9.61% |
| 10 | 11 | 26.185 | 30.244 | 4.058 | 15.50% | 10.15% |
| 10 | 12 | 26.284 | 30.210 | 3.926 | 14.94% | 9.81% |
| Max | | 26.885 | 31.140 | 4.438 | 16.62% | 11.10% |
| Average | | 26.464 | 28.391 | 1.926 | 7.28% | 5.02% |
| Min | | 26.185 | 26.012 | -0.459 | -1.73% | 0.00% |
| Std Dev | | 0.252 | 1.819 | 1.817 | 6.88% | 4.30% |




| 110.14_Vout_Vee_5V_10k_C | | | | |
|-----------------------------------|-----------|--------|-----------|--------|
| Test Site | TI Dallas | ETS364 | Tester | |
| Test Number | EB4632 | | Unit | mV |
| Max Limit | 45 | | Min Limit | 5 |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 26.012 | 26.239 | 28.398 | 30.050 |
| Average | 26.012 | 26.467 | 28.888 | 30.411 |
| Max | 26.012 | 26.948 | 29.474 | 31.140 |
| UL | 45.000 | 45.000 | 45.000 | 45.000 |




NDD Report

LMP7704-SP

| 110.15_Vout_Vee_5V_10k_D | | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | mV | mV | Max Limit | 45 | 45 | Min Limit | 5 |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 13 | 26.294 | 26.299 | 0.005 | 0.02% | 0.01% | |
| 1 | 1 | 26.623 | 27.317 | 0.694 | 2.61% | 1.74% | |
| 1 | 2 | 26.324 | 26.808 | 0.484 | 1.84% | 1.21% | |
| 1 | 3 | 26.029 | 26.496 | 0.467 | 1.79% | 1.17% | |
| 1 | 4 | 26.032 | 26.462 | 0.429 | 1.65% | 1.07% | |
| 5 | 5 | 26.511 | 29.527 | 3.016 | 11.38% | 7.54% | |
| 5 | 6 | 26.647 | 29.816 | 3.169 | 11.89% | 7.92% | |
| 5 | 7 | 26.039 | 28.834 | 2.795 | 10.73% | 6.99% | |
| 5 | 8 | 26.073 | 28.801 | 2.727 | 10.46% | 6.82% | |
| 10 | 9 | 26.413 | 31.384 | 4.971 | 18.82% | 12.43% | |
| 10 | 10 | 25.995 | 30.345 | 4.350 | 16.73% | 10.88% | |
| 10 | 11 | 26.100 | 30.583 | 4.482 | 17.17% | 11.21% | |
| 10 | 12 | 26.650 | 31.034 | 4.384 | 16.45% | 10.96% | |
| Max | | 26.650 | 31.384 | 4.971 | 18.82% | 12.43% | |
| Average | | 26.287 | 28.747 | 2.460 | 9.35% | 6.15% | |
| Min | | 25.995 | 26.299 | 0.005 | 0.02% | 0.01% | |
| Std Dev | | 0.258 | 1.870 | 1.821 | 6.92% | 4.55% | |




| 110.15_Vout_Vee_5V_10k_D | | | | | | | |
|-----------------------------------|-----------|--------|--------|-------------|--------|----|--|
| Test Site | TI Dallas | Tester | ETS364 | Test Number | EB4632 | | |
| Max Limit | 45 | mV | | Min Limit | 5 | mV | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | | |
| LL | 5.000 | 5.000 | 5.000 | 5.000 | | | |
| Min | 26.299 | 26.462 | 28.801 | 30.345 | | | |
| Average | 26.299 | 26.771 | 29.244 | 30.836 | | | |
| Max | 26.299 | 27.317 | 29.816 | 31.384 | | | |
| UL | 45.000 | 45.000 | 45.000 | 45.000 | | | |




NDD Report

LMP7704-SP

| 110.16_Vout_Vcc_10V_2k_A | | | | | | |
|-----------------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mV | mV | | | | |
| Max Limit | 108 | 108 | | | | |
| Min Limit | 5 | 5 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 69.840 | 69.673 | -0.166 | -0.24% | 0.16% |
| 1 | 1 | 70.172 | 70.451 | 0.278 | 0.40% | 0.27% |
| 1 | 2 | 69.914 | 70.182 | 0.268 | 0.38% | 0.26% |
| 1 | 3 | 69.079 | 69.779 | 0.699 | 1.01% | 0.68% |
| 1 | 4 | 69.313 | 69.605 | 0.292 | 0.42% | 0.28% |
| 5 | 5 | 69.972 | 71.950 | 1.979 | 2.83% | 1.92% |
| 5 | 6 | 70.267 | 72.341 | 2.074 | 2.95% | 2.01% |
| 5 | 7 | 69.575 | 71.360 | 1.785 | 2.57% | 1.73% |
| 5 | 8 | 70.271 | 71.967 | 1.697 | 2.41% | 1.65% |
| 10 | 9 | 69.320 | 73.104 | 3.784 | 5.46% | 3.67% |
| 10 | 10 | 69.208 | 72.395 | 3.187 | 4.60% | 3.09% |
| 10 | 11 | 69.429 | 72.521 | 3.092 | 4.45% | 3.00% |
| 10 | 12 | 69.649 | 72.456 | 2.807 | 4.03% | 2.72% |
| Max | | 70.271 | 73.104 | 3.784 | 5.46% | 3.67% |
| Average | | 69.693 | 71.368 | 1.675 | 2.41% | 1.65% |
| Min | | 69.079 | 69.605 | -0.166 | -0.24% | 0.16% |
| Std Dev | | 0.410 | 1.258 | 1.306 | 1.88% | 1.23% |




| 110.16_Vout_Vcc_10V_2k_A | | | | | | |
|-----------------------------------|-----------|---------|---------|---------|--|--|
| Test Site | TI Dallas | | | | | |
| Tester | ETS364 | | | | | |
| Test Number | EB4632 | | | | | |
| Max Limit | 108 | mV | | | | |
| Min Limit | 5 | mV | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 5.000 | 5.000 | 5.000 | 5.000 | | |
| Min | 69.673 | 69.606 | 71.360 | 72.395 | | |
| Average | 69.673 | 70.004 | 71.905 | 72.619 | | |
| Max | 69.673 | 70.451 | 72.341 | 73.104 | | |
| UL | 108.000 | 108.000 | 108.000 | 108.000 | | |




NDD Report

LMP7704-SP

| 110.17_Vout_Vcc_10V_2k_B | | | | | | |
|-----------------------------------|-----------|-----------|----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mV | mV | | | | |
| Max Limit | 108 | 108 | | | | |
| Min Limit | 5 | 5 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 69.688 | 70.336 | 0.648 | 0.93% | 0.63% |
| 1 | 1 | 70.339 | 71.453 | 1.113 | 1.58% | 1.08% |
| 1 | 2 | 69.820 | 71.310 | 1.490 | 2.13% | 1.45% |
| 1 | 3 | 69.097 | 70.271 | 1.174 | 1.70% | 1.14% |
| 1 | 4 | 69.488 | 70.359 | 0.872 | 1.25% | 0.85% |
| 5 | 5 | 70.353 | 73.083 | 2.730 | 3.88% | 2.65% |
| 5 | 6 | 70.584 | 73.474 | 2.890 | 4.09% | 2.81% |
| 5 | 7 | 69.610 | 72.139 | 2.529 | 3.63% | 2.46% |
| 5 | 8 | 69.674 | 72.353 | 2.678 | 3.84% | 2.60% |
| 10 | 9 | 69.800 | 73.898 | 4.098 | 5.87% | 3.98% |
| 10 | 10 | 69.461 | 73.222 | 3.762 | 5.42% | 3.65% |
| 10 | 11 | 69.633 | 73.321 | 3.687 | 5.30% | 3.58% |
| 10 | 12 | 69.596 | 73.311 | 3.714 | 5.34% | 3.61% |
| Max | | 70.584 | 73.898 | 4.098 | 5.87% | 3.98% |
| Average | | 69.780 | 72.195 | 2.414 | 3.46% | 2.34% |
| Min | | 69.097 | 70.271 | 0.648 | 0.93% | 0.63% |
| Std Dev | | 0.413 | 1.316 | 1.223 | 1.75% | 1.19% |




| 110.17_Vout_Vcc_10V_2k_B | | | | |
|-----------------------------------|-----------|---------|---------|---------|
| Test Site | TI Dallas | | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 108 | mV | | |
| Min Limit | 5 | mV | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 70.336 | 70.271 | 72.139 | 73.222 |
| Average | 70.336 | 70.848 | 72.762 | 73.438 |
| Max | 70.336 | 71.453 | 73.474 | 73.898 |
| UL | 108.000 | 108.000 | 108.000 | 108.000 |




NDD Report

LMP7704-SP

| 110.18_Vout_Vcc_10V_2k_C | | | | | | |
|--------------------------|-----------|-----------|----------|---------|------------------|------------------|
| Test Site | TI Dallas | TI Dallas | Delta | Delta % | % of Limit Range | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mV | mV | | | | |
| Max Limit | 108 | 108 | | | | |
| Min Limit | 5 | 5 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 69.175 | 69.156 | -0.019 | -0.03% | 0.02% |
| 1 | 1 | 69.909 | 70.724 | 0.815 | 1.17% | 0.79% |
| 1 | 2 | 69.525 | 70.225 | 0.700 | 1.01% | 0.68% |
| 1 | 3 | 69.335 | 69.940 | 0.605 | 0.87% | 0.59% |
| 1 | 4 | 69.189 | 69.757 | 0.568 | 0.82% | 0.55% |
| 5 | 5 | 69.633 | 71.884 | 2.251 | 3.23% | 2.19% |
| 5 | 6 | 69.505 | 71.711 | 2.207 | 3.18% | 2.14% |
| 5 | 7 | 69.168 | 71.338 | 2.170 | 3.14% | 2.11% |
| 5 | 8 | 69.566 | 71.772 | 2.207 | 3.17% | 2.14% |
| 10 | 9 | 69.338 | 73.096 | 3.758 | 5.42% | 3.65% |
| 10 | 10 | 69.301 | 72.594 | 3.293 | 4.75% | 3.20% |
| 10 | 11 | 69.328 | 72.682 | 3.354 | 4.84% | 3.26% |
| 10 | 12 | 69.542 | 72.909 | 3.368 | 4.84% | 3.27% |
| Max | | 69.909 | 73.096 | 3.758 | 5.42% | 3.65% |
| Average | | 69.424 | 71.368 | 1.944 | 2.80% | 1.89% |
| Min | | 69.168 | 69.156 | -0.019 | -0.03% | 0.02% |
| Std Dev | | 0.214 | 1.304 | 1.284 | 1.85% | 1.24% |




| 110.18_Vout_Vcc_10V_2k_C | | | | | | |
|--------------------------|-----------|-----------|---------|---------|------------------|--|
| Test Site | TI Dallas | TI Dallas | Delta | Delta % | % of Limit Range | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Max Limit | 108 | mV | | | | |
| Min Limit | 5 | mV | | | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | 5.000 | 5.000 | 5.000 | 5.000 | | |
| Min | 69.156 | 69.757 | 71.338 | 72.594 | | |
| Average | 69.156 | 70.161 | 71.677 | 72.820 | | |
| Max | 69.156 | 70.724 | 71.885 | 73.096 | | |
| UL | 108.000 | 108.000 | 108.000 | 108.000 | | |




NDD Report

LMP7704-SP

| 110.19_Vout_Vcc_10V_2k_D | | | | | | |
|-----------------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mV | mV | | | | |
| Max Limit | 108 | 108 | | | | |
| Min Limit | 5 | 5 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 69.947 | 69.886 | -0.061 | -0.09% | 0.06% |
| 1 | 1 | 70.324 | 70.782 | 0.459 | 0.65% | 0.45% |
| 1 | 2 | 70.605 | 71.071 | 0.465 | 0.66% | 0.45% |
| 1 | 3 | 70.045 | 70.466 | 0.421 | 0.60% | 0.41% |
| 1 | 4 | 69.889 | 70.246 | 0.357 | 0.51% | 0.35% |
| 5 | 5 | 70.150 | 72.136 | 1.986 | 2.83% | 1.93% |
| 5 | 6 | 70.615 | 72.622 | 2.007 | 2.84% | 1.95% |
| 5 | 7 | 70.113 | 72.031 | 1.918 | 2.74% | 1.86% |
| 5 | 8 | 70.503 | 72.371 | 1.867 | 2.65% | 1.81% |
| 10 | 9 | 70.473 | 73.895 | 3.422 | 4.86% | 3.32% |
| 10 | 10 | 70.398 | 73.488 | 3.089 | 4.39% | 3.00% |
| 10 | 11 | 69.889 | 73.162 | 3.273 | 4.68% | 3.18% |
| 10 | 12 | 70.660 | 74.000 | 3.341 | 4.73% | 3.24% |
| Max | | 70.660 | 74.000 | 3.422 | 4.86% | 3.32% |
| Average | | 70.278 | 72.012 | 1.734 | 2.47% | 1.69% |
| Min | | 69.889 | 69.886 | -0.061 | -0.09% | 0.06% |
| Std Dev | | 0.286 | 1.412 | 1.288 | 1.83% | 1.24% |




| 110.19_Vout_Vcc_10V_2k_D | | | | | | |
|-----------------------------------|-----------|---------|---------|---------|--|--|
| Test Site | TI Dallas | | | | | |
| Tester | ETS364 | | | | | |
| Test Number | EB4632 | | | | | |
| Max Limit | 108 | mV | | | | |
| Min Limit | 5 | mV | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 5.000 | 5.000 | 5.000 | 5.000 | | |
| Min | 69.886 | 70.246 | 72.031 | 73.162 | | |
| Average | 69.886 | 70.641 | 72.290 | 73.636 | | |
| Max | 69.886 | 71.071 | 72.622 | 74.000 | | |
| UL | 108.000 | 108.000 | 108.000 | 108.000 | | |




NDD Report

LMP7704-SP

| 110.20_Vout_Vee_10V_2k_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mV | mV | |
| Tester | ETS364 | ETS364 | Max Limit | 108 | 108 | |
| Test Number | EB4632 | EB4632 | Min Limit | 5 | 5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 81.716 | 81.384 | -0.331 | -0.41% | 0.32% |
| 1 | 1 | 82.568 | 83.271 | 0.703 | 0.85% | 0.68% |
| 1 | 2 | 82.089 | 82.521 | 0.432 | 0.53% | 0.42% |
| 1 | 3 | 81.366 | 82.033 | 0.666 | 0.82% | 0.65% |
| 1 | 4 | 81.118 | 81.799 | 0.680 | 0.84% | 0.66% |
| 5 | 5 | 81.933 | 85.134 | 3.201 | 3.91% | 3.11% |
| 5 | 6 | 83.447 | 86.356 | 2.909 | 3.49% | 2.82% |
| 5 | 7 | 81.522 | 84.015 | 2.492 | 3.06% | 2.42% |
| 5 | 8 | 81.767 | 84.143 | 2.377 | 2.91% | 2.31% |
| 10 | 9 | 82.232 | 87.286 | 5.054 | 6.15% | 4.91% |
| 10 | 10 | 81.397 | 85.881 | 4.484 | 5.51% | 4.35% |
| 10 | 11 | 81.057 | 85.911 | 4.854 | 5.99% | 4.71% |
| 10 | 12 | 81.539 | 85.871 | 4.331 | 5.31% | 4.21% |
| Max | | 83.447 | 87.286 | 5.054 | 6.15% | 4.91% |
| Average | | 81.827 | 84.277 | 2.450 | 3.00% | 2.43% |
| Min | | 81.057 | 81.384 | -0.331 | -0.41% | 0.32% |
| Std Dev | | 0.652 | 1.950 | 1.875 | 2.30% | 1.75% |




| 110.20_Vout_Vee_10V_2k_A | | | | |
|-----------------------------------|-----------|---------|---------|---------|
| Test Site | TI Dallas | ETS364 | EB4632 | |
| Tester | | | | |
| Test Number | | | | |
| Max Limit | 108 | mV | | |
| Min Limit | 5 | mV | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 81.385 | 81.799 | 84.015 | 85.871 |
| Average | 81.385 | 82.406 | 84.912 | 86.237 |
| Max | 81.385 | 83.271 | 86.356 | 87.286 |
| UL | 108.000 | 108.000 | 108.000 | 108.000 |




NDD Report

LMP7704-SP

| 110.21_Vout_Vee_10V_2k_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | mV | mV | |
| Max Limit | 108 | 108 | Min Limit | 5 | 5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 80.788 | 81.061 | 0.273 | 0.34% | 0.26% |
| 1 | 1 | 81.989 | 83.173 | 1.184 | 1.44% | 1.15% |
| 1 | 2 | 81.212 | 82.151 | 0.939 | 1.16% | 0.91% |
| 1 | 3 | 80.635 | 81.431 | 0.796 | 0.99% | 0.77% |
| 1 | 4 | 80.594 | 81.244 | 0.650 | 0.81% | 0.63% |
| 5 | 5 | 81.935 | 85.357 | 3.422 | 4.18% | 3.32% |
| 5 | 6 | 82.053 | 85.924 | 3.871 | 4.72% | 3.76% |
| 5 | 7 | 80.353 | 83.618 | 3.264 | 4.06% | 3.17% |
| 5 | 8 | 80.856 | 83.880 | 3.024 | 3.74% | 2.94% |
| 10 | 9 | 81.263 | 86.542 | 5.279 | 6.50% | 5.13% |
| 10 | 10 | 80.632 | 85.496 | 4.864 | 6.03% | 4.72% |
| 10 | 11 | 80.435 | 85.459 | 5.024 | 6.25% | 4.88% |
| 10 | 12 | 80.706 | 86.213 | 5.506 | 6.82% | 5.35% |
| Max | | 82.053 | 86.542 | 5.506 | 6.82% | 5.35% |
| Average | | 81.035 | 83.965 | 2.930 | 3.62% | 2.85% |
| Min | | 80.353 | 81.061 | 0.273 | 0.34% | 0.26% |
| Std Dev | | 0.604 | 2.007 | 1.944 | 2.40% | 1.89% |




| 110.21_Vout_Vee_10V_2k_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | mV | mV | |
| Max Limit | 108 | mV | Min Limit | 5 | mV | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 5.000 | 5.000 | 5.000 | 5.000 | | |
| Min | 81.061 | 81.244 | 83.618 | 85.459 | | |
| Average | 81.061 | 82.000 | 84.695 | 85.927 | | |
| Max | 81.061 | 83.173 | 85.924 | 86.542 | | |
| UL | 108.000 | 108.000 | 108.000 | 108.000 | | |




NDD Report

LMP7704-SP

| 110.22_Vout_Vee_10V_2k_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mV | mV | |
| Tester | ETS364 | ETS364 | Max Limit | 108 | 108 | |
| Test Number | EB4632 | EB4632 | Min Limit | 5 | 5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 81.419 | 81.123 | -0.296 | -0.36% | 0.29% |
| 1 | 1 | 82.356 | 82.738 | 0.382 | 0.46% | 0.37% |
| 1 | 2 | 81.514 | 81.703 | 0.189 | 0.23% | 0.18% |
| 1 | 3 | 81.127 | 81.316 | 0.189 | 0.23% | 0.18% |
| 1 | 4 | 81.039 | 81.191 | 0.152 | 0.19% | 0.15% |
| 5 | 5 | 82.122 | 84.876 | 2.754 | 3.35% | 2.67% |
| 5 | 6 | 82.465 | 85.290 | 2.826 | 3.43% | 2.74% |
| 5 | 7 | 81.147 | 83.512 | 2.365 | 2.91% | 2.30% |
| 5 | 8 | 81.311 | 83.624 | 2.313 | 2.85% | 2.25% |
| 10 | 9 | 81.891 | 86.689 | 4.798 | 5.86% | 4.66% |
| 10 | 10 | 81.046 | 85.219 | 4.174 | 5.15% | 4.05% |
| 10 | 11 | 80.862 | 85.199 | 4.337 | 5.36% | 4.21% |
| 10 | 12 | 81.168 | 85.518 | 4.350 | 5.36% | 4.22% |
| Max | | 82.465 | 86.689 | 4.798 | 5.86% | 4.66% |
| Average | | 81.497 | 83.692 | 2.195 | 2.69% | 2.17% |
| Min | | 80.862 | 81.123 | -0.296 | -0.36% | 0.15% |
| Std Dev | | 0.536 | 1.921 | 1.879 | 2.31% | 1.77% |




| 110.22_Vout_Vee_10V_2k_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|-----|--|
| Test Site | TI Dallas | TI Dallas | Unit | mV | mV | |
| Tester | ETS364 | ETS364 | Max Limit | 108 | 108 | |
| Test Number | EB4632 | EB4632 | Min Limit | 5 | 5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 5.000 | 5.000 | 5.000 | 5.000 | | |
| Min | 81.123 | 81.191 | 83.512 | 85.199 | | |
| Average | 81.123 | 81.737 | 84.326 | 85.656 | | |
| Max | 81.123 | 82.738 | 85.290 | 86.689 | | |
| UL | 108.000 | 108.000 | 108.000 | 108.000 | | |




NDD Report

LMP7704-SP

| 110.23_Vout_Vee_10V_2k_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mV | mV | |
| Tester | ETS364 | ETS364 | Max Limit | 108 | 108 | |
| Test Number | EB4632 | EB4632 | Min Limit | 5 | 5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 81.250 | 81.305 | 0.055 | 0.07% | 0.05% |
| 1 | 1 | 82.360 | 83.107 | 0.747 | 0.91% | 0.73% |
| 1 | 2 | 81.447 | 82.099 | 0.652 | 0.80% | 0.63% |
| 1 | 3 | 80.812 | 81.390 | 0.578 | 0.71% | 0.56% |
| 1 | 4 | 80.853 | 81.454 | 0.601 | 0.74% | 0.58% |
| 5 | 5 | 81.763 | 85.015 | 3.253 | 3.98% | 3.16% |
| 5 | 6 | 82.397 | 85.674 | 3.276 | 3.98% | 3.18% |
| 5 | 7 | 80.809 | 83.820 | 3.011 | 3.73% | 2.92% |
| 5 | 8 | 81.053 | 83.949 | 2.896 | 3.57% | 2.81% |
| 10 | 9 | 81.630 | 86.933 | 5.303 | 6.50% | 5.15% |
| 10 | 10 | 80.921 | 85.643 | 4.722 | 5.84% | 4.58% |
| 10 | 11 | 80.890 | 85.748 | 4.858 | 6.01% | 4.72% |
| 10 | 12 | 81.545 | 86.315 | 4.770 | 5.85% | 4.63% |
| Max | | 82.397 | 86.933 | 5.303 | 6.50% | 5.15% |
| Average | | 81.364 | 84.035 | 2.671 | 3.28% | 2.59% |
| Min | | 80.809 | 81.305 | 0.055 | 0.07% | 0.05% |
| Std Dev | | 0.558 | 2.011 | 1.925 | 2.37% | 1.87% |




| 110.23_Vout_Vee_10V_2k_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|-----|--|
| Test Site | TI Dallas | TI Dallas | Unit | mV | mV | |
| Tester | ETS364 | ETS364 | Max Limit | 108 | 108 | |
| Test Number | EB4632 | EB4632 | Min Limit | 5 | 5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 5.000 | 5.000 | 5.000 | 5.000 | | |
| Min | 81.305 | 81.390 | 83.820 | 85.643 | | |
| Average | 81.305 | 82.013 | 84.615 | 86.160 | | |
| Max | 81.305 | 83.108 | 85.674 | 86.933 | | |
| UL | 108.000 | 108.000 | 108.000 | 108.000 | | |




NDD Report

LMP7704-SP

| 110.24_Vout_Vcc_10V_10k_A | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mV | mV | |
| Tester | ETS364 | ETS364 | Max Limit | 54 | 54 | |
| Test Number | EB4632 | EB4632 | Min Limit | 5 | 5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 29.149 | 28.737 | -0.413 | -1.42% | 0.84% |
| 1 | 1 | 28.779 | 29.310 | 0.531 | 1.85% | 1.08% |
| 1 | 2 | 28.708 | 29.110 | 0.402 | 1.40% | 0.82% |
| 1 | 3 | 28.555 | 28.886 | 0.331 | 1.16% | 0.68% |
| 1 | 4 | 28.783 | 29.025 | 0.243 | 0.84% | 0.49% |
| 5 | 5 | 29.000 | 30.352 | 1.352 | 4.66% | 2.76% |
| 5 | 6 | 29.384 | 30.546 | 1.162 | 3.95% | 2.37% |
| 5 | 7 | 29.000 | 30.200 | 1.200 | 4.14% | 2.45% |
| 5 | 8 | 28.959 | 30.403 | 1.444 | 4.99% | 2.95% |
| 10 | 9 | 28.925 | 31.462 | 2.537 | 8.77% | 5.18% |
| 10 | 10 | 28.980 | 30.875 | 1.895 | 6.54% | 3.87% |
| 10 | 11 | 29.061 | 31.065 | 2.004 | 6.89% | 4.09% |
| 10 | 12 | 28.735 | 30.963 | 2.228 | 7.75% | 4.55% |
| Max | | 29.384 | 31.462 | 2.537 | 8.77% | 5.18% |
| Average | | 28.925 | 30.072 | 1.147 | 3.96% | 2.47% |
| Min | | 28.555 | 28.737 | -0.413 | -1.42% | 0.49% |
| Std Dev | | 0.215 | 0.939 | 0.884 | 3.05% | 1.61% |




| 110.24_Vout_Vcc_10V_10k_A | | | | |
|-----------------------------------|-----------|--------|--------|--------|
| Test Site | TI Dallas | ETS364 | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 54 | mV | | |
| Min Limit | 5 | mV | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 28.737 | 28.886 | 30.200 | 30.875 |
| Average | 28.737 | 29.083 | 30.375 | 31.091 |
| Max | 28.737 | 29.311 | 30.546 | 31.462 |
| UL | 54.000 | 54.000 | 54.000 | 54.000 |




NDD Report

LMP7704-SP

| 110.25_Vout_Vcc_10V_10k_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mV | mV | |
| Tester | ETS364 | ETS364 | Max Limit | 54 | 54 | |
| Test Number | EB4632 | EB4632 | Min Limit | 5 | 5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 28.872 | 29.204 | 0.333 | 1.15% | 0.68% |
| 1 | 1 | 29.062 | 29.585 | 0.523 | 1.80% | 1.07% |
| 1 | 2 | 28.797 | 29.785 | 0.988 | 3.43% | 2.02% |
| 1 | 3 | 28.502 | 29.194 | 0.692 | 2.43% | 1.41% |
| 1 | 4 | 28.756 | 29.089 | 0.333 | 1.16% | 0.68% |
| 5 | 5 | 29.167 | 31.201 | 2.034 | 6.98% | 4.15% |
| 5 | 6 | 29.062 | 31.035 | 1.973 | 6.79% | 4.03% |
| 5 | 7 | 28.811 | 30.777 | 1.966 | 6.82% | 4.01% |
| 5 | 8 | 28.953 | 30.400 | 1.447 | 5.00% | 2.95% |
| 10 | 9 | 28.902 | 32.247 | 3.345 | 11.57% | 6.83% |
| 10 | 10 | 28.797 | 31.694 | 2.897 | 10.06% | 5.91% |
| 10 | 11 | 28.865 | 31.741 | 2.876 | 9.97% | 5.87% |
| 10 | 12 | 28.828 | 31.279 | 2.452 | 8.51% | 5.00% |
| Max | | 29.167 | 32.247 | 3.345 | 11.57% | 6.83% |
| Average | | 28.875 | 30.556 | 1.681 | 5.82% | 3.43% |
| Min | | 28.502 | 29.089 | 0.333 | 1.15% | 0.68% |
| Std Dev | | 0.167 | 1.087 | 1.043 | 3.61% | 2.13% |




| 110.25_Vout_Vcc_10V_10k_B | | | | |
|-----------------------------------|-----------|-----------|--------|--------|
| Test Site | TI Dallas | Tester | ETS364 | |
| Test Number | EB4632 | Max Limit | 54 | mV |
| Min Limit | 5 | mV | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 29.204 | 29.089 | 30.400 | 31.279 |
| Average | 29.204 | 29.413 | 30.853 | 31.740 |
| Max | 29.204 | 29.785 | 31.201 | 32.247 |
| UL | 54.000 | 54.000 | 54.000 | 54.000 |




NDD Report

LMP7704-SP

| 110.26_Vout_Vcc_10V_10k_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mV | mV | |
| Tester | ETS364 | ETS364 | Max Limit | 54 | 54 | |
| Test Number | EB4632 | EB4632 | Min Limit | 5 | 5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 28.477 | 28.782 | 0.305 | 1.07% | 0.62% |
| 1 | 1 | 28.739 | 29.427 | 0.688 | 2.39% | 1.40% |
| 1 | 2 | 28.599 | 29.216 | 0.617 | 2.16% | 1.26% |
| 1 | 3 | 28.589 | 29.169 | 0.580 | 2.03% | 1.18% |
| 1 | 4 | 28.586 | 29.165 | 0.580 | 2.03% | 1.18% |
| 5 | 5 | 28.623 | 30.448 | 1.825 | 6.38% | 3.72% |
| 5 | 6 | 28.406 | 30.255 | 1.849 | 6.51% | 3.77% |
| 5 | 7 | 28.447 | 30.258 | 1.812 | 6.37% | 3.70% |
| 5 | 8 | 28.739 | 30.476 | 1.737 | 6.04% | 3.54% |
| 10 | 9 | 28.566 | 31.568 | 3.003 | 10.51% | 6.13% |
| 10 | 10 | 28.542 | 31.090 | 2.548 | 8.93% | 5.20% |
| 10 | 11 | 28.630 | 31.283 | 2.653 | 9.27% | 5.41% |
| 10 | 12 | 28.783 | 31.361 | 2.578 | 8.96% | 5.26% |
| Max | | 28.783 | 31.568 | 3.003 | 10.51% | 6.13% |
| Average | | 28.594 | 30.192 | 1.598 | 5.59% | 3.26% |
| Min | | 28.406 | 28.782 | 0.305 | 1.07% | 0.62% |
| Std Dev | | 0.113 | 0.959 | 0.943 | 3.30% | 1.92% |




| 110.26_Vout_Vcc_10V_10k_C | | | | |
|-----------------------------------|-----------|--------|--------|--------|
| Test Site | TI Dallas | ETS364 | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 54 | mV | | |
| Min Limit | 5 | mV | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 28.782 | 29.165 | 30.255 | 31.090 |
| Average | 28.782 | 29.244 | 30.359 | 31.326 |
| Max | 28.782 | 29.427 | 30.476 | 31.568 |
| UL | 54.000 | 54.000 | 54.000 | 54.000 |




NDD Report

LMP7704-SP

| 110.27_Vout_Vcc_10V_10k_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mV | mV | |
| Tester | ETS364 | ETS364 | Max Limit | 54 | 54 | |
| Test Number | EB4632 | EB4632 | Min Limit | 5 | 5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 28.830 | 28.761 | -0.069 | -0.24% | 0.14% |
| 1 | 1 | 28.867 | 29.128 | 0.261 | 0.90% | 0.53% |
| 1 | 2 | 29.207 | 29.417 | 0.210 | 0.72% | 0.43% |
| 1 | 3 | 28.901 | 29.165 | 0.264 | 0.91% | 0.54% |
| 1 | 4 | 28.806 | 29.009 | 0.203 | 0.70% | 0.41% |
| 5 | 5 | 28.827 | 30.367 | 1.540 | 5.34% | 3.14% |
| 5 | 6 | 29.142 | 30.530 | 1.388 | 4.76% | 2.83% |
| 5 | 7 | 28.966 | 30.381 | 1.415 | 4.88% | 2.89% |
| 5 | 8 | 29.098 | 30.483 | 1.384 | 4.76% | 2.83% |
| 10 | 9 | 29.197 | 31.816 | 2.620 | 8.97% | 5.35% |
| 10 | 10 | 29.166 | 31.749 | 2.583 | 8.85% | 5.27% |
| 10 | 11 | 28.945 | 31.504 | 2.559 | 8.84% | 5.22% |
| 10 | 12 | 29.360 | 31.918 | 2.559 | 8.72% | 5.22% |
| Max | | 29.360 | 31.918 | 2.620 | 8.97% | 5.35% |
| Average | | 29.024 | 30.325 | 1.301 | 4.47% | 2.68% |
| Min | | 28.806 | 28.761 | -0.069 | -0.24% | 0.14% |
| Std Dev | | 0.180 | 1.156 | 1.043 | 3.58% | 2.10% |




| 110.27_Vout_Vcc_10V_10k_D | | | | |
|-----------------------------------|-----------|--------|--------|--------|
| Test Site | TI Dallas | ETS364 | | |
| Tester | ETS364 | ETS364 | | |
| Test Number | EB4632 | | | |
| Max Limit | 54 | mV | | |
| Min Limit | 5 | mV | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 28.761 | 29.009 | 30.367 | 31.504 |
| Average | 28.761 | 29.180 | 30.440 | 31.747 |
| Max | 28.761 | 29.417 | 30.530 | 31.918 |
| UL | 54.000 | 54.000 | 54.000 | 54.000 |




NDD Report

LMP7704-SP

| 110.28_Vout_Vee_10V_10k_A | | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | mV | mV | Max Limit | 45 | 45 | Min Limit | 5 |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 13 | 35.117 | 34.574 | -0.543 | -1.55% | 1.36% | |
| 1 | 1 | 35.171 | 35.887 | 0.716 | 2.04% | 1.79% | |
| 1 | 2 | 35.011 | 35.263 | 0.251 | 0.72% | 0.63% | |
| 1 | 3 | 34.326 | 34.910 | 0.584 | 1.70% | 1.46% | |
| 1 | 4 | 34.655 | 34.903 | 0.248 | 0.72% | 0.62% | |
| 5 | 5 | 35.357 | 37.852 | 2.495 | 7.06% | 6.24% | |
| 5 | 6 | 36.196 | 39.036 | 2.840 | 7.85% | 7.10% | |
| 5 | 7 | 34.618 | 36.820 | 2.203 | 6.36% | 5.51% | |
| 5 | 8 | 34.702 | 36.997 | 2.294 | 6.61% | 5.74% | |
| 10 | 9 | 35.452 | 39.803 | 4.351 | 12.27% | 10.88% | |
| 10 | 10 | 34.410 | 38.588 | 4.178 | 12.14% | 10.44% | |
| 10 | 11 | 34.859 | 38.901 | 4.042 | 11.60% | 10.11% | |
| 10 | 12 | 34.482 | 38.904 | 4.422 | 12.82% | 11.06% | |
| Max | | 36.196 | 39.803 | 4.422 | 12.82% | 11.06% | |
| Average | | 34.950 | 37.111 | 2.160 | 6.18% | 5.61% | |
| Min | | 34.326 | 34.574 | -0.543 | -1.55% | 0.62% | |
| Std Dev | | 0.518 | 1.855 | 1.763 | 5.05% | 4.12% | |




| 110.28_Vout_Vee_10V_10k_A | | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|--------|-------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Max Limit | 45 | mV | Min Limit | 5 | mV | Unit | mV |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 5 | 10 | | | | |
| LL | 5.000 | 5.000 | 5.000 | 5.000 | | | |
| Min | 34.574 | 34.903 | 36.820 | 38.588 | | | |
| Average | 34.574 | 35.241 | 37.676 | 39.049 | | | |
| Max | 34.574 | 35.887 | 39.036 | 39.803 | | | |
| UL | 45.000 | 45.000 | 45.000 | 45.000 | | | |




NDD Report

LMP7704-SP

| 110.29_Vout_Vee_10V_10k_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mV | mV | |
| Tester | ETS364 | ETS364 | Max Limit | 45 | 45 | |
| Test Number | EB4632 | EB4632 | Min Limit | 5 | 5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 34.233 | 34.536 | 0.303 | 0.89% | 0.76% |
| 1 | 1 | 34.783 | 35.722 | 0.938 | 2.70% | 2.35% |
| 1 | 2 | 34.400 | 35.348 | 0.948 | 2.76% | 2.37% |
| 1 | 3 | 34.179 | 34.937 | 0.758 | 2.22% | 1.90% |
| 1 | 4 | 34.176 | 34.937 | 0.762 | 2.23% | 1.90% |
| 5 | 5 | 35.323 | 38.534 | 3.211 | 9.09% | 8.03% |
| 5 | 6 | 34.841 | 38.062 | 3.221 | 9.24% | 8.05% |
| 5 | 7 | 34.189 | 36.900 | 2.711 | 7.93% | 6.78% |
| 5 | 8 | 34.267 | 36.635 | 2.368 | 6.91% | 5.92% |
| 10 | 9 | 34.532 | 39.440 | 4.909 | 14.21% | 12.27% |
| 10 | 10 | 34.054 | 38.170 | 4.117 | 12.09% | 10.29% |
| 10 | 11 | 34.023 | 38.995 | 4.973 | 14.62% | 12.43% |
| 10 | 12 | 34.247 | 38.775 | 4.528 | 13.22% | 11.32% |
| Max | | 35.323 | 39.440 | 4.973 | 14.62% | 12.43% |
| Average | | 34.404 | 36.999 | 2.596 | 7.55% | 6.49% |
| Min | | 34.023 | 34.536 | 0.303 | 0.89% | 0.76% |
| Std Dev | | 0.375 | 1.757 | 1.716 | 5.00% | 4.29% |




| 110.29_Vout_Vee_10V_10k_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|----|--|
| Test Site | TI Dallas | TI Dallas | Unit | mV | mV | |
| Tester | ETS364 | ETS364 | Max Limit | 45 | mV | |
| Test Number | EB4632 | EB4632 | Min Limit | 5 | mV | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 5.000 | 5.000 | 5.000 | 5.000 | | |
| Min | 34.536 | 34.937 | 36.635 | 38.170 | | |
| Average | 34.536 | 35.236 | 37.533 | 38.845 | | |
| Max | 34.536 | 35.722 | 38.534 | 39.440 | | |
| UL | 45.000 | 45.000 | 45.000 | 45.000 | | |




NDD Report

LMP7704-SP

| 110.30_Vout_Vee_10V_10k_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mV | mV | |
| Tester | ETS364 | ETS364 | Max Limit | 45 | 45 | |
| Test Number | EB4632 | EB4632 | Min Limit | 5 | 5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 34.979 | 34.501 | -0.479 | -1.37% | 1.20% |
| 1 | 1 | 35.431 | 35.468 | 0.037 | 0.10% | 0.09% |
| 1 | 2 | 34.908 | 34.792 | -0.116 | -0.33% | 0.29% |
| 1 | 3 | 34.755 | 34.759 | 0.003 | 0.01% | 0.01% |
| 1 | 4 | 34.664 | 34.626 | -0.037 | -0.11% | 0.09% |
| 5 | 5 | 35.397 | 37.786 | 2.389 | 6.75% | 5.97% |
| 5 | 6 | 35.509 | 37.929 | 2.419 | 6.81% | 6.05% |
| 5 | 7 | 34.806 | 37.033 | 2.226 | 6.40% | 5.57% |
| 5 | 8 | 34.925 | 36.941 | 2.016 | 5.77% | 5.04% |
| 10 | 9 | 35.227 | 39.493 | 4.266 | 12.11% | 10.66% |
| 10 | 10 | 34.688 | 38.444 | 3.757 | 10.83% | 9.39% |
| 10 | 11 | 34.671 | 38.478 | 3.808 | 10.98% | 9.52% |
| 10 | 12 | 34.850 | 38.594 | 3.743 | 10.74% | 9.36% |
| Max | | 35.509 | 39.493 | 4.266 | 12.11% | 10.66% |
| Average | | 34.986 | 36.834 | 1.849 | 5.28% | 4.86% |
| Min | | 34.664 | 34.501 | -0.479 | -1.37% | 0.01% |
| Std Dev | | 0.303 | 1.786 | 1.761 | 5.04% | 4.11% |




| 110.30_Vout_Vee_10V_10k_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|----|--|
| Test Site | TI Dallas | TI Dallas | Unit | mV | mV | |
| Tester | ETS364 | ETS364 | Max Limit | 45 | 45 | |
| Test Number | EB4632 | EB4632 | Min Limit | 5 | 5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 5.000 | 5.000 | 5.000 | 5.000 | | |
| Min | 34.501 | 34.626 | 36.941 | 38.444 | | |
| Average | 34.501 | 34.911 | 37.422 | 38.752 | | |
| Max | 34.501 | 35.468 | 37.929 | 39.493 | | |
| UL | 45.000 | 45.000 | 45.000 | 45.000 | | |




NDD Report

LMP7704-SP

| 110.31_Vout_Vee_10V_10k_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mV | mV | |
| Tester | ETS364 | ETS364 | Max Limit | 45 | 45 | |
| Test Number | EB4632 | EB4632 | Min Limit | 5 | 5 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 34.478 | 34.532 | 0.054 | 0.16% | 0.13% |
| 1 | 1 | 34.954 | 35.768 | 0.814 | 2.33% | 2.04% |
| 1 | 2 | 34.455 | 35.150 | 0.695 | 2.02% | 1.74% |
| 1 | 3 | 34.173 | 34.777 | 0.604 | 1.77% | 1.51% |
| 1 | 4 | 34.180 | 34.722 | 0.542 | 1.59% | 1.36% |
| 5 | 5 | 34.607 | 37.638 | 3.031 | 8.76% | 7.58% |
| 5 | 6 | 34.964 | 38.137 | 3.173 | 9.08% | 7.93% |
| 5 | 7 | 34.193 | 37.030 | 2.837 | 8.30% | 7.09% |
| 5 | 8 | 34.278 | 37.064 | 2.786 | 8.13% | 6.97% |
| 10 | 9 | 34.655 | 39.583 | 4.928 | 14.22% | 12.32% |
| 10 | 10 | 34.268 | 38.568 | 4.300 | 12.55% | 10.75% |
| 10 | 11 | 34.288 | 38.667 | 4.378 | 12.77% | 10.95% |
| 10 | 12 | 35.242 | 39.715 | 4.473 | 12.69% | 11.18% |
| Max | | 35.242 | 39.715 | 4.928 | 14.22% | 12.32% |
| Average | | 34.518 | 37.027 | 2.509 | 7.26% | 6.27% |
| Min | | 34.173 | 34.532 | 0.054 | 0.16% | 0.13% |
| Std Dev | | 0.348 | 1.874 | 1.756 | 5.07% | 4.39% |




| 110.31_Vout_Vee_10V_10k_D | | | | |
|-----------------------------------|-----------|--------|--------|--------|
| Test Site | TI Dallas | ETS364 | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 45 | mV | | |
| Min Limit | 5 | mV | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | 5.000 | 5.000 | 5.000 | 5.000 |
| Min | 34.532 | 34.722 | 37.031 | 38.568 |
| Average | 34.532 | 35.104 | 37.468 | 39.133 |
| Max | 34.532 | 35.768 | 38.137 | 39.716 |
| UL | 45.000 | 45.000 | 45.000 | 45.000 |




NDD Report

LMP7704-SP

| 111.0_Isc_5V_Source_A | | | | | | |
|-----------------------|-----------|---|------------------|--------|-----------|--------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | -10 |
| Tester | ETS364 | ETS364 | Min Limit | -90 | Delta | -0.048 |
| Test Number | EB4632 | EB4632 <th>% of Limit Range</th> <td>0.06%</td> <th>Delta %</th> <td>0.08%</td> | % of Limit Range | 0.06% | Delta % | 0.08% |
| Serial # | PRE NDD | POST NDD | | | | |
| 0 | 13 | -59.182 | -59.230 | -0.048 | 0.08% | 0.06% |
| 1 | 1 | -58.860 | -58.565 | 0.294 | -0.50% | 0.37% |
| 1 | 2 | -59.410 | -59.420 | -0.010 | 0.02% | 0.01% |
| 1 | 3 | -58.194 | -57.414 | 0.780 | -1.34% | 0.98% |
| 1 | 4 | -58.027 | -58.036 | -0.009 | 0.02% | 0.01% |
| 5 | 5 | -59.846 | -58.898 | 0.948 | -1.58% | 1.18% |
| 5 | 6 | -58.240 | -57.340 | 0.900 | -1.55% | 1.13% |
| 5 | 7 | -58.461 | -57.362 | 1.099 | -1.88% | 1.37% |
| 5 | 8 | -58.771 | -57.181 | 1.591 | -2.71% | 1.99% |
| 10 | 9 | -59.167 | -57.600 | 1.567 | -2.65% | 1.96% |
| 10 | 10 | -58.894 | -57.047 | 1.847 | -3.14% | 2.31% |
| 10 | 11 | -58.730 | -54.436 | 4.295 | -7.31% | 5.37% |
| 10 | 12 | -58.657 | -55.725 | 2.932 | -5.00% | 3.66% |
| Max | | -58.027 | -54.436 | 4.295 | 0.08% | 5.37% |
| Average | | -58.803 | -57.558 | 1.245 | -2.12% | 1.57% |
| Min | | -59.846 | -59.420 | -0.048 | -7.31% | 0.01% |
| Std Dev | | 0.515 | 1.382 | 1.255 | 2.14% | 1.55% |




| 111.0_Isc_5V_Source_A | | | | | | |
|-----------------------|-----------|-----------|------------------|--------|-----------|--------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | -10 |
| Tester | ETS364 | ETS364 | Min Limit | -90 | Delta | -0.048 |
| Test Number | EB4632 | EB4632 | % of Limit Range | 0.06% | Delta % | 0.08% |
| Serial # | PRE NDD | POST NDD | | | | |
| 0 | 13 | -59.182 | -59.230 | -0.048 | 0.08% | 0.06% |
| 1 | 1 | -58.860 | -58.565 | 0.294 | -0.50% | 0.37% |
| 1 | 2 | -59.410 | -59.420 | -0.010 | 0.02% | 0.01% |
| 1 | 3 | -58.194 | -57.414 | 0.780 | -1.34% | 0.98% |
| 1 | 4 | -58.027 | -58.036 | -0.009 | 0.02% | 0.01% |
| 5 | 5 | -59.846 | -58.898 | 0.948 | -1.58% | 1.18% |
| 5 | 6 | -58.240 | -57.340 | 0.900 | -1.55% | 1.13% |
| 5 | 7 | -58.461 | -57.362 | 1.099 | -1.88% | 1.37% |
| 5 | 8 | -58.771 | -57.181 | 1.591 | -2.71% | 1.99% |
| 10 | 9 | -59.167 | -57.600 | 1.567 | -2.65% | 1.96% |
| 10 | 10 | -58.894 | -57.047 | 1.847 | -3.14% | 2.31% |
| 10 | 11 | -58.730 | -54.436 | 4.295 | -7.31% | 5.37% |
| 10 | 12 | -58.657 | -55.725 | 2.932 | -5.00% | 3.66% |
| Max | | -58.027 | -54.436 | 4.295 | 0.08% | 5.37% |
| Average | | -58.803 | -57.558 | 1.245 | -2.12% | 1.57% |
| Min | | -59.846 | -59.420 | -0.048 | -7.31% | 0.01% |
| Std Dev | | 0.515 | 1.382 | 1.255 | 2.14% | 1.55% |




NDD Report

LMP7704-SP

| 111.1_Isc_5V_Source_B | | | | | | |
|-----------------------------------|-----------|-----------|------------------|--------|-----------|--------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | -10 |
| Tester | ETS364 | ETS364 | Min Limit | -90 | Delta | -0.045 |
| Test Number | EB4632 | EB4632 | % of Limit Range | 0.06% | Delta % | 0.08% |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | | | |
| 0 | 13 | -59.029 | -59.074 | -0.045 | 0.08% | 0.06% |
| 1 | 1 | -57.799 | -57.736 | 0.063 | -0.11% | 0.08% |
| 1 | 2 | -58.157 | -58.180 | -0.022 | 0.04% | 0.03% |
| 1 | 3 | -57.475 | -57.330 | 0.145 | -0.25% | 0.18% |
| 1 | 4 | -57.687 | -57.621 | 0.066 | -0.11% | 0.08% |
| 5 | 5 | -58.709 | -54.998 | 3.712 | -6.32% | 4.64% |
| 5 | 6 | -56.558 | -55.899 | 0.659 | -1.17% | 0.82% |
| 5 | 7 | -57.561 | -56.759 | 0.801 | -1.39% | 1.00% |
| 5 | 8 | -58.230 | -56.507 | 1.724 | -2.96% | 2.15% |
| 10 | 9 | -59.501 | -46.882 | 12.619 | -21.21% | 15.77% |
| 10 | 10 | -58.119 | -56.671 | 1.448 | -2.49% | 1.81% |
| 10 | 11 | -58.399 | -43.711 | 14.688 | -25.15% | 18.36% |
| 10 | 12 | -57.840 | -56.348 | 1.492 | -2.58% | 1.86% |
| Max | | -56.558 | -43.711 | 14.688 | 0.08% | 18.36% |
| Average | | -58.082 | -55.209 | 2.873 | -4.89% | 3.60% |
| Min | | -59.501 | -59.074 | -0.045 | -25.15% | 0.03% |
| Std Dev | | 0.747 | 4.565 | 4.915 | 8.35% | 6.14% |




| 111.1_Isc_5V_Source_B | | | | | | |
|-----------------------------------|-----------|---------|------------------|---------|-----------|--------|
| Test Site | TI Dallas | ETS364 | Unit | mA | Max Limit | -10 |
| Tester | ETS364 | ETS364 | Min Limit | -90 | Delta | -0.045 |
| Test Number | EB4632 | EB4632 | % of Limit Range | 0.06% | Delta % | 0.08% |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -90.000 | -90.000 | -90.000 | -90.000 | | |
| Min | -59.074 | -58.180 | -56.759 | -56.671 | | |
| Average | -59.074 | -57.717 | -56.041 | -50.903 | | |
| Max | -59.074 | -57.330 | -54.998 | -43.711 | | |
| UL | -10.000 | -10.000 | -10.000 | -10.000 | | |




NDD Report

LMP7704-SP

| 111.2_Isc_5V_Source_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | mA | mA | |
| Max Limit | -10 | -10 | Min Limit | -90 | -90 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -59.175 | -59.231 | -0.056 | 0.09% | 0.07% |
| 1 | 1 | -58.585 | -58.026 | 0.560 | -0.96% | 0.70% |
| 1 | 2 | -58.197 | -58.230 | -0.034 | 0.06% | 0.04% |
| 1 | 3 | -58.579 | -58.547 | 0.032 | -0.05% | 0.04% |
| 1 | 4 | -58.795 | -58.667 | 0.128 | -0.22% | 0.16% |
| 5 | 5 | -59.407 | -57.361 | 2.046 | -3.44% | 2.56% |
| 5 | 6 | -58.348 | -57.647 | 0.701 | -1.20% | 0.88% |
| 5 | 7 | -58.675 | -57.526 | 1.150 | -1.96% | 1.44% |
| 5 | 8 | -59.315 | -58.038 | 1.278 | -2.15% | 1.60% |
| 10 | 9 | -59.952 | -56.215 | 3.737 | -6.23% | 4.67% |
| 10 | 10 | -58.960 | -56.125 | 2.836 | -4.81% | 3.54% |
| 10 | 11 | -58.475 | -56.793 | 1.683 | -2.88% | 2.10% |
| 10 | 12 | -58.768 | -57.210 | 1.558 | -2.65% | 1.95% |
| Max | | -58.197 | -56.125 | 3.737 | 0.09% | 4.67% |
| Average | | -58.864 | -57.663 | 1.201 | -2.03% | 1.52% |
| Min | | -59.952 | -59.231 | -0.056 | -6.23% | 0.04% |
| Std Dev | | 0.488 | 0.930 | 1.172 | 1.97% | 1.45% |




| 111.2_Isc_5V_Source_C | | | | |
|-----------------------------------|-----------|---------|-----------|---------|
| Test Site | TI Dallas | ETS364 | Tester | EB4632 |
| Test Number | EB4632 | EB4632 | Unit | mA |
| Max Limit | -10 | mA | Min Limit | -90 mA |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | -90.000 | -90.000 | -90.000 | -90.000 |
| Min | -59.231 | -58.667 | -58.038 | -57.211 |
| Average | -59.231 | -58.368 | -57.643 | -56.586 |
| Max | -59.231 | -58.026 | -57.361 | -56.125 |
| UL | -10.000 | -10.000 | -10.000 | -10.000 |




NDD Report

LMP7704-SP

| 111.3_Isc_5V_Source_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | -10 |
| Tester | ETS364 | ETS364 | Min Limit | -90 | Max Limit | -90 |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -58.021 | -58.053 | -0.031 | 0.05% | 0.04% |
| 1 | 1 | -58.381 | -58.223 | 0.158 | -0.27% | 0.20% |
| 1 | 2 | -57.681 | -57.752 | -0.071 | 0.12% | 0.09% |
| 1 | 3 | -57.473 | -57.446 | 0.027 | -0.05% | 0.03% |
| 1 | 4 | -57.127 | -57.101 | 0.025 | -0.04% | 0.03% |
| 5 | 5 | -58.983 | -57.749 | 1.234 | -2.09% | 1.54% |
| 5 | 6 | -57.699 | -56.818 | 0.881 | -1.53% | 1.10% |
| 5 | 7 | -57.108 | -56.279 | 0.829 | -1.45% | 1.04% |
| 5 | 8 | -58.337 | -57.500 | 0.837 | -1.43% | 1.05% |
| 10 | 9 | -59.124 | -56.973 | 2.150 | -3.64% | 2.69% |
| 10 | 10 | -57.500 | -55.760 | 1.740 | -3.03% | 2.17% |
| 10 | 11 | -57.795 | -53.411 | 4.384 | -7.58% | 5.48% |
| 10 | 12 | -57.673 | -55.789 | 1.884 | -3.27% | 2.36% |
| Max | | -57.108 | -53.411 | 4.384 | 0.12% | 5.48% |
| Average | | -57.915 | -56.835 | 1.081 | -1.86% | 1.37% |
| Min | | -59.124 | -58.223 | -0.071 | -7.58% | 0.03% |
| Std Dev | | 0.634 | 1.300 | 1.257 | 2.17% | 1.55% |




| 111.3_Isc_5V_Source_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|---------|-----------|-----|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | -10 |
| Tester | ETS364 | ETS364 | Min Limit | -90 | Max Limit | -90 |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -90.000 | -90.000 | -90.000 | -90.000 | | |
| Min | -58.053 | -58.223 | -57.749 | -56.973 | | |
| Average | -58.053 | -57.631 | -57.086 | -55.483 | | |
| Max | -58.053 | -57.101 | -56.279 | -53.411 | | |
| UL | -10.000 | -10.000 | -10.000 | -10.000 | | |




NDD Report

LMP7704-SP

| 111.4_Isc_5V_Sink_A | | | | | | |
|-----------------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | 90 | 90 | | | | |
| Min Limit | 10 | 10 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 70.922 | 70.875 | -0.047 | -0.07% | 0.06% |
| 1 | 1 | 69.867 | 69.624 | -0.242 | -0.35% | 0.30% |
| 1 | 2 | 70.335 | 70.123 | -0.212 | -0.30% | 0.26% |
| 1 | 3 | 70.870 | 70.714 | -0.157 | -0.22% | 0.20% |
| 1 | 4 | 70.948 | 70.791 | -0.157 | -0.22% | 0.20% |
| 5 | 5 | 70.639 | 70.116 | -0.524 | -0.74% | 0.65% |
| 5 | 6 | 69.636 | 69.309 | -0.327 | -0.47% | 0.41% |
| 5 | 7 | 71.179 | 70.698 | -0.482 | -0.68% | 0.60% |
| 5 | 8 | 70.537 | 70.244 | -0.293 | -0.42% | 0.37% |
| 10 | 9 | 70.730 | 68.193 | -2.537 | -3.59% | 3.17% |
| 10 | 10 | 70.489 | 69.938 | -0.551 | -0.78% | 0.69% |
| 10 | 11 | 70.873 | 70.246 | -0.628 | -0.89% | 0.78% |
| 10 | 12 | 70.581 | 70.027 | -0.554 | -0.78% | 0.69% |
| Max | | 71.179 | 70.875 | -0.047 | -0.07% | 3.17% |
| Average | | 70.585 | 70.069 | -0.516 | -0.73% | 0.65% |
| Min | | 69.636 | 68.193 | -2.537 | -3.59% | 0.06% |
| Std Dev | | 0.436 | 0.728 | 0.635 | 0.90% | 0.79% |




| 111.4_Isc_5V_Sink_A | | | | | | |
|-----------------------------------|-----------|--------|--------|--------|--|--|
| Test Site | TI Dallas | | | | | |
| Tester | ETS364 | | | | | |
| Test Number | EB4632 | | | | | |
| Max Limit | 90 | mA | | | | |
| Min Limit | 10 | mA | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 10.000 | 10.000 | 10.000 | 10.000 | | |
| Min | 70.875 | 69.624 | 69.309 | 68.193 | | |
| Average | 70.875 | 70.313 | 70.092 | 69.601 | | |
| Max | 70.875 | 70.791 | 70.698 | 70.246 | | |
| UL | 90.000 | 90.000 | 90.000 | 90.000 | | |




NDD Report

LMP7704-SP

| 111.5_Isc_5V_Sink_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | mA | |
| Tester | ETS364 | ETS364 | Max Limit | 90 | 90 | |
| Test Number | EB4632 | EB4632 | Min Limit | 10 | 10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 71.026 | 70.981 | -0.044 | -0.06% | 0.06% |
| 1 | 1 | 69.850 | 69.687 | -0.163 | -0.23% | 0.20% |
| 1 | 2 | 70.377 | 70.148 | -0.229 | -0.33% | 0.29% |
| 1 | 3 | 70.890 | 70.698 | -0.192 | -0.27% | 0.24% |
| 1 | 4 | 70.985 | 70.846 | -0.139 | -0.20% | 0.17% |
| 5 | 5 | 70.567 | 70.127 | -0.440 | -0.62% | 0.55% |
| 5 | 6 | 69.433 | 68.974 | -0.459 | -0.66% | 0.57% |
| 5 | 7 | 70.948 | 70.448 | -0.499 | -0.70% | 0.62% |
| 5 | 8 | 70.552 | 70.307 | -0.245 | -0.35% | 0.31% |
| 10 | 9 | 70.870 | 70.270 | -0.600 | -0.85% | 0.75% |
| 10 | 10 | 70.590 | 69.943 | -0.647 | -0.92% | 0.81% |
| 10 | 11 | 70.848 | 70.180 | -0.668 | -0.94% | 0.83% |
| 10 | 12 | 70.698 | 70.212 | -0.485 | -0.69% | 0.61% |
| Max | | 71.026 | 70.981 | -0.044 | -0.06% | 0.83% |
| Average | | 70.587 | 70.217 | -0.370 | -0.52% | 0.46% |
| Min | | 69.433 | 68.974 | -0.668 | -0.94% | 0.06% |
| Std Dev | | 0.470 | 0.516 | 0.210 | 0.30% | 0.26% |




| 111.5_Isc_5V_Sink_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|----|--|
| Test Site | TI Dallas | TI Dallas | Unit | mA | mA | |
| Tester | ETS364 | ETS364 | Max Limit | 90 | 90 | |
| Test Number | EB4632 | EB4632 | Min Limit | 10 | 10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 10.000 | 10.000 | 10.000 | 10.000 | | |
| Min | 70.982 | 69.687 | 68.974 | 69.943 | | |
| Average | 70.982 | 70.345 | 69.964 | 70.151 | | |
| Max | 70.982 | 70.846 | 70.448 | 70.270 | | |
| UL | 90.000 | 90.000 | 90.000 | 90.000 | | |




NDD Report

LMP7704-SP

| 111.6_Isc_5V_Sink_C | | | | | | |
|-----------------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | 90 | 90 | | | | |
| Min Limit | 10 | 10 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 71.047 | 70.997 | -0.050 | -0.07% | 0.06% |
| 1 | 1 | 69.815 | 69.649 | -0.167 | -0.24% | 0.21% |
| 1 | 2 | 70.308 | 70.159 | -0.149 | -0.21% | 0.19% |
| 1 | 3 | 70.742 | 70.578 | -0.164 | -0.23% | 0.21% |
| 1 | 4 | 70.693 | 70.549 | -0.144 | -0.20% | 0.18% |
| 5 | 5 | 70.470 | 70.055 | -0.415 | -0.59% | 0.52% |
| 5 | 6 | 69.943 | 69.568 | -0.375 | -0.54% | 0.47% |
| 5 | 7 | 71.006 | 70.634 | -0.372 | -0.52% | 0.47% |
| 5 | 8 | 70.571 | 70.331 | -0.240 | -0.34% | 0.30% |
| 10 | 9 | 70.717 | 70.169 | -0.548 | -0.77% | 0.68% |
| 10 | 10 | 70.755 | 70.139 | -0.616 | -0.87% | 0.77% |
| 10 | 11 | 70.793 | 70.083 | -0.710 | -1.00% | 0.89% |
| 10 | 12 | 70.760 | 70.091 | -0.669 | -0.95% | 0.84% |
| Max | | 71.047 | 70.997 | -0.050 | -0.07% | 0.89% |
| Average | | 70.586 | 70.231 | -0.355 | -0.50% | 0.44% |
| Min | | 69.815 | 69.568 | -0.710 | -1.00% | 0.06% |
| Std Dev | | 0.370 | 0.393 | 0.223 | 0.32% | 0.28% |




| 111.6_Isc_5V_Sink_C | | | | | | |
|-----------------------------------|-----------|--------|--------|--------|--|--|
| Test Site | TI Dallas | | | | | |
| Tester | ETS364 | | | | | |
| Test Number | EB4632 | | | | | |
| Max Limit | 90 | mA | | | | |
| Min Limit | 10 | mA | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 10.000 | 10.000 | 10.000 | 10.000 | | |
| Min | 70.997 | 69.649 | 69.568 | 70.083 | | |
| Average | 70.997 | 70.234 | 70.147 | 70.121 | | |
| Max | 70.997 | 70.578 | 70.634 | 70.169 | | |
| UL | 90.000 | 90.000 | 90.000 | 90.000 | | |




NDD Report

LMP7704-SP

| 111.7_Isc_5V_Sink_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | mA | |
| Tester | ETS364 | ETS364 | Max Limit | 90 | 90 | |
| Test Number | EB4632 | EB4632 | Min Limit | 10 | 10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 70.830 | 70.793 | -0.038 | -0.05% | 0.05% |
| 1 | 1 | 69.574 | 69.397 | -0.177 | -0.25% | 0.22% |
| 1 | 2 | 70.254 | 70.104 | -0.149 | -0.21% | 0.19% |
| 1 | 3 | 70.710 | 70.566 | -0.144 | -0.20% | 0.18% |
| 1 | 4 | 70.795 | 70.665 | -0.130 | -0.18% | 0.16% |
| 5 | 5 | 70.481 | 70.128 | -0.354 | -0.50% | 0.44% |
| 5 | 6 | 69.497 | 69.176 | -0.321 | -0.46% | 0.40% |
| 5 | 7 | 70.918 | 70.496 | -0.423 | -0.60% | 0.53% |
| 5 | 8 | 70.532 | 68.344 | -2.187 | -3.10% | 2.73% |
| 10 | 9 | 70.607 | 70.008 | -0.600 | -0.85% | 0.75% |
| 10 | 10 | 70.810 | 70.322 | -0.488 | -0.69% | 0.61% |
| 10 | 11 | 70.835 | 70.227 | -0.609 | -0.86% | 0.76% |
| 10 | 12 | 70.530 | 70.026 | -0.505 | -0.72% | 0.63% |
| Max | | 70.918 | 70.793 | -0.038 | -0.05% | 2.73% |
| Average | | 70.490 | 70.019 | -0.471 | -0.67% | 0.59% |
| Min | | 69.497 | 68.344 | -2.187 | -3.10% | 0.05% |
| Std Dev | | 0.462 | 0.683 | 0.549 | 0.78% | 0.69% |




| 111.7_Isc_5V_Sink_D | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|----|--|
| Test Site | TI Dallas | TI Dallas | Unit | mA | mA | |
| Tester | ETS364 | ETS364 | Max Limit | 90 | 90 | |
| Test Number | EB4632 | EB4632 | Min Limit | 10 | 10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 10.000 | 10.000 | 10.000 | 10.000 | | |
| Min | 70.793 | 69.397 | 68.344 | 70.008 | | |
| Average | 70.793 | 70.183 | 69.536 | 70.146 | | |
| Max | 70.793 | 70.665 | 70.496 | 70.322 | | |
| UL | 90.000 | 90.000 | 90.000 | 90.000 | | |




NDD Report

LMP7704-SP

| 111.8_Isc_10V_Source_A | | | | | | |
|-----------------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | -10 | -10 | | | | |
| Min Limit | -90 | -90 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -75.488 | -75.552 | -0.064 | 0.08% | 0.08% |
| 1 | 1 | -75.149 | -74.835 | 0.314 | -0.42% | 0.39% |
| 1 | 2 | -75.643 | -75.506 | 0.137 | -0.18% | 0.17% |
| 1 | 3 | -74.417 | -73.724 | 0.693 | -0.93% | 0.87% |
| 1 | 4 | -74.158 | -74.164 | -0.007 | 0.01% | 0.01% |
| 5 | 5 | -76.443 | -74.934 | 1.509 | -1.97% | 1.89% |
| 5 | 6 | -74.435 | -73.174 | 1.261 | -1.69% | 1.58% |
| 5 | 7 | -74.643 | -72.971 | 1.672 | -2.24% | 2.09% |
| 5 | 8 | -74.956 | -72.581 | 2.375 | -3.17% | 2.97% |
| 10 | 9 | -75.418 | -73.478 | 1.941 | -2.57% | 2.43% |
| 10 | 10 | -75.154 | -72.552 | 2.601 | -3.46% | 3.25% |
| 10 | 11 | -74.921 | -68.872 | 6.049 | -8.07% | 7.56% |
| 10 | 12 | -74.967 | -70.507 | 4.461 | -5.95% | 5.58% |
| Max | | -74.158 | -68.872 | 6.049 | 0.08% | 7.56% |
| Average | | -75.061 | -73.296 | 1.765 | -2.35% | 2.22% |
| Min | | -76.443 | -75.552 | -0.064 | -8.07% | 0.01% |
| Std Dev | | 0.606 | 1.926 | 1.813 | 2.42% | 2.25% |




| 111.8_Isc_10V_Source_A | | | | |
|-----------------------------------|-----------|---------|---------|---------|
| Test Site | TI Dallas | | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | -10 | mA | | |
| Min Limit | -90 | mA | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | -90.000 | -90.000 | -90.000 | -90.000 |
| Min | -75.552 | -75.506 | -74.934 | -73.478 |
| Average | -75.552 | -74.557 | -73.415 | -71.352 |
| Max | -75.552 | -73.724 | -72.581 | -68.872 |
| UL | -10.000 | -10.000 | -10.000 | -10.000 |




NDD Report

LMP7704-SP

| 111.9_Isc_10V_Source_B | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | -10 |
| Tester | ETS364 | ETS364 | Min Limit | mA | | -90 |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -75.257 | -75.313 | -0.056 | 0.07% | 0.07% |
| 1 | 1 | -73.969 | -73.837 | 0.132 | -0.18% | 0.16% |
| 1 | 2 | -74.236 | -74.272 | -0.036 | 0.05% | 0.05% |
| 1 | 3 | -73.501 | -73.248 | 0.254 | -0.35% | 0.32% |
| 1 | 4 | -73.730 | -73.618 | 0.113 | -0.15% | 0.14% |
| 5 | 5 | -74.900 | -71.005 | 3.895 | -5.20% | 4.87% |
| 5 | 6 | -72.260 | -70.937 | 1.323 | -1.83% | 1.65% |
| 5 | 7 | -73.535 | -72.405 | 1.130 | -1.54% | 1.41% |
| 5 | 8 | -74.342 | -71.828 | 2.513 | -3.38% | 3.14% |
| 10 | 9 | -75.736 | -63.451 | 12.285 | -16.22% | 15.36% |
| 10 | 10 | -74.194 | -72.207 | 1.987 | -2.68% | 2.48% |
| 10 | 11 | -74.621 | -59.055 | 15.566 | -20.86% | 19.46% |
| 10 | 12 | -73.969 | -71.636 | 2.334 | -3.15% | 2.92% |
| Max | | -72.260 | -59.055 | 15.566 | 0.07% | 19.46% |
| Average | | -74.173 | -70.986 | 3.188 | -4.26% | 4.00% |
| Min | | -75.736 | -75.313 | -0.056 | -20.86% | 0.05% |
| Std Dev | | 0.874 | 4.596 | 4.959 | 6.61% | 6.19% |




| 111.9_Isc_10V_Source_B | | | | |
|-----------------------------------|-----------|-----------|----------------------|-----------|
| Test Site | TI Dallas | Tester | ETS364 <th>Unit</th> | Unit |
| Test Number | EB4632 | Max Limit | mA | Min Limit |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 |
| LL | -90.000 | -90.000 | -90.000 | -90.000 |
| Min | -75.313 | -74.272 | -72.405 | -72.207 |
| Average | -75.313 | -73.744 | -71.544 | -66.587 |
| Max | -75.313 | -73.248 | -70.937 | -59.055 |
| UL | -10.000 | -10.000 | -10.000 | -10.000 |




NDD Report

LMP7704-SP

| 111.10_Isc_10V_Source_C | | | | | | |
|-------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | -10 | -10 | | | | |
| Min Limit | -90 | -90 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -75.439 | -75.513 | -0.074 | 0.10% | 0.09% |
| 1 | 1 | -74.665 | -73.927 | 0.738 | -0.99% | 0.92% |
| 1 | 2 | -74.362 | -74.373 | -0.011 | 0.01% | 0.01% |
| 1 | 3 | -74.874 | -74.777 | 0.097 | -0.13% | 0.12% |
| 1 | 4 | -75.190 | -74.965 | 0.225 | -0.30% | 0.28% |
| 5 | 5 | -75.742 | -73.083 | 2.660 | -3.51% | 3.32% |
| 5 | 6 | -74.519 | -73.679 | 0.840 | -1.13% | 1.05% |
| 5 | 7 | -74.856 | -73.284 | 1.573 | -2.10% | 1.97% |
| 5 | 8 | -75.767 | -73.928 | 1.840 | -2.43% | 2.30% |
| 10 | 9 | -76.473 | -71.752 | 4.721 | -6.17% | 5.90% |
| 10 | 10 | -75.233 | -70.918 | 4.315 | -5.74% | 5.39% |
| 10 | 11 | -74.681 | -72.109 | 2.572 | -3.44% | 3.22% |
| 10 | 12 | -75.103 | -72.854 | 2.250 | -3.00% | 2.81% |
| Max | | -74.362 | -70.918 | 4.721 | 0.10% | 5.90% |
| Average | | -75.147 | -73.474 | 1.673 | -2.22% | 2.11% |
| Min | | -76.473 | -75.513 | -0.074 | -6.17% | 0.01% |
| Std Dev | | 0.592 | 1.332 | 1.593 | 2.10% | 1.97% |




| 111.10_Isc_10V_Source_C | | | | |
|-------------------------|-----------|---------|---------|---------|
| Test Site | TI Dallas | | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | -10 | mA | | |
| Min Limit | -90 | mA | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 |
| LL | -90.000 | -90.000 | -90.000 | -90.000 |
| Min | -75.513 | -74.965 | -73.928 | -72.854 |
| Average | -75.513 | -74.510 | -73.493 | -71.908 |
| Max | -75.513 | -73.927 | -73.083 | -70.918 |
| UL | -10.000 | -10.000 | -10.000 | -10.000 |




NDD Report

LMP7704-SP

| 111.11_Isc_10V_Source_D | | | | | | |
|-------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | -10 | -10 | | | | |
| Min Limit | -90 | -90 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -74.014 | -74.059 | -0.045 | 0.06% | 0.06% |
| 1 | 1 | -74.557 | -74.230 | 0.326 | -0.44% | 0.41% |
| 1 | 2 | -73.644 | -73.718 | -0.074 | 0.10% | 0.09% |
| 1 | 3 | -73.586 | -73.519 | 0.066 | -0.09% | 0.08% |
| 1 | 4 | -73.007 | -72.965 | 0.041 | -0.06% | 0.05% |
| 5 | 5 | -75.297 | -73.473 | 1.824 | -2.42% | 2.28% |
| 5 | 6 | -73.785 | -72.321 | 1.465 | -1.99% | 1.83% |
| 5 | 7 | -72.781 | -71.648 | 1.133 | -1.56% | 1.42% |
| 5 | 8 | -74.587 | -73.586 | 1.002 | -1.34% | 1.25% |
| 10 | 9 | -75.383 | -72.388 | 2.995 | -3.97% | 3.74% |
| 10 | 10 | -73.398 | -70.978 | 2.421 | -3.30% | 3.03% |
| 10 | 11 | -73.792 | -67.754 | 6.038 | -8.18% | 7.55% |
| 10 | 12 | -73.708 | -70.452 | 3.255 | -4.42% | 4.07% |
| Max | | -72.781 | -67.754 | 6.038 | 0.10% | 7.55% |
| Average | | -73.965 | -72.392 | 1.573 | -2.12% | 1.99% |
| Min | | -75.383 | -74.230 | -0.074 | -8.18% | 0.05% |
| Std Dev | | 0.793 | 1.824 | 1.770 | 2.39% | 2.19% |




| 111.11_Isc_10V_Source_D | | | | | | |
|-------------------------|-----------|---------|---------|---------|--|--|
| Test Site | TI Dallas | | | | | |
| Tester | ETS364 | | | | | |
| Test Number | EB4632 | | | | | |
| Max Limit | -10 | mA | | | | |
| Min Limit | -90 | mA | | | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -90.000 | -90.000 | -90.000 | -90.000 | | |
| Min | -74.059 | -74.230 | -73.586 | -72.389 | | |
| Average | -74.059 | -73.608 | -72.757 | -70.393 | | |
| Max | -74.059 | -72.966 | -71.648 | -67.754 | | |
| UL | -10.000 | -10.000 | -10.000 | -10.000 | | |




NDD Report

LMP7704-SP

| 111.12_Isc_10V_Sink_A | | | | | | |
|-----------------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | 90 | 90 | | | | |
| Min Limit | 10 | 10 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 76.455 | 76.407 | -0.048 | -0.06% | 0.06% |
| 1 | 1 | 75.427 | 75.061 | -0.366 | -0.49% | 0.46% |
| 1 | 2 | 76.027 | 75.818 | -0.209 | -0.27% | 0.26% |
| 1 | 3 | 76.632 | 76.486 | -0.146 | -0.19% | 0.18% |
| 1 | 4 | 76.663 | 76.523 | -0.139 | -0.18% | 0.17% |
| 5 | 5 | 76.229 | 75.668 | -0.561 | -0.74% | 0.70% |
| 5 | 6 | 75.269 | 74.965 | -0.304 | -0.40% | 0.38% |
| 5 | 7 | 76.890 | 76.406 | -0.484 | -0.63% | 0.61% |
| 5 | 8 | 76.159 | 75.896 | -0.263 | -0.35% | 0.33% |
| 10 | 9 | 76.315 | 73.636 | -2.680 | -3.51% | 3.35% |
| 10 | 10 | 76.117 | 75.495 | -0.621 | -0.82% | 0.78% |
| 10 | 11 | 76.587 | 76.059 | -0.528 | -0.69% | 0.66% |
| 10 | 12 | 76.262 | 75.779 | -0.483 | -0.63% | 0.60% |
| Max | | 76.890 | 76.523 | -0.048 | -0.06% | 3.35% |
| Average | | 76.233 | 75.708 | -0.526 | -0.69% | 0.66% |
| Min | | 75.269 | 73.636 | -2.680 | -3.51% | 0.06% |
| Std Dev | | 0.465 | 0.803 | 0.672 | 0.88% | 0.84% |




| 111.12_Isc_10V_Sink_A | | | | | | |
|-----------------------------------|-----------|--------|--------|--------|--|--|
| Test Site | TI Dallas | | | | | |
| Tester | ETS364 | | | | | |
| Test Number | EB4632 | | | | | |
| Max Limit | 90 | mA | | | | |
| Min Limit | 10 | mA | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 10.000 | 10.000 | 10.000 | 10.000 | | |
| Min | 76.407 | 75.061 | 74.965 | 73.636 | | |
| Average | 76.407 | 75.972 | 75.734 | 75.242 | | |
| Max | 76.407 | 76.523 | 76.406 | 76.059 | | |
| UL | 90.000 | 90.000 | 90.000 | 90.000 | | |




NDD Report

LMP7704-SP

| 111.13_Isc_10V_Sink_B | | | | | | |
|-----------------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | 90 | 90 | | | | |
| Min Limit | 10 | 10 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 76.628 | 76.585 | -0.043 | -0.06% | 0.05% |
| 1 | 1 | 75.415 | 75.229 | -0.186 | -0.25% | 0.23% |
| 1 | 2 | 75.988 | 75.662 | -0.326 | -0.43% | 0.41% |
| 1 | 3 | 76.603 | 76.410 | -0.193 | -0.25% | 0.24% |
| 1 | 4 | 76.666 | 76.532 | -0.134 | -0.17% | 0.17% |
| 5 | 5 | 76.128 | 75.717 | -0.411 | -0.54% | 0.51% |
| 5 | 6 | 75.010 | 74.599 | -0.412 | -0.55% | 0.51% |
| 5 | 7 | 76.631 | 75.963 | -0.668 | -0.87% | 0.84% |
| 5 | 8 | 76.153 | 75.951 | -0.202 | -0.27% | 0.25% |
| 10 | 9 | 76.433 | 75.895 | -0.538 | -0.70% | 0.67% |
| 10 | 10 | 76.228 | 75.470 | -0.758 | -0.99% | 0.95% |
| 10 | 11 | 76.531 | 75.968 | -0.563 | -0.74% | 0.70% |
| 10 | 12 | 76.364 | 75.807 | -0.557 | -0.73% | 0.70% |
| Max | | 76.666 | 76.585 | -0.043 | -0.06% | 0.95% |
| Average | | 76.214 | 75.830 | -0.384 | -0.50% | 0.48% |
| Min | | 75.010 | 74.599 | -0.758 | -0.99% | 0.05% |
| Std Dev | | 0.502 | 0.540 | 0.223 | 0.29% | 0.28% |




| 111.13_Isc_10V_Sink_B | | | | | | |
|-----------------------------------|-----------|--------|--------|--------|--|--|
| Test Site | TI Dallas | | | | | |
| Tester | ETS364 | | | | | |
| Test Number | EB4632 | | | | | |
| Max Limit | 90 | mA | | | | |
| Min Limit | 10 | mA | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 10.000 | 10.000 | 10.000 | 10.000 | | |
| Min | 76.585 | 75.229 | 74.599 | 75.470 | | |
| Average | 76.585 | 75.958 | 75.557 | 75.785 | | |
| Max | 76.585 | 76.532 | 75.963 | 75.968 | | |
| UL | 90.000 | 90.000 | 90.000 | 90.000 | | |




NDD Report

LMP7704-SP

| 111.14_Isc_10V_Sink_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | mA | mA | |
| Max Limit | 90 | 90 | Min Limit | 10 | 10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 76.706 | 76.657 | -0.048 | -0.06% | 0.06% |
| 1 | 1 | 75.377 | 75.205 | -0.172 | -0.23% | 0.22% |
| 1 | 2 | 75.966 | 75.832 | -0.134 | -0.18% | 0.17% |
| 1 | 3 | 76.412 | 76.262 | -0.150 | -0.20% | 0.19% |
| 1 | 4 | 76.393 | 76.255 | -0.139 | -0.18% | 0.17% |
| 5 | 5 | 76.035 | 75.638 | -0.398 | -0.52% | 0.50% |
| 5 | 6 | 75.502 | 74.894 | -0.608 | -0.81% | 0.76% |
| 5 | 7 | 76.641 | 76.264 | -0.377 | -0.49% | 0.47% |
| 5 | 8 | 76.191 | 75.951 | -0.241 | -0.32% | 0.30% |
| 10 | 9 | 76.319 | 75.808 | -0.511 | -0.67% | 0.64% |
| 10 | 10 | 76.381 | 75.829 | -0.552 | -0.72% | 0.69% |
| 10 | 11 | 76.443 | 75.702 | -0.740 | -0.97% | 0.93% |
| 10 | 12 | 76.438 | 75.604 | -0.834 | -1.09% | 1.04% |
| Max | | 76.706 | 76.657 | -0.048 | -0.06% | 1.04% |
| Average | | 76.216 | 75.839 | -0.377 | -0.49% | 0.47% |
| Min | | 75.377 | 74.894 | -0.834 | -1.09% | 0.06% |
| Std Dev | | 0.402 | 0.468 | 0.255 | 0.33% | 0.32% |




| 111.14_Isc_10V_Sink_C | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|--------|--|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | |
| Test Number | EB4632 | EB4632 | Unit | mA | mA | |
| Max Limit | 90 | 90 | Min Limit | 10 | 10 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 10.000 | 10.000 | 10.000 | 10.000 | | |
| Min | 76.657 | 75.205 | 74.894 | 75.605 | | |
| Average | 76.657 | 75.888 | 75.687 | 75.736 | | |
| Max | 76.657 | 76.262 | 76.264 | 75.829 | | |
| UL | 90.000 | 90.000 | 90.000 | 90.000 | | |




NDD Report

LMP7704-SP

| 111.15_Isc_10V_Sink_D | | | | | | |
|-----------------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | 90 | 90 | | | | |
| Min Limit | 10 | 10 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 76.399 | 76.360 | -0.040 | -0.05% | 0.05% |
| 1 | 1 | 75.125 | 74.964 | -0.161 | -0.21% | 0.20% |
| 1 | 2 | 75.876 | 75.723 | -0.153 | -0.20% | 0.19% |
| 1 | 3 | 76.367 | 76.229 | -0.138 | -0.18% | 0.17% |
| 1 | 4 | 76.439 | 76.305 | -0.134 | -0.17% | 0.17% |
| 5 | 5 | 76.028 | 75.641 | -0.387 | -0.51% | 0.48% |
| 5 | 6 | 75.025 | 74.669 | -0.356 | -0.48% | 0.45% |
| 5 | 7 | 76.574 | 76.054 | -0.520 | -0.68% | 0.65% |
| 5 | 8 | 76.127 | 72.644 | -3.483 | -4.58% | 4.35% |
| 10 | 9 | 76.133 | 75.455 | -0.678 | -0.89% | 0.85% |
| 10 | 10 | 76.451 | 75.839 | -0.612 | -0.80% | 0.76% |
| 10 | 11 | 76.477 | 75.978 | -0.499 | -0.65% | 0.62% |
| 10 | 12 | 76.124 | 75.621 | -0.503 | -0.66% | 0.63% |
| Max | | 76.574 | 76.360 | -0.040 | -0.05% | 4.35% |
| Average | | 76.088 | 75.499 | -0.590 | -0.77% | 0.74% |
| Min | | 75.025 | 72.644 | -3.483 | -4.58% | 0.05% |
| Std Dev | | 0.494 | 0.991 | 0.894 | 1.17% | 1.12% |




| 111.15_Isc_10V_Sink_D | | | | | | |
|-----------------------------------|-----------|--------|--------|--------|--|--|
| Test Site | TI Dallas | | | | | |
| Tester | ETS364 | | | | | |
| Test Number | EB4632 | | | | | |
| Max Limit | 90 | mA | | | | |
| Min Limit | 10 | mA | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | 10.000 | 10.000 | 10.000 | 10.000 | | |
| Min | 76.360 | 74.964 | 72.644 | 75.455 | | |
| Average | 76.360 | 75.805 | 74.752 | 75.723 | | |
| Max | 76.360 | 76.305 | 76.054 | 75.978 | | |
| UL | 90.000 | 90.000 | 90.000 | 90.000 | | |




NDD Report

LMP7704-SP

| 112.0_Iq_end_Vcc_2p7V | | | | | | |
|-----------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | 3.33 | 3.33 | | | | |
| Min Limit | 1.1 | 1.1 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 2.673 | 2.677 | 0.004 | 0.13% | 0.16% |
| 1 | 1 | 2.695 | 2.695 | 0.000 | 0.02% | 0.02% |
| 1 | 2 | 2.679 | 2.684 | 0.005 | 0.19% | 0.22% |
| 1 | 3 | 2.634 | 2.635 | 0.001 | 0.04% | 0.04% |
| 1 | 4 | 2.634 | 2.638 | 0.004 | 0.16% | 0.19% |
| 5 | 5 | 2.688 | 2.668 | -0.020 | -0.75% | 0.90% |
| 5 | 6 | 2.669 | 2.661 | -0.008 | -0.30% | 0.36% |
| 5 | 7 | 2.636 | 2.616 | -0.020 | -0.77% | 0.91% |
| 5 | 8 | 2.651 | 2.626 | -0.025 | -0.96% | 1.14% |
| 10 | 9 | 2.677 | 2.625 | -0.052 | -1.95% | 2.34% |
| 10 | 10 | 2.632 | 2.589 | -0.043 | -1.65% | 1.94% |
| 10 | 11 | 2.643 | 2.606 | -0.037 | -1.42% | 1.68% |
| 10 | 12 | 2.623 | 2.581 | -0.042 | -1.61% | 1.90% |
| Max | | 2.695 | 2.695 | 0.005 | 0.19% | 2.34% |
| Average | | 2.656 | 2.638 | -0.018 | -0.68% | 0.91% |
| Min | | 2.623 | 2.581 | -0.052 | -1.95% | 0.02% |
| Std Dev | | 0.024 | 0.036 | 0.021 | 0.78% | 0.82% |




| 112.0_Iq_end_Vcc_2p7V | | | | | | |
|-----------------------|-----------|-------|-------|-------|--|--|
| Test Site | TI Dallas | | | | | |
| Tester | ETS364 | | | | | |
| Test Number | EB4632 | | | | | |
| Max Limit | 3.33 | mA | | | | |
| Min Limit | 1.1 | mA | | | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | 1.100 | 1.100 | 1.100 | 1.100 | | |
| Min | 2.677 | 2.635 | 2.616 | 2.581 | | |
| Average | 2.677 | 2.663 | 2.643 | 2.600 | | |
| Max | 2.677 | 2.695 | 2.668 | 2.625 | | |
| UL | 3.330 | 3.330 | 3.330 | 3.330 | | |




NDD Report

LMP7704-SP

| 112.1_Iq_end_Vee_2p7V | | | | | | |
|-----------------------|-----------|---|------------------|--------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | -1.1 |
| Tester | ETS364 | ETS364 | Min Limit | -3.33 | Delta | -0.003 |
| Test Number | EB4632 | EB4632 <th>% of Limit Range</th> <td>0.14%</td> <th>Delta %</th> <td>0.12%</td> | % of Limit Range | 0.14% | Delta % | 0.12% |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -2.674 | -2.678 | -0.003 | 0.12% | 0.14% |
| 1 | 1 | -2.696 | -2.695 | 0.000 | 0.00% | 0.00% |
| 1 | 2 | -2.680 | -2.684 | -0.004 | 0.17% | 0.20% |
| 1 | 3 | -2.635 | -2.635 | 0.000 | 0.02% | 0.02% |
| 1 | 4 | -2.635 | -2.638 | -0.003 | 0.13% | 0.16% |
| 5 | 5 | -2.689 | -2.668 | 0.021 | -0.77% | 0.92% |
| 5 | 6 | -2.670 | -2.661 | 0.009 | -0.33% | 0.39% |
| 5 | 7 | -2.637 | -2.616 | 0.021 | -0.79% | 0.93% |
| 5 | 8 | -2.652 | -2.626 | 0.026 | -0.98% | 1.17% |
| 10 | 9 | -2.678 | -2.625 | 0.053 | -1.96% | 2.36% |
| 10 | 10 | -2.633 | -2.589 | 0.044 | -1.67% | 1.97% |
| 10 | 11 | -2.644 | -2.606 | 0.038 | -1.44% | 1.71% |
| 10 | 12 | -2.624 | -2.581 | 0.043 | -1.63% | 1.92% |
| Max | | -2.624 | -2.581 | 0.053 | 0.17% | 2.36% |
| Average | | -2.657 | -2.639 | 0.019 | -0.70% | 0.92% |
| Min | | -2.696 | -2.695 | -0.004 | -1.96% | 0.00% |
| Std Dev | | 0.024 | 0.036 | 0.021 | 0.78% | 0.84% |




| 112.1_Iq_end_Vee_2p7V | | | | | | |
|-----------------------|-----------|-----------|------------------|--------|-----------|--------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | -1.1 |
| Tester | ETS364 | ETS364 | Min Limit | -3.33 | Delta | -0.003 |
| Test Number | EB4632 | EB4632 | % of Limit Range | 0.14% | Delta % | 0.12% |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -3.330 | -3.330 | -3.330 | -3.330 | | |
| Min | -2.678 | -2.696 | -2.668 | -2.626 | | |
| Average | -2.678 | -2.663 | -2.643 | -2.600 | | |
| Max | -2.678 | -2.635 | -2.617 | -2.581 | | |
| UL | -1.100 | -1.100 | -1.100 | -1.100 | | |




NDD Report

LMP7704-SP

| 112.2_Iq_end_Vcc_5V | | | | | | |
|---------------------|-----------|---|-----------|--------|------------------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | 3.33 |
| Tester | ETS364 | ETS364 | Min Limit | mA | Delta | 0.004 |
| Test Number | EB4632 | EB4632 <th>Delta %</th> <td>0.14%</td> <th>% of Limit Range</th> <td>0.18%</td> | Delta % | 0.14% | % of Limit Range | 0.18% |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 2.898 | 2.902 | 0.004 | 0.14% | 0.18% |
| 1 | 1 | 2.922 | 2.924 | 0.002 | 0.07% | 0.09% |
| 1 | 2 | 2.901 | 2.908 | 0.007 | 0.24% | 0.31% |
| 1 | 3 | 2.854 | 2.855 | 0.002 | 0.06% | 0.08% |
| 1 | 4 | 2.853 | 2.859 | 0.006 | 0.20% | 0.26% |
| 5 | 5 | 2.914 | 2.895 | -0.019 | -0.65% | 0.85% |
| 5 | 6 | 2.892 | 2.893 | 0.001 | 0.03% | 0.04% |
| 5 | 7 | 2.856 | 2.838 | -0.018 | -0.62% | 0.80% |
| 5 | 8 | 2.871 | 2.848 | -0.023 | -0.80% | 1.03% |
| 10 | 9 | 2.902 | 2.852 | -0.050 | -1.71% | 2.23% |
| 10 | 10 | 2.851 | 2.809 | -0.042 | -1.46% | 1.87% |
| 10 | 11 | 2.865 | 2.830 | -0.035 | -1.23% | 1.58% |
| 10 | 12 | 2.844 | 2.804 | -0.040 | -1.40% | 1.78% |
| Max | | 2.922 | 2.924 | 0.007 | 0.24% | 2.23% |
| Average | | 2.879 | 2.863 | -0.016 | -0.55% | 0.85% |
| Min | | 2.844 | 2.804 | -0.050 | -1.71% | 0.04% |
| Std Dev | | 0.027 | 0.038 | 0.021 | 0.72% | 0.78% |




| 112.2_Iq_end_Vcc_5V | | | | | | |
|---------------------|-----------|-----------|-----------|-------|------------------|-------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | 3.33 |
| Tester | ETS364 | ETS364 | Min Limit | mA | Delta | 0.004 |
| Test Number | EB4632 | EB4632 | Delta % | 0.14% | % of Limit Range | 0.18% |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | 1.100 | 1.100 | 1.100 | 1.100 | | |
| Min | 2.902 | 2.856 | 2.838 | 2.804 | | |
| Average | 2.902 | 2.887 | 2.869 | 2.824 | | |
| Max | 2.902 | 2.924 | 2.896 | 2.852 | | |
| UL | 3.330 | 3.330 | 3.330 | 3.330 | | |




NDD Report

LMP7704-SP

| 112.3_Iq_end_Vee_5V | | | | | | |
|-----------------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | -1.1 | -1.1 | | | | |
| Min Limit | -3.33 | -3.33 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -2.898 | -2.902 | -0.004 | 0.13% | 0.17% |
| 1 | 1 | -2.923 | -2.924 | -0.002 | 0.05% | 0.07% |
| 1 | 2 | -2.902 | -2.909 | -0.006 | 0.22% | 0.28% |
| 1 | 3 | -2.855 | -2.856 | -0.001 | 0.04% | 0.05% |
| 1 | 4 | -2.855 | -2.860 | -0.005 | 0.18% | 0.23% |
| 5 | 5 | -2.915 | -2.896 | 0.020 | -0.68% | 0.88% |
| 5 | 6 | -2.893 | -2.894 | 0.000 | 0.02% | 0.02% |
| 5 | 7 | -2.857 | -2.839 | 0.018 | -0.64% | 0.83% |
| 5 | 8 | -2.872 | -2.849 | 0.023 | -0.81% | 1.04% |
| 10 | 9 | -2.903 | -2.852 | 0.050 | -1.73% | 2.26% |
| 10 | 10 | -2.852 | -2.810 | 0.042 | -1.48% | 1.90% |
| 10 | 11 | -2.866 | -2.830 | 0.036 | -1.26% | 1.61% |
| 10 | 12 | -2.845 | -2.805 | 0.040 | -1.42% | 1.81% |
| Max | | -2.845 | -2.805 | 0.050 | 0.22% | 2.26% |
| Average | | -2.880 | -2.863 | 0.016 | -0.57% | 0.86% |
| Min | | -2.923 | -2.924 | -0.006 | -1.73% | 0.02% |
| Std Dev | | 0.027 | 0.038 | 0.021 | 0.72% | 0.80% |




| 112.3_Iq_end_Vee_5V | | | | | | |
|-----------------------------------|-----------|--------|--------|--------|--|--|
| Test Site | TI Dallas | | | | | |
| Tester | ETS364 | | | | | |
| Test Number | EB4632 | | | | | |
| Max Limit | -1.1 | mA | | | | |
| Min Limit | -3.33 | mA | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -3.330 | -3.330 | -3.330 | -3.330 | | |
| Min | -2.902 | -2.924 | -2.896 | -2.853 | | |
| Average | -2.902 | -2.887 | -2.869 | -2.824 | | |
| Max | -2.902 | -2.856 | -2.839 | -2.805 | | |
| UL | -1.100 | -1.100 | -1.100 | -1.100 | | |




NDD Report

LMP7704-SP

| 112.4_Iq_end_Vcc_10V | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | 3.78 |
| Tester | ETS364 | ETS364 | Min Limit | mA | Max Limit | 1.1 |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 3.211 | 3.215 | 0.005 | 0.15% | 0.18% |
| 1 | 1 | 3.228 | 3.232 | 0.004 | 0.14% | 0.16% |
| 1 | 2 | 3.206 | 3.215 | 0.009 | 0.27% | 0.33% |
| 1 | 3 | 3.163 | 3.167 | 0.004 | 0.11% | 0.13% |
| 1 | 4 | 3.162 | 3.169 | 0.007 | 0.23% | 0.27% |
| 5 | 5 | 3.227 | 3.210 | -0.016 | -0.50% | 0.60% |
| 5 | 6 | 3.201 | 3.214 | 0.013 | 0.40% | 0.48% |
| 5 | 7 | 3.165 | 3.152 | -0.013 | -0.42% | 0.50% |
| 5 | 8 | 3.180 | 3.160 | -0.020 | -0.63% | 0.74% |
| 10 | 9 | 3.214 | 3.172 | -0.042 | -1.31% | 1.57% |
| 10 | 10 | 3.160 | 3.123 | -0.038 | -1.19% | 1.40% |
| 10 | 11 | 3.177 | 3.147 | -0.030 | -0.96% | 1.13% |
| 10 | 12 | 3.159 | 3.125 | -0.034 | -1.08% | 1.28% |
| Max | | 3.228 | 3.232 | 0.013 | 0.40% | 1.57% |
| Average | | 3.189 | 3.177 | -0.012 | -0.37% | 0.68% |
| Min | | 3.159 | 3.123 | -0.042 | -1.31% | 0.13% |
| Std Dev | | 0.026 | 0.037 | 0.020 | 0.62% | 0.51% |




| 112.4_Iq_end_Vcc_10V | | | | | |
|-----------------------------------|-----------|--------|---|-------------|--------|
| Test Site | TI Dallas | Tester | ETS364 <th>Test Number</th> <td>EB4632</td> | Test Number | EB4632 |
| Max Limit | 3.78 | mA | | Min Limit | 1.1 |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | |
| LL | 1.100 | 1.100 | 1.100 | 1.100 | |
| Min | 3.215 | 3.167 | 3.152 | 3.123 | |
| Average | 3.215 | 3.196 | 3.184 | 3.141 | |
| Max | 3.215 | 3.232 | 3.214 | 3.172 | |
| UL | 3.780 | 3.780 | 3.780 | 3.780 | |




NDD Report

LMP7704-SP

| 112.5_Iq_end_Vee_10V | | | | | | |
|----------------------|-----------|-----------|------------------|------------------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | -1.1 |
| Tester | ETS364 | ETS364 | Min Limit | | Delta | Delta % |
| Test Number | EB4632 | EB4632 | Delta % | % of Limit Range | | |
| Unit | mA | mA | % of Limit Range | | | |
| Max Limit | -1.1 | -1.1 | | | | |
| Min Limit | -3.78 | -3.78 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -3.211 | -3.216 | -0.004 | 0.14% | 0.16% |
| 1 | 1 | -3.229 | -3.233 | -0.004 | 0.12% | 0.15% |
| 1 | 2 | -3.207 | -3.216 | -0.009 | 0.27% | 0.32% |
| 1 | 3 | -3.164 | -3.167 | -0.003 | 0.09% | 0.11% |
| 1 | 4 | -3.163 | -3.170 | -0.007 | 0.22% | 0.26% |
| 5 | 5 | -3.228 | -3.211 | 0.017 | -0.52% | 0.63% |
| 5 | 6 | -3.203 | -3.214 | -0.012 | 0.37% | 0.45% |
| 5 | 7 | -3.167 | -3.152 | 0.014 | -0.45% | 0.53% |
| 5 | 8 | -3.181 | -3.160 | 0.021 | -0.65% | 0.77% |
| 10 | 9 | -3.215 | -3.172 | 0.043 | -1.34% | 1.60% |
| 10 | 10 | -3.162 | -3.123 | 0.038 | -1.21% | 1.43% |
| 10 | 11 | -3.178 | -3.147 | 0.031 | -0.98% | 1.16% |
| 10 | 12 | -3.160 | -3.125 | 0.035 | -1.10% | 1.30% |
| Max | | -3.160 | -3.123 | 0.043 | 0.37% | 1.60% |
| Average | | -3.190 | -3.177 | 0.012 | -0.39% | 0.68% |
| Min | | -3.229 | -3.233 | -0.012 | -1.34% | 0.11% |
| Std Dev | | 0.026 | 0.037 | 0.020 | 0.62% | 0.53% |




| 112.5_Iq_end_Vee_10V | | | | | | |
|----------------------|-----------|-----------|------------------|------------------|-----------|---------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | -1.1 |
| Tester | ETS364 | ETS364 | Min Limit | | Delta | Delta % |
| Test Number | EB4632 | EB4632 | Delta % | % of Limit Range | | |
| Unit | mA | mA | % of Limit Range | | | |
| Max Limit | -1.1 | -1.1 | | | | |
| Min Limit | -3.78 | -3.78 | | | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -3.780 | -3.780 | -3.780 | -3.780 | | |
| Min | -3.216 | -3.233 | -3.215 | -3.172 | | |
| Average | -3.216 | -3.196 | -3.184 | -3.142 | | |
| Max | -3.216 | -3.167 | -3.152 | -3.123 | | |
| UL | -1.100 | -1.100 | -1.100 | -1.100 | | |




NDD Report

LMP7704-SP

| 112.6_Iq_end_Vcc_12V | | | | | | |
|----------------------|-----------|-----------|-----------|--------|-----------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | 3.78 |
| Tester | ETS364 | ETS364 | Min Limit | mA | Max Limit | 1.1 |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 3.339 | 3.345 | 0.005 | 0.16% | 0.19% |
| 1 | 1 | 3.354 | 3.359 | 0.005 | 0.14% | 0.18% |
| 1 | 2 | 3.332 | 3.341 | 0.009 | 0.28% | 0.35% |
| 1 | 3 | 3.291 | 3.295 | 0.004 | 0.12% | 0.15% |
| 1 | 4 | 3.289 | 3.297 | 0.008 | 0.24% | 0.30% |
| 5 | 5 | 3.355 | 3.339 | -0.016 | -0.48% | 0.60% |
| 5 | 6 | 3.329 | 3.345 | 0.016 | 0.48% | 0.60% |
| 5 | 7 | 3.293 | 3.281 | -0.013 | -0.38% | 0.47% |
| 5 | 8 | 3.307 | 3.287 | -0.020 | -0.59% | 0.73% |
| 10 | 9 | 3.343 | 3.302 | -0.041 | -1.22% | 1.52% |
| 10 | 10 | 3.288 | 3.251 | -0.037 | -1.12% | 1.37% |
| 10 | 11 | 3.305 | 3.276 | -0.030 | -0.90% | 1.11% |
| 10 | 12 | 3.289 | 3.255 | -0.034 | -1.02% | 1.26% |
| Max | | 3.355 | 3.359 | 0.016 | 0.48% | 1.52% |
| Average | | 3.316 | 3.306 | -0.011 | -0.33% | 0.68% |
| Min | | 3.288 | 3.251 | -0.041 | -1.22% | 0.15% |
| Std Dev | | 0.026 | 0.036 | 0.020 | 0.60% | 0.48% |




| 112.6_Iq_end_Vcc_12V | | | | | | |
|----------------------|-----------|-----------|-----------|-------|-----------|------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | 3.78 |
| Tester | ETS364 | ETS364 | Min Limit | mA | Max Limit | 1.1 |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | 1.100 | 1.100 | 1.100 | 1.100 | | |
| Min | 3.345 | 3.295 | 3.281 | 3.251 | | |
| Average | 3.345 | 3.323 | 3.313 | 3.271 | | |
| Max | 3.345 | 3.359 | 3.345 | 3.302 | | |
| UL | 3.780 | 3.780 | 3.780 | 3.780 | | |




NDD Report

LMP7704-SP

| 112.7_Iq_end_Vee_12V | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | mA | |
| Tester | ETS364 | ETS364 | Max Limit | -1.1 | -1.1 | |
| Test Number | EB4632 | EB4632 | Min Limit | -3.78 | -3.78 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -3.341 | -3.345 | -0.004 | 0.13% | 0.17% |
| 1 | 1 | -3.355 | -3.359 | -0.004 | 0.13% | 0.16% |
| 1 | 2 | -3.333 | -3.341 | -0.009 | 0.26% | 0.32% |
| 1 | 3 | -3.292 | -3.295 | -0.004 | 0.11% | 0.13% |
| 1 | 4 | -3.290 | -3.297 | -0.007 | 0.22% | 0.27% |
| 5 | 5 | -3.356 | -3.340 | 0.017 | -0.49% | 0.62% |
| 5 | 6 | -3.330 | -3.345 | -0.015 | 0.46% | 0.57% |
| 5 | 7 | -3.294 | -3.281 | 0.013 | -0.40% | 0.50% |
| 5 | 8 | -3.308 | -3.287 | 0.020 | -0.61% | 0.75% |
| 10 | 9 | -3.344 | -3.303 | 0.041 | -1.23% | 1.54% |
| 10 | 10 | -3.289 | -3.252 | 0.038 | -1.14% | 1.40% |
| 10 | 11 | -3.306 | -3.276 | 0.030 | -0.91% | 1.13% |
| 10 | 12 | -3.290 | -3.255 | 0.035 | -1.05% | 1.29% |
| Max | | -3.289 | -3.252 | 0.041 | 0.46% | 1.54% |
| Average | | -3.317 | -3.306 | 0.012 | -0.35% | 0.68% |
| Min | | -3.356 | -3.359 | -0.015 | -1.23% | 0.13% |
| Std Dev | | 0.026 | 0.036 | 0.020 | 0.60% | 0.50% |




| 112.7_Iq_end_Vee_12V | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|-------|--|
| Test Site | TI Dallas | TI Dallas | Unit | mA | mA | |
| Tester | ETS364 | ETS364 | Max Limit | -1.1 | -1.1 | |
| Test Number | EB4632 | EB4632 | Min Limit | -3.78 | -3.78 | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -3.780 | -3.780 | -3.780 | -3.780 | | |
| Min | -3.345 | -3.359 | -3.345 | -3.303 | | |
| Average | -3.345 | -3.323 | -3.313 | -3.271 | | |
| Max | -3.345 | -3.295 | -3.281 | -3.252 | | |
| UL | -1.100 | -1.100 | -1.100 | -1.100 | | |




NDD Report

LMP7704-SP

| 112.8_Iq_end_Vcc_MinMax | | | | | | |
|-----------------------------------|-----------|-----------|----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | 1.39 | 1.39 | | | | |
| Min Limit | -1 | -1 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 0.666 | 0.668 | 0.002 | 0.23% | 0.06% |
| 1 | 1 | 0.659 | 0.664 | 0.004 | 0.65% | 0.18% |
| 1 | 2 | 0.653 | 0.657 | 0.004 | 0.67% | 0.18% |
| 1 | 3 | 0.657 | 0.660 | 0.003 | 0.47% | 0.13% |
| 1 | 4 | 0.655 | 0.659 | 0.004 | 0.58% | 0.16% |
| 5 | 5 | 0.667 | 0.671 | 0.004 | 0.60% | 0.17% |
| 5 | 6 | 0.660 | 0.684 | 0.024 | 3.64% | 1.00% |
| 5 | 7 | 0.657 | 0.664 | 0.008 | 1.17% | 0.32% |
| 5 | 8 | 0.656 | 0.661 | 0.006 | 0.88% | 0.24% |
| 10 | 9 | 0.666 | 0.677 | 0.012 | 1.73% | 0.48% |
| 10 | 10 | 0.656 | 0.663 | 0.006 | 0.98% | 0.27% |
| 10 | 11 | 0.662 | 0.670 | 0.008 | 1.18% | 0.33% |
| 10 | 12 | 0.665 | 0.674 | 0.009 | 1.29% | 0.36% |
| Max | | 0.667 | 0.684 | 0.024 | 3.64% | 1.00% |
| Average | | 0.660 | 0.667 | 0.007 | 1.08% | 0.30% |
| Min | | 0.653 | 0.657 | 0.002 | 0.23% | 0.06% |
| Std Dev | | 0.005 | 0.008 | 0.006 | 0.87% | 0.24% |




| 112.8_Iq_end_Vcc_MinMax | | | | | | |
|-----------------------------------|-----------|--------|--------|--------|--|--|
| Test Site | TI Dallas | | | | | |
| Tester | ETS364 | | | | | |
| Test Number | EB4632 | | | | | |
| Max Limit | 1.39 | mA | | | | |
| Min Limit | -1 | mA | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -1.000 | -1.000 | -1.000 | -1.000 | | |
| Min | 0.668 | 0.657 | 0.661 | 0.663 | | |
| Average | 0.668 | 0.660 | 0.670 | 0.671 | | |
| Max | 0.668 | 0.664 | 0.684 | 0.677 | | |
| UL | 1.390 | 1.390 | 1.390 | 1.390 | | |




NDD Report

LMP7704-SP

| 112.9_Iq_end_Vee_MinMax | | | | | | |
|-------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | 1 | 1 | | | | |
| Min Limit | -1.39 | -1.39 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.666 | -0.668 | -0.001 | 0.21% | 0.06% |
| 1 | 1 | -0.659 | -0.664 | -0.004 | 0.68% | 0.19% |
| 1 | 2 | -0.653 | -0.657 | -0.004 | 0.64% | 0.18% |
| 1 | 3 | -0.657 | -0.660 | -0.003 | 0.46% | 0.13% |
| 1 | 4 | -0.655 | -0.659 | -0.004 | 0.56% | 0.15% |
| 5 | 5 | -0.667 | -0.671 | -0.004 | 0.61% | 0.17% |
| 5 | 6 | -0.660 | -0.684 | -0.024 | 3.64% | 1.00% |
| 5 | 7 | -0.657 | -0.664 | -0.007 | 1.14% | 0.31% |
| 5 | 8 | -0.656 | -0.661 | -0.006 | 0.90% | 0.25% |
| 10 | 9 | -0.666 | -0.677 | -0.011 | 1.71% | 0.48% |
| 10 | 10 | -0.656 | -0.663 | -0.006 | 0.96% | 0.26% |
| 10 | 11 | -0.662 | -0.670 | -0.008 | 1.19% | 0.33% |
| 10 | 12 | -0.666 | -0.674 | -0.008 | 1.25% | 0.35% |
| Max | | -0.653 | -0.657 | -0.001 | 3.64% | 1.00% |
| Average | | -0.660 | -0.667 | -0.007 | 1.07% | 0.30% |
| Min | | -0.667 | -0.684 | -0.024 | 0.21% | 0.06% |
| Std Dev | | 0.005 | 0.008 | 0.006 | 0.87% | 0.24% |




| 112.9_Iq_end_Vee_MinMax | | | | | | |
|-------------------------|-----------|--------|--------|--------|--|--|
| Test Site | TI Dallas | | | | | |
| Tester | ETS364 | | | | | |
| Test Number | EB4632 | | | | | |
| Max Limit | 1 | mA | | | | |
| Min Limit | -1.39 | mA | | | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -1.390 | -1.390 | -1.390 | -1.390 | | |
| Min | -0.668 | -0.664 | -0.684 | -0.677 | | |
| Average | -0.668 | -0.660 | -0.670 | -0.671 | | |
| Max | -0.668 | -0.657 | -0.662 | -0.663 | | |
| UL | 1.000 | 1.000 | 1.000 | 1.000 | | |




NDD Report

LMP7704-SP

| 112.10_Iq_end_Vcc_2p7V_PreP | | | | | | |
|-----------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | 0.1 | 0.1 | | | | |
| Min Limit | -0.1 | -0.1 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 0.011 | 0.009 | -0.001 | -12.04% | 0.65% |
| 1 | 1 | 0.011 | 0.009 | -0.002 | -15.93% | 0.90% |
| 1 | 2 | 0.010 | 0.010 | 0.000 | -0.98% | 0.05% |
| 1 | 3 | 0.010 | 0.010 | 0.000 | -3.85% | 0.20% |
| 1 | 4 | 0.011 | 0.010 | -0.001 | -5.66% | 0.30% |
| 5 | 5 | 0.011 | 0.009 | -0.002 | -18.87% | 1.00% |
| 5 | 6 | 0.011 | 0.010 | -0.001 | -4.67% | 0.25% |
| 5 | 7 | 0.010 | 0.009 | -0.002 | -16.67% | 0.85% |
| 5 | 8 | 0.010 | 0.009 | -0.001 | -11.54% | 0.60% |
| 10 | 9 | 0.010 | 0.009 | -0.002 | -17.31% | 0.90% |
| 10 | 10 | 0.011 | 0.008 | -0.003 | -27.36% | 1.45% |
| 10 | 11 | 0.010 | 0.009 | -0.002 | -15.84% | 0.80% |
| 10 | 12 | 0.010 | 0.009 | -0.001 | -10.10% | 0.50% |
| Max | | 0.011 | 0.010 | 0.000 | -0.98% | 1.45% |
| Average | | 0.010 | 0.009 | -0.001 | -12.37% | 0.65% |
| Min | | 0.010 | 0.008 | -0.003 | -27.36% | 0.05% |
| Std Dev | | 0.000 | 0.001 | 0.001 | 7.34% | 0.39% |




| 112.10_Iq_end_Vcc_2p7V_PreP | | | | | | |
|-----------------------------|-----------|--------|--------|--------|--|--|
| Test Site | TI Dallas | | | | | |
| Tester | ETS364 | | | | | |
| Test Number | EB4632 | | | | | |
| Max Limit | 0.1 | mA | | | | |
| Min Limit | -0.1 | mA | | | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -0.100 | -0.100 | -0.100 | -0.100 | | |
| Min | 0.010 | 0.010 | 0.009 | 0.008 | | |
| Average | 0.010 | 0.010 | 0.009 | 0.008 | | |
| Max | 0.010 | 0.010 | 0.010 | 0.009 | | |
| UL | 0.100 | 0.100 | 0.100 | 0.100 | | |




NDD Report

LMP7704-SP

| 112.11_Iq_end_Vee_2p7V_PrePost | | | | | | |
|--------------------------------|-----------|-----------|----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | 0.1 | 0.1 | | | | |
| Min Limit | -0.1 | -0.1 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.011 | -0.010 | 0.001 | -11.93% | 0.65% |
| 1 | 1 | -0.011 | -0.009 | 0.002 | -16.07% | 0.90% |
| 1 | 2 | -0.010 | -0.010 | 0.000 | 0.00% | 0.00% |
| 1 | 3 | -0.010 | -0.010 | 0.000 | -3.85% | 0.20% |
| 1 | 4 | -0.011 | -0.010 | 0.001 | -7.48% | 0.40% |
| 5 | 5 | -0.010 | -0.009 | 0.002 | -17.14% | 0.90% |
| 5 | 6 | -0.011 | -0.010 | 0.001 | -5.61% | 0.30% |
| 5 | 7 | -0.010 | -0.008 | 0.002 | -17.65% | 0.90% |
| 5 | 8 | -0.010 | -0.009 | 0.002 | -14.42% | 0.75% |
| 10 | 9 | -0.010 | -0.009 | 0.002 | -16.50% | 0.85% |
| 10 | 10 | -0.010 | -0.008 | 0.003 | -27.62% | 1.45% |
| 10 | 11 | -0.010 | -0.008 | 0.002 | -17.65% | 0.90% |
| 10 | 12 | -0.010 | -0.009 | 0.001 | -8.08% | 0.40% |
| Max | | -0.010 | -0.008 | 0.003 | 0.00% | 1.45% |
| Average | | -0.010 | -0.009 | 0.001 | -12.61% | 0.66% |
| Min | | -0.011 | -0.010 | 0.000 | -27.62% | 0.00% |
| Std Dev | | 0.000 | 0.001 | 0.001 | 7.41% | 0.39% |




| 112.11_Iq_end_Vee_2p7V_PrePost | | | | | | |
|--------------------------------|-----------|--------|--------|--------|--|--|
| Test Site | TI Dallas | | | | | |
| Tester | ETS364 | | | | | |
| Test Number | EB4632 | | | | | |
| Max Limit | 0.1 | mA | | | | |
| Min Limit | -0.1 | mA | | | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -0.100 | -0.100 | -0.100 | -0.100 | | |
| Min | -0.010 | -0.010 | -0.010 | -0.009 | | |
| Average | -0.010 | -0.010 | -0.009 | -0.008 | | |
| Max | -0.010 | -0.009 | -0.008 | -0.008 | | |
| UL | 0.100 | 0.100 | 0.100 | 0.100 | | |




NDD Report

LMP7704-SP

| 112.12_Iq_end_Vcc_5V_PrePost | | | | | | |
|------------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | 0.1 | 0.1 | | | | |
| Min Limit | -0.1 | -0.1 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 0.012 | 0.010 | -0.002 | -13.79% | 0.80% |
| 1 | 1 | 0.012 | 0.010 | -0.002 | -19.67% | 1.20% |
| 1 | 2 | 0.011 | 0.011 | 0.000 | -0.92% | 0.05% |
| 1 | 3 | 0.011 | 0.010 | -0.001 | -5.45% | 0.30% |
| 1 | 4 | 0.011 | 0.010 | -0.001 | -6.25% | 0.35% |
| 5 | 5 | 0.011 | 0.009 | -0.002 | -16.07% | 0.90% |
| 5 | 6 | 0.011 | 0.011 | 0.000 | 0.88% | 0.05% |
| 5 | 7 | 0.011 | 0.009 | -0.002 | -18.35% | 1.00% |
| 5 | 8 | 0.011 | 0.009 | -0.002 | -13.64% | 0.75% |
| 10 | 9 | 0.011 | 0.008 | -0.003 | -23.64% | 1.30% |
| 10 | 10 | 0.011 | 0.008 | -0.003 | -27.93% | 1.55% |
| 10 | 11 | 0.011 | 0.009 | -0.002 | -17.43% | 0.95% |
| 10 | 12 | 0.010 | 0.010 | -0.001 | -6.67% | 0.35% |
| Max | | 0.012 | 0.011 | 0.000 | 0.88% | 1.55% |
| Average | | 0.011 | 0.010 | -0.001 | -12.99% | 0.73% |
| Min | | 0.010 | 0.008 | -0.003 | -27.93% | 0.05% |
| Std Dev | | 0.000 | 0.001 | 0.001 | 8.76% | 0.48% |




| 112.12_Iq_end_Vcc_5V_PrePost | | | | |
|------------------------------|-----------|--------|--------|--------|
| Test Site | TI Dallas | | | |
| Tester | ETS364 | | | |
| Test Number | EB4632 | | | |
| Max Limit | 0.1 | mA | | |
| Min Limit | -0.1 | mA | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 |
| LL | -0.100 | -0.100 | -0.100 | -0.100 |
| Min | 0.010 | 0.010 | 0.009 | 0.008 |
| Average | 0.010 | 0.010 | 0.010 | 0.009 |
| Max | 0.010 | 0.011 | 0.011 | 0.010 |
| UL | 0.100 | 0.100 | 0.100 | 0.100 |




NDD Report

LMP7704-SP

| 112.13_Iq_end_Vee_5V_PrePost | | | | | | |
|------------------------------|-----------|-----------|----------|-------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | 0.1 | 0.1 | | | | |
| Min Limit | -0.1 | -0.1 | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.012 | -0.010 | 0.002 | -12.93% | 0.75% |
| 1 | 1 | -0.012 | -0.010 | 0.002 | -19.01% | 1.15% |
| 1 | 2 | -0.011 | -0.011 | 0.000 | -0.93% | 0.05% |
| 1 | 3 | -0.011 | -0.010 | 0.001 | -5.50% | 0.30% |
| 1 | 4 | -0.011 | -0.010 | 0.001 | -7.08% | 0.40% |
| 5 | 5 | -0.011 | -0.009 | 0.002 | -16.96% | 0.95% |
| 5 | 6 | -0.011 | -0.011 | 0.000 | 1.79% | 0.10% |
| 5 | 7 | -0.011 | -0.009 | 0.002 | -16.82% | 0.90% |
| 5 | 8 | -0.011 | -0.009 | 0.001 | -12.84% | 0.70% |
| 10 | 9 | -0.011 | -0.009 | 0.002 | -20.18% | 1.10% |
| 10 | 10 | -0.011 | -0.008 | 0.003 | -27.93% | 1.55% |
| 10 | 11 | -0.011 | -0.009 | 0.002 | -18.35% | 1.00% |
| 10 | 12 | -0.010 | -0.010 | 0.001 | -5.83% | 0.30% |
| Max | | -0.010 | -0.008 | 0.003 | 1.79% | 1.55% |
| Average | | -0.011 | -0.010 | 0.001 | -12.51% | 0.71% |
| Min | | -0.012 | -0.011 | 0.000 | -27.93% | 0.05% |
| Std Dev | | 0.000 | 0.001 | 0.001 | 8.53% | 0.45% |




| 112.13_Iq_end_Vee_5V_PrePost | | | | | | |
|------------------------------|-----------|-----------|--------|--------|--|--|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Max Limit | 0.1 | mA | | | | |
| Min Limit | -0.1 | mA | | | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -0.100 | -0.100 | -0.100 | -0.100 | | |
| Min | -0.010 | -0.011 | -0.011 | -0.010 | | |
| Average | -0.010 | -0.010 | -0.010 | -0.009 | | |
| Max | -0.010 | -0.010 | -0.009 | -0.008 | | |
| UL | 0.100 | 0.100 | 0.100 | 0.100 | | |




NDD Report

LMP7704-SP

| 112.14_Iq_end_Vcc_10V_PrePost | | | | | | |
|-------------------------------|-----------|-----------|-----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Delta | Delta % |
| Tester | ETS364 | ETS364 | Max Limit | 0.1 | -0.002 | -14.41% |
| Test Number | EB4632 | EB4632 | Min Limit | -0.1 | -0.001 | 0.85% |
| Unit | mA | mA | Max Limit | 0.1 | -0.001 | 1.30% |
| Max Limit | 0.1 | 0.1 | Min Limit | -0.1 | -0.001 | 0.15% |
| Min Limit | -0.1 | -0.1 | Max Limit | 0.1 | -0.001 | 0.35% |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 0.012 | 0.010 | -0.002 | -14.41% | 0.85% |
| 1 | 1 | 0.013 | 0.010 | -0.003 | -20.80% | 1.30% |
| 1 | 2 | 0.011 | 0.011 | 0.000 | -2.68% | 0.15% |
| 1 | 3 | 0.011 | 0.011 | -0.001 | -6.19% | 0.35% |
| 1 | 4 | 0.012 | 0.011 | -0.001 | -7.76% | 0.45% |
| 5 | 5 | 0.012 | 0.009 | -0.002 | -19.66% | 1.15% |
| 5 | 6 | 0.012 | 0.012 | 0.001 | 6.90% | 0.40% |
| 5 | 7 | 0.011 | 0.009 | -0.002 | -17.86% | 1.00% |
| 5 | 8 | 0.011 | 0.010 | -0.001 | -11.61% | 0.65% |
| 10 | 9 | 0.011 | 0.009 | -0.002 | -21.24% | 1.20% |
| 10 | 10 | 0.011 | 0.008 | -0.004 | -30.70% | 1.75% |
| 10 | 11 | 0.011 | 0.009 | -0.002 | -14.41% | 0.80% |
| 10 | 12 | 0.011 | 0.010 | -0.001 | -8.41% | 0.45% |
| Max | | 0.013 | 0.012 | 0.001 | 6.90% | 1.75% |
| Average | | 0.011 | 0.010 | -0.001 | -12.99% | 0.81% |
| Min | | 0.011 | 0.008 | -0.004 | -30.70% | 0.15% |
| Std Dev | | 0.000 | 0.001 | 0.001 | 9.63% | 0.46% |




| 112.14_Iq_end_Vcc_10V_PrePost | | | | |
|-------------------------------|-----------|--------|-----------|--------|
| Test Site | TI Dallas | ETS364 | Unit | mA |
| Tester | ETS364 | ETS364 | Max Limit | 0.1 |
| Test Number | EB4632 | EB4632 | Min Limit | -0.1 |
| Unit | mA | mA | Max Limit | 0.1 |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 |
| LL | -0.100 | -0.100 | -0.100 | -0.100 |
| Min | 0.010 | 0.010 | 0.009 | 0.008 |
| Average | 0.010 | 0.011 | 0.010 | 0.009 |
| Max | 0.010 | 0.011 | 0.012 | 0.010 |
| UL | 0.100 | 0.100 | 0.100 | 0.100 |




NDD Report

LMP7704-SP

| 112.15_Iq_end_Vee_10V_PrePost | | | | | | |
|-------------------------------|-----------|-----------|-----------|--------|------------------|------------------|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | 0.1 |
| Tester | ETS364 | ETS364 | Min Limit | -0.1 | Delta | |
| Test Number | EB4632 | EB4632 | Delta % | | % of Limit Range | |
| | | | | | | |
| 1*10^12 n/cm^2 | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | -0.012 | -0.010 | 0.002 | -14.41% | 0.85% |
| 1 | 1 | -0.012 | -0.010 | 0.002 | -18.70% | 1.15% |
| 1 | 2 | -0.011 | -0.011 | 0.000 | 0.91% | 0.05% |
| 1 | 3 | -0.011 | -0.011 | 0.001 | -5.36% | 0.30% |
| 1 | 4 | -0.012 | -0.011 | 0.001 | -6.09% | 0.35% |
| 5 | 5 | -0.012 | -0.009 | 0.002 | -18.97% | 1.10% |
| 5 | 6 | -0.012 | -0.012 | -0.001 | 6.90% | 0.40% |
| 5 | 7 | -0.011 | -0.009 | 0.002 | -19.82% | 1.10% |
| 5 | 8 | -0.011 | -0.010 | 0.001 | -13.39% | 0.75% |
| 10 | 9 | -0.011 | -0.008 | 0.003 | -25.89% | 1.45% |
| 10 | 10 | -0.011 | -0.008 | 0.003 | -29.82% | 1.70% |
| 10 | 11 | -0.011 | -0.009 | 0.002 | -15.32% | 0.85% |
| 10 | 12 | -0.010 | -0.010 | 0.001 | -6.67% | 0.35% |
| Max | | -0.010 | -0.008 | 0.003 | 6.90% | 1.70% |
| Average | | -0.011 | -0.010 | 0.001 | -12.82% | 0.80% |
| Min | | -0.012 | -0.012 | -0.001 | -29.82% | 0.05% |
| Std Dev | | 0.000 | 0.001 | 0.001 | 10.43% | 0.49% |




| 112.15_Iq_end_Vee_10V_PrePost | | | | | | |
|-------------------------------|-----------|-----------|-----------|--------|------------------|-----|
| Test Site | TI Dallas | TI Dallas | Unit | mA | Max Limit | 0.1 |
| Tester | ETS364 | ETS364 | Min Limit | -0.1 | Delta | |
| Test Number | EB4632 | EB4632 | Delta % | | % of Limit Range | |
| | | | | | | |
| 1*10^12 n/cm^2 | 0 | 1 | 5 | 10 | | |
| LL | -0.100 | -0.100 | -0.100 | -0.100 | | |
| Min | -0.010 | -0.011 | -0.012 | -0.010 | | |
| Average | -0.010 | -0.011 | -0.010 | -0.009 | | |
| Max | -0.010 | -0.010 | -0.009 | -0.008 | | |
| UL | 0.100 | 0.100 | 0.100 | 0.100 | | |




NDD Report

LMP7704-SP

| 112.16_Iq_end_Vcc_12V_PrePost | | | | | | |
|-----------------------------------|-----------|-----------|----------|--------|---------|------------------|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Unit | mA | mA | | | | |
| Max Limit | 0.1 | 0.1 | | | | |
| Min Limit | -0.1 | -0.1 | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range |
| 0 | 13 | 0.012 | 0.010 | -0.002 | -14.53% | 0.85% |
| 1 | 1 | 0.012 | 0.010 | -0.002 | -20.49% | 1.25% |
| 1 | 2 | 0.011 | 0.010 | -0.001 | -4.55% | 0.25% |
| 1 | 3 | 0.011 | 0.010 | 0.000 | -3.67% | 0.20% |
| 1 | 4 | 0.011 | 0.011 | -0.001 | -7.02% | 0.40% |
| 5 | 5 | 0.012 | 0.009 | -0.002 | -18.26% | 1.05% |
| 5 | 6 | 0.012 | 0.013 | 0.002 | 13.04% | 0.75% |
| 5 | 7 | 0.011 | 0.009 | -0.002 | -19.09% | 1.05% |
| 5 | 8 | 0.011 | 0.009 | -0.002 | -16.96% | 0.95% |
| 10 | 9 | 0.011 | 0.009 | -0.002 | -14.55% | 0.80% |
| 10 | 10 | 0.011 | 0.008 | -0.003 | -29.20% | 1.65% |
| 10 | 11 | 0.011 | 0.009 | -0.002 | -15.60% | 0.85% |
| 10 | 12 | 0.010 | 0.009 | -0.001 | -10.58% | 0.55% |
| Max | | 0.012 | 0.013 | 0.002 | 13.04% | 1.65% |
| Average | | 0.011 | 0.010 | -0.001 | -12.42% | 0.82% |
| Min | | 0.010 | 0.008 | -0.003 | -29.20% | 0.20% |
| Std Dev | | 0.000 | 0.001 | 0.001 | 10.35% | 0.40% |






| 112.16_Iq_end_Vcc_12V_PrePost | | | | | | |
|-----------------------------------|-----------|-----------|--------|--------|--|--|
| Test Site | TI Dallas | TI Dallas | | | | |
| Tester | ETS364 | ETS364 | | | | |
| Test Number | EB4632 | EB4632 | | | | |
| Max Limit | 0.1 | mA | | | | |
| Min Limit | -0.1 | mA | | | | |
| $1 \times 10^{12} \text{ n/cm}^2$ | 0 | 1 | 5 | 10 | | |
| LL | -0.100 | -0.100 | -0.100 | -0.100 | | |
| Min | 0.010 | 0.010 | 0.009 | 0.008 | | |
| Average | 0.010 | 0.010 | 0.010 | 0.009 | | |
| Max | 0.010 | 0.011 | 0.013 | 0.009 | | |
| UL | 0.100 | 0.100 | 0.100 | 0.100 | | |



NDD Report

LMP7704-SP

| 112.17_Iq_end_Vee_12V_PrePost | | | | | | | |
|-----------------------------------|-----------|-----------|-----------|--------|---------|------------------|--------|
| Test Site | TI Dallas | TI Dallas | Tester | ETS364 | ETS364 | Test Number | EB4632 |
| Unit | mA | mA | Max Limit | 0.1 | 0.1 | Min Limit | -0.1 |
| $1 \times 10^{12} \text{ n/cm}^2$ | Serial # | PRE NDD | POST NDD | Delta | Delta % | % of Limit Range | |
| 0 | 13 | -0.012 | -0.010 | 0.002 | -15.38% | 0.90% | |
| 1 | 1 | -0.012 | -0.010 | 0.002 | -19.67% | 1.20% | |
| 1 | 2 | -0.011 | -0.011 | 0.001 | -4.50% | 0.25% | |
| 1 | 3 | -0.011 | -0.010 | 0.000 | -2.78% | 0.15% | |
| 1 | 4 | -0.011 | -0.011 | 0.001 | -7.02% | 0.40% | |
| 5 | 5 | -0.011 | -0.009 | 0.002 | -17.54% | 1.00% | |
| 5 | 6 | -0.011 | -0.013 | -0.001 | 13.27% | 0.75% | |
| 5 | 7 | -0.011 | -0.009 | 0.002 | -19.27% | 1.05% | |
| 5 | 8 | -0.011 | -0.009 | 0.002 | -15.32% | 0.85% | |
| 10 | 9 | -0.011 | -0.009 | 0.002 | -13.76% | 0.75% | |
| 10 | 10 | -0.011 | -0.008 | 0.003 | -29.20% | 1.65% | |
| 10 | 11 | -0.011 | -0.009 | 0.002 | -13.89% | 0.75% | |
| 10 | 12 | -0.010 | -0.009 | 0.001 | -12.38% | 0.65% | |
| Max | | -0.010 | -0.008 | 0.003 | 13.27% | 1.65% | |
| Average | | -0.011 | -0.010 | 0.001 | -12.11% | 0.80% | |
| Min | | -0.012 | -0.013 | -0.001 | -29.20% | 0.15% | |
| Std Dev | | 0.000 | 0.001 | 0.001 | 10.30% | 0.40% | |



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](#) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2024, Texas Instruments Incorporated