### SN74ALS533A, SN74AS533A OCTAL D-TYPE TRANSPARENT LATCHES WITH 3-STATE OUTPUTS SDAS270 - DECEMBER 1994

<ul> <li>Eight Latches in a Single Package</li> <li>3-State Bus-Driving Inverting Outputs</li> </ul>	DW OR N PACKAGE (TOP VIEW)
• Full Parallel Access for Loading	
<ul> <li>Buffered Control Inputs</li> </ul>	
<ul> <li>pnp Inputs Reduce dc Loading on</li> </ul>	1D 🛛 3 18 🗍 8D
Data Lines	2 <u>D</u> <b>[</b> ] 4 17 <b>]</b> 7 <u>D</u>
Package Options Include Plastic	2 <u>Q</u> [] 5 16 [] 7 <u>Q</u>
Small-Outline (DW) Packages and Standard	3Q <b>[</b> 6 15 <b>[</b> 6Q
Plastic (N) 300-mil DIPs	3D 🛛 7 14 🗍 6D
	4 <u>D</u> <b>[</b> 8 13 <b>[</b> 5 <u>D</u>
description	4Q [] 9 12 [] 5Q
	GND [] 10 11 [] LE
These 8-bit D-type transparent latches feature	

These 8-bit D-type transparent latches feature 3-state outputs designed specifically for driving highly capacitive or relatively low-impedance loads. They are particularly suitable for implementing buffer registers, I/O ports, bidirectional bus drivers, and working registers.

While latch-enable (LE) input is high, the  $\overline{Q}$  outputs follow the complements of the data (D) inputs. When LE is taken low, the  $\overline{Q}$  outputs are latched at the inverses of the levels set up at the D inputs. The SN74ALS533A and SN74AS533A are functionally equivalent to the SN74ALS373A and SN74AS373, except for having inverted outputs.

A buffered output-enable  $(\overline{OE})$  input places the eight outputs in either a normal logic state (high or low logic levels) or a high-impedance state. In the high-impedance state, the outputs neither load nor drive the bus lines significantly. The high-impedance state and increased drive provide the capability to drive bus lines without interface or pullup components.

OE does not affect the internal operations of the latches. Old data can be retained or new data can be entered while the outputs are off.

The SN74ALS533A and SN74AS533A are characterized for operation from 0°C to 70°C.

	(ead		
	INPUTS	OUTPUT	
OE	LE	D	Q
L	Н	Н	L
L	Н	L	н
L	L	Х	$\overline{Q}_0$
Н	Х	Х	Z

FUNCTION TABLE (each latch)

### SN74ALS533A, SN74AS533A OCTAL D-TYPE TRANSPARENT LATCHES WITH 3-STATE OUTPUTS SDAS270 - DECEMBER 1994

### logic symbol<sup>†</sup>



<sup>&</sup>lt;sup>†</sup> This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

### logic diagram (positive logic)



#### absolute maximum ratings over operating free-air temperature range (unless otherwise noted)<sup>‡</sup>

Supply voltage, V <sub>CC</sub>	
Voltage applied to a disabled 3-state output	5.5 V
Operating free-air temperature range, T <sub>A</sub> : SN74ALS533A	0°C to 70°C
Storage temperature range	-65°C to 150°C

‡ Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.



# SN74ALS533A, SN74AS533A **OCTAL D-TYPE TRANSPARENT LATCHES** WITH 3-STATE OUTPUTS SDAS270 – DECEMBER 1994

### recommended operating conditions

		SN7	4ALS53	3A	UNIT
		MIN	NOM	MAX	UNIT
V <sub>CC</sub>	Supply voltage	4.5	5	5.5	V
VIH	High-level input voltage	2			V
VIL	Low-level input voltage			0.8	V
IOH	High-level output current			-2.6	mA
IOL	Low-level output current			24	mA
tw	Pulse duration, LE high	15			ns
t <sub>su</sub>	Setup time, data before LE $\downarrow$	15			ns
t <sub>h</sub>	Hold time, data after LE $\downarrow$	7			ns
TA	Operating free-air temperature	0		70	°C

#### electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

DADAMETED	TEST CONDI	SN7	LINIT			
FARAMETER	PARAMETER TEST CONDITIONS					
VIK	V <sub>CC</sub> = 4.5 V,	I <sub>I</sub> = –18 mA			-1.5	V
Vou	$V_{CC} = 4.5 V$ to 5.5 V,	$I_{OH} = -0.4 \text{ mA}$	V <sub>CC</sub> -2			V
VOH	V <sub>CC</sub> = 4.5 V,	$I_{OH} = -2.6 \text{ mA}$	2.4	3.2		v
Ve		I <sub>OL</sub> = 12 mA		0.25	0.4	V
VOL	VCC = 4.5 V	I <sub>OL</sub> = 24 mA		0.35	0.5	v
IOZH	V <sub>CC</sub> = 5.5 V,	V <sub>O</sub> = 2.7 V			20	μΑ
lozl	V <sub>CC</sub> = 5.5 V,	$V_{O} = 0.4 V$			-20	μΑ
lı	V <sub>CC</sub> = 5.5 V,	$V_{I} = 7 V$			0.1	mA
Ιн	V <sub>CC</sub> = 5.5 V,	V <sub>I</sub> = 2.7 V			20	μΑ
Ι <sub>Ι</sub>	V <sub>CC</sub> = 5.5 V,	V <sub>I</sub> = 0.4 V			-0.1	mA
IO‡	V <sub>CC</sub> = 5.5 V,	V <sub>O</sub> = 2.25 V	-30		-112	mA
		Outputs high		10	17	
ICC	V <sub>CC</sub> = 5.5 V	Outputs low		17	26	mA
		Outputs disabled		18.5	28	

<sup>†</sup> All typical values are at  $V_{CC} = 5 \text{ V}$ ,  $T_A = 25^{\circ}\text{C}$ .

<sup>‡</sup> The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, IOS.



## SN74ALS533A, SN74AS533A **OCTAL D-TYPE TRANSPARENT LATCHES** WITH 3-STATE OUTPUTS

SDAS270 - DECEMBER 1994

### switching characteristics (see Figure 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	$V_{CC} = 4.5$ $C_L = 50 \text{ pF}$ $R1 = 500 \Omega$ $R2 = 500 \Omega$ $T_A = \text{MIN to}$ SN74AL	V to 5.5 V, , , o MAX <sup>†</sup> _S533A	UNIT
			MIN	MAX	
<sup>t</sup> PLH	D	-	4	19	ne
<sup>t</sup> PHL	d	Q	4	13	115
<sup>t</sup> PLH	15	1 <u>-</u>	5	23	
<sup>t</sup> PHL	LE	Any Q	4	18	
<sup>t</sup> PZH			1	17	
<sup>t</sup> PZL	OE	Any Q	4	18	ns
<sup>t</sup> PHZ			2	10	
<sup>t</sup> PLZ	UE	Any Q	2	16	115

<sup>†</sup> For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

### absolute maximum ratings over operating free-air temperature range (unless otherwise noted)<sup>‡</sup>

Supply voltage, V <sub>CC</sub>	7 V
Input voltage, V <sub>1</sub>	
Voltage applied to a disabled 3-state output	5.5 V
Operating free-air temperature range, T <sub>A</sub> : SN74AS533A	0°C to 70°C
Storage temperature range	-65°C to 150°C

<sup>‡</sup> Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

#### recommended operating conditions

		SN	74AS533	3A	LINUT
		MIN	NOM	MAX	UNIT
VCC	Supply voltage	4.5	5	5.5	V
VIH	High-level input voltage	2			V
VIL	Low-level input voltage			0.8	V
IOH	High-level output current			-15	mA
I <sub>OL</sub>	Low-level output current			48	mA
tw	Pulse duration, LE high	2			ns
t <sub>su</sub>	Setup time, data before LE $\downarrow$	2			ns
th	Hold time, data after LE $\downarrow$	3			ns
TA	Operating free-air temperature	0		70	°C



## SN74ALS533A, SN74AS533A **OCTAL D-TYPE TRANSPARENT LATCHES** WITH 3-STATE OUTPUTS

SDAS270 - DECEMBER 1994

#### electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

DADAMETED	TEST CONDI	SN	SN74AS533A				
PARAMETER	TEST CONDI	MIN	TYP†	MAX	UNIT		
VIK	V <sub>CC</sub> = 4.5 V,	I <sub>I</sub> = –18 mA			-1.5	V	
Vou	V <sub>CC</sub> = 4.5 V to 5.5 V,	$I_{OH} = -2 \text{ mA}$	V <sub>CC</sub> -2			V	
VОН	V <sub>CC</sub> = 4.5 V,	I <sub>OH</sub> = -15 mA	2.4	3.3		v	
V <sub>OL</sub>	V <sub>CC</sub> = 4.5 V,	I <sub>OL</sub> = 48 mA		0.34	0.5	V	
I <sub>OZH</sub>	V <sub>CC</sub> = 5.5 V,	$V_{O} = 2.7 V$			50	μΑ	
IOZL	V <sub>CC</sub> = 5.5 V,	$V_{O} = 0.4 V$			-50	μA	
lı	V <sub>CC</sub> = 5.5 V,	$V_{I} = 7 V$			0.1	mA	
lih	V <sub>CC</sub> = 5.5 V,	V <sub>I</sub> = 2.7 V			20	μΑ	
۱ <sub>۱L</sub>	V <sub>CC</sub> = 5.5 V,	V <sub>I</sub> = 0.4 V		-0.02	-0.5	mA	
10 <sup>‡</sup>	V <sub>CC</sub> = 5.5 V,	V <sub>O</sub> = 2.25 V	-30		-112	mA	
		Outputs high		62	100		
lcc	V <sub>CC</sub> = 5.5 V	Outputs low		64	100	mA	
		Outputs disabled		71	110		

<sup>†</sup> All typical values are at  $V_{CC} = 5 \text{ V}$ ,  $T_A = 25^{\circ}\text{C}$ .

<sup>‡</sup> The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, IOS.

#### switching characteristics (see Figure 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	$V_{CC} = 4.5$ $C_L = 50 \text{ pF}$ $R1 = 500 \Omega$ $R2 = 500 \Omega$ $T_A = \text{MIN to}$ MIN	V to 5.5 V, , o MAX§ S533A MAX	UNIT
tPLH			4	7.5	
<sup>t</sup> PHL	D D	Q	4	7	ns
<sup>t</sup> PLH	15	A	5	9	
<sup>t</sup> PHL	LE	Any Q	4	8	ns
<sup>t</sup> PZH		A	2	6.5	
t <sub>PZL</sub>	OE	Any Q	4	9.5	115
<sup>t</sup> PHZ		Any O	2	6.5	
tPLZ	UE UE	Any Q	3	7	115

§ For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.



## SN74ALS533A, SN74AS533A OCTAL D-TYPE TRANSPARENT LATCHES WITH 3-STATE OUTPUTS

SDAS270 - DECEMBER 1994



PARAMETER MEASUREMENT INFORMATION

NOTES: A. CL includes probe and jig capacitance.

- B. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control. C. When measuring propagation delay items of 3-state outputs, switch S1 is open.
- D. All input pulses have the following characteristics:  $PRR \le 1$  MHz,  $t_f = t_f = 2$  ns, duty cycle = 50%.
- E. The outputs are measured one at a time with one transition per measurement.

#### Figure 1. Load Circuits and Voltage Waveforms





### **PACKAGING INFORMATION**

Orderable part number	Status	Material type	Package   Pins	Package qty   Carrier	RoHS	Lead finish/	MSL rating/	Op temp (°C)	Part marking
	(1)	(2)			(3)	Ball material	Peak reflow		(6)
						(4)	(5)		
SN74ALS533ADW	Active	Production	SOIC (DW)   20	25   TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	0 to 70	ALS533A
SN74ALS533ADW.A	Active	Production	SOIC (DW)   20	25   TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	0 to 70	ALS533A
SN74ALS533AN	Active	Production	PDIP (N)   20	20   TUBE	Yes	NIPDAU	N/A for Pkg Type	0 to 70	SN74ALS533AN
SN74ALS533AN.A	Active	Production	PDIP (N)   20	20   TUBE	Yes	NIPDAU	N/A for Pkg Type	0 to 70	SN74ALS533AN
SN74ALS533ANSR	Active	Production	SOP (NS)   20	2000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	0 to 70	ALS533A
SN74ALS533ANSR.A	Active	Production	SOP (NS)   20	2000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	0 to 70	ALS533A

<sup>(1)</sup> **Status:** For more details on status, see our product life cycle.

<sup>(2)</sup> Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

<sup>(4)</sup> Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

<sup>(5)</sup> MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

<sup>(6)</sup> Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.



www.ti.com

## PACKAGE OPTION ADDENDUM

29-May-2025



www.ti.com

### TAPE AND REEL INFORMATION





#### QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



1	*All dimensions are nominal												
	Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrai
	SN74ALS533ANSR	SOP	NS	20	2000	330.0	24.4	8.4	13.0	2.5	12.0	24.0	Q1



www.ti.com

# PACKAGE MATERIALS INFORMATION

24-Jul-2025



\*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
SN74ALS533ANSR	SOP	NS	20	2000	356.0	356.0	45.0

### TEXAS INSTRUMENTS

www.ti.com

24-Jul-2025

### TUBE



### - B - Alignment groove width

#### \*All dimensions are nominal

Device	Package Name	Package Type	Pins	SPQ	L (mm)	W (mm)	Τ (μm)	B (mm)
SN74ALS533ADW	DW	SOIC	20	25	507	12.83	5080	6.6
SN74ALS533ADW.A	DW	SOIC	20	25	507	12.83	5080	6.6
SN74ALS533AN	N	PDIP	20	20	506	13.97	11230	4.32
SN74ALS533AN.A	N	PDIP	20	20	506	13.97	11230	4.32

### MECHANICAL DATA

### PLASTIC SMALL-OUTLINE PACKAGE

#### 0,51 0,35 ⊕0,25⊛ 1,27 8 14 0,15 NOM 5,60 8,20 5,00 7,40 $\bigcirc$ Gage Plane ₽ 0,25 7 1 1,05 0,55 0-10 Δ 0,15 0,05 Seating Plane — 2,00 MAX 0,10PINS \*\* 14 16 20 24 DIM 10,50 10,50 12,90 15,30 A MAX A MIN 9,90 9,90 12,30 14,70 4040062/C 03/03

NOTES: A. All linear dimensions are in millimeters.

NS (R-PDSO-G\*\*)

**14-PINS SHOWN** 

- B. This drawing is subject to change without notice.
- C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15.



# N (R-PDIP-T\*\*)

PLASTIC DUAL-IN-LINE PACKAGE

16 PINS SHOWN



NOTES:

- A. All linear dimensions are in inches (millimeters).B. This drawing is subject to change without notice.
- Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).
- $\triangle$  The 20 pin end lead shoulder width is a vendor option, either half or full width.



# **DW0020A**



# **PACKAGE OUTLINE**

### SOIC - 2.65 mm max height

SOIC



NOTES:

- 1. All linear dimensions are in millimeters. Dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M. 2. This drawing is subject to change without notice. 3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not
- exceed 0.15 mm per side.
- 4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.43 mm per side.
- 5. Reference JEDEC registration MS-013.



# DW0020A

# **EXAMPLE BOARD LAYOUT**

## SOIC - 2.65 mm max height

SOIC



NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.



# DW0020A

# **EXAMPLE STENCIL DESIGN**

## SOIC - 2.65 mm max height

SOIC



NOTES: (continued)

- 8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
- 9. Board assembly site may have different recommendations for stencil design.



### IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265 Copyright © 2025, Texas Instruments Incorporated