

THVD14x9x 3V~5.5V、RS-485 トランシーバ、4kV サージ保護機能内蔵、1.8V VIO 対応

1 特長

- TIA/EIA-485A 規格の要件に適合またはそれを上回る性能
- 3V~5.5V の電源電圧
- 1.65V~V_{CC} 電源電圧レベルの V_{IO} をサポート (THVD1439V、THVD1449V)
- バス I/O 保護
 - ±4kV IEC 61000-4-5 1.2/50μs サージ
 - ±15kV IEC 61000-4-2 接触放電
 - ±15kV IEC 61000-4-2 エアギャップ放電
 - ±4kV IEC 61000-4-4 電気的高速過渡現象
 - ±15kV HBM ESD
 - ±15V DC バス・フォルト
- 2 つの速度グレードで供給
 - THVD1439、THVD1439V: 250kbps
 - THVD1449、THVD1449V: 12Mbps
- 広い周囲温度範囲:
-40°C~125°C
- 広い動作同相範囲:
±12V
- 大きなレシーバ・ヒステリシスによるノイズ除去
- 低い消費電力
 - スタンバイ時の消費電流: 3μA 未満
 - 動作時電流: 5mA 未満
- グリッチなしの電源オン / オフによる活線挿抜機能
- 開放、短絡、アイドル・バスのフェイルセーフ
- 1/8 単位負荷 (最大 256 のバス・ノード)
- 業界標準の 8 ピン SOIC によるドロップイン互換

2 アプリケーション

- ワイヤレス・インフラ
- ファクトリ・オートメーション
- モーター・ドライブ
- ビル・オートメーション
- HVAC
- グリッド・インフラストラクチャ

3 概要

THVD14x9(V) デバイスは、サージ保護機能を備えた半二重 RS-485 トランシーバです。標準の 8 ピン SOIC (D) パッケージに過渡電圧抑制 (TVS) ダイオードを内蔵することで、サージ保護機能を実現しています。この機能は、データ・ケーブルに結合するノイズ過渡に対する耐性を高めることで信頼性を向上させ、外付け保護部品を不要にします。


THVD1439 と THVD1449 は 3.3V または 5V の単一電源で動作します。

THVD1439V および THVD1449V デバイスは、1.65V から I/O を動作させるための追加 V_{IO} 電源をサポートしています。このファミリのデバイスは同相電圧範囲が広いと、長いケーブルを使用するマルチポイント・アプリケーションに適しています。


製品情報

部品番号	パッケージ ⁽¹⁾	本体サイズ (公称)
THVD1439 THVD1439V THVD1449 THVD1449V	SOIC (8)	4.90mm × 3.91mm

(1) 利用可能なすべてのデバイスについては、このデータシートの末尾にある注文情報を参照してください。



THVD14x9 のブロック図



THVD14x9V のブロック図



Table of Contents

1 特長	1	8 Detailed Description	14
2 アプリケーション	1	8.1 Overview.....	14
3 概要	1	8.2 Functional Block Diagrams.....	14
4 Revision History	2	8.3 Feature Description.....	14
5 Pin Configuration and Functions	4	8.4 Device Functional Modes.....	18
6 Specifications	5	9 Application and Implementation	19
6.1 Absolute Maximum Ratings	5	9.1 Application Information	19
6.2 ESD Ratings	5	9.2 Typical Application.....	19
6.3 ESD Ratings, IEC	5	10 Power Supply Recommendations	22
6.4 Recommended Operating Conditions	6	11 Layout	23
6.5 Thermal Information	6	11.1 Layout Guidelines.....	23
6.6 Power Dissipation	6	11.2 Layout Example.....	23
6.7 Electrical Characteristics	7	12 Device and Documentation Support	25
6.8 Switching Characteristics (THVD1439, THVD1439V)	9	12.1 Device Support.....	25
6.9 Switching Characteristics (THVD1449, THVD1449V)	9	12.2 Receiving Notification of Documentation Updates..	25
6.10 代表的特性.....	10	12.3 サポート・リソース.....	25
7 Parameter Measurement Information	12	12.4 Trademarks.....	25
		12.5 Electrostatic Discharge Caution.....	25
		12.6 Glossary.....	25

4 Revision History

Changes from Revision A (June 2021) to Revision B (September 2021)	Page
• ドキュメントのステータスを「事前情報」から「量産データ」に変更.....	1

Device Comparison Table

PART NUMBER	DUPLEX	ENABLES	V _{IO}	SIGNALING RATE	NODES
THVD1439	Half	Separate DE and RE	No	up to 250 kbps	256
THVD1439V		Combined DE / RE	Yes		
THVD1449		Separate DE and RE	No	up to 12 Mbps	
THVD1449V		Combined DE / RE	Yes		

5 Pin Configuration and Functions




图 5-1. THVD1439, THVD1449, 8-Pin (SOIC), Top View




图 5-2. THVD1439V, THVD1449V, 8-Pin (SOIC), Top View

PIN			I/O	DESCRIPTION
NAME	THVD1439, THVD1449	THVD1439 V, THVD1449V		
V _{IO}	-	1	P	1.8-V to 5-V supply for R, D, and RE/DE
R	1	2	O	Receiver data output
RE	2	-	I	Receiver enable, active low (2 MΩ internal pull-up)
DE	3	-	I	Driver enable, active high
DE/ RE	-	3	I	Driver enable (Active high), Receiver enable (Active Low). (2 MΩ internal pull-down)
D	4	4	I	Driver data input
GND	5	5	-	Device ground
A	6	6	I/O	Bus I/O port, A (complementary to B)
B	7	7	I/O	Bus I/O port, B (complementary to A)
V _{CC}	8	8	P	3.3-V to 5-V supply for the device

6 Specifications

6.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)⁽¹⁾

		MIN	MAX	UNIT
Supply voltage	V_{CC}	-0.5	7	V
Logic supply voltage	V_{IO}	-0.5	$V_{CC}+0.2$	V
Bus voltage	Range at any bus pin (A or B)	-15	15	V
Input voltage	Range at any logic pin (R, D, DE, or RE) THVD1439, THVD1449	-0.3	5.7	V
Input voltage	Range at any logic pin (R, D, DE, or RE) THVD1439V, THVD1449V	-0.3	$V_{IO}+0.2$	V
Receiver output current	I_O	-24	24	mA
Storage temperature	T_{stg}	-65	150	°C

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

6.2 ESD Ratings

			VALUE	UNIT
$V_{(ESD)}$	Electrostatic discharge	Human-body model (HBM), per ANSI/ESDA/JEDEC JS-001 ⁽¹⁾	±15,000	V
		All pins except bus terminals and GND	±4,000	
		Charged-device model (CDM), per JEDEC specification JESD22-C102 ⁽²⁾	±1,500	

- (1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

6.3 ESD Ratings, IEC

			VALUE	UNIT
$V_{(ESD)}$	Electrostatic discharge	Contact Discharge, per IEC 61000-4-2	±15,000	V
		Air-Gap Discharge, per IEC 61000-4-2	±15,000	
$V_{(EFT)}$	Electrical fast transient	Per IEC 61000-4-4	±4,000	V
$V_{(surge)}$	Surge	Per IEC 61000-4-5, 1.2/50 μ s	±4,000	V

6.4 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)

			MIN	NOM	MAX	UNIT
V _{CC}	Supply voltage		3		5.5	V
V _{IO}	IO Supply Voltage (V Variant)		1.65		V _{CC}	V
V _I	Input voltage on logic pins (R, D, DE, or RE)	THVD1439, THVD1449	0		5.5	V
V _I		THVD1439V, THVD1449V	0		V _{IO}	V
V _I	Input voltage at bus pins (A or B) ⁽¹⁾		-12		12	V
V _{IH}	High-level input voltage (R, D, DE, or RE)	THVD1439V, THVD1449V	0.67 * V _{IO}		V _{IO}	V
V _{IL}	Low-level input voltage (R, D, DE, or RE)		0	0.33 * V _{IO}		V
V _{IH}	High-level input voltage (R, D, DE, or RE)	THVD1439, THVD1449	2		5.5	V
V _{IL}	Low-level input voltage (R, D, DE, or RE)		0		0.8	V
V _{ID}	Differential input voltage		-12		12	V
I _O	Output current, driver		-60		60	mA
I _{OR}	Output current, receiver		-8		8	mA
R _L	Differential load resistance		54			Ω
1/t _{UI}	Signaling rate	THVD1439, THVD1439V			250	kbps
		THVD1449, THVD1449V			12	Mbps
T _A	Operating ambient temperature		-40		125	°C

(1) The algebraic convention, in which the least positive (most negative) limit is designated as minimum is used in this data sheet.

6.5 Thermal Information

THERMAL METRIC ⁽¹⁾		THVD1439 THVD1439V THVD1449 THVD1449V	UNIT
		D (SOIC)	
		8 PINS	
R _{θJA}	Junction-to-ambient thermal resistance	120.7	°C/W
R _{θJC(top)}	Junction-to-case (top) thermal resistance	50.3	°C/W
R _{θJB}	Junction-to-board thermal resistance	62.8	°C/W
Ψ _{JT}	Junction-to-top characterization parameter	7.5	°C/W
Ψ _{JB}	Junction-to-board characterization parameter	62.2	°C/W
R _{θJC(bot)}	Junction-to-case (bottom) thermal resistance	N/A	°C/W

(1) For more information about traditional and new thermal metrics, see the [Semiconductor and IC Package Thermal Metrics](#) application report.

6.6 Power Dissipation

over operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS			VALUE	UNIT
PD	Driver and receiver enabled, V _{CC} = 5.5 V, T _A = 125 °C, 50% duty cycle square wave at signaling rate	Unterminated R _L = 300 Ω, C _L = 50 pF (driver)	THVD1439	250 kbps	160	mW
			THVD1449	12 Mbps	290	
		RS-422 load R _L = 100 Ω, C _L = 50 pF (driver)	THVD1439	250 kbps	190	mW
			THVD1449	12 Mbps	290	
		RS-485 load R _L = 54 Ω, C _L = 50 pF (driver)	THVD1439	250 kbps	250	mW
			THVD1449	12 Mbps	320	

6.7 Electrical Characteristics

over operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
Driver							
V _{OD}	Driver differential output voltage magnitude	R _L = 60 Ω, -12 V ≤ V _{test} ≤ 12 V (See Figure 7-1)		1.5	2		V
		R _L = 60 Ω, -12 V ≤ V _{test} ≤ 12 V, 4.5 V ≤ V _{CC} ≤ 5.5 V (See Figure 7-1)		2.1			V
		R _L = 100 Ω (See Figure 7-2)		2	2.5		V
		R _L = 54 Ω (See Figure 7-2)		1.5	2		V
Δ V _{OD}	Change in differential output voltage	R _L = 54 Ω (See Figure 7-2)		−50		50	mV
V _{OC}	Common-mode output voltage	R _L = 54 Ω (See Figure 7-2)		1	V _{CC} / 2	3	V
ΔV _{OC(SS)}	Change in steady-state common-mode output voltage	R _L = 54 Ω (See Figure 7-2)		−50		50	mV
I _{OS}	Short-circuit output current	DE = V _{CC} , -12 V ≤ V _O ≤ 12 V		−250		250	mA
Receiver							
I _I	Bus input current	DE = 0 V, V _{CC} = 0 V or 5.5 V	V _I = 12 V		75	135	μA
			V _I = -7 V	−100	−40		
			V _I = -12 V	−135	−75		
V _{TH+}	Positive-going input threshold voltage ⁽¹⁾	Over common-mode range of ±12 V		40	125	200	mV
V _{TH-}	Negative-going input threshold voltage ⁽¹⁾			−200	−125	−40	mV
V _{HYS}	Input hysteresis				250		mV
V _{TH_FSH}	Input fail-safe threshold			−40		40	mV
V _{OH}	Output high voltage	THVD1439V, THVD1449V	I _{OH} = -4 mA; V _{IO} = 1.65 V - 3 V	V _{IO} - 0.4	V _{IO} - 0.2	V	
			I _{OH} = -8 mA; V _{IO} = 3 V - 5.5 V				
		THVD1439, THVD1449	I _{OH} = -8 mA	V _{CC} - 0.4	V _{CC} - 0.2		
V _{OL}	Output low voltage	THVD1439V, THVD1449V	I _{OL} = 8 mA; V _{IO} = 3 V - 5.5 V	0.2	0.4	V	
			I _{OL} = 4 mA; V _{IO} = 1.65 V - 3 V				
		THVD1439, THVD1449	I _{OL} = 8 mA				
I _{OZ}	Output high-impedance current	V _O = 0 V or V _{CC} , RE = V _{CC}		−1		1	μA
Logic							
I _{IN}	Input current (D, DE, RE)	THVD1439V, THVD1449V	3 V ≤ V _{CC} ≤ 5.5 V, 1.65 ≤ V _{IO} ≤ V _{CC} V, 0 V ≤ V _{IN} ≤ V _{IO}	−5		5	μA
		THVD1439, THVD1449	3 V ≤ V _{CC} ≤ 5.5 V, 0 V ≤ V _{IN} ≤ V _{CC}	−5		5	μA
Thermal Protection							
T _{SHDN}	Thermal shutdown threshold	Temperature rising		150	170		°C
T _{HYS}	Thermal shutdown hysteresis				10		°C

6.7 Electrical Characteristics (continued)

over operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS			MIN	TYP	MAX	UNIT
Supply								
I _{CC}	Supply current (quiescent)	V _{CC} =3.6 V	Driver and receiver enabled (THVD1439, THVD1449)	RE = 0 V, DE = V _{CC} , No load		3	4	mA
			Driver enabled, receiver disabled	RE = V _{CC} , DE = V _{CC} , No load		2	3	mA
			Driver disabled, receiver enabled	RE = 0 V, DE = 0 V, No load		1.7	2.2	mA
			Driver and receiver disabled (THVD1439, THVD1449)	RE = V _{CC} , DE = 0 V, D = open, No load		0.1	1.5	μA
	Supply current (quiescent)	V _{CC} =5.5 V	Driver and receiver enabled (THVD1439, THVD1449)	RE = 0 V, DE = V _{CC} , No load		3.5	5	mA
			Driver enabled, receiver disabled	RE = V _{CC} , DE = V _{CC} , No load		2.5	3.8	mA
			Driver disabled, receiver enabled	RE = 0 V, DE = 0 V, No load		1.8	2.4	mA
			Driver and receiver disabled (THVD1439, THVD1449)	RE = V _{CC} , DE = 0 V, D = open, No load		0.2	3	μA
I _{IO}	VIO supply current (quiescent)	THVD1439V, THVD1449V	Driver Enabled	DE/RE=V _{IO} , D=open, No load			5	μA
			Receiver enabled	DE/RE= 0 V, D=open, No load			5	μA

(1) Under any specific conditions, V_{TH+} is assured to be at least V_{HYS} higher than V_{TH-} .

6.8 Switching Characteristics (THVD1439, THVD1439V)

250-kbps devices (THVD1439, 39V), over recommended operating conditions. All typical values are at 25 °C.

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
Driver							
t _r , t _f	Differential output rise/fall time	R _L = 54 Ω, C _L = 50 pF	See 7-3	300	570	1200	ns
t _{PHL} , t _{PLH}	Propagation delay				450	650	ns
t _{SK(P)}	Pulse skew, t _{PHL} – t _{PLH}					50	ns
t _{PHZ} , t _{PLZ}	Disable time		See 7-4 and 7-5		25	125	ns
t _{PZH} , t _{PZL}	Enable time	RE = 0 V			240	600	ns
		RE = V _{CC}			2	4	μs
t _{SHDN}	Pulse width (logic low) on DE pin to initiate device shutdown	RE = V _{CC}			300		ns
Receiver							
t _r , t _f	Differential output rise/fall time	C _L = 15 pF	See 7-6		9	25	ns
t _{PHL} , t _{PLH}	Propagation delay				70	110	ns
t _{SK(P)}	Pulse skew, t _{PHL} – t _{PLH}					7	ns
t _{PHZ} , t _{PLZ}	Disable time				22	60	ns
t _{PZH(1)} , t _{PZL(1)} , t _{PZH(2)} , t _{PZL(2)}	Enable time	DE = V _{CC}	See 7-7		120	185	ns
			DE = 0 V	See 7-8		4	10
t _{D(OFS)}	Delay to enter fail-safe operation	C _L = 15 pF	See 7-9	14	20	36	μs
t _{D(FSO)}	Delay to exit fail-safe operation				25	40	66
t _{SHDN}	RE pulse width to initiate device shutdown	DE = 0 V			300		ns

6.9 Switching Characteristics (THVD1449, THVD1449V)

12-Mbps devices (THVD1449, 49V), over recommended operating conditions. All typical values are at 25 °C.

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
Driver							
t _r , t _f	Differential output rise/fall time	R _L = 54 Ω, C _L = 50 pF	See 7-3	2	12	25	ns
t _{PHL} , t _{PLH}	Propagation delay			7	10	25	ns
t _{SK(P)}	Pulse skew, t _{PHL} – t _{PLH}					3.5	ns
t _{PHZ} , t _{PLZ}	Disable time		See 7-4 and 7-5		25	75	ns
t _{PZH} , t _{PZL}	Enable time	RE = 0 V			18	65	ns
		RE = V _{CC}			2	4	μs
t _{SHDN}	Pulse width (logic low) on DE pin to initiate device shutdown	RE = V _{CC}			300		ns
Receiver							
t _r , t _f	Differential output rise/fall time	C _L = 15 pF	See 7-6		3	10	ns
t _{PHL} , t _{PLH}	Propagation delay			30	60	110	ns
t _{SK(P)}	Pulse skew, t _{PHL} – t _{PLH}					4	ns
t _{PHZ} , t _{PLZ}	Disable time				10	30	ns
t _{PZH(1)} , t _{PZL(1)} , t _{PZH(2)} , t _{PZL(2)}	Enable time	DE = V _{CC}	See 7-7		90	130	ns
			DE = 0 V	See 7-8		4	10
t _{D(OFS)}	Delay to enter fail-safe operation	C _L = 15 pF	See 7-9	14	20	36	μs
t _{D(FSO)}	Delay to exit fail-safe operation			25	35	55	ns
t _{SHDN}	Pulse width (logic high) on RE pin to initiate device shutdown	DE = 0 V			300		ns

6.10 代表的特性




図 6-1. ドライバ出力電圧とドライバ出力電流との関係




図 6-2. ドライバ差動出力電圧とドライバ出力電流との関係




図 6-3. ドライバ出力電流と電源電圧との関係




図 6-4. THVD1439、THVD1439V ドライバ立ち上がり / 立ち下がり時間と温度との関係




図 6-5. THVD1439、THVD1439V ドライバ伝搬遅延と温度との関係




図 6-6. THVD1439、THVD1439V 消費電流と信号速度との関係




図 6-7. THVD1449、THVD1449V ドライバ伝搬遅延と温度との関係





図 6-8. THVD1449、THVD1449V ドライバ立ち上がり / 立ち下がり時間と温度との関係




$T_A = 25^\circ\text{C}$



$R_L = 54\Omega$

図 6-9. THVD1449、THVD1449V 消費電流と信号速度との関係



7 Parameter Measurement Information





7-1. Measurement of Driver Differential Output Voltage With Common-Mode Load





7-2. Measurement of Driver Differential and Common-Mode Output With RS-485 Load





7-3. Measurement of Driver Differential Output Rise and Fall Times and Propagation Delays





7-4. Measurement of Driver Enable and Disable Times With Active High Output and Pull-Down Load





7-5. Measurement of Driver Enable and Disable Times With Active Low Output and Pull-up Load





7-6. Measurement of Receiver Output Rise and Fall Times and Propagation Delays



7-7. Measurement of Receiver Enable/Disable Times With Driver Enabled



7-8. Measurement of Receiver Enable Times With Driver Disabled



Copyright © 2017, Texas Instruments Incorporated

7-9. Fail-Safe Delay Measurements


8 Detailed Description

8.1 Overview


THVD14x9(V) devices are surge-protected, half duplex RS-485 transceivers available in two speed grades suitable for data transmission up to 250 kbps and 12 Mbps respectively. Surge protection is achieved by integrating transient voltage suppressor (TVS) diodes in the standard 8-pin SOIC (D) package.

THVD1439 and THVD1449 devices have active-high driver enables and active-low receiver enables. A standby current of less than 1.5 μ A ($V_{CC} = 3.6$ V) can be achieved by disabling both driver and receiver. THVD1439V and THVD1449V have a single enable/disable pin that either enables the driver or the receiver at a time.

8.2 Functional Block Diagrams



8-1. THVD1439 and THVD1449 Block Diagram



8-2. THVD1439V and THVD1449V Block Diagram

8.3 Feature Description

8.3.1 Electrostatic Discharge (ESD) Protection

The bus pins of the THVD14x9(V) transceiver family include on-chip ESD protection against ± 15 -kV HBM and ± 15 -kV IEC 61000-4-2 contact discharge. The International Electrotechnical Commission (IEC) ESD test is far more severe than the HBM ESD test. The 50% higher charge capacitance, $C_{(S)}$, and 78% lower discharge resistance, $R_{(D)}$, of the IEC model produce significantly higher discharge currents than the HBM model. As stated in the IEC 61000-4-2 standard, contact discharge is the preferred transient protection test method.




Figure 8-3. HBM and IEC ESD Models and Currents in Comparison (HBM Values in Parenthesis)

The on-chip implementation of IEC ESD protection significantly increases the robustness of equipment. Common discharge events occur because of human contact with connectors and cables.

8.3.2 Electrical Fast Transient (EFT) Protection

Inductive loads such as relays, switch contactors, or heavy-duty motors can create high-frequency bursts during transition. The IEC 61000-4-4 test is intended to simulate the transients created by such switching of inductive loads on AC power lines. Figure 8-4 shows the voltage waveforms in to 50-Ω termination as defined by the IEC standard.




Figure 8-4. EFT Voltage Waveforms

Internal ESD protection circuits of the THVD14x9(V) protect the transceivers against ± 4 -kV EFT. With careful system design, one could achieve EFT Criterion A (no data loss when transient noise is present).

8.3.3 Surge Protection

Surge transients often result from lightning strikes (direct strike or an indirect strike which induce voltages and currents), or the switching of power systems, including load changes and short circuit switching. These transients are often encountered in industrial environments, such as factory automation and power-grid systems.

Figure 8-5 compares the pulse-power of the EFT and surge transients with the power caused by an IEC ESD transient. The diagram on the left shows the relative pulse-power for a 0.5-kV surge transient and 4-kV EFT transient, both of which dwarf the 10-kV ESD transient visible in the lower-left corner. 500-V surge transients are representative of events that may occur in factory environments in industrial and process automation.

The diagram on the right shows the pulse-power of a 6-kV surge transient, relative to the same 0.5-kV surge transient. 6-kV surge transients are most likely to occur in power generation and power-grid systems.




Figure 8-5. Power Comparison of ESD, EFT, and Surge Transients

Figure 8-6 shows the test setup used to validate THVD14x9 surge performance according to the IEC 61000-4-5 1.2/50-μs surge pulse.






Figure 8-6. THVD14x9(V) Surge Test Setup

THVD14x9(V) product family is robust to ± 4 -kV surge transients without the need for any external components. The transient current and voltage waveforms resulting from a +4-kV surge test as described in [8-6](#) are shown in [8-7](#). The bus pin voltage is clamped by the integrated surge protection diodes such that the internal circuitry is not damaged during the surge event. The clamping voltage at the bus pins for versus the total current from the surge generator is shown in [8-8](#).



8-7. Transient current and voltage waveforms from +4-kV Surge Test. The current waveform is the total current output from the generator and the voltage waveform is the voltage at A or B pin of the transceiver.



8-8. Clamping voltage at bus pins vs total surge current from the surge generator

8.3.4 Enhanced Receiver Noise Immunity

The differential receivers of THVD14x9(V) family feature fully symmetric thresholds to maintain duty cycle of the signal even with small input amplitudes. In addition, 250 mV (typical) hysteresis guarantees excellent noise immunity.

8.3.5 Failsafe Receiver

The differential receivers of the THVD14x9(V) family are failsafe to invalid bus states caused by the following:

- Open bus conditions, such as a disconnected connector
- Shorted bus conditions, such as cable damage shorting the twisted-pair together
- Idle bus conditions that occur when no driver on the bus is actively driving

In any of these cases, the receiver will output a fail-safe logic high state if the input amplitude stays for longer than $t_{D(OFs)}$ at less than $|V_{TH_FSH}|$.

8.4 Device Functional Modes

When the driver enable pin, DE, is logic high, the differential outputs A and B follow the logic states at data input D. A logic high at D causes A to turn high and B to turn low. In this case the differential output voltage defined as $V_{OD} = V_A - V_B$ is positive. When D is low, the output states reverse: B turns high, A becomes low, and V_{OD} is negative.

When DE is low, both outputs turn high-impedance. In this condition the logic state at D is irrelevant. The DE pin has an internal pull-down resistor to ground, thus when left open the driver is disabled (high-impedance) by default. The D pin has an internal pull-up resistor to V_{CC} , thus, when left open while the driver is enabled, output A turns high and B turns low.

表 8-1. Driver Function Table

INPUT	ENABLE	OUTPUTS		FUNCTION
D	DE	A	B	
H	H	H	L	Actively drive bus high
L	H	L	H	Actively drive bus low
X	L	Z	Z	Driver disabled
X	OPEN	Z	Z	Driver disabled by default
OPEN	H	H	L	Actively drive bus high by default

When the receiver enable pin, $\overline{RE}$, is logic low, the receiver is enabled. When the differential input voltage defined as $V_{ID} = V_A - V_B$ is higher than the positive input threshold, V_{TH+} , the receiver output, R, turns high. When V_{ID} is lower than the negative input threshold, V_{TH-} , the receiver output, R, turns low. If V_{ID} is between V_{TH+} and V_{TH-} , the output is indeterminate.

When $\overline{RE}$ is logic high or left open, the receiver output is high-impedance and the magnitude and polarity of V_{ID} are irrelevant. Internal biasing of the receiver inputs causes the output to go failsafe-high when the transceiver is disconnected from the bus (open-circuit), the bus lines are shorted to one another (short-circuit), or the bus is not actively driven (idle bus).

表 8-2. Receiver Function Table

DIFFERENTIAL INPUT	ENABLE	OUTPUT	FUNCTION
$V_{ID} = V_A - V_B$	$\overline{RE}$	R	
$V_{TH+} < V_{ID}$	L	H	Receive valid bus high
$V_{TH-} < V_{ID} < V_{TH+}$	L	Indeterminate	Indeterminate bus state
$V_{ID} < V_{TH-}$	L	L	Receive valid bus low
X	H	Z	Receiver disabled
X	OPEN	Z	Receiver disabled by default
Open-circuit bus	L	H	Fail-safe high output
Short-circuit bus	L	H	Fail-safe high output
Idle (terminated) bus	L	H	Fail-safe high output

9 Application and Implementation

Note

以下のアプリケーション情報は、TI の製品仕様に含まれるものではなく、TI ではその正確性または完全性を保証いたしません。個々の目的に対する製品の適合性については、お客様の責任で判断していただくことになります。お客様は自身の設計実装を検証しテストすることで、システムの機能を確認する必要があります。

9.1 Application Information

THVD14x9(V) are half-duplex RS-485 transceivers with integrated system-level surge protection. Standard 8-pin SOIC (D) package allows drop-in replacement into existing systems and eliminate system-level protection components.

9.2 Typical Application

An RS-485 bus consists of multiple transceivers connecting in parallel to a bus cable. To eliminate line reflections, each cable end is terminated with a termination resistor, R_T , with a value that matches the characteristic impedance, Z_0 , of the cable. This method, known as parallel termination, allows for higher data rates over longer cable length.





図 9-1. Typical RS-485 Network With Half-Duplex Transceivers

9.2.1 Design Requirements

RS-485 is a robust electrical standard suitable for long-distance networking that may be used in a wide range of applications with varying requirements, such as distance, data rate, and number of nodes.

9.2.1.1 Data Rate and Bus Length

There is an inverse relationship between data rate and cable length, which means the higher the data rate, the shorter the cable length; and conversely, the lower the data rate, the longer the cable length. While most RS-485 systems use data rates between 10 kbps and 100 kbps, some applications require data rates up to 250 kbps at distances of 4000 feet and longer. Longer distances are possible by allowing for small signal jitter of up to 5 or 10%.



9-2. Cable Length vs Data Rate Characteristic

Even higher data rates are achievable (that is, 12 Mbps for the THVD1449(V)) in cases where the interconnect is short enough (or has suitably low attenuation at signal frequencies) to not degrade the data.

9.2.1.2 Stub Length

When connecting a node to the bus, the distance between the transceiver inputs and the cable trunk, known as the stub, should be as short as possible. Stubs present a non-terminated piece of bus line which can introduce reflections as the length of the stub increases. As a general guideline, the electrical length, or round-trip delay, of a stub should be less than one-tenth of the rise time of the driver, thus giving a maximum physical stub length as shown in 式 1.

$$L_{(\text{STUB})} \leq 0.1 \times t_r \times v \times c \quad (1)$$

where

- t_r is the 10/90 rise time of the driver
- c is the speed of light (3×10^8 m/s)
- v is the signal velocity of the cable or trace as a factor of c

9.2.1.3 Bus Loading

The RS-485 standard specifies that a compliant driver must be able to driver 32 unit loads (UL), where 1 unit load represents a load impedance of approximately 12 kΩ. Because the THVD14x9(V) devices consist of 1/8 UL transceivers, connecting up to 256 receivers to the bus is possible.

9.2.2 Detailed Design Procedure

RS-485 transceivers operate in noisy industrial environments typically require surge protection at the bus pins. [Figure 9-3](#) compares 4-kV surge protection implementation with a regular RS-485 transceiver (such as THVD14x0) against with the THVD14x9(V). The internal TVS protection of the THVD14x9(V) achieves ± 4 -kV IEC 61000-4-5 surge protection without any additional external components, reducing system level bill of materials.






Figure 9-3. Implementation of System-Level Surge Protection Using THVD14x9(V)

9.2.3 Application Curves



10 Power Supply Recommendations

To ensure reliable operation at all data rates and supply voltages, each supply should be decoupled with a 100 nF ceramic capacitor located as close to the supply pins as possible. This helps to reduce supply voltage ripple present on the outputs of switched-mode power supplies and also helps to compensate for the resistance and inductance of the PCB power planes.

11 Layout

11.1 Layout Guidelines

Additional external protection components generally are not needed when using THVD14x9(V) transceivers.

1. Use V_{CC} and ground planes to provide low-inductance. Note that high-frequency currents tend to follow the path of least impedance and not the path of least resistance. Apply 100-nF to 220-nF decoupling capacitors as close as possible to the V_{CC} pins of transceiver, UART and/or controller ICs on the board.
2. Use at least two vias for V_{CC} and ground connections of decoupling capacitors to minimize effective via inductance.
3. Use 1-k Ω to 10-k Ω pull-up and pull-down resistors for enable lines to limit noise currents in these lines during transient events.

11.2 Layout Example




FIG 11-1. THVD1439, THVD1449 Layout Example




图 11-2. THVD1439V THVD1449V Layout Example

12 Device and Documentation Support

12.1 Device Support

12.2 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on [ti.com](https://www.ti.com). Click on *Subscribe to updates* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

12.3 サポート・リソース

TI E2E™ サポート・フォーラムは、エンジニアが検証済みの回答と設計に関するヒントをエキスパートから迅速かつ直接得ることができる場所です。既存の回答を検索したり、独自の質問をしたりすることで、設計に必要な支援を迅速に得ることができます。

リンクされているコンテンツは、該当する貢献者により、現状のまま提供されるものです。これらは TI の仕様を構成するものではなく、必ずしも TI の見解を反映したものではありません。TI の[使用条件](#)を参照してください。

12.4 Trademarks

TI E2E™ is a trademark of Texas Instruments.

すべての商標は、それぞれの所有者に帰属します。

12.5 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

12.6 Glossary

[TI Glossary](#) This glossary lists and explains terms, acronyms, and definitions.

Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package Pins	Package qty Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
THVD1439DR	Active	Production	SOIC (D) 8	2500 LARGE T&R	Yes	NIPDAUAG	Level-3-260C-168 HR	-40 to 125	T1439
THVD1439DR.A	Active	Production	SOIC (D) 8	2500 LARGE T&R	Yes	NIPDAUAG	Level-3-260C-168 HR	-40 to 125	T1439
THVD1439DR.B	Active	Production	SOIC (D) 8	2500 LARGE T&R	Yes	NIPDAUAG	Level-3-260C-168 HR	-40 to 125	T1439
THVD1439VDR	Active	Production	SOIC (D) 8	2500 LARGE T&R	Yes	NIPDAUAG	Level-3-260C-168 HR	-40 to 125	1439V
THVD1439VDR.A	Active	Production	SOIC (D) 8	2500 LARGE T&R	Yes	NIPDAUAG	Level-3-260C-168 HR	-40 to 125	1439V
THVD1439VDR.B	Active	Production	SOIC (D) 8	2500 LARGE T&R	Yes	NIPDAUAG	Level-3-260C-168 HR	-40 to 125	1439V
THVD1449DR	Active	Production	SOIC (D) 8	2500 LARGE T&R	Yes	NIPDAUAG	Level-3-260C-168 HR	-40 to 125	T1449
THVD1449DR.A	Active	Production	SOIC (D) 8	2500 LARGE T&R	Yes	NIPDAUAG	Level-3-260C-168 HR	-40 to 125	T1449
THVD1449DR.B	Active	Production	SOIC (D) 8	2500 LARGE T&R	Yes	NIPDAUAG	Level-3-260C-168 HR	-40 to 125	T1449
THVD1449VDR	Active	Production	SOIC (D) 8	2500 LARGE T&R	Yes	NIPDAUAG	Level-3-260C-168 HR	-40 to 125	T1449V
THVD1449VDR.A	Active	Production	SOIC (D) 8	2500 LARGE T&R	Yes	NIPDAUAG	Level-3-260C-168 HR	-40 to 125	T1449V
THVD1449VDR.B	Active	Production	SOIC (D) 8	2500 LARGE T&R	Yes	NIPDAUAG	Level-3-260C-168 HR	-40 to 125	T1449V

⁽¹⁾ **Status:** For more details on status, see our [product life cycle](#).

⁽²⁾ **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

⁽⁴⁾ **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

⁽⁵⁾ **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

⁽⁶⁾ **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "-" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

重要なお知らせと免責事項

テキサス・インスツルメンツは、技術データと信頼性データ (データシートを含みます)、設計リソース (リファレンス デザインを含みます)、アプリケーションや設計に関する各種アドバイス、Web ツール、安全性情報、その他のリソースを、欠陥が存在する可能性のある「現状のまま」提供しており、商品性および特定目的に対する適合性の黙示保証、第三者の知的財産権の非侵害保証を含むいかなる保証も、明示的または黙示的にかかわらず拒否します。

これらのリソースは、テキサス・インスツルメンツ製品を使用する設計の経験を積んだ開発者への提供を意図したものです。(1) お客様のアプリケーションに適した テキサス・インスツルメンツ製品の選定、(2) お客様のアプリケーションの設計、検証、試験、(3) お客様のアプリケーションに該当する各種規格や、その他のあらゆる安全性、セキュリティ、規制、または他の要件への確実な適合に関する責任を、お客様のみが単独で負うものとします。

上記の各種リソースは、予告なく変更される可能性があります。これらのリソースは、リソースで説明されている テキサス・インスツルメンツ製品を使用するアプリケーションの開発の目的でのみ、テキサス・インスツルメンツはその使用をお客様に許諾します。これらのリソースに関して、他の目的で複製することや掲載することは禁止されています。テキサス・インスツルメンツや第三者の知的財産権のライセンスが付与されている訳ではありません。お客様は、これらのリソースを自身で使用した結果発生するあらゆる申し立て、損害、費用、損失、責任について、テキサス・インスツルメンツおよびその代理人を完全に補償するものとし、テキサス・インスツルメンツは一切の責任を拒否します。

テキサス・インスツルメンツの製品は、[テキサス・インスツルメンツの販売条件](#)、または [ti.com](https://www.ti.com) やかかる テキサス・インスツルメンツ製品の関連資料などのいずれかを通じて提供する適用可能な条項の下で提供されています。テキサス・インスツルメンツがこれらのリソースを提供することは、適用される テキサス・インスツルメンツの保証または他の保証の放棄の拡大や変更を意味するものではありません。

お客様がいかなる追加条項または代替条項を提案した場合でも、テキサス・インスツルメンツはそれらに異議を唱え、拒否します。

郵送先住所：Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2025, Texas Instruments Incorporated