


- Power-On Reset Generator
- Automatic Reset Generation After Voltage Drop
- $\overline{\text{RESET}}$  Defined When  $V_{CC}$  Exceeds 1 V
- Wide Supply-Voltage Range . . . 3.5 V to 18 V
- Precision Overvoltage and Undervoltage Sensing
- 250-mA Peak Output Current for Driving SCR Gates
- 2-mA Active-Low SCR Gate Drive for False-Trigger Protection
- Temperature-Compensated Voltage Reference
- True and Complementary Reset Outputs
- Externally Adjustable Output Pulse Duration



## description

The TL7770 is an integrated-circuit system supervisor designed for use as a reset controller in microcomputer and microprocessor power-supply systems. This device contains two independent supply-voltage supervisors that monitor the supplies for overvoltage and undervoltage conditions at the VSO and VSU terminals, respectively. When  $V_{CC}$  attains the minimum voltage of 1 V during power up, the  $\overline{\text{RESET}}$  output becomes active (low). As  $V_{CC}$  approaches 3.5 V, the time-delay function activates, latching RESET and  $\overline{\text{RESET}}$  active (high and low, respectively) for a time delay ( $t_d$ ) after system voltages have achieved normal levels. Above  $V_{CC} = 3.5$  V, taking  $\overline{\text{RESIN}}$  low activates the time-delay function during normal system-voltage levels. To ensure that the microcomputer system has reset, the outputs remain active until the voltage at VSU exceeds the threshold value,  $V_{IT+}$ , for a time delay, which is determined by an external timing capacitor such that:

$$t_d \approx 20 \times 10^3 \times \text{capacitance}$$

where  $t_d$  is in seconds and capacitance is in farads.

The overvoltage-detection circuit is programmable for a wide range of designs. During an overvoltage condition, an internal silicon-controlled rectifier (SCR) is triggered, providing 250-mA peak instantaneous current and 25-mA continuous current to the SCR gate drive terminal, which can drive an external high-current SCR gate or an overvoltage-warning circuit.

The TL7770C series is characterized for operation from 0°C to 70°C. The TL7770I series is characterized for operation from -40°C to 85°C.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

**TEXAS  
INSTRUMENTS**

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 1999, Texas Instruments Incorporated

# TL7770-5, TL7770-12

## DUAL POWER-SUPPLY SUPERVISORS


SLVS019F – OCTOBER 1987 – REVISED JULY 1999

AVAILABLE OPTIONS


| T <sub>A</sub> | PACKAGED DEVICES            |                           | CHIP FORM (Y)           |
|----------------|-----------------------------|---------------------------|-------------------------|
|                | SMALL OUTLINE (DW)          | PLASTIC DIP (N)           |                         |
| 0°C to 70°C    | TL7770-5CDW<br>TL7770-12CDW | TL7770-5CN<br>TL7770-12CN | TL7770-5Y<br>TL7770-12Y |
| –40°C to 85°C  | TL7770-5IDW                 | TL7770-5IN                | —                       |

DW package is available taped and reeled. Add the suffix R to the device type (e.g., TL7770-5CDWR). Chip forms are tested at 25°C.

functional block diagram (each channel)



## timing requirements



## absolute maximum ratings over operating free-air temperature range (unless otherwise noted)<sup>†</sup>

|   |                |
|---|----------------|
| Supply voltage, $V_{CC}$ (see Note 1)                                       | 20 V           |
| Input voltage range, $V_I$ : 1VSU, 2VSU, 1VSO, and 2VSO (see Note 1)        | -0.3 V to 18 V |
| Low-level output current (1RESET and 2RESET), $I_{OL}$                      | 20 mA          |
| High-level output current (1RESET and 2RESET), $I_{OH}$                     | -20 mA         |
| Package thermal impedance, $\theta_{JA}$ (see Notes 2 and 3): DW package    | 57°C/W         |
| N package   | 88°C/W         |
| Lead temperature 1,6 mm (1/16 in) from case for 10 seconds: DW or N package | 260°C          |
| Storage temperature range, $T_{stg}$  | -65°C to 150°C |

<sup>†</sup> Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

- NOTES:
1. All voltage values are with respect to the network ground terminal.
  2. Maximum power dissipation is a function of  $T_J(\text{max})$ ,  $\theta_{JA}$ , and  $T_A$ . The maximum allowable power dissipation at any allowable ambient temperature is  $P_D = (T_J(\text{max}) - T_A)/\theta_{JA}$ . Operating at the absolute maximum  $T_J$  of 150°C can impact reliability.
  3. The package thermal impedance is calculated in accordance with JEDEC 51, except for through-hole packages, which use a trace length of zero.

# TL7770-5, TL7770-12

## DUAL POWER-SUPPLY SUPERVISORS

SLVS019F – OCTOBER 1987 – REVISED JULY 1999

### recommended operating conditions

|  |                        | MIN | MAX | UNIT        |
|--|------------------------|-----|-----|-------------|
| Supply voltage, $V_{CC}$   |                        | 3.5 | 18  | V           |
| Input voltage range, $V_I$ (see Note 4)  | 1VSU, 2VSU, 2VSO, 1VSO | 0   | 18  | V           |
| Output voltage, $V_O$ (1CT, 2CT)   |                        |     | 5   | V           |
| High-level input voltage range, $V_{IH}$ ( $\overline{1RESIN}$ , $\overline{2RESIN}$ ) |                        | 2   | 18  | V           |
| Low-level input voltage range, $V_{IL}$ ( $\overline{1RESIN}$ , $\overline{2RESIN}$ )  |                        | 0   | 0.8 | V           |
| Output sink current, $I_O$ (1CT, 2CT)  |                        |     | 50  | $\mu A$     |
| High-level output current, $I_{OH}$ ( $\overline{1RESET}$ , $\overline{2RESET}$ )      |                        |     | –16 | mA          |
| Low-level output current, $I_{OL}$ ( $\overline{1RESET}$ , $\overline{2RESET}$ )       |                        |     | 16  | mA          |
| Continuous output current, $I_O$ (1SCR DRIVE, 2SCR DRIVE)                              |                        |     | 25  | mA          |
| Timing capacitor, $C_T$  |                        |     | 10  | $\mu F$     |
| Operating free-air temperature, $T_A$  | TL7770C series         | 0   | 70  | $^{\circ}C$ |
|  | TL7770I series         | –40 | 85  | $^{\circ}C$ |

NOTE 4: The algebraic convention, in which the least positive (most negative) value is designated minimum, is used in this data sheet for logic voltage levels only.



# TL7770-5, TL7770-12 DUAL POWER-SUPPLY SUPERVISORS

SLVS019F – OCTOBER 1987 – REVISED JULY 1999

electrical characteristics over recommended operating conditions (unless otherwise noted)

## supply supervisor section

| PARAMETER |  |  | TEST<br>CONDITION†  | TL7770-5C<br>TL7770-12C<br>TL7770-5I |       |     | UNIT |
|-----------|--|--|---------------------|--------------------------------------|-------|-----|------|
|           |  |  |                     | MIN                                  | TYP‡  | MAX |      |
| VOH       | High-level output voltage                            | RESET  | IOH = −15 mA        | VCC−1.5                              |       | V   |      |
|           |  | SCR DRIVE                                      | IOH = −20 mA        | VCC−1.5                              |       |     |      |
| VOL       | Low-level output voltage                             | RESET  | IOL = 15 mA         | 0.4                                  |       | V   |      |
| VIT−      | Undervoltage input threshold at VSU (negative-going) | TL7770-5 (5-V sense, 1VSU)                     | TA = MIN to MAX     | 4.46                                 | 4.64  | V   |      |
|           |  | TL7770-12 (12-V sense, 1VSU)                   |                     | 10.68                                | 11.12 |     |      |
|           |  | TL7770-5, TL7770-12 (programmable sense, 2VSU) |                     | 1.47                                 | 1.53  |     |      |
| Vhys      | Hysteresis at VSU (VIT+ − VIT−)                      | TL7770-5 (5-V sense, 1VSU)                     | TA = MIN to MAX     | 15                                   | mV    |     |      |
|           |  | TL7770-12 (12-V sense, 1VSU)                   |                     | 36                                   |       |     |      |
|           |  | TL7770-5, TL7770-12 (programmable sense, 2VSU) |                     | 5                                    |       |     |      |
| VT        | Overvoltage threshold at VSO                         | TL7770-5, TL7770-12 (VSO)                      | TA = MIN to MAX     | 2.48                                 | 2.68  | V   |      |
| II        | Input current  | RESIN  | VI = 5.5 V or 0.4 V | −10                                  |       | μA  |      |
|           |  | VSO  | VI = 2.4 V          | 0.5 2                                |       |     |      |
| IOH       | High-level output current                            | RESET  | VO = 18 V           | 50                                   |       | μA  |      |
| IOL       | Low-level output current                             | RESET  | VO = 0              | −50                                  |       | μA  |      |
| IOH       | Peak output current                                  | SCR DRIVE                                      | Duration = 1 ms     | 250                                  |       | mA  |      |

† For conditions shown as MIN or MAX, use the appropriate value specified in the recommended operating conditions.

‡ Typical values are at V<sub>CC</sub> = 5 V, T<sub>A</sub> = 25°C.

## total device

| PARAMETER |                        | TEST CONDITION†   |                 | TL7770-5C<br>TL7770-12C<br>TL7770-5I |      |     | UNIT |
|-----------|------------------------|---|-----------------|--------------------------------------|------|-----|------|
|           |                        |   |                 | MIN                                  | TYP‡ | MAX |      |
| Vres§     | Power-up reset voltage | VCC = VSU   |                 | 0.8                                  | 1    |     | V    |
| ICC       | Supply current         | 1VSU = 18 V, 2VSU = 2 V,<br>1RESIN and 2RESIN at VCC,<br>1VSO and 2VSO at 0 V | TA = 25°C       | 5                                    |      |     | mA   |
|           |                        |   | TA = MIN to MAX | 6.5                                  |      |     |      |

† For conditions shown as MIN or MAX, use the appropriate value specified in the recommended operating conditions.

‡ Typical values are at V<sub>CC</sub> = 5 V, T<sub>A</sub> = 25°C.

§ This is the lowest voltage at which RESET becomes active.



# TL7770-5, TL7770-12

## DUAL POWER-SUPPLY SUPERVISORS

SLVS019F – OCTOBER 1987 – REVISED JULY 1999

### electrical characteristics over recommended operating conditions (unless otherwise noted)

#### supply supervisor section

| PARAMETER  |  | TEST CONDITIONS           | TL7770-5Y<br>TL7770-12Y |      |       | UNIT          |
|--|--|---------------------------|-------------------------|------|-------|---------------|
|  |  |                           | MIN                     | TYP† | MAX   |               |
| $V_{IT-}$ Undervoltage input threshold at VSU (negative-going) | TL7770-5 (5-V sense, 1VSU)                     | $T_A = \text{MIN to MAX}$ | 4.46                    |      | 4.64  | V             |
|  | TL7770-12 (12-V sense, 1VSU)                   |                           | 10.68                   |      | 11.12 |               |
|  | TL7770-5, TL7770-12 (programmable sense, 2VSU) |                           | 1.47                    |      | 1.53  |               |
| $V_{hys}$ Hysteresis at VSU ( $V_{IT+} - V_{IT-}$ )            | TL7770-5 (5-V sense, 1VSU)                     | $T_A = \text{MIN to MAX}$ |                         | 15   |       | mV            |
|  | TL7770-12 (12-V sense, 1VSU)                   |                           |                         | 36   |       |               |
|  | TL7770-5, TL7770-12 (programmable sense, 2VSU) |                           |                         | 5    |       |               |
| $V_T$ Overvoltage threshold at VSO                             | TL7770-5, TL7770-12 (VSO)                      | $T_A = \text{MIN to MAX}$ | 2.48                    |      | 2.68  | V             |
| $I_I$ Input current  | VSO  | $V_I = 2.4 \text{ V}$     |                         | 0.5  |       | $\mu\text{A}$ |

† Typical values are at  $V_{CC} = 5 \text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

#### total device

| PARAMETER                                 |  | TEST CONDITIONS   | TL7770-5Y<br>TL7770-12Y |      |     | UNIT |
|---|--|---|-------------------------|------|-----|------|
|   |  |   | MIN                     | TYP† | MAX |      |
| $V_{res}^\ddagger$ Power-up reset voltage |  | $V_{CC} = \text{VSU}$ , $V_{OL} = 0.4 \text{ V}$ , $I_{OL} = 1 \text{ mA}$  |                         | 0.8  |     | V    |
| $I_{CC}$ Supply current                   |  | $1\text{VSU} = 18 \text{ V}$ , $2\text{VSU} = 2 \text{ V}$ ,<br>$1\text{RESIN}$ and $2\text{RESIN}$ at $V_{CC}$ ,<br>$1\text{VSO}$ and $2\text{VSO}$ at $0 \text{ V}$ |                         |      | 5   | mA   |

† Typical values are at  $V_{CC} = 5 \text{ V}$ ,  $T_A = 25^\circ\text{C}$ .


‡ This is the lowest voltage at which RESET becomes active.

#### switching characteristics, $V_{CC} = 5 \text{ V}$ , $C_T$ open, $T_A = 25^\circ\text{C}$


| PARAMETER           |  | FROM (INPUT)              | TO (OUTPUT)               | TEST CONDITIONS     | MIN | TYP | MAX | UNIT |
|---------------------|--|---------------------------|---------------------------|---------------------|-----|-----|-----|------|
| $t_{PLH}$           | Propagation delay time, low-to-high-level output | $\overline{\text{RESIN}}$ | RESET                     | See Figures 1 and 3 |     | 270 | 500 | ns   |
| $t_{PHL}$           | Propagation delay time, high-to-low-level output | $\overline{\text{RESIN}}$ | $\overline{\text{RESET}}$ |                     |     | 270 | 500 | ns   |
| $t_r$               | Rise time  |                           | RESET                     |                     |     |     | 75  | ns   |
| $t_f$               | Fall time  |                           | RESET                     |                     |     | 150 |     |      |
| $t_r$               | Rise time  |                           | $\overline{\text{RESET}}$ |                     |     | 75  |     | ns   |
| $t_f$               | Fall time  |                           | $\overline{\text{RESET}}$ |                     |     |     | 50  |      |
| $t_{w(\text{min})}$ | Minimum effective pulse duration                 | $\overline{\text{RESIN}}$ |                           | See Figure 2a       |     | 150 |     | ns   |
|                     |  | VSU                       |                           | See Figure 2b       |     | 100 |     |      |



## PARAMETER MEASUREMENT INFORMATION




RESET OUTPUT CONFIGURATION



RESET OUTPUT CONFIGURATION

NOTE A: This includes jig and probe capacitance.

Figure 1.  $\overline{\text{RESET}}$  and RESET Output Configurations



WAVEFORMS

Figure 2. Input Pulse Definition





Figure 3. Voltage Waveforms

# TL7770-5, TL7770-12 DUAL POWER-SUPPLY SUPERVISORS

SLVS019F – OCTOBER 1987 – REVISED JULY 1999

## APPLICATION INFORMATION



NOTE B: When  $V_{CC}$  and 1VSU are connected to the same point, it is recommended that series resistance ( $R_T$ ) be added between the time-delay programming capacitor ( $C_T$ ) and the voltage-supervisor device terminal (1CT). The suggested  $R_T$  value is given by:

$$R_T > \frac{V_I - V_{IT-}}{1 \times 10^{-3}}, \text{ where } V_I = (\text{the lesser of } 7.1 \text{ V or } V_S)$$

When this series resistor is used, the  $t_d$  calculation is as follows:

$$t_d = \frac{1.3 - [(6.5E - 5) \times 10^{-5}] \times R_T}{6.5 \times 10^{-5}} \times C_T$$

**Figure 4. System Reset Controller With Undervoltage Sensing**



## PACKAGING INFORMATION

| Orderable part number         | Status<br>(1) | Material type<br>(2) | Package   Pins | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6) |
|-------------------------------|---------------|----------------------|----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| <a href="#">TL7770-12CDWR</a> | Active        | Production           | SOIC (DW)   16 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 7770-12C            |
| TL7770-12CDWR.A               | Active        | Production           | SOIC (DW)   16 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 7770-12C            |
| <a href="#">TL7770-5CDWR</a>  | Active        | Production           | SOIC (DW)   16 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | TL7770-5C           |
| TL7770-5CDWR.A                | Active        | Production           | SOIC (DW)   16 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | TL7770-5C           |
| <a href="#">TL7770-5CN</a>    | Active        | Production           | PDIP (N)   16  | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | TL7770-5CN          |
| TL7770-5CN.A                  | Active        | Production           | PDIP (N)   16  | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | TL7770-5CN          |
| <a href="#">TL7770-5IDW</a>   | Obsolete      | Production           | SOIC (DW)   16 | -                     | -           | Call TI                              | Call TI                           | -40 to 85    | TL7770-5I           |
| <a href="#">TL7770-5IDWR</a>  | Active        | Production           | SOIC (DW)   16 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | TL7770-5I           |
| TL7770-5IDWR.A                | Active        | Production           | SOIC (DW)   16 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | TL7770-5I           |

<sup>(1)</sup> **Status:** For more details on status, see our [product life cycle](#).

<sup>(2)</sup> **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

<sup>(4)</sup> **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

<sup>(5)</sup> **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

<sup>(6)</sup> **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative

and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

## TAPE AND REEL INFORMATION



\*All dimensions are nominal

| Device        | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|---------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| TL7770-12CDWR | SOIC         | DW              | 16   | 2000 | 330.0              | 16.4               | 10.75   | 10.7    | 2.7     | 12.0    | 16.0   | Q1            |
| TL7770-5CDWR  | SOIC         | DW              | 16   | 2000 | 330.0              | 16.4               | 10.75   | 10.7    | 2.7     | 12.0    | 16.0   | Q1            |
| TL7770-5IDWR  | SOIC         | DW              | 16   | 2000 | 330.0              | 16.4               | 10.75   | 10.7    | 2.7     | 12.0    | 16.0   | Q1            |


## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device        | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|---------------|--------------|-----------------|------|------|-------------|------------|-------------|
| TL7770-12CDWR | SOIC         | DW              | 16   | 2000 | 350.0       | 350.0      | 43.0        |
| TL7770-5CDWR  | SOIC         | DW              | 16   | 2000 | 350.0       | 350.0      | 43.0        |
| TL7770-5IDWR  | SOIC         | DW              | 16   | 2000 | 350.0       | 350.0      | 43.0        |

## TUBE



\*All dimensions are nominal

| Device       | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|--------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| TL7770-5CN   | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| TL7770-5CN.A | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |

## GENERIC PACKAGE VIEW


**DW 16**

**SOIC - 2.65 mm max height**

7.5 x 10.3, 1.27 mm pitch

SMALL OUTLINE INTEGRATED CIRCUIT

This image is a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.



4224780/A



DW0016A

# PACKAGE OUTLINE

## SOIC - 2.65 mm max height

SOIC



4220721/A 07/2016

### NOTES:

1. All linear dimensions are in millimeters. Dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm, per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm, per side.
5. Reference JEDEC registration MS-013.

# EXAMPLE BOARD LAYOUT


DW0016A

SOIC - 2.65 mm max height

SOIC



LAND PATTERN EXAMPLE  
SCALE:7X



SOLDER MASK DETAILS

4220721/A 07/2016

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.



# EXAMPLE STENCIL DESIGN

DW0016A

SOIC - 2.65 mm max height

SOIC



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:7X

4220721/A 07/2016

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

N (R-PDIP-T\*\*)

16 PINS SHOWN

## PLASTIC DUAL-IN-LINE PACKAGE



| PINS **<br>DIM      | 14               | 16               | 18               | 20               |
|---------------------|------------------|------------------|------------------|------------------|
| A MAX               | 0.775<br>(19,69) | 0.775<br>(19,69) | 0.920<br>(23,37) | 1.060<br>(26,92) |
| A MIN               | 0.745<br>(18,92) | 0.745<br>(18,92) | 0.850<br>(21,59) | 0.940<br>(23,88) |
| MS-001<br>VARIATION | AA               | BB               | AC               | AD               |



4040049/E 12/2002

NOTES:

- A. All linear dimensions are in inches (millimeters).  
B. This drawing is subject to change without notice.
-  Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).  
 The 20 pin end lead shoulder width is a vendor option, either half or full width.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2025, Texas Instruments Incorporated