

TPS7H1101A-SP 1.5V～7V入力、3A、放射線強化型LDOレギュレータ

1 特長

- 5962R13202:
 - 放射線強度保証(RHA): 最大TID 100krad (Si)
 - 総照射線量耐性: 100krad (Si)
 - ELDRSフリー: 100krad (Si)
 - 線量率: 10mrad (Si)/s
 - 単一イベント・ラッチアップ(SEL)耐性:
 - LET = 85 MeV-cm²/mg
 - SEBおよびSEGR耐性:
 - LET = 85 MeV-cm²/mg
 - SET/SEFI開始スレッショルド > 40 MeV-cm²/mg、詳細については「[放射線レポート](#)」(SNAA257)を参照
 - 下流の重要なコンポーネントの損傷を防止するため、常にLOWにアップセットするよう設計
 - SET/SEFIクロスセクション・プロット、詳細については「[放射線レポート](#)」(SNAA257)を参照
- 非常に低いV_{IN}範囲: 1.5V～7V
- 最大出力電流 3A
- 電流共有/並列動作により、最大6Aの出力電流を供給可能
- セラミック出力コンデンサで安定動作
- ライン、負荷、温度の範囲全体にわたって±2%の精度
- 外付けのコンデンサによりソフトスタートをプログラム可能
- すべての入力電圧にわたる入力イネーブルとパワー・グッド出力によるパワー・シーケンス
- 非常に低いドロップアウトLDO電圧:
 - 1A (25°C)、V_{OUT} = 1.8Vにおいて62mV
- 低ノイズ:
 - V_{IN} = 2V、V_{OUT} = 1.8V、3A時に20.33μVRMS
- PSRR: 1kHzにおいて45dB超
- 非常に優れた負荷/ライン過渡応答
- フォールドバック電流制限
- 「[ツールとソフトウェア](#)」タブを参照
- 熱的に強化されたCFPパッケージ(0.6°C/W R_{θJC})

2 アプリケーション

- 人工衛星のポイント・オブ・ロード電源: FPGA、マイクロコントローラ、ASIC、データ・コンバータ用
- 人工衛星のペイロード
- RF、VCO、受信機、アンプ用の、放射線強化された低ノイズのリニア・レギュレータ電源
- クリーンなアナログ電源要件
- 軍用温度範囲(-55°C～125°C)で利用可能
- エンジニアリング評価(EM)サンプルを利用可能⁽¹⁾

3 概要

TPS7H1101A-SPはTPS7H1101-SPの改良版で、入力電圧範囲の全体にわたってイネーブル機能を使用できます。放射線強化されたLDOリニア・レギュレータであり、PMOSパス素子構成を使用します。1.5V～7Vの広い入力電圧範囲で動作し、非常に優れたPSRRを実現しています。TPS7H1101A-SPには、正確でプログラム可能、かつ非常に広い範囲で調整可能な、フォールドバック電流制限が実装されています。FPGA、DSP、マイクロコントローラの複雑な電力要件に対応するため、TPS7H1101A-SPにはイネーブル・オンおよびオフ機能、ソフトスタートのプログラム機能、電流共有機能、パワー・グッドのオープン・ドレイン出力が搭載されています。


製品情報⁽²⁾

型番	パッケージ	本体サイズ(公称)
TPS7H1101A-SP	CFP (16)	11.00mm×9.60mm
	KGD	—

(1) これらのユニットは、技術的な評価のみを目的としています。標準とは異なるフロー(バーニンがないなど)に従って処理されており、25°Cの温度定格のみがテストされています。これらのユニットは、認定、量産、放射線テスト、航空での使用には適していません。これらの部品は、MILに規定されている温度範囲-55°C～125°C、または動作寿命全体にわたる性能を保証されていません。

(2) 提供されているすべてのパッケージについては、データシートの末尾にある注文情報を参照してください。

代表的なアプリケーション回路



Copyright © 2017, Texas Instruments Incorporated



目次


1	特長	1	8	Application and Implementation	15
2	アプリケーション	1	8.1	Application Information.....	15
3	概要	1	8.2	Typical Application	16
4	改訂履歴	2	9	Power Supply Recommendations	26
5	Pin Configuration and Functions	3	10	Layout	26
6	Specifications	6	10.1	Layout Guidelines	26
6.1	Absolute Maximum Ratings	6	10.2	Layout Example	26
6.2	ESD Ratings.....	6	11	デバイスおよびドキュメントのサポート	27
6.3	Recommended Operating Conditions.....	6	11.1	デバイス・サポート	27
6.4	Thermal Information	6	11.2	ドキュメントのサポート	27
6.5	Electrical Characteristics.....	7	11.3	ドキュメントの更新通知を受け取る方法.....	27
6.6	Typical Characteristics	10	11.4	コミュニティ・リソース	27
7	Detailed Description	12	11.5	商標	27
7.1	Overview	12	11.6	静電気放電に関する注意事項	27
7.2	Functional Block Diagram	13	11.7	Glossary	27
7.3	Feature Description	13	12	メカニカル、パッケージ、および注文情報	27
7.4	Device Functional Modes.....	14			

4 改訂履歴

資料番号末尾の英字は改訂を表しています。その改訂履歴は英語版に準じています。

2017年4月発行のものから更新		Page
•	Added Bare Die Information table	4
•	Added Bond Pad Coordinates in Microns table.....	5

5 Pin Configuration and Functions



Pin Functions

PIN		I/O	DESCRIPTION
NAME	NO.		
SS	1	I/O	Soft-start terminal. Connecting an external capacitor slows down the output voltage ramp rate after enable event.
EN	2	I	Enable terminal. Driving this terminal to logic high enables the device; driving the terminal to logic low disables the device.
V _{IN}	3	I	Unregulated supply voltage. TI recommends to connect an input capacitor as a good analog circuit practice.
	4		
	5		
	6		
PCL	7	I/O	Programmable current limit. A resistor to GND sets the overcurrent limit activation point. The range of resistor that can be used on the PCL terminal to GND is 8.2 kΩ to 160 kΩ.
GND	8	—	Ground/thermal pad. ⁽¹⁾
PG/OC	9	O	Power Good terminal. PG is an open-drain output to indicate the output voltage reaches 90% of target. PG terminal is also used as indicator when an overcurrent condition is activated. PG pin should have a pull-up resistor to the V _{OUT} pin.
CS	10	I/O	Current sense terminal. Resistor connected from CS to V _{IN} . CS terminal indicates voltage proportional to output current. CS terminal low: Foldback current limit disabled. CS terminal high: Foldback current limit enabled.
V _{OUT}	11	O	Regulated output.
	12		
	13		
	14		
COMP	15	I/O	Internal compensation point for error amplifier.
FB	16	I	The output voltage feedback input through voltage dividers. See the Adjustable Output Voltage (Feedback Circuit) section.


(1) Thermal pad must be connected to GND.

TPS7H1101A-SP

JAJSD99A –APRIL 2017 –REVISED AUGUST 2017

www.ti.com
Bare Die Information

DIE THICKNESS	BACKSIDE FINISH	BACKSIDE POTENTIAL	BOND PAD METALLIZATION COMPOSITION	BOND PAD THICKNESS
15 mils	Silicon with backgrind	Ground	AlCu	30 kÅ



NOTE: All dimensions are in microns.

Bond Pad Coordinates in Microns

DESCRIPTION	PAD NUMBER	X MIN	Y MIN	X MAX	Y MAX
SS	1	109.89	4046.805	287.19	4224.105
EN	2	109.89	3493.35	287.19	3670.65
VIN	3	1359.99	3021.345	1537.29	3198.645
VIN	4	1359.99	2749.005	1537.29	2926.305
VIN	5	1359.99	2553.705	1537.29	2731.005
VIN	6	1359.99	2281.365	1537.29	2458.665
VIN	7	1359.99	2086.065	1537.29	2263.365
VIN	8	1359.99	1813.725	1537.29	1991.025
VIN	9	1359.99	1618.425	1537.29	1795.725
PCL	10	109.89	660.285	287.19	837.585
GND	11	109.89	319.455	287.19	496.755
GND	12	392.58	109.935	569.88	287.235
VIN	13	1359.99	1346.085	1537.29	1523.385
PG/OC	14	2898.945	379.62	3076.245	556.92
CS	15	2898.945	724.32	3076.245	901.62
VOUT	16	2829.105	1384.695	3006.405	1561.995
VOUT	17	2829.105	1579.815	3006.405	1757.115
VOUT	18	2829.105	1852.335	3006.405	2029.635
VOUT	19	2829.105	2047.455	3006.405	2224.755
VOUT	20	2829.105	2319.975	3006.405	2497.275
VOUT	21	2829.105	2515.095	3006.405	2692.395
VOUT	22	2829.105	2787.615	3006.405	2964.915
VOUT	23	2829.105	2982.735	3006.405	3160.035
COMP	24	2898.945	3519.72	3076.245	3697.02
FB	25	2898.945	3956.535	3076.245	4133.835

6 Specifications

6.1 Absolute Maximum Ratings

 over operating free-air temperature range (unless otherwise noted) ⁽¹⁾

		MIN	MAX	UNIT
Input voltage	V _{IN} , PG	–0.3	7.5	V
	FB, COMP, PCL, CS, EN	–0.3	V _{IN} + 0.3	
Output voltage	V _{OUT} , SS	–0.3	7.5	V
PG terminal sink current		0.001	5	mA
Maximum operating junction temperature, T _J		–55	150	°C
Storage temperature, T _{stg}		–55	150	°C

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

6.2 ESD Ratings

		VALUE	UNIT
V _(ESD) Electrostatic discharge	Human-body model (HBM), per ANSI/ESDA/JEDEC JS-001, all pins ⁽¹⁾	±2000	V
	Charged-device model (CDM), per JEDEC specification JESD22-C101, all pins ⁽²⁾	±1000	

- (1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
 (2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

6.3 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)

		MIN	NOM	MAX	UNIT
T _J	Operating junction temperature	–55		125	°C

6.4 Thermal Information

THERMAL METRIC ⁽¹⁾⁽²⁾		TPS7H1101A-SP	UNIT
		HKR (CFP)	
		16 PINS	
R _{θJC(bot)}	Junction-to-case (bottom) thermal resistance	0.6	°C/W

- (1) Do not allow package body temperature to exceed 265°C at any time or permanent damage may result.
 (2) Maximum power dissipation may be limited by overcurrent protection.

6.5 Electrical Characteristics

$1.5\text{ V} \leq V_{\text{IN}} \leq 7\text{ V}$, $V_{\text{OUT(target)}} = V_{\text{IN}} - 0.35\text{ V}$, $I_{\text{OUT}} = 10\text{ mA}$, $V_{\text{EN}} = 1.1\text{ V}$, $C_{\text{OUT}} = 22\text{ }\mu\text{F}$, PG terminal pulled up to V_{IN} with $50\text{ k}\Omega$, over operating temperature range ($T_{\text{J}} = -55^{\circ}\text{C}$ to 125°C), unless otherwise noted. Typical values are at $T_{\text{J}} = 25^{\circ}\text{C}$.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{IN} Input voltage range		1.5		7	V
V_{FB} Feedback terminal voltage ⁽¹⁾	$0\text{ A} \leq I_{\text{OUT}} \leq 3\text{ A}$, $1.5\text{ V} \leq V_{\text{IN}} \leq 7\text{ V}$	0.594	0.605	0.616	V
V_{OUT} Output voltage range		0.8		V_{IN}	V
Output voltage accuracy ⁽¹⁾	$0\text{ A} \leq I_{\text{OUT}} \leq 3\text{ A}$, $1.5\text{ V} \leq V_{\text{IN}} \leq 7\text{ V}$, $V_{\text{OUT}} = 0.8\text{ V}, 1.2\text{ V}, 1.8\text{ V}, 6.65\text{ V}$	-2%		2%	
$\frac{\Delta V_{\text{OUT}}\%}{\Delta V_{\text{IN}}}$ Line regulation	$1.5\text{ V} \leq V_{\text{IN}} \leq 7\text{ V}$	-0.07	0.01	0.07	%/V
$\frac{\Delta V_{\text{OUT}}\%}{\Delta I_{\text{OUT}}}$ Load regulation	$0.8\text{ V} \leq V_{\text{OUT}} \leq 6.65\text{ V}$, $0 \leq I_{\text{Load}} \leq 3\text{ A}$		0.08		%/A
ΔV_{OUT} DC input line regulation	$1.5\text{ V} \leq V_{\text{IN}} \leq 7\text{ V}$, $V_{\text{OUT}} = 0.8\text{ V}, 1.2\text{ V}, 1.8\text{ V}$, $I_{\text{OUT}} = 10\text{ mA}$, $T_{\text{J}} = -55^{\circ}\text{C}$ ⁽²⁾		0.5	3	mV
	$1.5\text{ V} \leq V_{\text{IN}} \leq 7\text{ V}$, $V_{\text{OUT}} = 0.8\text{ V}, 1.2\text{ V}, 1.8\text{ V}$, $I_{\text{OUT}} = 10\text{ mA}$, $T_{\text{J}} = 25^{\circ}\text{C}$ ⁽²⁾		0.2	0.6	
	$1.5\text{ V} \leq V_{\text{IN}} \leq 7\text{ V}$, $V_{\text{OUT}} = 0.8\text{ V}, 1.2\text{ V}, 1.8\text{ V}$, $I_{\text{OUT}} = 10\text{ mA}$, $T_{\text{J}} = 125^{\circ}\text{C}$ ⁽²⁾		0.2	1	

(1) The output voltage accuracy of condition at $I_{\text{OUT}} = 2\text{ A}$ and $I_{\text{OUT}} = 3\text{ A}$ is specified by characterization, but not production tested.

(2) Line and load regulations done under pulse condition for $t < 10\text{ ms}$.

Electrical Characteristics (continued)

1.5 V ≤ V_{IN} ≤ 7 V, V_{OUT(target)} = V_{IN} – 0.35 V, I_{OUT} = 10 mA, V_{EN} = 1.1 V, C_{OUT} = 22 μF, PG terminal pulled up to V_{IN} with 50 kΩ, over operating temperature range (T_J = –55°C to 125°C), unless otherwise noted. Typical values are at T_J = 25°C.

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
ΔV _O	DC output load regulation ⁽³⁾	V _{OUT} = 0.8 V, 0 ≤ I _{Load} ≤ 1 A, T _J = –55°C ⁽²⁾		0.4	1	mV
		V _{OUT} = 0.8 V, 0 ≤ I _{Load} ≤ 1 A, T _J = 25°C ⁽²⁾		0.6	1.1	
		V _{OUT} = 0.8 V, 0 ≤ I _{Load} ≤ 1 A, T _J = 125°C ⁽²⁾		0.8	1.3	
		V _{OUT} = 0.8 V, 0 ≤ I _{Load} ≤ 2 A, T _J = –55°C ⁽²⁾		0.8	1.8	
		V _{OUT} = 0.8 V, 0 ≤ I _{Load} ≤ 2 A, T _J = 25°C ⁽²⁾		1.3	1.8	
		V _{OUT} = 0.8 V, 0 ≤ I _{Load} ≤ 2 A, T _J = 125°C ⁽²⁾		1.6	2.4	
		V _{OUT} = 0.8 V, 0 ≤ I _{Load} ≤ 3 A, T _J = –55°C ⁽²⁾		1.1	1.9	
		V _{OUT} = 0.8 V, 0 ≤ I _{Load} ≤ 3 A, T _J = 25°C ⁽²⁾		1.9	2.6	
		V _{OUT} = 0.8 V, 0 ≤ I _{Load} ≤ 3 A, T _J = 125°C ⁽²⁾		2.5	3.4	
		V _{OUT} = 1.2 V, 0 ≤ I _{Load} ≤ 1 A, T _J = –55°C ⁽²⁾		0.3	1.2	
		V _{OUT} = 1.2 V, 0 ≤ I _{Load} ≤ 1 A, T _J = 25°C ⁽²⁾		0.5	1.3	
		V _{OUT} = 1.2 V, 0 ≤ I _{Load} ≤ 1 A, T _J = 125°C ⁽²⁾		0.6	1.3	
		V _{OUT} = 1.2 V, 0 ≤ I _{Load} ≤ 2 A, T _J = –55°C ⁽²⁾		0.8	1.6	
		V _{OUT} = 1.2 V, 0 ≤ I _{Load} ≤ 2 A, T _J = 25°C ⁽²⁾		1.1	2.1	
		V _{OUT} = 1.2 V, 0 ≤ I _{Load} ≤ 2 A, T _J = 125°C ⁽²⁾		1.5	2.1	
		V _{OUT} = 1.2 V, 0 ≤ I _{Load} ≤ 3 A, T _J = –55°C ⁽²⁾		1	1.7	
		V _{OUT} = 1.2 V, 0 ≤ I _{Load} ≤ 3 A, T _J = 25°C ⁽²⁾		1.1	2.4	
		V _{OUT} = 1.2 V, 0 ≤ I _{Load} ≤ 3 A, T _J = 125°C ⁽²⁾		2.2	3.5	
		V _{OUT} = 1.8 V, 0 ≤ I _{Load} ≤ 1 A, T _J = –55°C ⁽²⁾		0.1	0.9	
		V _{OUT} = 1.8 V, 0 ≤ I _{Load} ≤ 1 A, T _J = 25°C ⁽²⁾		0.3	0.9	
		V _{OUT} = 1.8 V, 0 ≤ I _{Load} ≤ 1 A, T _J = 125°C ⁽²⁾		0.4	1.2	
		V _{OUT} = 1.8 V, 0 ≤ I _{Load} ≤ 2 A, T _J = –55°C ⁽²⁾		1.4	2.4	
		V _{OUT} = 1.8 V, 0 ≤ I _{Load} ≤ 2 A, T _J = 25°C ⁽²⁾		0.7	1.4	
		V _{OUT} = 1.8 V, 0 ≤ I _{Load} ≤ 2 A, T _J = 125°C ⁽²⁾		0.6	1.9	
		V _{OUT} = 1.8 V, 0 ≤ I _{Load} ≤ 3 A, T _J = –55°C ⁽²⁾		2.5	3.9	
		V _{OUT} = 1.8 V, 0 ≤ I _{Load} ≤ 3 A, T _J = 25°C ⁽²⁾		1.2	2.1	
		V _{OUT} = 1.8 V, 0 ≤ I _{Load} ≤ 3 A, T _J = 125°C ⁽²⁾		1.2	2.5	
		V _{OUT} = 6.65 V, 0 ≤ I _{Load} ≤ 1 A, T _J = –55°C ⁽²⁾		1.5	2.9	
		V _{OUT} = 6.65 V, 0 ≤ I _{Load} ≤ 1 A, T _J = 25°C ⁽²⁾		0.4	2.6	
		V _{OUT} = 6.65 V, 0 ≤ I _{Load} ≤ 1 A, T _J = 125°C ⁽²⁾		2.8	3.5	
		V _{OUT} = 6.65 V, 0 ≤ I _{Load} ≤ 2 A, T _J = –55°C ⁽²⁾		3.5	5.9	
		V _{OUT} = 6.65 V, 0 ≤ I _{Load} ≤ 2 A, T _J = 25°C ⁽²⁾		1.1	4.7	
		V _{OUT} = 6.65 V, 0 ≤ I _{Load} ≤ 2 A, T _J = 125°C ⁽²⁾		5.8	8	
		V _{OUT} = 6.65 V, 0 ≤ I _{Load} ≤ 3 A, T _J = –55°C ⁽²⁾		5.6	9.3	
		V _{OUT} = 6.65 V, 0 ≤ I _{Load} ≤ 3 A, T _J = 25°C ⁽²⁾		3.7	8	
		V _{OUT} = 6.65 V, 0 ≤ I _{Load} ≤ 3 A, T _J = 125°C ⁽²⁾		13	25	
		V _{DO}	Dropout voltage ⁽³⁾	I _{OUT} = 3 A, V _{OUT} = 1.3 V, V _{IN} = V _{OUT} + V _{DO}		
I _{CL}	Programmable output current limit range	V _{IN} = 1.5 V, V _{OUT} = 1.2 V, PCL resistance = 47 kΩ	500		750	mA
		V _{IN} = 1.5 V, V _{OUT} = 1.2 V, PCL resistance varies	200		3500 ⁽⁴⁾	
V _{CS}	Operating voltage range at CS		0.3		V _{IN}	V
CSR	Current sense ratio	I _{LOAD} / I _{CS} , V _{IN} = 2.3 V, V _{OUT} = 1.9 V	47394	47500	56000	A/A

(3) The parameter is specified to the limit in characterization, but not production tested.

(4) The maximum limit of the I_{CL} parameter is specified to the limit in characterization, but not production tested.

Electrical Characteristics (continued)

$1.5\text{ V} \leq V_{IN} \leq 7\text{ V}$, $V_{OUT(target)} = V_{IN} - 0.35\text{ V}$, $I_{OUT} = 10\text{ mA}$, $V_{EN} = 1.1\text{ V}$, $C_{OUT} = 22\text{ }\mu\text{F}$, PG terminal pulled up to V_{IN} with $50\text{ k}\Omega$, over operating temperature range ($T_J = -55^\circ\text{C}$ to 125°C), unless otherwise noted. Typical values are at $T_J = 25^\circ\text{C}$.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
I_{GND}	GND terminal current	$V_{IN} = 1.5\text{ V}$, $V_{OUT} = 1.2\text{ V}$, $I_{OUT} = 2\text{ A}$	10	16	mA
I_Q	Quiescent current (no load)	$V_{IN} = V_{OUT} + 0.5\text{ V}$, $I_{OUT} = 0\text{ A}$	7	10	mA
I_{SHDN}	Shutdown current	$1.5\text{ V} \leq V_{IN} \leq 7\text{ V}$, pre and post 100 krads (Si), $T_J = 25^\circ\text{C}^{(5)}$	26	230	μA
I_{SNS} , I_{FB}	FB/SNS terminal current	$V_{IN} = 7\text{ V}$, $V_{OUT} = 6.65\text{ V}$	1	5	nA
I_{EN}	EN terminal input current	$V_{IN} = 7\text{ V}$, $V_{EN} = 7\text{ V}$, $V_{OUT} = 6.65\text{ V}$	20	150	nA
V_{ILEN}	EN terminal input low (disable)	$1.5\text{ V} < V_{IN} < 7\text{ V}$		0.55	V
V_{IHEN}	EN terminal input high (enable)	$1.5\text{ V} < V_{IN} < 7\text{ V}$	$V_{IN} - 0.7$		V
Eprop Dly	Enable terminal propagation delay	$V_{IN} = 2.2\text{ V}$, EN rise to $I_{OUTrise}$	650	1000	μs
T_{EN}	Enable terminal turn-on delay	$V_{IN} = 2.2\text{ V}$, $V_{OUT} = 1.8\text{ V}$, $I_{LOAD} = 1\text{ A}$, $C_{OUT} = 220\text{ }\mu\text{F}$, $C_{SS} = 2\text{ nF}$	1.4	1.6	ms
V_{THPG}	PG threshold	No load, $0.8\text{ V} \leq V_{OUT} \leq 6.65\text{ V}$	86%	90%	
$V_{THPGHYS}$	PG hysteresis	$1.5\text{ V} \leq V_{IN} \leq 7\text{ V}$	2%		
V_{OLPG}	PG terminal output low	$I_{PG} = 0\text{ mA}$ to -1 mA	120	300	mV
I_{LKPGPG}	PG terminal leakage current	$V_{OUT} > V_{THPG}$, $V_{PG} = 1.2\text{ V}$	0.2	1.5	μA
		$V_{OUT} > V_{THPG}$, $V_{PG} = 7\text{ V}$	0.5	2.5	
I_{SS}	SS terminal charge current	$V_{IN} = 1.5\text{ V}$ to 7 V	2.5	3.5	μA
I_{SSdisb}	SS terminal disable current	$V_{IN} = 1.5\text{ V}$ to 7 V	5	10	μA
V_{SS}	SS terminal voltage (device enabled) ⁽⁶⁾	$V_{IN} = 1.5\text{ V}$ to 7 V		1.232	V
V_{SSdisb}	SS terminal low-level input voltage to disable device	$V_{IN} = 1.5\text{ V}$ to 7 V		0.4	V
PSRR	Power-supply rejection ratio	$V_{IN} = 2.5\text{ V}$, $V_{OUT} = 1.8\text{ V}$, $C_{OUT} = 220\text{ }\mu\text{F}$	1 kHz	48	dB
			100 kHz	25	
V_N	Output noise voltage	BW = 10 Hz to 100 kHz, $I_{OUT} = 3\text{ A}$, $V_{IN} = 2\text{ V}$, $V_{OUT} = 1.8\text{ V}$	20.33		μV_{RMS}
TSD	Thermal shutdown temperature		185		$^\circ\text{C}$

(5) This maximum limit applies to SMD 5962R13202 post 100-krads (Si) test at 25°C .

(6) Any external pullup voltage should not exceed 1.188 V.

6.6 Typical Characteristics




FIG 1. Feedback Voltage vs Temperature




FIG 2. Quiescent Current vs Temperature




FIG 3. Ground Current vs Temperature




FIG 4. Dropout Voltage vs Temperature




FIG 5. Shutdown Current vs Temperature




FIG 6. PG Threshold vs Temperature

Typical Characteristics (continued)




图 7. Power Supply Ripple Rejection vs Frequency

7 Detailed Description

7.1 Overview

The TPS7H1101A-SP is 3-A, 1.5-V to 7-V LDO linear regulator that uses PMOS pass element configuration.

It uses TI's proprietary process to achieve low noise, high PSRR combined with high-thermal performance in a 16-pin ceramic flatpack package (HKR).

A number of features are incorporated in the design to provide high reliability and system flexibility. Current foldback, current limit, and thermal protection are incorporated in the design to make it viable for harsh environments.

The device also has a current sense monitoring feature. A resistor connected from the current sense (CS) terminal to VIN indicates voltage proportional to the output current. When CS is held high, foldback current limit is enabled. Shorting CS low disables the foldback current limit.

A resistor connected from the programmable current limit (PCL) terminal to ground sets the overcurrent limit activation point. When overcurrent limit activation point is reached, it results in LDO going into current foldback mode. Output current is reduced to approximately 50% of the current limit set point. The [PCL](#) section provides a detailed description of this feature.


TPS7H1101A-SP incorporates thermal protection, which disables the output when the junction temperature rises approximately 185°C, allowing the device to cool. Cycling limits the dissipation of the regulator, protecting it from damage as a result of overheating.

A resistor connected from the CS terminal to VIN indicates voltage proportional to the output load current.

To provide system flexibility for demanding current needs, the LDO can be configured in parallel operation as indicated in [Figure 20](#). The [Current Sharing](#) section provides detailed parallel operation information.

An enable feature is incorporated in the design allowing the user to enable or disable the LDO. Power Good, an open-drain connection, indicates the status of the output voltage. These provide the customers system flexibility in monitoring and controlling the LDO operation.

7.2 Functional Block Diagram



Copyright © 2017, Texas Instruments Incorporated

7.3 Feature Description

7.3.1 Soft Start

Connecting a capacitor from the SS terminal to GND (C_{SS}) slows down the output voltage ramp rate. The soft-start capacitor charges up to 1.2 V.

$$C_{SS} = \frac{t_{SS} \cdot I_{SS}}{V_{FB}}$$

where


- t_{SS} = soft-start time
- I_{SS} = 2.5 μ A
- $V_{FB} = V_{REF} / 2 = 0.605$ V

(1)

7.3.2 Power Good (PG)

Power Good terminal (9) is an open-drain connection and can be used to sequence multiple LDOs. [Figure 8](#) shows typical connection. The PG terminal will be pulled low until the output voltage reaches 90% of its maximum level. At that point, the PG pin will be pulled up. Since the PG pin is open drain, it can be pulled up to any voltage as long as it does not exceed the absolute max of 7.5 V listed in the [Electrical Characteristics](#) table.

Feature Description (continued)



Copyright © 2017, Texas Instruments Incorporated

图 8. Sequencing LDOs with Power Good

注

For PSpice models, WEBENCH, and mini-POL reference design, see the *Tools & Software* tab.

1. PSpice average model (stability – Bode plot)
2. PSpice transient model (switching waveforms)
3. WEBENCH design tool, www.ti.com/product/TPS7H1101A-SP/toolssoftware

7.4 Device Functional Modes

7.4.1 Enable/Disable

For V_{IN} from 1.5 V to 7 V, TPS7H1101A-SP can be disabled by pulling the enable terminal to logic low at a minimum of 0.7 V. In all cases, the enable terminal should be connected to V_{IN} .

8 Application and Implementation

注

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

8.1 Application Information

The TPS7H1101A-SP LDO linear regulator is targeted to harsh environment applications. This regulator has various features such as low dropout, soft start, output current foldback, high-side current sensing (where sensing voltage at CS pin provides voltage proportional to output current), and current sharing.

8.1.1 Stability

Conventional Bode plots are a standard approach in assessing stability as shown in [Figure 9](#). This approach requires that we have a single feedback path where an AC signal is injected across a resistor (typically 50 Ω) and measurements are taken on either side of the resistor. From this, loop gain and phase plots can be generated. Crossover frequency, f_C , is defined as the frequency where the magnitude of the loop gain is unity and phase margin is evaluated at the crossover frequency f_C .




Figure 9. Conventional Bode Plot

However, there are conditions where the feedback loop is not accessible or there may be multiple feedback paths, as with the TPS7H1101A-SP. When there are multiple feedback loops the conventional Bode plot approach will not be representative of the device's true response. The TPS7H1101A-SP uses a conventional feedback loop in addition to an inner fast loop that injects current into the error amplifier, which in turn greatly improves the transient response of the device. The Bode plot method can still be used to understand the behavior of the main loop, but this will show a lower crossover frequency and thus imply a slower transient response than the actual performance of the device. Fortunately, accurate and quantitative stability metrics can still be assessed from output impedance measurements and simulations.

There are multiple ways output impedance can be measured. One approach is to inject a small current at the output of the regulator and compare it to the resulting voltage response. The variation in the phase of the output impedance across frequency can be related to the phase margin through the group delay.


Group delay, T_g , is the rate of change of phase with respect to frequency as shown in [Equation 2](#). Most SPICE simulation packages can plot this parameter and certain frequency analyzers boast software that supports a direct measurement. Using this software, phase margin can be extracted from the group delay plot. The phase margin and crossover frequency reported from these measurements will include the effects of both feedback loops.

$$T_g = \frac{d\phi}{d\omega} \quad (2)$$

Application Information (continued)

The stability of the device can be qualitatively validated by applying a step load to the output and observing the response. The SPICE models for the device can be found in [Tools & Software](#) on the product page. To simulate impedance measurements, the transient model should be used. For a more detailed explanation of this approach and how to use the model to simulate the output impedance and group delay, please see reference (1) in the [関連資料](#) section.

8.2 Typical Application



Copyright © 2017, Texas Instruments Incorporated

図 10. Typical Application Circuit

Typical Application (continued)

8.2.1 Detailed Design Procedure

8.2.1.1 Adjustable Output Voltage (Feedback Circuit)

The output voltage of the TPS7H1101A-SP can be set to a user-programmable level between 0.8 V and 6.65 V. Achieve this by using a resistor divider connected between V_{OUT} , FB, and GND terminals. R_{TOP} connected between V_{OUT} and V_{FB} , and R_{BOTTOM} connected between V_{FB} and GND.

Use 式 3 to determine V_{OUT} .

$$V_{OUT} = \frac{(R_{TOP} + R_{BOTTOM}) \cdot V_{FB}}{R_{BOTTOM}}$$

where

- $V_{FB} = 0.605 \text{ V}$ (3)

表 1. Resistor Values for Typical Voltages

V_{OUT}	Standard 1% Resistors		Standard 0.1% Resistors	
	R_{TOP}	R_{BOTTOM}	R_{TOP}	R_{BOTTOM}
0.8 V	10.7 k Ω	33.2 k Ω	10.7 k Ω	33.2 k Ω
1 V	13.7 k Ω	21 k Ω	12.6 k Ω	19.3 k Ω
1.2 V	11.3 k Ω	11.5 k Ω	11.8 k Ω	12 k Ω
1.5 V	15.8 k Ω	10.7 k Ω	18.2 k Ω	12.3 k Ω
1.8 V	23.2 k Ω	11.8 k Ω	32 k Ω	16.2 k Ω
2.5 V	10.7 k Ω	3.4 k Ω	37.9 k Ω	12.1 k Ω
3.3 V	51.1 k Ω	11.5 k Ω	10.2 k Ω	2.29 k Ω
4 V	13.3 k Ω	2.37 k Ω	31.2 k Ω	5.56 k Ω
5 V	11.5 k Ω	1.58 k Ω	16.2 k Ω	2.23 k Ω
5.5 V	17.4 k Ω	2.15 k Ω	89.8 k Ω	11.1 k Ω
6 V	90.9 k Ω	10.2 k Ω	10.7 k Ω	1.2 k Ω
6.5 V	26.7 k Ω	2.74 k Ω	15.2 k Ω	1.56 k Ω
6.6 V	11.3 k Ω	1.15 k Ω	22.1 k Ω	2.23 k Ω
6.7 V	39.2 k Ω	3.92 k Ω	13.8 k Ω	1.37 k Ω

8.2.1.2 PCL

PCL resistor, R_{PCL} , sets the overcurrent limit activation point and can be calculated per 式 4.

$$R_{PCL} = (CSR \times V_{REF}) / (I_{CL} - 0.0403)$$


where

- $V_{REF} = 0.605 \text{ V}$
- I_{CL} = Programmable current limit (A)
- Current sense ratio (CSR) is the ratio of output load current to I_{CS} . The typical value of the CSR is 47394. (4)

図 11 shows the output load current (I_{OUT}) versus PCL terminal current (I_{CL}).

A suitable resistor R_{PCL} must be chosen to ensure the CS terminal is within its operating range of 0.3 V to V_{IN} .

The maximum PCL is 3.5 A. The range of resistor that can be used on the PCL terminal to GND is 8.2 k Ω to 160 k Ω .



$$V_{IN} = 2.3 \text{ V} \quad V_{OUT} = 1.8 \text{ V} \quad y = 47394x + 0.0403$$

FIG 11. I_{OUT} (A) vs I_{PCL} (μA)

8.2.1.3 High-Side Current Sense

FIG 12 shows the cascode NMOS current mirror. V_{CS} must be in the range as specified in the [Electrical Characteristics](#) table. The following example shows the typical calculation of R_{CS} .

$$I_{CS} = \frac{I_{LOAD} + I_{offset}}{CSR} \quad (5)$$

$$R_{CS} = \frac{V_{IN} - V_{CS}}{I_{CS}}$$

where

- I_{LOAD} is the output load current.
- CSR is the current sense ratio.

(6)

When $V_{IN} = 2.3 \text{ V}$, select $V_{CS} = 2.05 \text{ V}$, $I_{LOAD} = 3 \text{ A}$, $CSR = 47394$, and $I_{offset} = 0.1899 \text{ A}$, then $I_{CS} = 67.306 \text{ μA}$ and $R_{CS} = 3.714 \text{ kΩ}$.




FIG 12. Cascode NMOS Current Mirror

For TPS7H1101A-SP, FIG 13 shows the typical curve V_{CS} vs I_{OUT} for $V_{IN} = 2.28 \text{ V}$ and $R_{CS} = 3.65 \text{ kΩ}$. A resistor connected from the CS terminal to V_{IN} indicates voltage proportional to the output current.

Monitoring current in the CS terminal (I_{CS} vs I_{OUT}) indicates the current sense ratio between the main PMOSFET and the current sense MOSFET as shown in [Figure 14](#).

[Figure 15](#) shows I_{OUT} vs I_{CS} when the voltage on CS terminal is varied from 0.3 V to 7 V.




Figure 13. V_{CS} (V) vs I_{OUT} (A)




Figure 14. I_{OUT} (A) vs I_{CS} (A)




Figure 15. I_{OUT} (A) vs I_{CS} (A)

8.2.1.4 Current Foldback

- The TPS7H1101A-SP has a current foldback feature which can be enabled when the CS terminal is held high. Shorting CS low disables the foldback current limit. If the foldback current limit is disabled, then the LDO will begin regulating again as soon as the current falls below the clamp threshold.
- With foldback current limit enabled, when current limit trip point is activated,
 - Output voltage drops low, and
 - Output current folds back to approximately 50% of the current limit trip point.
 This results in minimizing the power loss under fault conditions. Monitoring the voltage at the CS terminal indicates voltage proportional to the output current.


8.2.1.5 Transient Response

Figure 16, Figure 17, and Figure 18 indicate the transient response behavior of the LDO for 50% step load change.

Channel 1: Input voltage

Channel 2: Output voltage overshoot/undershoot

Channel 3: Step load in current



8.2.1.6 Current Sharing

For demanding load requirements, multiple LDOs can be paralleled as indicated in [Figure 20](#). In parallel mode, the CS terminal of LDO1 must be connected to the PCL terminal of LDO2 via a series resistor, R_{CL} , and CS terminal of LDO2 must be connected to PCL terminal of LDO1 via series resistor, R_{CL} . The typical value of R_{CL} in parallel operation is 3.75 k Ω for current limit > 6 A. In parallel configuration, R_{CL} (resistor from PCL to GND) and R_{CS} (resistor from CS terminal to V_{IN}) must be left open (unpopulated). The R_{CL} value must be selected so that the operating condition of the CS terminal is maintained, as specified in the [Electrical Characteristics](#) table. The current from PCL through R_{CL} of LDO1 is determined by the output load current of LDO2 divided by the CSR. Hence, the voltage at CS terminal of the LDO1 is 0.605 V – ((output load current of LDO2 + 0.2458) / CSR $\times$ R_{CL}).

Alternately, it can also provide twice the output current to meet system needs. When using two LDOs in parallel operation for higher output load current, use POL TPS50601-SP as an input source.






Figure 19. LDO Current Share



Copyright © 2017, Texas Instruments Incorporated

8.2.1.7 Compensation

Figure 21 shows a generic block diagram for TPS7H1101A-SP LDO with external compensation components. LDO incorporates nested loops, thus providing the high gain necessary to meet design performance.



Copyright © 2017, Texas Instruments Incorporated

Figure 21. TPS7H1101A-SP Compensation

Resistor divider composed of R_{top} and R_{bottom} determine the output voltage set points as indicated by Equation 3.

Output capacitor C_{OUT} introduces a pole and a zero as shown in the following.

$$F_{p_{co}} = \frac{1}{2 \cdot \pi \cdot C_o \cdot R_L} \quad (7)$$

$$F_{z_{co}} = \frac{1}{2 \cdot \pi \cdot C_o \cdot C_{esr}} \quad (8)$$

The TPS7H1101A-SP was designed so that the ESR of the output capacitor will not have a strong influence on the response of the LDO. However, an optional capacitor, C_x , can be added in parallel with the bottom feedback resistor to introduce a pole to cancel $F_{z_{co}}$. Equation 9 shows how to calculate the location of the pole introduced by C_x . To cancel the zero directly, F_p should be equal to $F_{z_{co}}$.

$$F_p = \frac{1}{2 \cdot \pi \cdot C_x \cdot R_{bottom}} \quad (9)$$



C_x is calculated to be 1000 pF for $C_o = 220 \mu F$, $C_{esr} = 45 m\Omega$, and $R_{bottom} = 10 k\Omega$.

Internal compensation in the LDO cancels the output capacitor pole introduced by C_{OUT} and R_L .

C_{comp} introduces a dominant pole at low frequency. TI recommends that a C_{comp} value of 10 nF.

8.2.1.8 Output Noise

Output noise is measured using an HP3495A. Figure 22 and Figure 23 show noise of the TPS7H1101A-SP in $\mu V/\sqrt{Hz}$ vs frequency.



8.2.1.9 Capacitors

TPS7H1101A-SP requires the use of a combination of tantalum and ceramic capacitors to achieve good volume to capacitance ratio. 表 2 highlights some of the capacitors used in the device. TI recommends to follow proper derating guidelines as recommended by the capacitor manufacturer based upon output voltage and operating temperature.

Note that polymer-based tantalum capacitors must be derated to at least 60% of rated voltage, whereas manganese oxide (MnO_2) based tantalum capacitors should be derated to 33% of rated voltage depending upon the operating temperature.

TI recommends to use a tantalum capacitor along with a 0.1- μF ceramic capacitor. The device is stable for input and output tantalum capacitor values of 10 μF to 220 μF with the ESR range of 10 m Ω to 2 Ω . However, the dynamic performance of the device varies based on load conditions and the capacitor values used.

TI recommends a minimum output capacitor of 22 μF with ESR of 1 Ω or less to prevent oscillations. X7R dielectrics are preferred. See 表 2 for various capacitor recommendations.

表 2. TPS7H1101A-SP Capacitors

CAPACITOR PART NUMBER	CAPACITOR DETAILS (CAPACITOR, VOLTAGE, ESR)	TYPE	VENDOR
T493X107K016CH612A ⁽¹⁾	100 μ F, 16 V, 100 m Ω	Tantalum - MnO ₂	Kemet
T493X226M025AH6x20 ⁽¹⁾	22 μ F, 25 V, 35 m Ω	Tantalum - MnO ₂	Kemet
T525D476M016ATE035 ⁽¹⁾	47 μ F, 10 V, 35 m Ω	Tantalum - Polymer	Kemet
T540D476M016AH6520 ⁽¹⁾	47 μ F, 16 V, 20 m Ω	Tantalum - Polymer	Kemet
T525D107M010ATE025 ⁽¹⁾	100 μ F, 10 V, 25 m Ω	Tantalum - Polymer	Kemet
T541X337M010AH6720 ⁽¹⁾	330 μ F, 10 V, 6 m Ω	Tantalum - Polymer	Kemet
T525D227M010ATE025 ⁽¹⁾	220 μ F, 10 V, 25 m Ω	Tantalum - Polymer	Kemet
T495X107K016ATE100 ⁽¹⁾	100 μ F, 16 V, 100 m Ω	Tantalum - MnO ₂	Kemet
CWR29FK227JTHC ⁽¹⁾	220 μ F, 10 V, 180 m Ω	Tantalum - MnO ₂	AVX
THJE107K016AJH	100 μ F, 16 V, 58 m Ω	Tantalum	AVX
THJE227K010AJH	220 μ F, 10 V, 40 m Ω	Tantalum	AVX
SMX33C336KAN360	33 μ F, 25 V	Stacked ceramic	AVX
SR2225X7R335K1P5#M123	3.3 μ F, 25 V, 10 m Ω	Ceramic	Presidio Components Inc

(1) Operating temperature is -55°C to 125°C .

8.2.2 Application Curves




図 24. VDO vs I_{OUT}

9 Power Supply Recommendations


This device is designed to operate with an input voltage supply up to 7 V. The minimum input voltage should provide adequate headroom greater than the dropout voltage for the device to have a regulated output. If the input supply is noisy, additional input capacitors with low ESR can help improve the output noise performance.

10 Layout

10.1 Layout Guidelines

- For best performance, all traces should be as short as possible, and no longer than 5 cm.
- Use wide traces for IN, OUT and GND to minimize the parasitic electrical effects.
- Place the output capacitors (COUT) as close as possible to the OUT pin of the device.

10.2 Layout Example



✕ 25. PCB Layout Example

11 デバイスおよびドキュメントのサポート

11.1 デバイス・サポート

11.1.1 デベロッパー・ネットワークの製品に関する免責事項

デベロッパー・ネットワークの製品またはサービスに関するTIの出版物は、単独またはTIの製品、サービスと一緒に提供される場合に関係なく、デベロッパー・ネットワークの製品またはサービスの適合性に関する是認、デベロッパー・ネットワークの製品またはサービスの是認の表明を意味するものではありません。

11.1.2 デバイスの項目表記

KGD 品質保証のベア・ダイ

RHA 宇宙用システム向けの放射線強度保証

5962R13202 TPS50601-SPと同じデバイスで、標準のマイクロ回路図面(SMD)とともに示されています。

TPS7H1101A-SP 5962R10221と同じデバイスで、TIのパッケージ図とともに示されています。

11.2 ドキュメントのサポート

11.2.1 関連資料

(1) 『固定レギュレータの安定性評価』, Tom Boehler, Paul Ho, AEI Systems

11.3 ドキュメントの更新通知を受け取る方法

ドキュメントの更新についての通知を受け取るには、ti.comのデバイス製品フォルダを開いてください。右上の隅にある「通知を受け取る」をクリックして登録すると、変更されたすべての製品情報に関するダイジェストを毎週受け取れます。変更の詳細については、修正されたドキュメントに含まれている改訂履歴をご覧ください。

11.4 コミュニティ・リソース

The following links connect to TI community resources. Linked contents are provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's [Terms of Use](#).

TI E2E™ オンライン・コミュニティ TIのE2E (Engineer-to-Engineer) コミュニティ。エンジニア間の共同作業を促進するために開設されたものです。e2e.ti.comでは、他のエンジニアに質問し、知識を共有し、アイデアを検討して、問題解決に役立てることができます。

設計サポート TIの設計サポート役に立つE2Eフォーラムや、設計サポート・ツールをすばやく見つけることができます。技術サポート用の連絡先情報も参照できます。

11.5 商標

E2E is a trademark of Texas Instruments.

All other trademarks are the property of their respective owners.

11.6 静電気放電に関する注意事項



これらのデバイスは、限定的なESD(静電破壊)保護機能を内蔵しています。保存時または取り扱い時は、MOSゲートに対する静電破壊を防止するために、リード線同士をショートさせておくか、デバイスを導電フォームに入れる必要があります。

11.7 Glossary

SLYZ022 — TI Glossary.

This glossary lists and explains terms, acronyms, and definitions.

12 メカニカル、パッケージ、および注文情報

以降のページには、メカニカル、パッケージ、および注文に関する情報が記載されています。この情報は、そのデバイスについて利用可能な最新のデータです。このデータは予告なく変更されることがあり、ドキュメントが改訂される場合もあります。本データシートのブラウザ版を使用されている場合は、画面左側の説明をご覧ください。

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package Pins	Package qty Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
5962R1320202V9A	Active	Production	XCEPT (KGD) 0	70 OTHER	Yes	Call TI	N/A for Pkg Type	-55 to 125	
5962R1320202VXC	Active	Production	CFP (HKR) 16	25 TUBE	ROHS Exempt	NIAU	N/A for Pkg Type	-55 to 125	5962R1320202VXC TPS7H1101-RHA
5962R1320202VXC.A	Active	Production	CFP (HKR) 16	25 TUBE	ROHS Exempt	NIAU	N/A for Pkg Type	-55 to 125	5962R1320202VXC TPS7H1101-RHA
TPS7H1101AHKR/EM	Active	Production	CFP (HKR) 16	25 TUBE	ROHS Exempt	NIAU	N/A for Pkg Type	25 to 25	TPS7H1101AHKR/EM EVAL ONLY
TPS7H1101AY/EM	Active	Production	XCEPT (KGD) 0	5 OTHER	Yes	Call TI	N/A for Pkg Type	25 to 25	
TPS7H1101HKR/EM	Active	Production	CFP (HKR) 16	25 TUBE	ROHS Exempt	NIAU	N/A for Pkg Type	25 to 25	TPS7H1101HKREM

⁽¹⁾ **Status:** For more details on status, see our [product life cycle](#).

⁽²⁾ **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

⁽⁴⁾ **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.



⁽⁵⁾ **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

⁽⁶⁾ **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.



4226020/C 08/2022

NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This package is hermetically sealed with a metal lid. Lid is connected to Heatsink.
4. The terminals are gold plated.
5. Falls within MIL-STD-1835 CDFP-F11A.

EXAMPLE BOARD LAYOUT

HKR0016A

CFP - 2.416 mm max height

CERAMIC DUAL FLATPACK



HEATSINK LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE:10X

4226020/C 08/2022

重要なお知らせと免責事項

テキサス・インスツルメンツは、技術データと信頼性データ (データシートを含みます)、設計リソース (リファレンス デザインを含みます)、アプリケーションや設計に関する各種アドバイス、Web ツール、安全性情報、その他のリソースを、欠陥が存在する可能性のある「現状のまま」提供しており、商品性および特定目的に対する適合性の黙示保証、第三者の知的財産権の非侵害保証を含むいかなる保証も、明示的または黙示的にかかわらず拒否します。

これらのリソースは、テキサス・インスツルメンツ製品を使用する設計の経験を積んだ開発者への提供を意図したものです。(1) お客様のアプリケーションに適した テキサス・インスツルメンツ製品の選定、(2) お客様のアプリケーションの設計、検証、試験、(3) お客様のアプリケーションに該当する各種規格や、その他のあらゆる安全性、セキュリティ、規制、または他の要件への確実な適合に関する責任を、お客様のみが単独で負うものとします。

上記の各種リソースは、予告なく変更される可能性があります。これらのリソースは、リソースで説明されている テキサス・インスツルメンツ製品を使用するアプリケーションの開発の目的でのみ、テキサス・インスツルメンツはその使用をお客様に許諾します。これらのリソースに関して、他の目的で複製することや掲載することは禁止されています。テキサス・インスツルメンツや第三者の知的財産権のライセンスが付与されている訳ではありません。お客様は、これらのリソースを自身で使用した結果発生するあらゆる申し立て、損害、費用、損失、責任について、テキサス・インスツルメンツおよびその代理人を完全に補償するものとし、テキサス・インスツルメンツは一切の責任を拒否します。

テキサス・インスツルメンツの製品は、[テキサス・インスツルメンツの販売条件](#)、または [ti.com](https://www.ti.com) やかかる テキサス・インスツルメンツ製品の関連資料などのいずれかを通じて提供する適用可能な条項の下で提供されています。テキサス・インスツルメンツがこれらのリソースを提供することは、適用される テキサス・インスツルメンツの保証または他の保証の放棄の拡大や変更を意味するものではありません。

お客様がいかなる追加条項または代替条項を提案した場合でも、テキサス・インスツルメンツはそれらに異議を唱え、拒否します。

郵送先住所：Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2025, Texas Instruments Incorporated