

CC1312R SimpleLink[™] High-Performance Sub-1 GHz Wireless MCU

1 Features

- Microcontroller
 - Powerful 48-MHz Arm[®] Cortex[®]-M4F processor
 - EEMBC CoreMark® score: 148
 - 352KB of in-system programmable flash
 - 256KB of ROM for protocols and library functions
 - 8KB of cache SRAM (alternatively available as general-purpose RAM)
 - 80KB of ultra-low leakage SRAM. The SRAM is protected by parity to ensure high reliability of operation.
 - 2-pin cJTAG and JTAG debugging
 - Supports over-the-air (OTA) update
- Ultra-low power sensor controller with 4KB of SRAM
 - Sample, store, and process sensor data
 - Operation independent from system CPU
 - Fast wake-up for low-power operation
- TI-RTOS, drivers, bootloader, and IEEE 802.15.4 MAC in ROM for optimized application size
- RoHS-compliant package
 - 7-mm × 7-mm RGZ VQFN48 (30 GPIOs)
- Peripherals
 - Digital peripherals can be routed to any GPIO
 - 4× 32-bit or 8× 16-bit general-purpose timers
 - 12-bit ADC, 200 kSamples/s, 8 channels
 - 2× comparators with internal reference DAC (1× continuous time, 1× ultra-low power)
 - Programmable current source
 - 2× UART
 - 2× SSI (SPI, MICROWIRE, TI)
 - I²C
 - I²S
 - Real-time clock (RTC)
 - AES 128- and 256-bit cryptographic accelerator
 - ECC and RSA public key hardware accelerator
 - SHA2 accelerator (full suite up to SHA-512)
 - True random number generator (TRNG)
 - Capacitive sensing, up to 8 channels
 - Integrated temperature and battery monitor
- External system
 - On-chip buck DC/DC converter
- TCXO support
- Low power
 - Wide supply voltage range: 1.8 V to 3.8 V

- Active mode RX: 5.8 mA (3.6 V, 868 MHz)
- Active mode TX at +14 dBm: 24.9 mA (868 MHz)
- Active mode MCU 48 MHz (CoreMark): 2.9 mA (60 µA/MHz)
- Sensor controller, low power-mode, 2 MHz, running infinite loop: 30.1 μA
- Sensor controller, active mode, 24 MHz, running infinite loop: 808 μA
- Standby: 0.85 µA (RTC on, 80KB RAM and CPU retention)
- Shutdown: 150 nA (wakeup on external events)
- Radio section
 - Flexible high-performance sub-1 GHz RF transceiver
 - Excellent receiver sensitivity:
 -121 dBm for SimpleLink long-range mode
 -110 dBm at 50 kbps
 - Output power up to +14 dBm with temperature compensation
 - Suitable for systems targeting compliance with worldwide radio frequency regulations
 - ETSI EN 300 220 Receiver Category 1.5 and 2, EN 303 131, EN 303 204 (Europe)
 - FCC CFR47 Part 15
 - ARIB STD-T108
 - Wide standard support
- Wireless protocols
 - IEEE 802.15.4g, IPv6-enabled smart objects (6LoWPAN), MIOTY[®], Wireless M-Bus, Wi-SUN[®], KNX RF, Amazon Sidewalk, proprietary systems, SimpleLink[™] TI 15.4 stack (Sub-1 GHz), and dynamic multiprotocol manager (DMM) driver.
- Development Tools and Software
 - CC1312R LaunchPad™ Development Kit
 - SimpleLink™ CC13x2 and CC26x2 Software Development Kit (SDK)
 - SmartRF[™] Studio for simple radio configuration
 - Sensor Controller Studio for building low-power sensing applications

An IMPORTANT NOTICE at the end of this data sheet addresses availability, warranty, changes, use in safety-critical applications, intellectual property matters and other important disclaimers. PRODUCTION DATA.



2 Applications

- 169, 433, 470 to 510, 868, and 902 to 928 MHz ISM and SRD systems ¹ with down to 4 kHz of receive bandwidth
- Building automation
 - Building security systems motion detector, electronic smart lock, door and window sensor, garage door system, gateway
 - HVAC thermostat, wireless environmental sensor, HVAC system controller, gateway
 - Fire safety system smoke and heat detector, fire alarm control panel (FACP)
 - Video surveillance IP network camera
 - Elevators and escalators elevator main control panel for elevators and escalators
- Grid infrastructure
 - Smart meters water meter, gas meter, electricity meter, and heat cost allocators

- Grid communications wireless communications – Long-range sensor applications
- Other alternative energy energy harvesting
- Industrial transport asset tracking
- Factory automation and control
- Medical
- Electronic point of sale (EPOS) Electronic Shelf Label (ESL)
- Personal electronics
 - Connected peripherals consumer wireless module
 - Home theater & entertainment smart speakers, set-top box
 - Gaming
 - Wearables (non-medical)

3 Description

The SimpleLink[™] CC1312R device is a multiprotocol Sub-1 GHz wireless microcontroller (MCU) supporting IEEE 802.15.4g, IPv6-enabled smart objects (6LoWPAN), MIOTY[®], Wi-SUN[®], proprietary systems, including the TI 15.4-Stack (Sub-1 GHz). The device is optimized for low-power wireless communication and advanced sensing in building security systems, HVAC, smart meters, medical, wired networking, portable electronics, home theater & entertainment, and connected peripherals markets. The highlighted features of this device include:

- Flexible Sub-1 GHz radio supporting industry standard frequency bands (315 MHz, 433 MHz, 868 MHz, 900 MHz, and more) to meet the industrial needs.
- Wide flexibility of protocol stack support in the SimpleLink[™] CC13x2 and CC26x2 Software Development Kit (SDK) including complete SimpleLink[™] 15.4-Stack (Sub-1 GHz) solution.
- Maximum transmit power of +14 dBm at Sub-1 GHz with 24.9 mA current consumption.
- Longer battery life wireless applications with low standby current of 0.85 µA and full RAM retention.
- Industrial temperature ready with lowest standby current of 11 μA at 105°C.
- Advanced sensing with a programmable, autonomous ultra-low power Sensor Controller CPU with fast wakeup capability. As an example, the sensor controller is capable of 1-Hz ADC sampling at 1 µA system current.
- Low SER (Soft Error Rate) FIT (Failure-in-time) for long operation lifetime with no disruption for industrial markets with always-on SRAM parity against corruption due to potential radiation events.
- Dedicated software controlled radio controller (Arm[®] Cortex[®]-M0) providing flexible low-power RF transceiver capability to support multiple physical layers and RF standards.
- Excellent radio sensitivity (-121 dBm) and robustness (selectivity and blocking) performance for SimpleLink™ long-range mode.

The CC1312R device is part of the SimpleLink™ MCU platform, which consists of

Wi-Fi[®], *Bluetooth* Low Energy, Thread, Zigbee, Sub-1 GHz MCUs, and host MCUs that all share a common, easy-to-use development environment with a single core software development kit (SDK) and rich tool set. A one-time integration of the SimpleLink[™] platform enables you to add any combination of the portfolio's devices into your design, allowing 100 percent code reuse when your design requirements change. For more information, visit SimpleLink[™] MCU platform.

¹ See *RF Core* for additional details on supported protocol standards, modulation formats, and data rates.



Device Information				
PART NUMBER ⁽¹⁾	PACKAGE	BODY SIZE (NOM)		
CC1312R1F3RGZ	VQFN (48)	7.00 mm × 7.00 mm		

(1) For the most current part, package, and ordering information for all available devices, see the Package Option Addendum in Section 12, or see the TI website.

4 Functional Block Diagram







Table of Contents

1 Features	1
2 Applications	2
3 Description	2
4 Functional Block Diagram	3
5 Revision History	5
6 Device Comparison	<mark>6</mark>
7 Terminal Configuration and Functions	7
7.1 Pin Diagram – RGZ Package (Top View)	7
7.2 Signal Descriptions – RGZ Package	8
7.3 Connections for Unused Pins and Modules	9
8 Specifications	10
8.1 Absolute Maximum Ratings	10
8.2 ESD Ratings	10
8.3 Recommended Operating Conditions	10
8.4 Power Supply and Modules	11
8.5 Power Consumption - Power Modes	12
8.6 Power Consumption - Radio Modes	13
8.7 Nonvolatile (Flash) Memory Characteristics	13
8.8 Thermal Resistance Characteristics	14
8.9 RF Frequency Bands	14
8.10 861 MHz to 1054 MHz - Receive (RX)	15
8.11 861 MHz to 1054 MHz - Transmit (TX)	18
8.12 861 MHz to 1054 MHz - PLL Phase Noise	
Wideband Mode	19
8.13 861 MHz to 1054 MHz - PLL Phase Noise	
Narrowband Mode	19
8.14 359 MHz to 527 MHz - Receive (RX)	20
8.15 359 MHz to 527 MHz - Transmit (TX)	22
8.16 359 MHZ to 527 MHZ - PLL Phase Noise	23
8.1/ 143 MHZ to 1/6 MHZ - Receive (RX)	24
8.18 143 MHZ to 1/6 MHZ - Iransmit (IX)	25
8.19 143 WHZ TO 1/6 MHZ - PLL Phase Noise	25

	8.20 Timing and Switching Characteristics	25
	8.21 Peripheral Characteristics	31
	8.22 Typical Characteristics	39
9	Detailed Description	55
	9.1 Overview	55
	9.2 System CPU	55
	9.3 Radio (RF Core)	.56
	9.4 Memory	57
	9.5 Sensor Controller	58
	9.6 Cryptography	59
	9.7 Timers	60
	9.8 Serial Peripherals and I/O	61
	9.9 Battery and Temperature Monitor	61
	9.10 µDMA	61
	9.11 Debug	.61
	9.12 Power Management	62
	9.13 Clock Systems	63
	9.14 Network Processor	.63
1() Application, Implementation, and Layout	64
	10.1 Reference Designs	64
	10.2 Junction Temperature Calculation	.65
11	Device and Documentation Support	66
	11.1 Tools and Software	.66
	11.2 Documentation Support	68
	11.3 Support Resources	69
	11.4 Trademarks	69
	11.5 Electrostatic Discharge Caution	69
	11.6 Glossary	69
12	2 Mechanical, Packaging, and Orderable	
	Information	70
	12.1 Packaging Information	70



5 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

Changes from May 19, 2020 to November 18, 2020 (from Revision G (May 2020) to Revision H (November 2020))

(N	lovember 2020))	Page
•	Updated the numbering format for tables, figures, and cross-references throughout the document	1
•	Added Amazon Sidewalk to the Wireless protocols list item in Section 1, Features	1
•	Added TCXO support in Section 1, Features	1
•	Added 169 MHz band in Section 2, Applications	2
•	Changed the test condition to "Zero cycles" for the Flash sector erase time parameter in Section 8.7,	
	Nonvolatile (Flash) Memory Characteristics	10
•	Added the 169 MHz band in Section 8.9, RF Frequency Bands	10
•	Changed the name of "802.15.4g Mandatory Mode" to "IEEE 802.15.4" and added deviation to condition Section 8.10, 861 MHz to 1054 MHz - Receive (RX)	s in 10
•	Added the following sections to Section 8.10, 861 MHz to 1054 MHz - Receive (RX): 100 kbps, ±25 kHz deviation, 2-GFSK, 137 kHz RX Bandwidth; 200 kbps, ±50 kHz deviation, 2-GFSK, 311 kHz RX Bandwidth; 500 kbps, ±190 kHz deviation, 2-GFSK, 1150 kHz RX Bandwidth; OOK, 4.8 kbps; Narrowband, 9.6 kbps kHz deviation, 2-GFSK, 868 MHz, 17.1 kHz RX Bandwidth; 1 Mbps, ±350 kHz deviation, 2-GFSK, 2.2 MI RX Bandwidth; Wi-SUN; WB-DSSS, 240/120/60/30 kbps (480 ksym/s, 2-GFSK, ±195 kHz Deviation, FEG (Half Rate), DSSS = 1/2/4/8, 622 kHz RX BW).	lth; ±2.4 Hz C 10
•	Added the Adjacent Channel Power and Alternate Channel Power parameters to Section 8.11, 861 MHz 1054 MHz - Receive (TX)	<i>to</i> 10
•	Added the OOK 4.8 kbps section to Section 8.14, 359 MHz to 527 MHz - Receive (RX)	10
•	Added 143 MHz to 176 MHz band specifications: Section 8.17, Section 8.18, and Section 8.19	10
•	Added Section 8.20.3.1, 48 MHz Clock Input (TCXO)	27
•	Changed the frequency of the input tone for 14-bit and 15-bit mode in Section 8.21.1.1	31
•	Updated Figure 8-17; added Figure 8-18, Figure 8-19, and Figure 8-20	45
•	Added the TXCO option in the paragraph that begins "The 48 MHz SCLK_HF is used as" in Section 9. <i>Clock Systems</i>	13, 63
•	Added the paragraph that begins "Integrated matched filter-balun devices can be used" in Section 10.1 <i>Reference Designs</i>	l, 64



6 Device Comparison

DEVICE	VICE RADIO SUPPORT		RAM (KB)	GPIO	PACKAGE SIZE
CC1312R	Sub-1 GHz	352	80	30	RGZ (7-mm × 7-mm VQFN48)
CC1352P	Multiprotocol Sub-1 GHz Bluetooth 5.1 Low Energy Zigbee Thread 2.4 GHz proprietary FSK-based formats +20-dBm high-power amplifier	352	80	26	RGZ (7-mm × 7-mm VQFN48)
CC1352R	Multiprotocol Sub-1 GHz Bluetooth 5.1 Low Energy Zigbee Thread 2.4 GHz proprietary FSK-based formats	352	80	28	RGZ (7-mm × 7-mm VQFN48)
CC2642R	Bluetooth 5.1 Low Energy 2.4 GHz proprietary FSK-based formats	352	80	31	RGZ (7-mm × 7-mm VQFN48)
CC2642R-Q1	Bluetooth 5.1 Low Energy	352	80	31	RTC (7-mm × 7-mm VQFN48)
CC2652R	Multiprotocol Bluetooth 5.1 Low Energy Zigbee Thread 2.4 GHz proprietary FSK-based formats	352	80	31	RGZ (7-mm × 7-mm VQFN48)
CC2652RB	Multiprotocol Bluetooth 5.1 Low Energy Zigbee Thread 2.4 GHz proprietary FSK-based formats	352	80	31	RGZ (7-mm × 7-mm VQFN48)
CC2652P	Multiprotocol Bluetooth 5.1 Low Energy Zigbee Thread 2.4 GHz proprietary FSK-based formats +19.5-dBm high-power amplifier	352	80	26	RGZ (7-mm × 7-mm VQFN48)
CC1310	Sub-1 GHz	32–128	16–20	10–31	RGZ (7-mm × 7-mm VQFN48) RHB (5-mm × 5-mm VQFN32) RSM (4-mm × 4-mm VQFN32)
CC1350	Sub-1 GHz Bluetooth 4.2 Low Energy	128	20	10–31	RGZ (7-mm × 7-mm VQFN48) RHB (5-mm × 5-mm VQFN32) RSM (4-mm × 4-mm VQFN32)
CC2640R2F	Bluetooth 5.1 Low Energy 2.4 GHz proprietary FSK-based formats	128	20	10–31	RGZ (7-mm × 7-mm VQFN48) RHB (5-mm × 5-mm VQFN32) RSM (4-mm × 4-mm VQFN32) YFV (2.7-mm × 2.7-mm DSBGA34)
CC2640R2F-Q1	Bluetooth 5.1 Low Energy 2.4 GHz proprietary FSK-based formats	128	20	31	RGZ (7-mm × 7-mm VQFN48)

Table 6-1. Device Family Overview



7 Terminal Configuration and Functions

7.1 Pin Diagram – RGZ Package (Top View)



Figure 7-1. RGZ (7-mm × 7-mm) Pinout, 0.5-mm Pitch (Top View)

The following I/O pins marked in Figure 7-1 in **bold** have high-drive capabilities:

- Pin 10, DIO_5
- Pin 11, DIO_6
- Pin 12, DIO_7
- Pin 24, JTAG_TMSC
- Pin 26, DIO_16
- Pin 27, DIO_17

The following I/O pins marked in Figure 7-1 in *italics* have analog capabilities:

- Pin 36, DIO_23
- Pin 37, DIO 24
- Pin 38, DIO_25
- Pin 39, DIO_26
- Pin 40, DIO_27
- Pin 41, DIO 28
- Pin 42, DIO_29
- Pin 43, DIO_30



7.2 Signal Descriptions – RGZ Package

Table 7-1. Signal Descriptions – RGZ Package

PIN		1/0	TVDE	DESCRIPTION		
NAME	NO.		ITPE	DESCRIPTION		
DCDC_SW	33	_	Power	Output from internal DC/DC converter ⁽¹⁾		
DCOUPL	23	_	Power	For decoupling of internal 1.27 V regulated digital-supply ⁽²⁾		
DIO_1	6	I/O	Digital	GPIO		
DIO_2	7	I/O	Digital	GPIO		
DIO_3	8	I/O	Digital	GPIO		
DIO_4	9	I/O	Digital	GPIO		
DIO_5	10	I/O	Digital	GPIO, high-drive capability		
DIO_6	11	I/O	Digital	GPIO, high-drive capability		
DIO_7	12	I/O	Digital	GPIO, high-drive capability		
DIO_8	14	I/O	Digital	GPIO		
DIO_9	15	I/O	Digital	GPIO		
DIO_10	16	I/O	Digital	GPIO		
DIO_11	17	I/O	Digital	GPIO		
DIO_12	18	I/O	Digital	GPIO		
DIO_13	19	I/O	Digital	GPIO		
DIO_14	20	I/O	Digital	GPIO		
DIO_15	21	I/O	Digital	GPIO		
DIO_16	26	I/O	Digital	GPIO, JTAG_TDO, high-drive capability		
DIO_17	27	I/O	Digital	GPIO, JTAG_TDI, high-drive capability		
DIO_18	28	I/O	Digital	GPIO		
DIO_19	29	I/O	Digital	GPIO		
DIO_20	30	I/O	Digital	GPIO		
DIO_21	31	I/O	Digital	GPIO		
DIO_22	32	I/O	Digital	GPIO		
DIO_23	36	I/O	Digital or Analog	GPIO, analog capability		
DIO_24	37	I/O	Digital or Analog	GPIO, analog capability		
DIO_25	38	I/O	Digital or Analog	GPIO, analog capability		
DIO_26	39	I/O	Digital or Analog	GPIO, analog capability		
DIO_27	40	I/O	Digital or Analog	GPIO, analog capability		
DIO_28	41	I/O	Digital or Analog	GPIO, analog capability		
DIO_29	42	I/O	Digital or Analog	GPIO, analog capability		
DIO_30	43	I/O	Digital or Analog	GPIO, analog capability		
EGP	_	_	GND	Ground – exposed ground pad ⁽³⁾		
JTAG_TMSC	24	I/O	Digital	JTAG TMSC, high-drive capability		
JTAG_TCKC	25	I	Digital	JTAG TCKC		
RESET_N	35	I	Digital	Reset, active low. No internal pullup resistor		
RF_P	1	_	RF	Positive RF input signal to LNA during RX Positive RF output signal from PA during TX		
RF_N	2	_	RF	Negative RF input signal to LNA during RX Negative RF output signal from PA during TX		
RX_TX	3		RF	Optional bias pin for the RF LNA		
VDDR	45	_	Power	Internal supply, must be powered from the internal DC/DC converter or the internal LDO ⁽⁴⁾ $^{(2)}$ $^{(6)}$		



Table 7-1. Signal Descriptions – RGZ Package (continued)

PIN		1/0	TVDE	DESCRIPTION	
NAME	NO.	1/0	ITFE	DESCRIPTION	
VDDR_RF	48	_	Power	Internal supply, must be powered from the internal DC/DC converter or the internal LDO ⁽⁵⁾ $^{(2)}$ $^{(6)}$	
VDDS	44	_	Power	1.8-V to 3.8-V main chip supply ⁽¹⁾	
VDDS2	13	_	Power 1.8-V to 3.8-V DIO supply ⁽¹⁾		
VDDS3	22	—	Power 1.8-V to 3.8-V DIO supply ⁽¹⁾		
VDDS_DCDC	34	_	Power	1.8-V to 3.8-V DC/DC converter supply	
X48M_N	46	—	Analog	48-MHz crystal oscillator pin 1	
X48M_P	47	_	Analog	48-MHz crystal oscillator pin 2	
X32K_Q1	4	—	Analog	32-kHz crystal oscillator pin 1	
X32K_Q2	5	_	Analog	32-kHz crystal oscillator pin 2	

(1) For more details, see technical reference manual listed in Section 11.2.

(2) Do not supply external circuitry from this pin.

(3) EGP is the only ground connection for the device. Good electrical connection to device ground on printed circuit board (PCB) is imperative for proper device operation.

(4) If internal DC/DC converter is not used, this pin is supplied internally from the main LDO.

(5) If internal DC/DC converter is not used, this pin must be connected to VDDR for supply from the main LDO.

(6) Output from internal DC/DC and LDO is trimmed to 1.68 V.

7.3 Connections for Unused Pins and Modules

Table 7-2. Connections for Unused Pins

FUNCTION	SIGNAL NAME	PIN NUMBER	ACCEPTABLE PRACTICE ⁽¹⁾	PREFERRED PRACTICE ⁽¹⁾
GPIO	DIO_n	6–12 14–21 26–32 36–43	NC or GND	NC
32 768-kHz crystal	X32K_Q1	4		NC
52.700-K12 Ci ystai	X32K_Q2	5		NO
DC/DC converter ⁽²⁾	DCDC_SW	33	NC	NC
	VDDS_DCDC	34	VDDS	VDDS

(1) NC = No connect

(2) When the DC/DC converter is not used, the inductor between DCDC_SW and VDDR can be removed. VDDR and VDDR_RF must still be connected and the 22 uF DCDC capacitor must be kept on the VDDR net.

8 Specifications

8.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)⁽¹⁾ (2)

			MIN	MAX	UNIT
VDDS ⁽³⁾	Supply voltage		-0.3	4.1	V
	Voltage on any digital p	in ⁽⁴⁾	-0.3	VDDS + 0.3, max 4.1	V
	Voltage on crystal oscil	lator pins, X32K_Q1, X32K_Q2, X48M_N and X48M_P	-0.3	VDDR + 0.3, max 2.25	V
	V _{in} Voltage on ADC input	Voltage scaling enabled	-0.3	VDDS	
Vin		Voltage scaling disabled, internal reference	-0.3	1.49	V
		Voltage scaling disabled, VDDS as reference	-0.3	VDDS / 2.9	
	Input level, RF pins			10	dBm
T _{stg}	Storage temperature		-40	150	°C

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under Recommended Operating Conditions is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

(2) All voltage values are with respect to ground, unless otherwise noted.

(3) VDDS_DCDC, VDDS2 and VDDS3 must be at the same potential as VDDS.

(4) Including analog capable DIOs.

8.2 ESD Ratings

				VALUE	UNIT
V	Electrostatic	Human body model (HBM), per ANSI/ESDA/JEDEC JS-001 ⁽¹⁾	All pins	±2000	V
VESD	discharge	Charged device model (CDM), per ANSI/ESDA/JEDEC JS-002 ⁽²⁾	All pins	±500	V

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process

8.3 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)

		MIN	MAX	UNIT
Operating junction temperature ⁽²⁾		-40	105	°C
Operating supply voltage (VDDS)		1.8	3.8	V
Operating supply voltage (VDDS), boost mode	VDDR = 1.95 V +14 dBm RF output power	2.1	3.8	V
Rising supply voltage slew rate		0	100	mV/µs
Falling supply voltage slew rate ⁽¹⁾		0	20	mV/µs

(1) For small coin-cell batteries, with high worst-case end-of-life equivalent source resistance, a 22-µF VDDS input capacitor must be used to ensure compliance with this slew rate.

(2) For thermal resistance characteristics refer to Section 8.8. For application considerations, refer to Section 10.2.



8.4 Power Supply and Modules

over operating free-air temperature range (unless otherwise noted)

PARAMETER		MIN	TYP	MAX	UNIT
VDDS Power-on-Reset (POR) threshold			1.1 - 1.55		V
VDDS Brown-out Detector (BOD) ⁽¹⁾	Rising threshold		1.77		V
VDDS Brown-out Detector (BOD), before initial boot ⁽²⁾	Rising threshold		1.70		V
VDDS Brown-out Detector (BOD) ⁽¹⁾	Falling threshold		1.75		V

(1) For boost mode (VDDR =1.95 V), TI drivers software initialization will trim VDDS BOD limits to maximum (approximately 2.0 V)

(2) Brown-out Detector is trimmed at initial boot, value is kept until device is reset by a POR reset or the RESET_N pin



8.5 Power Consumption - Power Modes

When measured on the CC1312REM-XD7793 reference design with T_c = 25 °C, V_{DDS} = 3.6 V with DC/DC enabled unless otherwise noted.

PARAMETER		TEST CONDITIONS	TYP	UNIT
Core Current Consumption		· · · · · · · · · · · · · · · · · · ·		
	Reset and Shutdown	Reset. RESET_N pin asserted or VDDS below power-on-reset threshold	150	nA
		Shutdown. No clocks running, no retention	150	
	Standby	RTC running, CPU, 80KB RAM and (partial) register retention. RCOSC_LF	0.85	μA
I _{core}	retention	RTC running, CPU, 80KB RAM and (partial) register retention XOSC_LF	0.99	μA
	Standby	RTC running, CPU, 80KB RAM and (partial) register retention. RCOSC_LF	2.78	μA
	with cache retention	RTC running, CPU, 80KB RAM and (partial) register retention. XOSC_LF	2.92	μA
	Idle	Supply Systems and RAM powered RCOSC_HF	590	μA
	Active	MCU running CoreMark at 48 MHz RCOSC_HF	2.89	mA
Peripheral Cur	rent Consumption ⁽¹⁾ ,	(2)		
	Peripheral power domain	Delta current with domain enabled	82.3	
	Serial power domain	Delta current with domain enabled	5.5	
	RF Core	Delta current with power domain enabled, clock enabled, RF core idle	178.9	
	μDMA	Delta current with clock enabled, module is idle	53.6	
	Timers	Delta current with clock enabled, module is idle ⁽⁵⁾	67.8	
I _{peri}	12C	Delta current with clock enabled, module is idle	8.2	μΑ
	12S	Delta current with clock enabled, module is idle	21.7	
	SSI	Delta current with clock enabled, module is idle ⁽⁴⁾	69.4	
	UART	Delta current with clock enabled, module is idle ⁽³⁾	140.8	
	CRYPTO (AES)	Delta current with clock enabled, module is idle	21.1	
	РКА	Delta current with clock enabled, module is idle	71.1	
	TRNG	Delta current with clock enabled, module is idle	29.7	
Sensor Contro	ller Engine Consump	tion		
1	Active mode	24 MHz, infinite loop, V _{DDS} = 3.0 V	808.5	
SCE	Low-power mode	2 MHz, infinite loop, V _{DDS} = 3.0 V	30.1	μΑ

(1) Adds to core current I_{core} for each peripheral unit activated.

(2) I_{peri} is not supported in Standby or Shutdown modes.

(3) Only one UART running

(4) Only one SSI running

(5) Only one GPTimer running



8.6 Power Consumption - Radio Modes

When measured on the CC1312REM-XD7793 reference design with $T_c = 25$ °C, $V_{DDS} = 3.6$ V with DC/DC enabled unless otherwise noted.

Using boost mode (increasing VDDR up to 1.95 V), will increase system current by 15% (does not apply to TX +14 dBm setting where this current is already included).

Relevant I_{core} and I_{peri} currents are included in below numbers.

PARAMETER	TEST CONDITIONS	TYP	UNIT
Radio receive current, 868 MHz		5.8	mA
Radio transmit current	0 dBm output power setting 868 MHz	8.0	mA
	+10 dBm output power setting 868 MHz	14.3	mA
Radio transmit current Boost mode	+14 dBm output power setting 868 MHz	24.9	mA

8.7 Nonvolatile (Flash) Memory Characteristics

Over operating free-air temperature range and V_{DDS} = 3.0 V (unless otherwise noted)

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Flash sector size			8		KB
Supported flash erase cycles before failure, full bank ⁽¹⁾ ⁽⁵⁾		30			k Cycles
Supported flash erase cycles before failure, single sector ⁽²⁾		60			k Cycles
Maximum number of write operations per row before sector erase ⁽³⁾				83	Write Operations
Flash retention	105 °C	11.4			Years at 105 °C
Flash sector erase current	Average delta current		10.7		mA
Flash sector erase time ⁽⁴⁾	Zero cycles		10		ms
Flash write current	Average delta current, 4 bytes at a time		6.2		mA
Flash write time ⁽⁴⁾	4 bytes at a time		21.6		μs

(1) A full bank erase is counted as a single erase cycle on each sector

- (3) Each wordline is 2048 bits (or 256 bytes) wide. This limitation corresponds to sequential memory writes of 4 (3.1) bytes minimum per write over a whole wordline. If additional writes to the same wordline are required, a sector erase is required once the maximum number of write operations per row is reached.
- (4) This number is dependent on Flash aging and increases over time and erase cycles
- (5) Aborting flash during erase or program modes is not a safe operation.

⁽²⁾ Up to 4 customer-designated sectors can be individually erased an additional 30k times beyond the baseline bank limitation of 30k cycles

8.8 Thermal Resistance Characteristics

		PACKAGE	
	THERMAL METRIC ⁽¹⁾	RGZ (VQFN)	UNIT
		48 PINS	
R _{θJA}	Junction-to-ambient thermal resistance	23.4	°C/W ⁽²⁾
R _{0JC(top)}	Junction-to-case (top) thermal resistance	13.3	°C/W ⁽²⁾
R _{θJB}	Junction-to-board thermal resistance	8.0	°C/W ⁽²⁾
ΨJT	Junction-to-top characterization parameter	0.1	°C/W ⁽²⁾
ΨЈВ	Junction-to-board characterization parameter	7.9	°C/W ⁽²⁾
R _{θJC(bot)}	Junction-to-case (bottom) thermal resistance	1.7	°C/W ⁽²⁾

(1) For more information about traditional and new thermal metrics, see Semiconductor and IC Package Thermal Metrics.

(2) °C/W = degrees Celsius per watt.

8.9 RF Frequency Bands

Over operating free-air temperature range (unless otherwise noted).

PARAMETER	MIN	TYP MAX	UNIT
	1076	1315	
	861	1054	
Fraguency bands	431	527	MU-7
Frequency bands	359	439	INITIZ
	287	351	
	143	176	



8.10 861 MHz to 1054 MHz - Receive (RX)

When measured on the CC1312REM-XD7793 reference design with $T_c = 25$ °C, $V_{DDS} = 3.0$ V with DC/DC enabled unless otherwise noted. All measurements are performed at the antenna input with a combined RX and TX path. All measurements are performed conducted.

PARAMETER	TEST CONDITIONS	MIN TY	P MAX	UNIT	
General Parameters	·				
Digital channel filter programmable receive bandwidth		4	4000	kHz	
Data rate step size		1.	5	bps	
Spurious emissions 25 MHz to 1 GHz	868 MHz	< -5	7	dBm	
Spurious emissions 1 GHz to 13 GHz	Conducted emissions measured according to ETSI EN 300 220	< -4	7	dBm	
IEEE 802.15.4, 50 kbps, ±25 kHz Devi	ation, 2-GFSK, 100 kHz RX Bandwidth				
Sensitivity	BER = 10 ⁻² , 868 MHz	-11	C	dBm	
Saturation limit	BER = 10 ⁻² , 868 MHz	1)	dBm	
Selectivity, ±200 kHz	BER = 10 ⁻² , 868 MHz ⁽¹⁾	4	4	dB	
Selectivity, ±400 kHz	BER = 10 ⁻² , 868 MHz ⁽¹⁾	4	3	dB	
Blocking, ±1 MHz	BER = 10 ⁻² , 868 MHz ⁽¹⁾	5	7	dB	
Blocking, ±2 MHz	BER = 10 ⁻² , 868 MHz ⁽¹⁾	6	1	dB	
Blocking, ±5 MHz	BER = 10 ⁻² , 868 MHz ⁽¹⁾	6	7	dB	
Blocking, ±10 MHz	BER = 10 ⁻² , 868 MHz ⁽¹⁾	7	3	dB	
Image rejection (image compensation enabled)	BER = 10 ⁻² , 868 MHz ⁽¹⁾	3	9	dB	
RSSI dynamic range	Starting from the sensitivity limit	9	5	dB	
RSSI accuracy	Starting from the sensitivity limit across the given dynamic range	±	3	dB	
100 kbps, ±25 kHz Deviation, 2-GFSK, 137 kHz RX Bandwidth					
Sensitivity 100 kbps	1% PER, 127 byte payload, 868 MHz	-10	4	dBm	
Selectivity, ±200 kHz	1% PER, 127 byte payload, 868 MHz. Wanted signal at -96 dBm	3	1	dB	
Selectivity, ±400 kHz	1% PER, 127 byte payload, 868 MHz. Wanted signal at -96 dBm	3	7	dB	
Co-channel rejection	1% PER, 127 byte payload, 868 MHz. Wanted signal at -79 dBm	-	9	dB	
200 kbps, ±50 kHz Deviation, 2-GFSK	, 311 kHz RX Bandwidth				
Sensitivity	BER = 10 ⁻² , 868 MHz	-10	3	dBm	
Sensitivity	BER = 10 ⁻² , 915 MHz	-10	3	dBm	
Selectivity, ±400 kHz	BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.	4	1	dB	
Selectivity, ±800 kHz	BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.	4	7	dB	
Blocking, ±2 MHz	BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.	5	5	dB	
Blocking, ±10 MHz	BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.	6	7	dB	
500 kbps, ±190 kHz Deviation, 2-GFSK, 1150 kHz RX Bandwidth					
Sensitivity 500 kbps	1% PER, 127 byte payload, 915 MHz	-9	4	dBm	
Selectivity, ±1 MHz	1% PER, 127 byte payload, 915 MHz. Wanted signal at -88 dBm	1	4	dB	
Selectivity, ±2 MHz	1% PER, 127 byte payload, 915 MHz. Wanted signal at -88 dBm	4	2	dB	

8.10 861 MHz to 1054 MHz - Receive (RX) (continued)

When measured on the CC1312REM-XD7793 reference design with $T_c = 25$ °C, $V_{DDS} = 3.0$ V with DC/DC enabled unless otherwise noted. All measurements are performed at the antenna input with a combined RX and TX path. All measurements are performed conducted

Co-channel rejection 1% PER, 127 byte payload, 915 MHz. Wanted signal at -71 dBm -9 1 Mbps, ±350 kHz Deviation, 2-GFSK, 2.2 MHz RX Bandwidth Sensitivity BER = 10 ⁻² , 868 MHz -97 Sensitivity BER = 10 ⁻² , 915 MHz -96 -96 Blocking, +2 MHz BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit. 96 Blocking, -2 MHz BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit. 26 Blocking, -10 MHz BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit. 26 Blocking, -10 MHz BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit. 54 Blocking, -10 MHz BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit. 48 SimpleLink™ Long Range, 2.5/5 kbps, BER = 10 ⁻² , 968 MHz -121 Sensitivity 5 kbps, BER = 10 ⁻² , 868 MHz -120 Saturation limit 2.5 kbps, BER = 10 ⁻² , 868 MHz 10 Selectivity, ±200 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz 10 Selectivity, ±300 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz 63 Blocking, ±2 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz 63 Blocking, ±2 MHz 2.5	dB dBm dBm dB dB dB dB dB dBm dBm dBm dB
1 Mbps, ±350 kHz Deviation, 2-GFSK, 2.2 MHz RX Bandwidth Sensitivity BER = 10 ⁻² , 868 MHz -97 Sensitivity BER = 10 ⁻² , 915 MHz -96 Blocking, +2 MHz BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit. 43 Blocking, -2 MHz BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit. 26 Blocking, -10 MHz BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit. 54 Blocking, -10 MHz BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit. 48 SimpleLink™ Long Range, 2.5/5 kbps (20 ksps), ±5 kHz Deviation, 2-GFSK, 34 kHz RX Bandwidth, FEC = 1:2, DSSS = 1:4/ Sensitivity 2.5 kbps, BER = 10 ⁻² , 868 MHz -121 Sensitivity 2.5 kbps, BER = 10 ⁻² , 868 MHz -121 Sensitivity 5 kbps, BER = 10 ⁻² , 868 MHz 10 Selectivity, ±100 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 49 Selectivity, ±200 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 51 Blocking, ±2 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 63 Blocking, ±2 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 63 Blocking, ±1 MHz 2.5 kbps,	dBm dBm dB dB
Sensitivity BER = 10 ⁻² , 868 MHz -97 Sensitivity BER = 10 ⁻² , 915 MHz -96 Blocking, +2 MHz BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit. 43 Blocking, +2 MHz BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit. 26 Blocking, -2 MHz BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit. 26 Blocking, -10 MHz BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit. 54 Blocking, -10 MHz BER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit. 48 SimpleLink™ Long Range, 2.5/5 kbps (20 ksps), ±5 kHz Deviation, 2-GFSK, 34 kHz RX Bandwidth, FEC = 1:2, DSSS = 1:4/ Sensitivity 2.5 kbps, BER = 10 ⁻² , 868 MHz -121 Sensitivity 2.5 kbps, BER = 10 ⁻² , 868 MHz -121 20 21 Sensitivity 5 kbps, BER = 10 ⁻² , 868 MHz 10 20 21 Selectivity, ±100 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 49 21 25 Selectivity, ±200 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 50 26 25 Selectivity, ±300 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 63	dBm dB dB dB dB dB dB dB dB dB dB dB dB dB
SensitivityBER = 10 ⁻² , 915 MHz-96Blocking, +2 MHzBER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.43Blocking, -2 MHzBER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.26Blocking, -10 MHzBER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.26Blocking, +10 MHzBER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.54Blocking, -10 MHzBER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.48SimpleLink™ Long Range, 2.5/5 kbps(20 ksps), ±5 KHz Deviation, 2-GFSK, 34 kHz RX Bandwidth, FEC = 1:2, DSSS = 1:4/Sensitivity2.5 kbps, BER = 10 ⁻² , 868 MHz-121Sensitivity5 kbps, BER = 10 ⁻² , 868 MHz10Selectivity, ±100 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz10Selectivity, ±200 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 49Selectivity, ±300 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 50Selectivity, ±300 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 51Blocking, ±1 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 63Blocking, ±2 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 88Image rejection (image compensation enabled)2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ RSSI	dBm dB dB dB dB dB dBm dBm dB dB dB dB dB dB dB dB
Blocking, +2 MHzBER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.43Blocking, +2 MHzBER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.26Blocking, +10 MHzBER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.54Blocking, -10 MHzBER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.48SimpleLink™ Long Range, 2.5/5 kbps(20 ksps), ±5 kHz Deviation, 2-GFSK, 34 kHz RX Bandwidth, FEC = 1:2, DSSS = 1:4/Sensitivity2.5 kbps, BER = 10 ⁻² , 868 MHz-121Sensitivity5 kbps, BER = 10 ⁻² , 868 MHz10Selectivity, ±100 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz10Selectivity, ±100 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 49Selectivity, ±300 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 50Selectivity, ±300 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 51Blocking, ±1 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 63Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 81Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 81Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 81Blocking, ±10 MHz2.5 kbps, B	dB dB dB dB dB dBm dBm dB dB dB dB dB dB dB
Blocking, -2 MHzBER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.26Blocking, +10 MHzBER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.54Blocking, -10 MHzBER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.48SimpleLink™ Long Range, 2.5/5 kbps (20 ksps), ±5 kHz Deviation, 2-GFSK, 34 kHz RX Bandwidth, FEC = 1:2, DSSS = 1:4/Sensitivity2.5 kbps, BER = 10 ⁻² , 868 MHz-121Sensitivity5 kbps, BER = 10 ⁻² , 868 MHz-120Saturation limit2.5 kbps, BER = 10 ⁻² , 868 MHz10Selectivity, ±100 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz'10Selectivity, ±200 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz'50Selectivity, ±300 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz'51Blocking, ±1 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz'63Blocking, ±2 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz'63Blocking, ±1 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz'63Blocking, ±1 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz'63Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz'63Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz'45RSSI dynamic rangeStarting from the sensitivity limit97RSSI accuracyStarting from the sensitivity limit across the given dynamic range±3 4.8 kbps, OOK, 39 kHz RX Bandwidth 5454SensitivityBER = 10 ⁻² , 868 MHz, 38.9 kHz RX bandwidth-115SensitivityBER = 10 ⁻² , 915 MHz, 41.0 kHz RX bandwidth-115	dB dB dB dBm dBm dBm dB dB dB dB dB dB dB dB
Blocking, +10 MHzBER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.54Blocking, -10 MHzBER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.48SimpleLink™ Long Range, 2.5/5 kbps (20 ksps), ±5 kHz Deviation, 2-GFSK, 34 kHz RX Bandwidth, FEC = 1:2, DSSS = 1:4/Sensitivity2.5 kbps, BER = 10 ⁻² , 868 MHz-121Sensitivity5 kbps, BER = 10 ⁻² , 868 MHz100Saturation limit2.5 kbps, BER = 10 ⁻² , 868 MHz10Selectivity, ±100 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz10Selectivity, ±200 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 49Selectivity, ±200 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 50Selectivity, ±300 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 51Blocking, ±1 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 63Blocking, ±2 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68Blocking, ±1 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68Blocking, ±1 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 88Image rejection (image compensation enabled)2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 45RSSI dynamic rangeStarting from the sensitivity limit across the given dynamic range±3 4.8 kbps, OOK, 39 kHz RX Bandwidth 415SensitivityBER = 10 ⁻² , 868 MHz, 38.9 kHz RX bandwidth415SensitivityBER = 10 ⁻² , 915 MHz, 41.0 kHz RX bandwidth415	dB dB dBm dBm dBm dB dB dB dB dB dB dB
Blocking, -10 MHzBER = 10 ⁻² , 915 MHz. Wanted signal 3 dB above sensitivity limit.48SimpleLink ™ Long Range, 2.5/5 kbps(20 ksps), ±5 kHz Deviation, 2-GFSK, 34 kHz RX Bandwidth, FEC = 1:2, DSSS = 1:4/ Sensitivity2.5 kbps, BER = 10 ⁻² , 868 MHz-121Sensitivity2.5 kbps, BER = 10 ⁻² , 868 MHz-120Saturation limit2.5 kbps, BER = 10 ⁻² , 868 MHz10Selectivity, ±100 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz10Selectivity, ±200 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 49Selectivity, ±200 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 50Selectivity, ±300 kHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 51Blocking, ±1 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 63Blocking, ±2 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 78Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 88Image rejection (image compensation enabled)2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 45RSSI dynamic rangeStarting from the sensitivity limit across the given dynamic range±3 4.8 kbps, OOK, 39 kHz RX Bandwidth -115SensitivityBER = 10 ⁻² , 915 MHz, 41.0 kHz RX bandwidth-115	dB dBm dBm dBm dB dB dB dB dB dB dB
SimpleLink™ Long Range, 2.5/5 kbps (20 ksps), ±5 kHz Deviation, 2-GFSK, 34 kHz RX Bandwidth, FEC = 1:2, DSSS = 1:4/ Sensitivity 2.5 kbps, BER = 10 ⁻² , 868 MHz -121 Sensitivity 5 kbps, BER = 10 ⁻² , 868 MHz -120 Saturation limit 2.5 kbps, BER = 10 ⁻² , 868 MHz 10 Selectivity, ±100 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz(1) 49 Selectivity, ±200 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz(1) 50 Selectivity, ±300 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz(1) 63 Blocking, ±1 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz(1) 63 Blocking, ±2 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz(1) 68 Blocking, ±0 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz(1) 68 Blocking, ±10 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz(1) 78 Blocking, ±10 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz(1) 88 Image rejection (image compensation enabled) 2.5 kbps, BER = 10 ⁻² , 868 MHz(1) 45 RSSI dynamic range Starting from the sensitivity limit across the given dynamic range ±3 4.8 kbps, OOK, 39 kHz RX Bandwidth -115 58 Sensitivity BER = 10 ⁻² , 868 MHz, 38.9 kHz RX band	:2 dBm dBm dBm dB dB dB dB dB dB
Sensitivity 2.5 kbps, BER = 10 ⁻² , 868 MHz -121 Sensitivity 5 kbps, BER = 10 ⁻² , 868 MHz -120 Saturation limit 2.5 kbps, BER = 10 ⁻² , 868 MHz 10 Selectivity, ±100 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 49 Selectivity, ±200 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 50 Selectivity, ±300 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 51 Blocking, ±1 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 63 Blocking, ±2 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68 Blocking, ±2 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68 Blocking, ±10 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68 Blocking, ±10 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 78 Blocking, ±10 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 88 Image rejection (image compensation enabled) 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 45 RSSI dynamic range Starting from the sensitivity limit across the given dynamic range ±3 4.8 kbps, OOK, 39 kHz RX Bandwidth -115 58 -115 Sensitivity BER = 10 ⁻² , 95 MHz, 41.0	dBm dBm dBm dB dB dB dB dB
Sensitivity 5 kbps, BER = 10 ⁻² , 868 MHz -120 Saturation limit 2.5 kbps, BER = 10 ⁻² , 868 MHz 10 Selectivity, ±100 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 49 Selectivity, ±200 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 50 Selectivity, ±200 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 50 Selectivity, ±300 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 51 Blocking, ±1 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 63 Blocking, ±2 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 63 Blocking, ±1 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68 Blocking, ±1 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68 Blocking, ±10 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 78 Blocking, ±10 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 45 RSSI dynamic range Starting from the sensitivity limit across the given dynamic range ±3 RSSI accuracy Starting from the sensitivity limit across the given dynamic range ±3 4.8 kbps, OOK, 39 kHz RX Bandwidth -115 5 Sensitivity BER = 10 ⁻² , 868 MHz, 38.9 kHz RX ban	dBm dBm dB dB dB dB dB
Saturation limit 2.5 kbps, BER = 10 ⁻² , 868 MHz 10 Selectivity, ±100 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 49 Selectivity, ±200 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 50 Selectivity, ±200 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 50 Selectivity, ±300 kHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 51 Blocking, ±1 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 63 Blocking, ±2 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68 Blocking, ±10 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 78 Blocking, ±10 MHz 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 88 Image rejection (image compensation enabled) 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 45 RSSI dynamic range Starting from the sensitivity limit 97 RSSI accuracy Starting from the sensitivity limit across the given dynamic range ±3 4.8 kbps, OOK, 39 kHz RX Bandwidth 51 51 Sensitivity BER = 10 ⁻² , 868 MHz, 38.9 kHz RX bandwidth -115	dBm dB dB dB dB dB
Selectivity, ±100 kHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 49 Selectivity, ±200 kHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 50 Selectivity, ±300 kHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 51 Blocking, ±1 MHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 63 Blocking, ±2 MHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 68 Blocking, ±2 MHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 68 Blocking, ±10 MHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 78 Blocking, ±10 MHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 88 Image rejection (image compensation enabled) 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 45 RSSI dynamic range Starting from the sensitivity limit across the given dynamic range ±3 4.8 kbps, OOK, 39 kHz RX Bandwidth -115 -115 Sensitivity BER = 10^{-2} , 915 MHz, 41.0 kHz RX bandwidth -115	dB dB dB dB
Selectivity, ±200 kHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 50 Selectivity, ±300 kHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 51 Blocking, ±1 MHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 63 Blocking, ±2 MHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 68 Blocking, ±2 MHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 68 Blocking, ±0 MHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 78 Blocking, ±10 MHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 88 Image rejection (image compensation enabled) 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 88 RSSI dynamic range Starting from the sensitivity limit 97 RSSI accuracy Starting from the sensitivity limit across the given dynamic range ±3 4.8 kbps, OOK, 39 kHz RX Bandwidth 51 -115 Sensitivity BER = 10^{-2} , 915 MHz, 41.0 kHz RX bandwidth -115	dB dB dB
Selectivity, $\pm 300 \text{ kHz}$ 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 51 Blocking, $\pm 1 \text{ MHz}$ 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 63 Blocking, $\pm 2 \text{ MHz}$ 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68 Blocking, $\pm 5 \text{ MHz}$ 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 68 Blocking, $\pm 10 \text{ MHz}$ 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 78 Blocking, $\pm 10 \text{ MHz}$ 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 88 Image rejection (image compensation enabled) 2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 45 RSSI dynamic range Starting from the sensitivity limit 97 RSSI accuracy Starting from the sensitivity limit across the given dynamic range ± 3 4.8 kbps, OOK, 39 kHz RX Bandwidth 58 $\pm 10^{-2}$, 868 MHz, 38.9 kHz RX bandwidth -115 Sensitivity BER = 10 ⁻² , 915 MHz, 41.0 kHz RX bandwidth -115	dB dB
Blocking, ±1 MHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 63 Blocking, ±2 MHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 68 Blocking, ±5 MHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 78 Blocking, ±10 MHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 78 Blocking, ±10 MHz 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 88 Image rejection (image compensation enabled) 2.5 kbps, BER = 10^{-2} , 868 MHz ⁽¹⁾ 45 RSSI dynamic range Starting from the sensitivity limit 97 RSSI accuracy Starting from the sensitivity limit across the given dynamic range ±3 4.8 kbps, OOK, 39 kHz RX Bandwidth -115 Sensitivity BER = 10^{-2} , 868 MHz, 38.9 kHz RX bandwidth -115	dB
Blocking, ± 2 MHz2.5 kbps, BER = 10^{-2} , 868 MHz(1)68Blocking, ± 5 MHz2.5 kbps, BER = 10^{-2} , 868 MHz(1)78Blocking, ± 10 MHz2.5 kbps, BER = 10^{-2} , 868 MHz(1)88Image rejection (image compensation enabled)2.5 kbps, BER = 10^{-2} , 868 MHz(1)45RSSI dynamic rangeStarting from the sensitivity limit97RSSI accuracyStarting from the sensitivity limit across the given dynamic range ± 3 4.8 kbps, OOK, 39 kHz RX Bandwidth BER = 10^{-2} , 868 MHz, 38.9 kHz RX bandwidth-115SensitivityBER = 10^{-2} , 915 MHz, 41.0 kHz RX bandwidth-115	
Blocking, $\pm 5 \text{ MHz}$ 2.5 kbps, BER = 10^{-2} , 868 MHz(1)78Blocking, $\pm 10 \text{ MHz}$ 2.5 kbps, BER = 10^{-2} , 868 MHz(1)88Image rejection (image compensation enabled)2.5 kbps, BER = 10^{-2} , 868 MHz(1)45RSSI dynamic rangeStarting from the sensitivity limit97RSSI accuracyStarting from the sensitivity limit across the given dynamic range ± 3 4.8 kbps, OOK, 39 kHz RX Bandwidth BER = 10^{-2} , 868 MHz, 38.9 kHz RX bandwidth-115SensitivityBER = 10^{-2} , 915 MHz, 41.0 kHz RX bandwidth-115	dB
Blocking, ±10 MHz2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 88Image rejection (image compensation enabled)2.5 kbps, BER = 10 ⁻² , 868 MHz ⁽¹⁾ 45RSSI dynamic rangeStarting from the sensitivity limit97RSSI accuracyStarting from the sensitivity limit across the given dynamic range±3 4.8 kbps, OOK, 39 kHz RX Bandwidth 588 MHz, 38.9 kHz RX bandwidth-115SensitivityBER = 10 ⁻² , 915 MHz, 41.0 kHz RX bandwidth-115	dB
Image rejection (image compensation enabled)2.5 kbps, BER = 10 ⁻² , 868 MHz(1)45RSSI dynamic rangeStarting from the sensitivity limit97RSSI accuracyStarting from the sensitivity limit across the given dynamic range±3 4.8 kbps, OOK, 39 kHz RX Bandwidth BER = 10 ⁻² , 868 MHz, 38.9 kHz RX bandwidth-115SensitivityBER = 10 ⁻² , 915 MHz, 41.0 kHz RX bandwidth-115	dB
RSSI dynamic range Starting from the sensitivity limit 97 RSSI accuracy Starting from the sensitivity limit across the given dynamic range ±3 4.8 kbps, OOK, 39 kHz RX Bandwidth 5 Sensitivity BER = 10 ⁻² , 868 MHz, 38.9 kHz RX bandwidth -115 Sensitivity BER = 10 ⁻² , 915 MHz, 41.0 kHz RX bandwidth -115	dB
RSSI accuracy Starting from the sensitivity limit across the given dynamic range ±3 4.8 kbps, OOK, 39 kHz RX Bandwidth Sensitivity BER = 10 ⁻² , 868 MHz, 38.9 kHz RX bandwidth -115 Sensitivity BER = 10 ⁻² , 915 MHz, 41.0 kHz RX bandwidth -115	dB
4.8 kbps, OOK, 39 kHz RX Bandwidth Sensitivity BER = 10 ⁻² , 868 MHz, 38.9 kHz RX bandwidth -115 Sensitivity BER = 10 ⁻² , 915 MHz, 41.0 kHz RX bandwidth -115	dB
Sensitivity BER = 10 ⁻² , 868 MHz, 38.9 kHz RX bandwidth -115 Sensitivity BER = 10 ⁻² , 915 MHz, 41.0 kHz RX bandwidth -115	
SensitivityBER = 10 ⁻² , 915 MHz, 41.0 kHz RX bandwidth-115	dBm
	dBm
Narrowband, 9.6 kbps, ±2.4 kHz Deviation, 2-GFSK, 17.1 kHz RX Bandwidth	
Sensitivity BER = 10 ⁻² , 868 MHz -118	dBm
Adjacent Channel RejectionBER = 10^{-2}, 868 MHz. Wanted signal 3 dB above the ETSI reference sensitivity limit (-104.6 dBm). Interferer ±20 kHz39	dB
Alternate Channel RejectionBER = 10^{-2}, 868 MHz. Wanted signal 3 dB above the ETSI reference sensitivity limit (-104.6 dBm). Interferer ±40 kHz40	dB
Blocking, ±1 MHzBER = 10^{-2}, 868 MHz. Wanted signal 3 dB above the ETSI reference sensitivity limit (-104.6 dBm).65	dB
Blocking, $\pm 2 \text{ MHz}$ BER = 10^{-2} , 868 MHz. Wanted signal 3 dB above the ETSI reference sensitivity limit (-104.6 dBm).69	dB
Blocking, $\pm 10 \text{ MHz}$ BER = 10^{-2} , 868 MHz. Wanted signal 3 dB above the ETSI reference sensitivity limit (-104.6 dBm).85	dB



www.ti.com

8.10 861 MHz to 1054 MHz - Receive (RX) (continued)

When measured on the CC1312REM-XD7793 reference design with $T_c = 25$ °C, $V_{DDS} = 3.0$ V with DC/DC enabled unless otherwise noted. All measurements are performed at the antenna input with a combined RX and TX path. All measurements are performed conducted.

PARAMETER	TEST CONDITIONS	MIN	ТҮР	MAX	UNIT		
Sensitivity	50 kbps, ±12.5 kHz Deviation, 2-GFSK, 68 kHz RX Bandwidth, 868 MHz, 10% PER, 250 byte payload		-107		dBm		
Sensitivity	100 kbps, ±25 kHz Deviation, 2-GFSK, 135 kHz RX Bandwidth, 868 MHz, 10% PER, 250 byte payload		-104		dBm		
Sensitivity	100 kbps, ±50 kHz Deviation, 2-GFSK, 196 kHz RX Bandwidth, 920.9 MHz, 10% PER, 250 byte payload		-102		dBm		
Sensitivity	200 kbps, ±100 kHz Deviation, 2-GFSK, 273 kHz RX Bandwidth, 920.8 MHz, 10% PER, 250 byte payload		-99		dBm		
WB-DSSS, 30/60/120/240 kbps (480 ks	WB-DSSS, 30/60/120/240 kbps (480 ksps), ±195 kHz Deviation, 2-GFSK, 622 RX Bandwidth, FEC = 1:2, DSSS = 1:8/1:4/1:2/1:1						
Sensitivity	30 kbps, BER = 10 ⁻² , 915 MHz		-109		dBm		
Sensitivity	60 kbps, BER = 10 ⁻² , 915 MHz		-108		dBm		
Sensitivity	120 kbps, BER = 10 ⁻² , 915 MHz		-106		dBm		
Sensitivity	240 kbps, BER = 10 ⁻² , 915 MHz		-105		dBm		
Blocking ±1 MHz	240 kbps, BER = 10 ⁻² , 915 MHz		49		dB		
Blocking ±2 MHz	240 kbps, BER = 10 ⁻² , 915 MHz		53		dB		
Blocking ±5 MHz	240 kbps, BER = 10 ⁻² , 915 MHz		54		dB		
Blocking ±10 MHz	240 kbps, BER = 10 ⁻² , 915 MHz		65		dB		

(1) Wanted signal 3 dB above the reference sensitivity limit according to ETSI EN 300 220 v. 3.1.1

8.11 861 MHz to 1054 MHz - Transmit (TX)

When measured on the CC1312REM-XD7793 reference design with $T_c = 25$ °C, $V_{DDS} = 3.0$ V with DC/DC enabled unless otherwise noted. All measurements are performed at the antenna input with a combined RX and TX path. All measurements are performed conducted. ⁽¹⁾

PARAMETER		TEST CONDITIONS	MIN TYP	MAX	UNIT
General parameters		· · · · ·			
Max output power, boos	st mode	VDDR = 1.95 V Minimum supply voltage (VDDS) for boost mode is 2.1 V 868 MHz and 915 MHz	14		dBm
Max output power		868 MHz and 915 MHz	12		dBm
Output power programmable range 4 Output power variation over temperature -		868 MHz and 915 MHz	24		dB
Output power variation over temperature + Output power variation over temperature + Boost mode -		+10 dBm setting Over recommended temperature operating range	±2		dB
Output power variation over temperature Boost mode		+14 dBm setting Over recommended temperature operating range	±1.5		dB
Spurious emissions a	nd harmonics				
	30 MHz to 1 CHz	+14 dBm setting ETSI restricted bands	< -54		dBm
Spurious emissions (excluding harmonics) (2)		+14 dBm setting ETSI outside restricted bands	< -36		dBm
Adjacent Channel	1 GHz to 12.75 GHz (outside ETSI restricted bands)	+14 dBm setting measured in 1 MHz bandwidth (ETSI)	< -30		dBm
Adjacent Channel Power	9.6 kbps, ±2.4 kHz deviation, 2- GFSK, 20 kHz channel spacing. Narrowband mode.	Adjacent channel (ETSI EN 300 220 requirement). TxPower = 12.5 dBm. 868 MHz	-24		dBm
Alternate Channel Power	9.6 kbps, ±2.4 kHz deviation, 2- GFSK, 20 kHz channel spacing. Narrowband mode.	Alternate channel (ETSI EN 300 220 requirement). TxPower = 12.5 dBm. 868 MHz	-31		dBm
Alternate Channel Power	30 MHz to 88 MHz (within FCC restricted bands)	+14 dBm setting	< -56		dBm
	88 MHz to 216 MHz (within FCC restricted bands)	+14 dBm setting	< -52		dBm
Spurious emissions out-of-band, 915 MHz	216 MHz to 960 MHz (within FCC restricted bands)	+14 dBm setting	< -50		dBm
out-of-band, 915 MHz (2)	960 MHz to 2390 MHz and above 2483.5 MHz (within FCC restricted band)	+14 dBm setting	<-42		dBm
	1 GHz to 12.75 GHz (outside FCC restricted bands)	+14 dBm setting	< -40		dBm
	Below 710 MHz (ARIB T-108)	+14 dBm setting	< -36		dBm
	710 MHz to 900 MHz (ARIB T-108)	+14 dBm setting	< -55		dBm
Spurious emissions	900 MHz to 915 MHz (ARIB T-108)	+14 dBm setting	< -55		dBm
MHz ⁽²⁾	930 MHz to 1000 MHz (ARIB T-108)	+14 dBm setting	< -55		dBm
	1000 MHz to 1215 MHz (ARIB T-108)	+14 dBm setting	< -45		dBm
	Above 1215 MHz (ARIB T-108)	+14 dBm setting	< -30		dBm



www.ti.com

8.11 861 MHz to 1054 MHz - Transmit (TX) (continued)

When measured on the CC1312REM-XD7793 reference design with $T_c = 25$ °C, $V_{DDS} = 3.0$ V with DC/DC enabled unless otherwise noted. All measurements are performed at the antenna input with a combined RX and TX path. All measurements are performed conducted. ⁽¹⁾

I	PARAMETER	TEST CONDITIONS	MIN TYP M	AX UNIT
Harmonics	Second harmonia	+14 dBm setting, 868 MHz	< -30	dPm
	Second narmonic	+14 dBm setting, 915 MHz	< -30	
	Third hormonic	+14 dBm setting, 868 MHz	< -30	dPm
		+14 dBm setting, 915 MHz	< -42	
	Fourth hormonia	+14 dBm setting, 868 MHz	< -30	dDm
	Fourth harmonic	+14 dBm setting, 915 MHz	< -30	
	Fifth hormonic	+14 dBm setting, 868 MHz	< -30	dPm
		+14 dBm setting, 915 MHz	< -42	

(1) Some combinations of frequency, data rate and modulation format requires use of external crystal load capacitors for regulatory compliance. More details can be found in the device errata.

(2) Suitable for systems targeting compliance with EN 300 220, EN 303 131, EN 303 204, FCC CFR47 Part 15, ARIB STD-T108.

8.12 861 MHz to 1054 MHz - PLL Phase Noise Wideband Mode

When measured on the CC1312REM-XD7793 reference design with $T_c = 25$ °C, $V_{DDS} = 3.0$ V.

PARAMETER	TEST CONDITIONS	MIN	ТҮР	MAX	UNIT
Phase noise in the 868- and 915-MHz bands	±10 kHz offset		-74		dBc/Hz
	±100 kHz offset		-97		dBc/Hz
	±200 kHz offset		-107		dBc/Hz
	±400 kHz offset		-113		dBc/Hz
20 kHz PLL loop bandwidth	±1000 kHz offset		-120		dBc/Hz
	±2000 kHz offset		-127		dBc/Hz
	±10000 kHz offset		-141		dBc/Hz

8.13 861 MHz to 1054 MHz - PLL Phase Noise Narrowband Mode

When measured on the CC1312REM-XD7793 reference design with $T_c = 25$ °C, $V_{DDS} = 3.0$ V.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Phase noise in the 868- and 915-MHz bands 150 kHz PLL loop bandwith	±10 kHz offset		-93		dBc/Hz
	±100 kHz offset		-93		dBc/Hz
	±200 kHz offset		-94		dBc/Hz
	±400 kHz offset		-104		dBc/Hz
	±1000 kHz offset		-121		dBc/Hz
	±2000 kHz offset		-130		dBc/Hz
	±10000 kHz offset		-140		dBc/Hz

8.14 359 MHz to 527 MHz - Receive (RX)

When measured on the LAUNCHXL-CC1352P-4 reference design with $T_c = 25$ °C, $V_{DDS} = 3.0$ V with DC/DC enabled unless otherwise noted. All measurements are performed at the antenna input with a combined RX and TX path. All measurements are performed conducted.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
General Parameters	1				
Spurious emissions 25 MHz to 1 GHz	433.92 MHz		< -57		dBm
Spurious emissions 1 GHz to 13 GHz	Conducted emissions measured according to ETSI EN 300 220		< -47		dBm
IEEE 802.15.4, 50 kbps, ±25 kHz Devi	ation, 2-GFSK, 78 kHz RX Bandwidth				
Sensitivity	BER = 10 ⁻² , 433.92 MHz		-110		dBm
Saturation limit	BER = 10 ⁻² , 433.92 MHz		10		dBm
Selectivity, +200 kHz	BER = 10 ⁻² , 433.92 MHz ⁽¹⁾		48		dB
Selectivity, -200 kHz	BER = 10 ⁻² , 433.92 MHz ⁽¹⁾		43		dB
Selectivity, +400 kHz	BER = 10 ⁻² , 433.92 MHz ⁽¹⁾		53		dB
Selectivity, -400 kHz	BER = 10 ⁻² , 433.92 MHz ⁽¹⁾		44		dB
Blocking, +1 MHz	BER = 10 ⁻² , 433.92 MHz ⁽¹⁾		60		dB
Blocking, -1 MHz	BER = 10 ⁻² , 433.92 MHz ⁽¹⁾		54		dB
Blocking, +2 MHz	BER = 10 ⁻² , 433.92 MHz ⁽¹⁾		62		dB
Blocking, -2 MHz	BER = 10 ⁻² , 433.92 MHz ⁽¹⁾		61		dB
Blocking, +10 MHz	BER = 10 ⁻² , 433.92 MHz ⁽¹⁾		75		dB
Blocking, -10 MHz	BER = 10 ⁻² , 433.92 MHz ⁽¹⁾		75		dB
Image rejection (image compensation enabled)	BER = 10 ⁻² , 433.92 MHz ⁽¹⁾		44		dB
RSSI dynamic range	Starting from the sensitivity limit		95		dB
RSSI accuracy	Starting from the sensitivity limit across the given dynamic range		±3		dB
200 kbps, ±50 kHz Deviation, 2-GFSK	, 273 kHz RX Bandwidth			I	
Sensitivity	BER = 10 ⁻² , 433.92 MHz		-104		dBm
Saturation limit	BER = 10 ⁻² , 433.92 MHz		10		dBm
Selectivity, ±400 kHz	BER = 10 ⁻² , 433.92 MHz ⁽¹⁾		48		dB
Blocking, ±1 MHz	BER = 10 ⁻² , 433.92 MHz ⁽¹⁾		51		dB
Blocking, ±2 MHz	BER = 10 ⁻² , 433.92 MHz ⁽¹⁾		53		dB
Blocking, ±10 MHz	BER = 10 ⁻² , 433.92 MHz ⁽¹⁾		68		dB
Image rejection (image compensation enabled)	BER = 10 ⁻² , 433.92 MHz ⁽¹⁾		45		dB
RSSI dynamic range	Starting from the sensitivity limit		89		dB
RSSI accuracy	Starting from the sensitivity limit across the given dynamic range		±3		dB
Narrowband, 4.8 kbps, ±2 kHz Deviat	ion, 2-GFSK, 10.1 kHz RX Bandwidth				
Sensitivity	BER = 10 ⁻² , 426.1 MHz		-120		dBm
Saturation limit	BER = 10 ⁻² , 426.1 MHz		10		dBm
Selectivity, +12.5 kHz	BER = 10 ⁻² , 426.1 MHz ⁽¹⁾		53		dB
Selectivity, -12.5 kHz	BER = 10 ⁻² , 426.1 MHz ⁽¹⁾		52		dB
Selectivity, +25 kHz	BER = 10 ⁻² , 426.1 MHz ⁽¹⁾		53		dB
Selectivity, -25 kHz	BER = 10 ⁻² , 426.1 MHz ⁽¹⁾		52		dB
Blocking, +1 MHz	BER = 10 ⁻² , 426.1 MHz ⁽¹⁾		70		dB
Blocking, -1 MHz	BER = 10 ⁻² , 426.1 MHz ⁽¹⁾		66		dB
Blocking, +2 MHz	BER = 10 ⁻² , 426.1 MHz ⁽¹⁾		72		dB



8.14 359 MHz to 527 MHz - Receive (RX) (continued)

When measured on the LAUNCHXL-CC1352P-4 reference design with $T_c = 25$ °C, $V_{DDS} = 3.0$ V with DC/DC enabled unless otherwise noted. All measurements are performed at the antenna input with a combined RX and TX path. All measurements are performed conducted.

PARAMETER	TEST CONDITIONS	MIN TYP	MAX	UNIT
Blocking, -2 MHz	BER = 10 ⁻² , 426.1 MHz ⁽¹⁾	70		dB
Blocking, +10 MHz	BER = 10 ⁻² , 426.1 MHz ⁽¹⁾	84		dB
Blocking, -10 MHz	BER = 10 ⁻² , 426.1 MHz ⁽¹⁾	84		dB
Image rejection (image compensation enabled)	BER = 10 ⁻² , 426.1 MHz ⁽¹⁾	44		dB
RSSI dynamic range	Starting from the sensitivity limit	102		dB
RSSI accuracy	Starting from the sensitivity limit across the given dynamic range	±3		dB
4.8 kbps, OOK, 34.1 kHz RX Bandwid	th			
Sensitivity	BER = 10 ⁻² , 433.92 MHz	-115		dBm
SimpleLink™ Long Range, 2.5/5 kbps	; (20 ksps), ±5 kHz Deviation, 2-GFSK, 34 kHz RX Bandw	vidth, FEC = 1:2, DSS	5 = 1:4/1:2	2
Sensitivity	2.5 kbps, BER = 10 ⁻² , 433.92 MHz	-121		dBm
Sensitivity	5 kbps, BER = 10 ⁻² , 433.92 MHz	-119		dBm
Saturation limit	5 kbps, BER = 10 ⁻² , 433.92 MHz	10		dBm
Selectivity, +100 kHz	5 kbps, BER = 10 ⁻² , 433.92 MHz ⁽¹⁾	55		dB
Selectivity, -100 kHz	5 kbps, BER = 10 ⁻² , 433.92 MHz ⁽¹⁾	53		dB
Blocking, +1 MHz	5 kbps, BER = 10 ⁻² , 433.92 MHz ⁽¹⁾	69		dB
Blocking, -1 MHz	5 kbps, BER = 10 ⁻² , 433.92 MHz ⁽¹⁾	65		dB
Blocking, +2 MHz	5 kbps, BER = 10 ⁻² , 433.92 MHz ⁽¹⁾	71		dB
Blocking, -2 MHz	5 kbps, BER = 10 ⁻² , 433.92 MHz ⁽¹⁾	70		dB
Blocking, +10 MHz	5 kbps, BER = 10 ⁻² , 433.92 MHz ⁽¹⁾	84		dB
Blocking, -10 MHz	5 kbps, BER = 10 ⁻² , 433.92 MHz ⁽¹⁾	84		dB
Image rejection (image compensation enabled)	5 kbps, BER = 10 ⁻² , 433.92 MHz	49		dB
RSSI dynamic range	Starting from the sensitivity limit	101		dB
RSSI accuracy	Starting from the sensitivity limit across the given dynamic range	±3		dB

(1) Wanted signal 3 dB above sensitivity limit

8.15 359 MHz to 527 MHz - Transmit (TX)

When measured on the LAUNCHXL-CC1352P-4 reference design with $T_c = 25$ °C, $V_{DDS} = 3.0$ V with DC/DC enabled unless otherwise noted. All measurements are performed at the antenna input with a combined RX and TX path. All measurements are performed conducted. ⁽¹⁾

PARAMETER		TEST CONDITIONS	MIN TYP	MAX	UNIT
General parameters					
Max output power		433.92 MHz, without BOOST (VDDR = 1.7 V)	13		dBm
Output power program	nable range	433.92 MHz, without BOOST (VDDR = 1.7 V)	24		dB
Output power variation	over temperature	+13 dBm setting. 433.92 MHz Over recommended temperature operating range			dB
Spurious emissions a	nd harmonics				
		+10 dBm setting ETSI restricted bands	< -54		dBm
Spurious emissions (excluding harmonics) (2)		+10 dBm setting ETSI outside restricted bands	< -36		dBm
	1 GHz to 12.75 GHz (outside ETSI restricted bands)	+10 dBm setting measured in 1 MHz bandwidth (ETSI)	< -30		dBm
	Outside the necessary requency band (ARIB T-67)	+10 dBm setting	< -26		dBm
	710 MHz to 900 MHz (ARIB T-67)	+10 dBm setting	< -55		dBm
Spurious emissions out-of-band, 429 MHz	900 MHz to 915 MHz (ARIB T-67)	+10 dBm setting	< -55		dBm
(2)	930 MHz to 1000 MHz (ARIB T-67)	+10 dBm setting	< -55		dBm
	1000 MHz to 1215 MHz (ARIB T-67)	+10 dBm setting	< -45		dBm
	Above 1215 MHz (ARIB T-67)	+10 dBm setting	< -30		dBm
Harmonics	Second harmonic	+13 dBm setting, 433 MHz	< -36		dBm
Harmonics	Third harmonic	+13 dBm setting, 433 MHz	< -30		dBm
Harmonics	Fourth harmonic	+13 dBm setting, 433 MHz	< -30		dBm
Harmonics	Fifth harmonic	+13 dBm setting, 433 MHz	< -30		dBm

(1) Some combinations of frequency, data rate and modulation format requires use of external crystal load capacitors for regulatory compliance. More details can be found in the device errata.

(2) Suitable for systems targeting compliance with EN 300 220, EN 303 131, EN 303 204, FCC CFR47 Part 15, ARIB STD-T108.



8.16 359 MHz to 527 MHz - PLL Phase Noise

When measured on the LAUNCHXL-CC1352P-4 reference design with $T_c = 25$ °C, $V_{DDS} = 3.0$ V.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
	±10 kHz offset		-103		dBc/Hz
	±100 kHz offset		-101		dBc/Hz
	±200 kHz offset		-101		dBc/Hz
Phase noise in the 429 MHz band 200 kHz PLL loop bandwidth	±400 kHz offset		-106		dBc/Hz
	±1000 kHz offset		-122		dBc/Hz
	±2000 kHz offset		-133		dBc/Hz
	±10000 kHz offset		-143		dBc/Hz
	±10 kHz offset		-86		dBc/Hz
	±100 kHz offset		-108		dBc/Hz
	±200 kHz offset		-115		dBc/Hz
Phase noise in the 433 MHz band	±400 kHz offset		-122		dBc/Hz
	±1000 kHz offset		-130		dBc/Hz
	±2000 kHz offset		-137		dBc/Hz
	±10000 kHz offset		-145		dBc/Hz

8.17 143 MHz to 176 MHz - Receive (RX)

When measured on the CC1352EM-XS169-XS24 reference design with $T_c = 25$ °C, $V_{DDS} = 3.0$ V with DC/DC enabled unless otherwise noted. All measurements are performed at the antenna input with a combined RX and TX path. All measurements are performed conducted.

PARAMETER	TEST CONDITIONS	MIN TYP	MAX	UNIT
General Parameters				
Spurious emissions 25 MHz to 1 GHz	169.44375 MHz	< -57		dBm
Spurious emissions 1 GHz to 13 GHz	Conducted emissions measured according to ETSI EN 300 220	< -47		dBm
WMBUS N-MODE, 4.8 kbps, ±2.4 kHz	Deviation, 2-GFSK, 10 kHz RX Bandwidth			
Sensitivity 4.8 kbps ± 2.4 kHz	BER = 10 ^{−2} , 169.40625 MHz	–119		dBm
Saturation limit	BER = 10 ^{−2} , 169.40625 MHz	10		dBm
Selectivity, +12.5 kHz ⁽¹⁾	BER = 10 ⁻² , 169.40625 MHz	51		dB
Selectivity, -12.5 kHz ⁽¹⁾	BER = 10 ⁻² , 169.40625 MHz	51		dB
Selectivity, +25 kHz ⁽¹⁾	BER = 10 ^{−2} , 169.40625 MHz	52		dB
Selectivity, -25 kHz ⁽¹⁾	BER = 10 ^{−2} , 169.40625 MHz	52		dB
Blocking, +1 MHz ⁽¹⁾	BER = 10 ^{−2} , 169.40625 MHz	73		dB
Blocking, -1 MHz ⁽¹⁾	BER = 10 ^{−2} , 169.40625 MHz	72		dB
Blocking, +2 MHz ⁽¹⁾	BER = 10 ⁻² , 169.40625 MHz	77		dB
Blocking, -2 MHz ⁽¹⁾	BER = 10 ⁻² , 169.40625 MHz	75		dB
Blocking, +10 MHz ⁽¹⁾	BER = 10 ⁻² , 169.40625 MHz	86		dB
Blocking, -10 MHz ⁽¹⁾	BER = 10 ⁻² , 169.40625 MHz	86		dB
Image rejection (image compensation enabled) ⁽¹⁾	BER = 10 ⁻² , 169.40625 MHz	46		dB
RSSI dynamic range	Starting from the sensitivity limit	91		dB
RSSI accuracy	Starting from the sensitivity limit across the given dynamic range	±3		dB
WMBUS N-MODE, 2.4 kbps, ±2.4 kHz	Deviation, 2-GFSK, 10 kHz RX Bandwidth			
Sensitivity	BER = 10 ⁻² , 169.43125 MHz	-121		dBm
Saturation limit	BER = 10 ⁻² , 169.43125 MHz	10		dBm
Selectivity, +12.5 kHz ⁽¹⁾	BER = 10 ⁻² , 169.43125 MHz	51		dB
Selectivity, -12.5 kHz ⁽¹⁾	BER = 10 ⁻² , 169.43125 MHz	51		dB
Selectivity, +25 kHz ⁽¹⁾	BER = 10 ⁻² , 169.43125 MHz	52		dB
Selectivity, -25 kHz ⁽¹⁾	BER = 10 ⁻² , 169.43125 MHz	52		dB
Blocking, +1 MHz ⁽¹⁾	BER = 10 ⁻² , 169.43125 MHz	74		dB
Blocking, -1 MHz ⁽¹⁾	BER = 10 ⁻² , 169.43125 MHz	73		dB
Blocking, +2 MHz ⁽¹⁾	BER = 10 ⁻² , 169.43125 MHz	78		dB
Blocking, -2 MHz ⁽¹⁾	BER = 10 ⁻² , 169.43125 MHz	77		dB
Blocking, +10 MHz ⁽¹⁾	BER = 10 ⁻² , 169.43125 MHz	88		dB
Blocking, -10 MHz ⁽¹⁾	BER = 10 ⁻² , 169.43125 MHz	87		dB
Image rejection (image compensation enabled) ⁽¹⁾	BER = 10 ⁻² , 169.43125 MHz	50		dB
RSSI dynamic range	Starting from the sensitivity limit	92		dB
RSSI accuracy	Starting from the sensitivity limit across the given dynamic range	±3		dB

(1) Wanted signal 3 dB above sensitivity limit



8.18 143 MHz to 176 MHz - Transmit (TX)

When measured on the CC1352EM-XS169-XS24 reference design with $T_c = 25$ °C, $V_{DDS} = 3.0$ V with DC/DC enabled unless otherwise noted. All measurements are performed at the antenna input with a combined RX and TX path. All measurements are performed conducted.

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
General parameters						
Min output power, Sub-1 GHz PA	Min output power, Sub-1 GHz PA	169.44375 MHz, without BOOST (VDDR = 1.7 V), single ended configuration.	5 MHz, without BOOST 1.7 V), single ended -10 ion.			dBm
Max output power, Sub-1 GHz PA		169.44375 MHz, without BOOST (VDDR = 1.7 V), single ended configuration.		9		dBm
Adjacent channel power		0 dBm setting, 4.8 kbit/s, 169.44375 MHz, without BOOST (VDDR = 1.7 V), single ended configuration.		-47		dBc
Spurious emissions a	nd harmonics					
	20 MHz to 1 CHz	0 dBm setting, ETSI restricted bands. Measured in 100 kHz bandwidth		< -54		dBm
Spurious emissions (excluding harmonics) (1)		0 dBm setting, ETSI outside restricted bands		< -36		dBm
	1 GHz to 12.75 GHz (outside ETSI restricted bands)	0 dBm setting, measured in 1 MHz bandwidth (ETSI)		< -30		dBm
Harmonics	Second harmonic	0 dBm setting, 169.44375 MHz		< -36		dBm
Harmonics	Third harmonic	0 dBm setting, 169.44375 MHz		< -54		dBm
Harmonics	Fourth harmonic	0 dBm setting, 169.44375 MHz		< -54		dBm
Harmonics	Fifth harmonic	0 dBm setting, 169.44375 MHz		< -36		dBm

(1) Suitable for systems targeting compliance with EN 300 220.

8.19 143 MHz to 176 MHz - PLL Phase Noise

When measured on the CC1312REM-XD7793 reference design with $T_c = 25$ °C, $V_{DDS} = 3.0$ V. PLL settings for narrowband operation is used.

PARAMETER	TEST CONDITIONS	MIN	ТҮР	MAX	UNIT
	±10 kHz offset		-108		dBc/Hz
	±100 kHz offset		-108		dBc/Hz
	±200 kHz offset		-110		dBc/Hz
Phase noise in the 169 MHz band	±400 kHz offset		-114		dBc/Hz
	±1000 kHz offset		-131		dBc/Hz
	±2000 kHz offset		-141		dBc/Hz
	±10000 kHz offset		-150		dBc/Hz

8.20 Timing and Switching Characteristics

8.20.1 Reset Timing

PARAMETER	MIN	ТҮР	MAX	UNIT
RESET_N low duration	1			μs



8.20.2 Wakeup Timing

Measured over operating free-air temperature with V_{DDS} = 3.0 V (unless otherwise noted). The times listed here do not include software overhead.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
MCU, Reset to Active ⁽¹⁾		85	50 - 3000		μs
MCU, Shutdown to Active ⁽¹⁾		85	50 - 3000		μs
MCU, Standby to Active			160		μs
MCU, Active to Standby			36		μs
MCU, Idle to Active			14		μs

(1) The wakeup time is dependent on remaining charge on VDDR capacitor when starting the device, and thus how long the device has been in Reset or Shutdown before starting up again.

8.20.3 Clock Specifications

8.20.3.1 48 MHz Clock Input (TCXO)

Measured on a Texas Instruments reference design with $T_c = 25 \degree C$, $V_{DDS} = 3.0 \text{ V}$, unless otherwise noted.⁽¹⁾ (2)

PARAMETER	TEST CONDITIONS	MIN	TYP MAX	UNIT
Clock frequency			48	MHz
TCXO clipped sine output, peak-to-peak	TCXO clipped sine output connected to pin X48M_P through series capacitor	0.8	1.7	V
TCXO with CMOS output, High input voltage	TCXO with CMOS output	1.3	VDDR	V
TCXO with CMOS output, Low input voltage	directly coupled to pin X48M_P	0	0.3	V

(1) Probing or otherwise stopping the TCXO while the DC/DC converter is enabled may cause permanent damage to the device.

(2) See CC13xx/CC26xx Hardware Configuration and PCB Design Considerations on how to add TCXO support

8.20.3.2 48 MHz Crystal Oscillator (XOSC_HF)

Measured on a Texas Instruments reference design with $T_c = 25 \text{ °C}$, $V_{DDS} = 3.0 \text{ V}$, unless otherwise noted.⁽¹⁾

	PARAMETER	MIN	ТҮР	MAX	UNIT
	Crystal frequency		48		MHz
ESR	Equivalent series resistance 6 pF < C _L ≤ 9 pF		20	60	Ω
ESR	Equivalent series resistance 5 pF < C _L ≤ 6 pF			80	Ω
L _M	Motional inductance, relates to the load capacitance that is used for the crystal $(C_L \text{ in Farads})^{(5)}$		$< 3 \times 10^{-25}$ / C _L ²		Н
CL	Crystal load capacitance ⁽⁴⁾	5	7 ⁽³⁾	9	pF
	Start-up time ⁽²⁾		200		μs

(1) Probing or otherwise stopping the crystal while the DC/DC converter is enabled may cause permanent damage to the device.

(2) Start-up time using the TI-provided power driver. Start-up time may increase if driver is not used.

(3) On-chip default connected capacitance including reference design parasitic capacitance. Connected internal capacitance is changed through software in the Customer Configuration section (CCFG).

(4) Adjustable load capacitance is integrated into the device. External load capacitors are required for systems targeting compliance with certain regulations. See the device errata for further details.

(5) The crystal manufacturer's specification must satisfy this requirement for proper operation.

8.20.3.3 48 MHz RC Oscillator (RCOSC_HF)

Measured on a Texas Instruments reference design with T_c = 25 °C, V_{DDS} = 3.0 V, unless otherwise noted.

	MIN	ТҮР	MAX	UNIT
Frequency		48		MHz
Uncalibrated frequency accuracy		±1		%
Calibrated frequency accuracy ⁽¹⁾		±0.25		%
Start-up time		5		μs

(1) Accuracy relative to the calibration source (XOSC_HF)



8.20.3.4 2 MHz RC Oscillator (RCOSC_MF)

Measured on a Texas Instruments reference design with T_c = 25 °C, V_{DDS} = 3.0 V, unless otherwise noted.

	MIN	TYP	MAX	UNIT
Calibrated frequency		2		MHz
Start-up time		5		μs

8.20.3.5 32.768 kHz Crystal Oscillator (XOSC_LF)

Measured on a Texas Instruments reference design with $T_c = 25$ °C, $V_{DDS} = 3.0$ V, unless otherwise noted.

		MIN	TYP	MAX	UNIT
	Crystal frequency		32.768		kHz
ESR	Equivalent series resistance		30	100	kΩ
CL	Crystal load capacitance	6	7 ⁽¹⁾	12	pF

(1) Default load capacitance using TI reference designs including parasitic capacitance. Crystals with different load capacitance may be used.

8.20.3.6 32 kHz RC Oscillator (RCOSC_LF)

Measured on a Texas Instruments reference design with T_c = 25 °C, V_{DDS} = 3.0 V, unless otherwise noted.

	MIN	TYP	MAX	UNIT
Calibrated frequency		32.8 ⁽¹⁾		kHz
Temperature coefficient.		50		ppm/°C

(1) When using RCOSC_LF as source for the low frequency system clock (SCLK_LF), the accuracy of the SCLK_LF-derived Real Time Clock (RTC) can be improved by measuring RCOSC_LF relative to XOSC_HF and compensating for the RTC tick speed. This functionality is available through the TI-provided Power driver.



8.20.4 Synchronous Serial Interface (SSI) Characteristics

8.20.4.1 Synchronous Serial Interface (SSI) Characteristics

over operating free-air temperature range (unless otherwise noted)

PARAMETER NO.	PARAMETER		MIN TYP MAX		UNIT	
S1	t _{clk_per}	SSIClk cycle time	12		65024	System Clocks ⁽²⁾
S2 ⁽¹⁾	t _{clk_high}	SSIClk high time		0.5		t _{clk_per}
S3 ⁽¹⁾	t _{clk_low}	SSIClk low time		0.5		t _{clk_per}

(1) Refer to SSI timing diagrams Figure 8-1, Figure 8-2, and Figure 8-3

(2) When using the TI-provided Power driver, the SSI system clock is always 48 MHz.



Figure 8-1. SSI Timing for TI Frame Format (FRF = 01), Single Transfer Timing Measurement



Figure 8-2. SSI Timing for MICROWIRE Frame Format (FRF = 10), Single Transfer

Copyright © 2020 Texas Instruments Incorporated







8.20.5 UART 8.20.5.1 UART Characteristics

over operating free-air temperature range (unless otherwise noted)

PARAMETER	MIN	TYP	MAX	UNIT
UART rate			3	MBaud



8.21 Peripheral Characteristics

8.21.1 ADC

8.21.1.1 Analog-to-Digital Converter (ADC) Characteristics

 $T_c = 25$ °C, $V_{DDS} = 3.0$ V and voltage scaling enabled, unless otherwise noted.⁽¹⁾ Performance numbers require use of offset and gain adjustements in software by TI-provided ADC drivers.

	PARAMETER	TEST CONDITIONS	MIN TYP	MAX	UNIT
	Input voltage range		0	VDDS	V
	Resolution		12		Bits
	Sample Rate			200	ksps
	Offset	Internal 4.3 V equivalent reference ⁽²⁾	-0.24		LSB
	Gain error	Internal 4.3 V equivalent reference ⁽²⁾	7.14		LSB
DNL ⁽⁴⁾	Differential nonlinearity		>–1		LSB
INL	Integral nonlinearity		±4		LSB
		Internal 4.3 V equivalent reference ⁽²⁾ , 200 kSamples/s, 9.6 kHz input tone	9.8		
		Internal 4.3 V equivalent reference ⁽²⁾ , 200 kSamples/s, 9.6 kHz input tone, DC/DC enabled	9.8		
		VDDS as reference, 200 kSamples/s, 9.6 kHz input tone	10.1		
ENOB	Effective number of bits	Internal reference, voltage scaling disabled, 32 samples average, 200 kSamples/s, 300 Hz input tone	11.1		Bits
		Internal reference, voltage scaling disabled, 14-bit mode, 200 kSamples/s, 600 Hz input tone ⁽⁵⁾	11.3		
		Internal reference, voltage scaling disabled, 15-bit mode, 200 kSamples/s, 150 Hz input tone ⁽⁵⁾	11.6		
	Total harmonic distortion	Internal 4.3 V equivalent reference ⁽²⁾ , 200 kSamples/s, 9.6 kHz input tone	-65		
THD		VDDS as reference, 200 kSamples/s, 9.6 kHz input tone	-70		dB
		Internal reference, voltage scaling disabled, 32 samples average, 200 kSamples/s, 300 Hz input tone	-72		
		Internal 4.3 V equivalent reference ⁽²⁾ , 200 kSamples/s, 9.6 kHz input tone	60		
SINAD, SNDR	Signal-to-noise and	VDDS as reference, 200 kSamples/s, 9.6 kHz input tone	63		dB
SNDR	distortion ratio	Internal reference, voltage scaling disabled, 32 samples average, 200 kSamples/s, 300 Hz input tone	68		
		Internal 4.3 V equivalent reference ⁽²⁾ , 200 kSamples/s, 9.6 kHz input tone	70		
SFDR	Spurious-free dynamic	VDDS as reference, 200 kSamples/s, 9.6 kHz input tone	73		dB
	Тануе	Internal reference, voltage scaling disabled, 32 samples average, 200 kSamples/s, 300 Hz input tone	75		
	Conversion time	Serial conversion, time-to-output, 24 MHz clock	50		Clock Cycles
	Current consumption	Internal 4.3 V equivalent reference ⁽²⁾	0.42		mA
	Current consumption	VDDS as reference	0.6		mA



8.21.1.1 Analog-to-Digital Converter (ADC) Characteristics (continued)

 $T_c = 25 \text{ °C}$, $V_{DDS} = 3.0 \text{ V}$ and voltage scaling enabled, unless otherwise noted.⁽¹⁾ Performance numbers require use of offset and gain adjustements in software by TI-provided ADC drivers.

PARAMETER	TEST CONDITIONS	MIN TYP	MAX	UNIT
Reference voltage	Equivalent fixed internal reference (input voltage scaling enabled). For best accuracy, the ADC conversion should be initiated through the TI-RTOS API in order to include the gain/offset compensation factors stored in FCFG1	4.3(2) (3)		v
Reference voltage	Fixed internal reference (input voltage scaling disabled). For best accuracy, the ADC conversion should be initiated through the TI-RTOS API in order to include the gain/offset compensation factors stored in FCFG1. This value is derived from the scaled value (4.3 V) as follows: $V_{ref} = 4.3 V \times 1408 / 4095$	1.48		V
Reference voltage	VDDS as reference, input voltage scaling enabled	VDDS		V
Reference voltage	VDDS as reference, input voltage scaling disabled	VDDS / 2.82 ⁽³⁾		V
Input impedance	200 kSamples/s, voltage scaling enabled. Capacitive input, Input impedance depends on sampling frequency and sampling time	>1		MΩ

(1) Using IEEE Std 1241-2010 for terminology and test methods

(2) Input signal scaled down internally before conversion, as if voltage range was 0 to 4.3 V $\,$

(3) Applied voltage must be within Absolute Maximum Ratings (see Section 8.1) at all times

(4) No missing codes

(5) ADC_output = $\Sigma(4^n \text{ samples }) >> n, n = \text{desired extra bits}$



8.21.2 DAC

8.21.2.1 Digital-to-Analog Converter (DAC) Characteristics

 T_c = 25 °C, V_{DDS} = 3.0 V, unless otherwise noted.

	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT	
Genera	I Parameters						
	Resolution			8		Bits	
		Any load, any V_{REF} pre-charge OFF, DAC charge-pump ON	1.8		3.8		
V _{DDS}	Supply voltage	External Load ⁽⁴⁾ , any V_{REF} , pre-charge OFF, DAC charge-pump OFF	2.0		3.8	V	
		Any load, V _{REF} = DCOUPL, pre-charge ON	2.6		3.8		
-	Cleak fraguanay	Buffer ON (recommended for external load)	16		250	1.1 I 	
FDAC	Clock frequency	Buffer OFF (internal load)	16		1000	KITZ	
	Voltage output eattling	V _{REF} = VDDS, buffer OFF, internal load		13			
	time	V_{REF} = VDDS, buffer ON, external capacitive load = 20 $pF^{(3)}$		13.8		1 / F _{DAC}	
	External capacitive load			20	200	pF	
	External resistive load		10			MΩ	
	Short circuit current				400	μA	
		VDDS = 3.8 V, DAC charge-pump OFF		50.8			
		VDDS = 3.0 V, DAC charge-pump ON		51.7			
	Max output impedance	VDDS = 3.0 V, DAC charge-pump OFF		53.2			
Z _{MAX}	Vref = VDDS, buffer ON, CLK 250 kHz	VDDS = 2.0 V, DAC charge-pump ON		48.7		kΩ	
		VDDS = 2.0 V, DAC charge-pump OFF		70.2			
		VDDS = 1.8 V, DAC charge-pump ON		46.3			
		VDDS = 1.8 V, DAC charge-pump OFF		88.9			
Interna	Load - Continuous Time	Comparator / Low Power Clocked Comparator			I		
	Differential nonlinearity	V _{REF} = VDDS, load = Continuous Time Comparator or Low Power Clocked Comparator F _{DAC} = 250 kHz		±1		L CD(1)	
DINE	Differential nonlinearity	V _{REF} = VDDS, load = Continuous Time Comparator or Low Power Clocked Comparator F _{DAC} = 16 kHz		±1.2		LOD	
		V _{REF} = VDDS = 3.8 V		±0.64			
		V _{REF} = VDDS= 3.0 V		±0.81			
	Offset error ⁽²⁾	V _{REF} = VDDS = 1.8 V		±1.27			
	Comparator	V _{REF} = DCOUPL, pre-charge ON		±3.43		LSD()	
		V _{REF} = DCOUPL, pre-charge OFF		±2.88			
		V _{REF} = ADCREF		±2.37			
		V _{REF} = VDDS= 3.8 V		±0.78			
		V _{REF} = VDDS = 3.0 V		±0.77		1.0.0(1)	
	Offset error ⁽²⁾	V _{REF} = VDDS= 1.8 V		±3.46			
	Clocked Comparator	V _{REF} = DCOUPL, pre-charge ON		±3.44		LOB	
		V _{REF} = DCOUPL, pre-charge OFF		±4.70			
		V _{REF} = ADCREF		±4.11			



8.21.2.1 Digital-to-Analog Converter (DAC) Characteristics (continued)

 T_c = 25 °C, V_{DDS} = 3.0 V, unless otherwise noted.

	PARAMETER	TEST CONDITIONS	MIN TYP	MAX	UNIT	
		V _{REF} = VDDS = 3.8 V	±1.53			
		V _{REF} = VDDS = 3.0 V	±1.71			
	variation ⁽²⁾	V _{REF} = VDDS= 1.8 V	±2.10			
	Load = Continuous Time Comparator	V _{REF} = DCOUPL, pre-charge ON	±6.00		LOB(')	
		V _{REF} = DCOUPL, pre-charge OFF	±3.85			
		V _{REF} = ADCREF	±5.84			
		V _{REF} = VDDS= 3.8 V	±2.92			
	Max and a output voltage	V _{REF} =VDDS= 3.0 V	±3.06			
	variation ⁽²⁾	V _{REF} = VDDS= 1.8 V	±3.91			
	Load = Low Power	V _{REF} = DCOUPL, pre-charge ON	±7.84		LSD	
	Clocked Comparator	V _{REF} = DCOUPL, pre-charge OFF	±4.06			
		V _{REF} = ADCREF	±6.94			
		V _{REF} = VDDS = 3.8 V, code 1	0.03			
		V _{REF} = VDDS = 3.8 V, code 255	3.62			
		V _{REF} = VDDS= 3.0 V, code 1	0.02			
		V _{REF} = VDDS= 3.0 V, code 255	2.86			
	Output voltage range ⁽²⁾ Load = Continuous Time Comparator	V _{REF} = VDDS= 1.8 V, code 1	0.01			
		V _{REF} = VDDS = 1.8 V, code 255	1.71		Ň	
		V _{REF} = DCOUPL, pre-charge OFF, code 1	0.01		v	
		V _{REF} = DCOUPL, pre-charge OFF, code 255	1.21			
		V _{REF} = DCOUPL, pre-charge ON, code 1	1.27			
		V _{REF} = DCOUPL, pre-charge ON, code 255	2.46			
		V _{REF} = ADCREF, code 1	0.01			
		V _{REF} = ADCREF, code 255	1.41			
		V _{REF} = VDDS = 3.8 V, code 1	0.03			
		V _{REF} = VDDS= 3.8 V, code 255	3.61			
		V _{REF} = VDDS= 3.0 V, code 1	0.02			
		V _{REF} = VDDS= 3.0 V, code 255	2.85			
		V _{REF} = VDDS = 1.8 V, code 1	0.01			
	Output voltage range ⁽²⁾	V _{REF} = VDDS = 1.8 V, code 255	1.71		M	
	Clocked Comparator	V _{REF} = DCOUPL, pre-charge OFF, code 1	0.01		v	
		V _{REF} = DCOUPL, pre-charge OFF, code 255	1.21			
		V _{REF} = DCOUPL, pre-charge ON, code 1	1.27			
		V _{REF} = DCOUPL, pre-charge ON, code 255	2.46			
		V _{REF} = ADCREF, code 1	0.01			
		V _{REF} = ADCREF, code 255	1.41			
Externa	I Load (Keysight 34401A	Multimeter)				
		V _{REF} = VDDS, F _{DAC} = 250 kHz	±1			
INL	Integral nonlinearity	V _{REF} = DCOUPL, F _{DAC} = 250 kHz	±1		LSB ⁽¹⁾	
		V _{REF} = ADCREF, F _{DAC} = 250 kHz	±1			
DNL	Differential nonlinearity	V _{REF} = VDDS, F _{DAC} = 250 kHz	±1		LSB ⁽¹⁾	



8.21.2.1 Digital-to-Analog Converter (DAC) Characteristics (continued)

T = 25 °C	$V_{PPO} = 3.0 V$	unless otherwise noted
$1_{c} = 20$ 0	, v nns - 3.0 v,	

PARAMETER	TEST CONDITIONS	MIN TYP	MAX	UNIT
	V _{REF} = VDDS= 3.8 V	±0.20		
	V _{REF} = VDDS= 3.0 V	±0.25		
Offect error	V _{REF} = VDDS = 1.8 V	±0.45		
Oliset error	V _{REF} = DCOUPL, pre-charge ON	±1.55		LOD
	V _{REF} = DCOUPL, pre-charge OFF	±1.30		
	V _{REF} = ADCREF	±1.10		
	V _{REF} = VDDS= 3.8 V	±0.60		
	V _{REF} = VDDS= 3.0 V	±0.55		
Max code output voltage	V _{REF} = VDDS= 1.8 V	±0.60		L SB(1)
variation	V _{REF} = DCOUPL, pre-charge ON	±3.45		LOD
	V _{REF} = DCOUPL, pre-charge OFF	±2.10		
	V _{REF} = ADCREF	±1.90		
	V _{REF} = VDDS = 3.8 V, code 1	0.03		
	V _{REF} = VDDS = 3.8 V, code 255	3.61		
	V _{REF} = VDDS = 3.0 V, code 1	0.02		
	V _{REF} = VDDS= 3.0 V, code 255	2.85		
	V _{REF} = VDDS= 1.8 V, code 1	0.02		
Output voltage range	V _{REF} = VDDS = 1.8 V, code 255	1.71		V
Clocked Comparator	V_{REF} = DCOUPL, pre-charge OFF, code 1	0.02		v
	V_{REF} = DCOUPL, pre-charge OFF, code 255	1.20		
	V _{REF} = DCOUPL, pre-charge ON, code 1	1.27		
	V_{REF} = DCOUPL, pre-charge ON, code 255	2.46		
	V _{REF} = ADCREF, code 1	0.02		
	V _{REF} = ADCREF, code 255	1.42		

(1) 1 LSB (V_{REF} 3.8 V/3.0 V/1.8 V/DCOUPL/ADCREF) = 14.10 mV/11.13 mV/6.68 mV/4.67 mV/5.48 mV

(2) Includes comparator offset

(3) A load > 20 pF will increases the settling time

(4) Keysight 34401A Multimeter

8.21.3 Temperature and Battery Monitor

8.21.3.1 Temperature Sensor

Measured on a Texas Instruments reference design with T_c = 25 °C, V_{DDS} = 3.0 V, unless otherwise noted.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Resolution			2		°C
Accuracy	-40 °C to 0 °C		±4.0		°C
Accuracy	0 °C to 105 °C		±2.5		°C
Supply voltage coefficient ⁽¹⁾			3.6		°C/V

(1) The temperature sensor is automatically compensated for VDDS variation when using the TI-provided driver.

8.21.3.2 Battery Monitor

Measured on a Texas Instruments reference design with T_c = 25 °C, unless otherwise noted.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Resolution			25		mV
Range		1.8		3.8	V
Integral nonlinearity (max)			23		mV
Accuracy	VDDS = 3.0 V		22.5		mV
Offset error			-32		mV
Gain error			-1		%


8.21.4 Comparators

8.21.4.1 Low-Power Clocked Comparator

 T_c = 25 °C, V_{DDS} = 3.0 V, unless otherwise noted.

PARAMETER	TEST CONDITIONS	MIN	ТҮР	MAX	UNIT
Input voltage range		0		V _{DDS}	V
Clock frequency			SCLK_LF		
Internal reference voltage ⁽¹⁾	Using internal DAC with VDDS as reference voltage, DAC code = 0 - 255		0.024 - 2.865		V
Offset	Measured at V _{DDS} / 2, includes error from internal DAC		±5		mV
Decision time	Step from –50 mV to 50 mV		1		Clock Cycle

(1) The comparator can use an internal 8 bits DAC as its reference. The DAC output voltage range depends on the reference voltage selected. See Section 8.21.2.1

8.21.4.2 Continuous Time Comparator

 $T_c = 25^{\circ}C$, $V_{DDS} = 3.0$ V, unless otherwise noted.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Input voltage range ⁽¹⁾		0		V_{DDS}	V
Offset	Measured at V _{DDS} / 2		±5		mV
Decision time	Step from –10 mV to 10 mV		0.78		μs
Current consumption	Internal reference		8.6		μΑ

(1) The input voltages can be generated externally and connected throughout I/Os or an internal reference voltage can be generated using the DAC

8.21.5 Current Source

8.21.5.1 Programmable Current Source

T_c = 25 °C, V_{DDS} = 3.0 V, unless otherwise noted.

PARAMETER	TEST CONDITIONS	MIN TYP	MAX	UNIT
Current source programmable output range (logarithmic range)		0.25 - 20		μA
Resolution		0.25		μA



8.21.6 GPIO

8.21.6.1 GPIO DC Characteristics

PARAMETER	TEST CONDITIONS	MIN TYP	MAX	UNIT
T _A = 25 °C, V _{DDS} = 1.8 V				
GPIO VOH at 8 mA load	IOCURR = 2, high-drive GPIOs only	1.56		V
GPIO VOL at 8 mA load	IOCURR = 2, high-drive GPIOs only	0.24		V
GPIO VOH at 4 mA load	IOCURR = 1	1.59		V
GPIO VOL at 4 mA load	IOCURR = 1	0.21		V
GPIO pullup current	Input mode, pullup enabled, Vpad = 0 V	73		μA
GPIO pulldown current	Input mode, pulldown enabled, Vpad = VDDS	19		μA
GPIO low-to-high input transition, with hysteresis	IH = 1, transition voltage for input read as 0 \rightarrow 1	1.08		V
GPIO high-to-low input transition, with hysteresis	IH = 1, transition voltage for input read as $1 \rightarrow 0$	0.73		V
GPIO input hysteresis	IH = 1, difference between $0 \rightarrow 1$ and $1 \rightarrow 0$ points	0.35		V
T _A = 25 °C, V _{DDS} = 3.0 V				
GPIO VOH at 8 mA load	IOCURR = 2, high-drive GPIOs only	2.59		V
GPIO VOL at 8 mA load	IOCURR = 2, high-drive GPIOs only	0.42		V
GPIO VOH at 4 mA load	IOCURR = 1	2.63		V
GPIO VOL at 4 mA load	IOCURR = 1	0.40		V
T _A = 25 °C, V _{DDS} = 3.8 V				
GPIO pullup current	Input mode, pullup enabled, Vpad = 0 V	282		μA
GPIO pulldown current	Input mode, pulldown enabled, Vpad = VDDS	110		μA
GPIO low-to-high input transition, with hysteresis	IH = 1, transition voltage for input read as 0 \rightarrow 1	1.97		V
GPIO high-to-low input transition, with hysteresis	IH = 1, transition voltage for input read as 1 \rightarrow 0	1.55		V
GPIO input hysteresis	IH = 1, difference between $0 \rightarrow 1$ and $1 \rightarrow 0$ points	0.42		V
T _A = 25 °C				
VIH	Lowest GPIO input voltage reliably interpreted as a <i>High</i>	0.8*V _{DDS}		V
VIL	Highest GPIO input voltage reliably interpreted as a <i>Low</i>			V



8.22 Typical Characteristics

All measurements in this section are done with $T_c = 25$ °C and $V_{DDS} = 3.0$ V, unless otherwise noted. See *Recommended Operating Conditions* for device limits. Values exceeding these limits are for reference only.

8.22.1 MCU Current







Temperature





Temperature (VDDS = 3.6 V)



8.22.2 RX Current



Figure 8-8. RX Current vs. Temperature (50 kbps, 868.3 MHz, VDDS = 3.6 V)





Figure 8-9. RX Current vs. Supply Voltage (VDDS) (50 kbps, 868.3 MHz)



8.22.3 TX Current



Figure 8-11. TX Current vs. Supply Voltage (VDDS) (50 kbps, 868.3 MHz)



Table 8-1 shows typical TX current and output power for different output power settings.

CC1312R at 915 MHz, VDDS = 3.6 V (Measured on CC1312REM-XD7793)								
txPower TX Power Setting (SmartRF Studio) Typical Output Power [dBm] Typical Current Consumpt								
0x013F	14	14.3	25					
0xB224	12.5	12.7	18.3					
0xA410	12	12.2	17.4					
0x669A	11	11	15.8					
0x3E92	10	10	14.2					
0x3EDC	9	8.8	13.3					
0x2CD8	8	7.9	12.4					
0x26D4	7	6.7	11.5					
0x20D1	6	5.6	10.6					
0x1CCE	5	4.2	9.8					
0x16CD	4	3.4	9.4					
0x14CB	3	2.1	8.8					
0x12CA	2	1.3	8.4					
0x12C9	1	0.4	8.0					
0x10C8	0	-0.7	7.7					
0x0AC4	-5	-7	6.1					
0x0AC2	-10	-12.8	5.4					
0x06C1	-15	-17	5.0					
0x04C0	-20	-23	4.7					

Table 8-1. Typical TX Current and Output Power



8.22.4 RX Performance



Sensitivity vs. Frequency

Frequency (50 kbps, 915 MHz)





Figure 8-15. Sensitivity vs. Supply Voltage (VDDS) (50 kbps, 868.3 MHz)





Figure 8-17. PER vs. Level vs. Frequency (SimpleLink™ Long Range 5 kbps, 868 MHz)



Figure 8-18. Narrowband, 9.6 kbps ±2.4 kHz deviation, 2-GFSK, 868 MHz, 17.1 kHz RX Bandwidth



Figure 8-19. Narrowband, 4.8 kbps ±2 kHz deviation, 2-GFSK, 426.1 MHz, 10.1 kHz RX Bandwidth





Figure 8-20. Narrowband, WMBUS N-MODE, 2.4 kbps, 169 MHz



8.22.5 TX Performance



Supply Voltage (VDDS) (50 kbps, 868.3 MHz)





Output Power vs. Frequency 50 kbps, +14 dBm



Frequency (50 kbps, 915 MHz)



8.22.6 ADC Performance















9 Detailed Description

9.1 Overview

Section 4 shows the core modules of the CC1312R device.

9.2 System CPU

The CC1312R SimpleLink[™] Wireless MCU contains an Arm[®] Cortex[®]-M4F system CPU, which runs the application and the higher layers of radio protocol stacks.

The system CPU is the foundation of a high-performance, low-cost platform that meets the system requirements of minimal memory implementation, and low-power consumption, while delivering outstanding computational performance and exceptional system response to interrupts.

Its features include the following:

- · ARMv7-M architecture optimized for small-footprint embedded applications
- Arm Thumb[®]-2 mixed 16- and 32-bit instruction set delivers the high performance expected of a 32-bit Arm core in a compact memory size
- Fast code execution permits increased sleep mode time
- Deterministic, high-performance interrupt handling for time-critical applications
- Single-cycle multiply instruction and hardware divide
- Hardware division and fast digital-signal-processing oriented multiply accumulate
- Saturating arithmetic for signal processing
- IEEE 754-compliant single-precision Floating Point Unit (FPU)
- · Memory Protection Unit (MPU) for safety-critical applications
- Full debug with data matching for watchpoint generation
 - Data Watchpoint and Trace Unit (DWT)
 - JTAG Debug Access Port (DAP)
 - Flash Patch and Breakpoint Unit (FPB)
- Trace support reduces the number of pins required for debugging and tracing
 - Instrumentation Trace Macrocell Unit (ITM)
 - Trace Port Interface Unit (TPIU) with asynchronous serial wire output (SWO)
- Optimized for single-cycle flash memory access
- Tightly connected to 8-KB 4-way random replacement cache for minimal active power consumption and wait states
- Ultra-low-power consumption with integrated sleep modes
- 48 MHz operation
- 1.25 DMIPS per MHz



9.3 Radio (RF Core)

The RF Core is a highly flexible and future proof radio module which contains an Arm Cortex-M0 processor that interfaces the analog RF and base-band circuitry, handles data to and from the system CPU side, and assembles the information bits in a given packet structure. The RF core offers a high level, command-based API to the main CPU that configurations and data are passed through. The Arm Cortex-M0 processor is not programmable by customers and is interfaced through the TI-provided RF driver that is included with the SimpleLink Software Development Kit (SDK).

The RF core can autonomously handle the time-critical aspects of the radio protocols, thus offloading the main CPU, which reduces power and leaves more resources for the user application. Several signals are also available to control external circuitry such as RF switches or range extenders autonomously.

The various physical layer radio formats are partly built as a software defined radio where the radio behavior is either defined by radio ROM contents or by non-ROM radio formats delivered in form of firmware patches with the SimpleLink SDKs. This allows the radio platform to be updated for support of future versions of standards even with over-the-air (OTA) updates while still using the same silicon.

Note

Not all combinations of features, frequencies, data rates, and modulation formats described in this chapter are supported. Over time, TI can enable new physical radio formats (PHYs) for the device and provides performance numbers for selected PHYs in the data sheet. Supported radio formats for a specific device, including optimized settings to use with the TI RF driver, are included in the SmartRF Studio tool with performance numbers of selected formats found in the Specifications section.

9.3.1 Proprietary Radio Formats

The CC1312R radio can support a wide range of physical radio formats through a set of hardware peripherals combined with firmware available in the device ROM, covering various customer needs for optimizing towards parameters such as speed or sensitivity. This allows great flexibility in tuning the radio both to work with legacy protocols as well as customizing the behavior for specific application needs.

Table 9-1 gives a simplified overview of features of the various radio formats available in ROM. Other radio formats may be available in the form of radio firmware patches or programs through the Software Development Kit (SDK) and may combine features in a different manner, as well as add other features.

Eastura	Main 2 (G)ESK Mode	High Data Batas	Low Data Batas	Simplet ink TM Long Bongo
Feature	Main 2-(G)FSK Mode	nigii Dala Kales	LOW Data Rates	SimpleLink Long Range
Programmable preamble, sync word and CRC	Yes	Yes	Yes	No
Programmable receive bandwidth	Yes	Yes	Yes (down to 4 kHz)	Yes
Data / Symbol rate ⁽³⁾	20 to 1000 kbps	≤ 2 Msps	≤ 100 ksps	≤ 20 ksps
Modulation format	2-(G)FSK	2-(G)FSK 4-(G)FSK	2-(G)FSK 4-(G)FSK	2-(G)FSK
Dual Sync Word	Yes	Yes	No	No
Carrier Sense (1) (2)	Yes	No	No	No
Preamble Detection ⁽²⁾	Yes	Yes	Yes	No
Data Whitening	Yes	Yes	Yes	Yes
Digital RSSI	Yes	Yes	Yes	Yes
CRC filtering	Yes	Yes	Yes	Yes
Direct-sequence spread spectrum (DSSS)	No	No	No	1:2 1:4 1:8
Forward error correction (FEC)	No	No	No	Yes
Link Quality Indicator (LQI)	Yes	Yes	Yes	Yes

			-	
Table 9)-1. F	eature	Supp	ort

(1) Carrier Sense can be used to implement HW-controlled listen-before-talk (LBT) and Clear Channel Assessment (CCA) for compliance with such requirements in regulatory standards. This is available through the CMD_PROP_CS radio API.

(2) Carrier Sense and Preamble Detection can be used to implement sniff modes where the radio is duty cycled to save power.

(3) Data rates are only indicative. Data rates outside this range may also be supported. For some specific combinations of settings, a smaller range might be supported.

9.4 Memory

The up to 352-KB nonvolatile (Flash) memory provides storage for code and data. The flash memory is insystem programmable and erasable. The last flash memory sector must contain a Customer Configuration section (CCFG) that is used by boot ROM and TI provided drivers to configure the device. This configuration is done through the ccfg.c source file that is included in all TI provided examples.

The ultra-low leakage system static RAM (SRAM) is split into up to five 16-KB blocks and can be used for both storage of data and execution of code. Retention of SRAM contents in Standby power mode is enabled by default and included in Standby mode power consumption numbers. Parity checking for detection of bit errors in memory is built-in, which reduces chip-level soft errors and thereby increases reliability. System SRAM is always initialized to zeroes upon code execution from boot.

To improve code execution speed and lower power when executing code from nonvolatile memory, a 4-way nonassociative 8-KB cache is enabled by default to cache and prefetch instructions read by the system CPU. The cache can be used as a general-purpose RAM by enabling this feature in the Customer Configuration Area (CCFG).



There is a 4-KB ultra-low leakage SRAM available for use with the Sensor Controller Engine which is typically used for storing Sensor Controller programs, data and configuration parameters. This RAM is also accessible by the system CPU. The Sensor Controller RAM is not cleared to zeroes between system resets.

The ROM includes a TI-RTOS kernel and low-level drivers, as well as significant parts of selected radio stacks, which frees up flash memory for the application. The ROM also contains a serial (SPI and UART) bootloader that can be used for initial programming of the device.

9.5 Sensor Controller

The Sensor Controller contains circuitry that can be selectively enabled in both Standby and Active power modes. The peripherals in this domain can be controlled by the Sensor Controller Engine, which is a proprietary power-optimized CPU. This CPU can read and monitor sensors or perform other tasks autonomously; thereby significantly reducing power consumption and offloading the system CPU.

The Sensor Controller Engine is user programmable with a simple programming language that has syntax similar to C. This programmability allows for sensor polling and other tasks to be specified as sequential algorithms rather than static configuration of complex peripheral modules, timers, DMA, register programmable state machines, or event routing.

The main advantages are:

- Flexibility data can be read and processed in unlimited manners while still ensuring ultra-low power
- 2 MHz low-power mode enables lowest possible handling of digital sensors
- Dynamic reuse of hardware resources
- · 40-bit accumulator supporting multiplication, addition and shift
- · Observability and debugging options

Sensor Controller Studio is used to write, test, and debug code for the Sensor Controller. The tool produces C driver source code, which the System CPU application uses to control and exchange data with the Sensor Controller. Typical use cases may be (but are not limited to) the following:

- Read analog sensors using integrated ADC or comparators
- Interface digital sensors using GPIOs, SPI, UART, or I²C (UART and I²C are bit-banged)
- Capacitive sensing
- Waveform generation
- Very low-power pulse counting (flow metering)
- Key scan

The peripherals in the Sensor Controller include the following:

- The low-power clocked comparator can be used to wake the system CPU from any state in which the comparator is active. A configurable internal reference DAC can be used in conjunction with the comparator. The output of the comparator can also be used to trigger an interrupt or the ADC.
- Capacitive sensing functionality is implemented through the use of a constant current source, a time-to-digital converter, and a comparator. The continuous time comparator in this block can also be used as a higher-accuracy alternative to the low-power clocked comparator. The Sensor Controller takes care of baseline tracking, hysteresis, filtering, and other related functions when these modules are used for capacitive sensing.
- The ADC is a 12-bit, 200-ksamples/s ADC with eight inputs and a built-in voltage reference. The ADC can be triggered by many different sources including timers, I/O pins, software, and comparators.
- The analog modules can connect to up to eight different GPIOs
- Dedicated SPI master with up to 6 MHz clock speed

The peripherals in the Sensor Controller can also be controlled from the main application processor.



9.6 Cryptography

The CC1312R device comes with a wide set of modern cryptography-related hardware accelerators, drastically reducing code footprint and execution time for cryptographic operations. It also has the benefit of being lower power and improves availability and responsiveness of the system because the cryptography operations runs in a background hardware thread.

Together with a large selection of open-source cryptography libraries provided with the Software Development Kit (SDK), this allows for secure and future proof IoT applications to be easily built on top of the platform. The hardware accelerator modules are:

- **True Random Number Generator (TRNG)** module provides a true, nondeterministic noise source for the purpose of generating keys, initialization vectors (IVs), and other random number requirements. The TRNG is built on 24 ring oscillators that create unpredictable output to feed a complex nonlinear-combinatorial circuit.
- Secure Hash Algorithm 2 (SHA-2) with support for SHA224, SHA256, SHA384, and SHA512
- Advanced Encryption Standard (AES) with 128 and 256 bit key lengths
- **Public Key Accelerator** Hardware accelerator supporting mathematical operations needed for elliptic curves up to 512 bits and RSA key pair generation up to 1024 bits.

Through use of these modules and the TI provided cryptography drivers, the following capabilities are available for an application or stack:

Key Agreement Schemes

- Elliptic curve Diffie-Hellman with static or ephemeral keys (ECDH and ECDHE)
- Elliptic curve Password Authenticated Key Exchange by Juggling (ECJ-PAKE)
- Signature Generation
 - Elliptic curve Diffie-Hellman Digital Signature Algorithm (ECDSA)
- Curve Support
 - Short Weierstrass form (full hardware support), such as:
 - NIST-P224, NIST-P256, NIST-P384, NIST-P521
 - Brainpool-256R1, Brainpool-384R1, Brainpool-512R1
 - secp256r1
 - Montgomery form (hardware support for multiplication), such as:
 - Curve25519
- SHA2 based MACs
 - HMAC with SHA224, SHA256, SHA384, or SHA512
- Block cipher mode of operation
 - AESCCM
 - AESGCM
 - AESECB
 - AESCBC
 - AESCBC-MAC
- True random number generation

Other capabilities, such as RSA encryption and signatures as well as Edwards type of elliptic curves such as Curve1174 or Ed25519, can also be implemented using the provided hardware accelerators but are not part of the TI SimpleLink SDK for the CC1312R device.



9.7 Timers

A large selection of timers are available as part of the CC1312R device. These timers are:

• Real-Time Clock (RTC)

A 70-bit 3-channel timer running on the 32 kHz low frequency system clock (SCLK_LF) This timer is available in all power modes except Shutdown. The timer can be calibrated to compensate for frequency drift when using the LF RCOSC as the low frequency system clock. If an external LF clock with frequency different from 32.768 kHz is used, the RTC tick speed can be adjusted to compensate for this. When using TI-RTOS, the RTC is used as the base timer in the operating system and should thus only be accessed through the kernel APIs such as the Clock module. The real time clock can also be read by the Sensor Controller Engine to timestamp sensor data and also has dedicated capture channels. By default, the RTC halts when a debugger halts the device.

• General Purpose Timers (GPTIMER)

The four flexible GPTIMERs can be used as either 4× 32 bit timers or 8× 16 bit timers, all running on up to 48 MHz. Each of the 16- or 32-bit timers support a wide range of features such as one-shot or periodic counting, pulse width modulation (PWM), time counting between edges and edge counting. The inputs and outputs of the timer are connected to the device event fabric, which allows the timers to interact with signals such as GPIO inputs, other timers, DMA and ADC. The GPTIMERs are available in Active and Idle power modes.

Sensor Controller Timers

The Sensor Controller contains 3 timers:

AUX Timer 0 and 1 are 16-bit timers with a 2^N prescaler. Timers can either increment on a clock or on each edge of a selected tick source. Both one-shot and periodical timer modes are available.

AUX Timer 2 is a 16-bit timer that can operate at 24 MHz, 2 MHz or 32 kHz independent of the Sensor Controller functionality. There are 4 capture or compare channels, which can be operated in one-shot or periodical modes. The timer can be used to generate events for the Sensor Controller Engine or the ADC, as well as for PWM output or waveform generation.

Radio Timer

A multichannel 32-bit timer running at 4 MHz is available as part of the device radio. The radio timer is typically used as the timing base in wireless network communication using the 32-bit timing word as the network time. The radio timer is synchronized with the RTC by using a dedicated radio API when the device radio is turned on or off. This ensures that for a network stack, the radio timer seems to always be running when the radio is enabled. The radio timer is in most cases used indirectly through the trigger time fields in the radio APIs and should only be used when running the accurate 48 MHz high frequency crystal is the source of SCLK_HF.

Watchdog timer

The watchdog timer is used to regain control if the system operates incorrectly due to software errors. It is typically used to generate an interrupt to and reset of the device for the case where periodic monitoring of the system components and tasks fails to verify proper functionality. The watchdog timer runs on a 1.5 MHz clock rate and cannot be stopped once enabled. The watchdog timer pauses to run in Standby power mode and when a debugger halts the device.



9.8 Serial Peripherals and I/O

The SSIs are synchronous serial interfaces that are compatible with SPI, MICROWIRE, and TI's synchronous serial interfaces. The SSIs support both SPI master and slave up to 4 MHz. The SSI modules support configurable phase and polarity.

The UARTs implement universal asynchronous receiver and transmitter functions. They support flexible baudrate generation up to a maximum of 3 Mbps.

The I²S interface is used to handle digital audio and can also be used to interface pulse-density modulation microphones (PDM).

The I²C interface is also used to communicate with devices compatible with the I²C standard. The I²C interface can handle 100 kHz and 400 kHz operation, and can serve as both master and slave.

The I/O controller (IOC) controls the digital I/O pins and contains multiplexer circuitry to allow a set of peripherals to be assigned to I/O pins in a flexible manner. All digital I/Os are interrupt and wake-up capable, have a programmable pullup and pulldown function, and can generate an interrupt on a negative or positive edge (configurable). When configured as an output, pins can function as either push-pull or open-drain. Five GPIOs have high-drive capabilities, which are marked in **bold** in Section 7. All digital peripherals can be connected to any digital pin on the device.

For more information, see the CC13x2, CC26x2 SimpleLink™ Wireless MCU Technical Reference Manual.

9.9 Battery and Temperature Monitor

A combined temperature and battery voltage monitor is available in the CC1312R device. The battery and temperature monitor allows an application to continuously monitor on-chip temperature and supply voltage and respond to changes in environmental conditions as needed. The module contains window comparators to interrupt the system CPU when temperature or supply voltage go outside defined windows. These events can also be used to wake up the device from Standby mode through the Always-On (AON) event fabric.

9.10 µDMA

The device includes a direct memory access (μ DMA) controller. The μ DMA controller provides a way to offload data-transfer tasks from the system CPU, thus allowing for more efficient use of the processor and the available bus bandwidth. The μ DMA controller can perform a transfer between memory and peripherals. The μ DMA controller has dedicated channels for each supported on-chip module and can be programmed to automatically perform transfers between peripherals and memory when the peripheral is ready to transfer more data.

Some features of the µDMA controller include the following (this is not an exhaustive list):

- Highly flexible and configurable channel operation of up to 32 channels
- Transfer modes: memory-to-memory, memory-to-peripheral, peripheral-to-memory, and peripheral-to-peripheral
- Data sizes of 8, 16, and 32 bits
- Ping-pong mode for continuous streaming of data

9.11 Debug

The on-chip debug support is done through a dedicated cJTAG (IEEE 1149.7) or JTAG (IEEE 1149.1) interface. The device boots by default into cJTAG mode and must be reconfigured to use 4-pin JTAG.



9.12 Power Management

To minimize power consumption, the CC1312R supports a number of power modes and power management features (see Table 9-2).

Table 9-2. Power Modes								
MODE	SOFT	RESET PIN						
MODE	ACTIVE	IDLE	STANDBY	SHUTDOWN	HELD			
CPU	Active	Off	Off	Off	Off			
Flash	On	Available	Off	Off	Off			
SRAM	On	On	Retention	Off	Off			
Supply System	On	On	Duty Cycled	Off	Off			
Register and CPU retention	Full	Full	Partial	No	No			
SRAM retention	Full	Full	Full	No	No			
48 MHz high-speed clock (SCLK_HF)	eed clock XOSC_HF or XOSC_HF or RCOSC_HF RCOSC_HF		Off	Off	Off			
2 MHz medium-speed clock (SCLK_MF)	RCOSC_MF	RCOSC_MF	Available	Off	Off			
32 kHz low-speed clock (SCLK_LF)	XOSC_LF or RCOSC_LF	XOSC_LF or RCOSC_LF	XOSC_LF or RCOSC_LF	Off	Off			
Peripherals	Available	Available	Off	Off	Off			
Sensor Controller	Available	Available	Available	Off	Off			
Wake-up on RTC	Available	Available	Available	Off	Off			
Wake-up on pin edge	Available	Available	Available	Available	Off			
Wake-up on reset pin	On	On	On	On	On			
Brownout detector (BOD)	On	On	Duty Cycled	Off	Off			
Power-on reset (POR)	On	On	On	Off	Off			
Watchdog timer (WDT)	Available	Available	Paused	Off	Off			

In **Active** mode, the application system CPU is actively executing code. Active mode provides normal operation of the processor and all of the peripherals that are currently enabled. The system clock can be any available clock source (see Table 9-2).

In **Idle** mode, all active peripherals can be clocked, but the Application CPU core and memory are not clocked and no code is executed. Any interrupt event brings the processor back into active mode.

In **Standby** mode, only the always-on (AON) domain is active. An external wake-up event, RTC event, or Sensor Controller event is required to bring the device back to active mode. MCU peripherals with retention do not need to be reconfigured when waking up again, and the CPU continues execution from where it went into standby mode. All GPIOs are latched in standby mode.

In **Shutdown** mode, the device is entirely turned off (including the AON domain and Sensor Controller), and the I/Os are latched with the value they had before entering shutdown mode. A change of state on any I/O pin defined as a *wake from shutdown pin* wakes up the device and functions as a reset trigger. The CPU can differentiate between reset in this way and reset-by-reset pin or power-on reset by reading the reset status register. The only state retained in this mode is the latched I/O state and the flash memory contents.



The Sensor Controller is an autonomous processor that can control the peripherals in the Sensor Controller independently of the system CPU. This means that the system CPU does not have to wake up, for example to perform an ADC sampling or poll a digital sensor over SPI, thus saving both current and wake-up time that would otherwise be wasted. The Sensor Controller Studio tool enables the user to program the Sensor Controller, control its peripherals, and wake up the system CPU as needed. All Sensor Controller peripherals can also be controlled by the system CPU.

Note

The power, RF and clock management for the CC1312R device require specific configuration and handling by software for optimized performance. This configuration and handling is implemented in the TI-provided drivers that are part of the CC1312R software development kit (SDK). Therefore, TI highly recommends using this software framework for all application development on the device. The complete SDK with TI-RTOS (optional), device drivers, and examples are offered free of charge in source code.

9.13 Clock Systems

The CC1312R device has several internal system clocks.

The 48 MHz SCLK_HF is used as the main system (MCU and peripherals) clock. This can be driven by the internal 48 MHz RC Oscillator (RCOSC_HF) or an external 48 MHz crystal (XOSC_HF). Radio operation requires an external 48 MHz crystal or TCXO.

SCLK_MF is an internal 2 MHz clock that is used by the Sensor Controller in low-power mode and also for internal power management circuitry. The SCLK_MF clock is always driven by the internal 2 MHz RC Oscillator (RCOSC_MF).

SCLK_LF is the 32.768 kHz internal low-frequency system clock. It can be used by the Sensor Controller for ultra-low-power operation and is also used for the RTC and to synchronize the radio timer before or after Standby power mode. SCLK_LF can be driven by the internal 32.8 kHz RC Oscillator (RCOSC_LF), a 32.768 kHz watch-type crystal, or a clock input on any digital IO.

When using a crystal or the internal RC oscillator, the device can output the 32 kHz SCLK_LF signal to other devices, thereby reducing the overall system cost.

9.14 Network Processor

Depending on the product configuration, the CC1312R device can function as a wireless network processor (WNP - a device running the wireless protocol stack with the application running on a separate host MCU), or as a system-on-chip (SoC) with the application and protocol stack running on the system CPU inside the device.

In the first case, the external host MCU communicates with the device using SPI or UART. In the second case, the application must be written according to the application framework supplied with the wireless protocol stack.



10 Application, Implementation, and Layout

Note

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

For general design guidelines and hardware configuration guidelines, refer to CC13xx/CC26xx Hardware Configuration and PCB Design Considerations Application Report.

10.1 Reference Designs

The following reference designs should be followed closely when implementing designs using the CC1312R device.

Special attention must be paid to RF component placement, decoupling capacitors and DCDC regulator components, as well as ground connections for all of these.

Integrated matched filter-balun devices can be used both at sub-1 GHz frequencies and at 2.4 GHz for the lowpower RF outputs. Refer to the "Integrated Passive Component" section in CC13xx/CC26xx Hardware Configuration and PCB Design Considerations for further information.

CC1312REM-XD7793 Design Files	The CC1312REM-XD7793 reference design provides schematic, layout and production files for the characterization board used for deriving the performance number found in this document.					
LAUNCHXL-CC1312R1 Design Files	The CC1312R LaunchPad Design Files contain detailed schematics and layouts to build application specific boards using the CC1312R device.					
LAUNCHXL-CC1352P-4 Design Files	Detailed schematics and layouts for the multi-band CC1352P LaunchPad evaluation board featuring 2.4 GHz RF matching optimized for 10 dBm operation on the 20 dBm PA output and up to 13 dBm TX power at 433 MHz.					
Sub-1 GHz and 2.4 GHz Antenna Kit for LaunchPad™ Development Kit and SensorTag	 The antenna kit allows real-life testing to identify the optimal antenna for your application. The antenna kit includes 16 antennas for frequencies from 169 MHz to 2.4 GHz, including: PCB antennas Helical antennas Chip antennas Dual-band antennas for 868 MHz and 915 MHz combined with 2.4 GHz 					

The antenna kit includes a JSC cable to connect to the Wireless MCU LaunchPad development kits and SensorTags.



10.2 Junction Temperature Calculation

This section shows the different techniques for calculating the junction temperature under various operating conditions. For more details, see Semiconductor and IC Package Thermal Metrics.

There are three recommended ways to derive the junction temperature from other measured temperatures:

1. From package temperature:

$$\Gamma_{\rm J} = \psi_{\rm JT} \times P + T_{\rm case} \tag{1}$$

2. From board temperature:

$$\Gamma_{\rm J} = \psi_{\rm JB} \times P + T_{\rm board} \tag{2}$$

3. From ambient temperature:

$$T_{J} = R_{\theta JA} \times P + T_{A}$$
(3)

P is the power dissipated from the device and can be calculated by multiplying current consumption with supply voltage. Thermal resistance coefficients are found in *Thermal Resistance Characteristics*.

Example:

Using Equation 3, the temperature difference between ambient temperature and junction temperature is calculated. In this example, we assume a simple use case where the radio is transmitting continuously at 10 dBm output power. Let us assume the ambient temperature is 85 °C and the supply voltage is 3.6 V. To calculate P, we need to look up the current consumption for Tx at 85 °C in Section 8.22. From the plot, we see that the current consumption is 14.4 mA. This means that P is 14.4 mA × 3.6 V = 51.8 mW.

The junction temperature is then calculated as:

$$T_J = 23.4 \frac{°C}{W} \times 51.8 mW + T_A = 1.2 °C + T_A$$
 (4)

As can be seen from the example, the junction temperature is 1.2 °C higher than the ambient temperature when running continuous Tx at 85 °C and, thus, well within the recommended operating conditions.

For various application use cases current consumption for other modules may have to be added to calculate the appropriate power dissipation. For example, the MCU may be running simultaneously as the radio, peripheral modules may be enabled, etc. Typically, the easiest way to find the peak current consumption, and thus the peak power dissipation in the device, is to measure as described in Measuring CC13xx and CC26xx current consumption.



11 Device and Documentation Support

TI offers an extensive line of development tools. Tools and software to evaluate the performance of the device, generate code, and develop solutions are listed as follows.

11.1 Tools and Software

The CC1312R device is supported by a variety of software and hardware development tools.

Development Kit

CC1312R LaunchPad[™] Development Kit Development Kit Development Kit Development Kit CC1312R LaunchPad[™] Development Kit enables development of high-performance Sub-1 GHz wireless applications that benefit from low-power operation. The kit features the CC1312R Sub-1 GHz SimpleLink Wireless MCU. The kit works with the LaunchPad ecosystem, easily enabling additional functionality like sensors, display, and more. The built-in EnergyTrace[™] software is an energy-based code analysis tool that measures and displays the application's energy profile and helps to optimize it for ultra-low power consumption.

Software

SimpleLink™ CC13x2-CC26x2 SDK

The SimpleLink CC13x2-CC26x2 Software Development Kit (SDK) provides a complete package for the development of wireless applications on the CC13x2 / CC26x2 family of devices. The SDK includes a comprehensive software package for the CC1312R device, including the following protocol stacks:

- Bluetooth Low Energy 4 and 5.1
- Thread (based on OpenThread)
- Zigbee 3.0
- TI 15.4-Stack an IEEE 802.15.4-based star networking solution for Sub-1 GHz and 2.4 GHz
- · EasyLink a large set of building blocks for building proprietary RF software stacks
- Multiprotocol support concurrent operation between stacks using the Dynamic Multiprotocol Manager (DMM)

The SimpleLink CC13x2-CC26x2 SDK is part of TI's SimpleLink MCU platform, offering a single development environment that delivers flexible hardware, software and tool options for customers developing wired and wireless applications. For more information about the SimpleLink MCU Platform, visit http://www.ti.com/simplelink.



Development Tools

Code Composer Studio [™] Integrated Development Environment (IDE)	Code Composer Studio is an integrated development environment (IDE) that supports TI's Microcontroller and Embedded Processors portfolio. Code Composer Studio comprises a suite of tools used to develop and debug embedded applications. It includes an optimizing C/C++ compiler, source code editor, project build environment, debugger, profiler, and many other features. The intuitive IDE provides a single user interface taking you through each step of the application development flow. Familiar tools and interfaces allow users to get started faster than ever before. Code Composer Studio combines the advantages of the Eclipse [®] software framework with advanced embedded debug capabilities from TI resulting in a compelling feature-rich development environment for embedded developers.
	CCS has support for all SimpleLink Wireless MCUs and includes support for EnergyTrace [™] software (application energy usage profiling). A real-time object viewer plugin is available for TI-RTOS, part of the SimpleLink SDK.
	Code Composer Studio is provided free of charge when used in conjunction with the XDS debuggers included on a LaunchPad Development Kit.
Code Composer Studio™ Cloud IDE	Code Composer Studio (CCS) Cloud is a web-based IDE that allows you to create, edit and build CCS and Energia™ projects. After you have successfully built your project, you can download and run on your connected LaunchPad. Basic debugging, including features like setting breakpoints and viewing variable values is now supported with CCS Cloud.
IAR Embedded Workbench [®] for Arm [®]	IAR Embedded Workbench [®] is a set of development tools for building and debugging embedded system applications using assembler, C and C++. It provides a completely integrated development environment that includes a project manager, editor, and build tools. IAR has support for all SimpleLink Wireless MCUs. It offers broad debugger support, including XDS110, IAR I-jet [™] and Segger J-Link [™] . A real-time object viewer plugin is available for TI-RTOS, part of the SimpleLink SDK. IAR is also supported out-of-the-box on most software examples provided as part of the SimpleLink SDK.
	A 30-day evaluation or a 32 KB size-limited version is available through iar.com.
SmartRF™ Studio	 SmartRF™ Studio is a Windows[®] application that can be used to evaluate and configure SimpleLink Wireless MCUs from Texas Instruments. The application will help designers of RF systems to easily evaluate the radio at an early stage in the design process. It is especially useful for generation of configuration register values and for practical testing and debugging of the RF system. SmartRF Studio can be used either as a standalone application or together with applicable evaluation boards or debug probes for the RF device. Features of the SmartRF Studio include: Link tests - send and receive packets between nodes Antenna and radiation tests - set the radio in continuous wave TX and RX states Export radio configuration code for use with the TI SimpleLink SDK RF driver Custom GPIO configuration for signaling and control of external switches



- Sensor Controller Studio Sensor Controller Studio is used to write, test and debug code for the Sensor Controller peripheral. The tool generates a Sensor Controller Interface driver, which is a set of C source files that are compiled into the System CPU application. These source files also contain the Sensor Controller binary image and allow the System CPU application to control and exchange data with the Sensor Controller. Features of the Sensor Controller Studio include:
 - Ready-to-use examples for several common use cases
 - Full toolchain with built-in compiler and assembler for programming in a C-like programming language
 - Provides rapid development by using the integrated sensor controller task testing and debugging functionality, including visualization of sensor data and verification of algorithms
- **CCS UniFlash** CCS UniFlash is a standalone tool used to program on-chip flash memory on TI MCUs. UniFlash has a GUI, command line, and scripting interface. CCS UniFlash is available free of charge.

11.1.1 SimpleLink[™] Microcontroller Platform

The SimpleLink microcontroller platform sets a new standard for developers with the broadest portfolio of wired and wireless Arm[®] MCUs (System-on-Chip) in a single software development environment. Delivering flexible hardware, software and tool options for your IoT applications. Invest once in the SimpleLink software development kit and use throughout your entire portfolio. Learn more on ti.com/simplelink.

11.2 Documentation Support

To receive notification of documentation updates on data sheets, errata, application notes and similar, navigate to the device product folder on ti.com/product/CC1312R. In the upper right corner, click on *Alert me* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

The current documentation that describes the MCU, related peripherals, and other technical collateral is listed as follows.

TI Resource Explorer

TI Resource Explorer Software examples, libraries, executables, and documentation are available for your device and development board.

Errata

CC1312R Silicon Errata The silicon errata describes the known exceptions to the functional specifications for each silicon revision of the device and description on how to recognize a device revision.

Application Reports

All application reports for the CC1312R device are found on the device product folder at: ti.com/product/ CC1312R/technicaldocuments.

Technical Reference Manual (TRM)

CC13x2, CC26x2 SimpleLink ^{IM}	The	TRM	provides	а	detailed	description	of	all	modules	and
Wireless MCU TRM	perip	herals	available	in t	the device	e family.				



11.3 Support Resources

TI E2E[™] support forums are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's Terms of Use.

11.4 Trademarks

SimpleLink[™], SmartRF[™], LaunchPad[™], EnergyTrace[™], Code Composer Studio[™], TI E2E[™] are trademarks of Texas Instruments.

I-jet[™] is a trademark of IAR Systems AB.

J-Link[™] is a trademark of SEGGER Microcontroller Systeme GmbH.

Arm[®], Cortex[®], and Arm Thumb[®] are registered trademarks of Arm Limited (or its subsidiaries).

CoreMark[®] is a registered trademark of Embedded Microprocessor Benchmark Consortium.

MIOTY[®], Wi-SUN[®], are registered trademarks of Wi-SUN Alliance Inc.

Wi-Fi[®] is a registered trademark of Wi-Fi Alliance.

Eclipse® is a registered trademark of Eclipse Foundation.

IAR Embedded Workbench® is a registered trademark of IAR Systems AB.

Windows[®] is a registered trademark of Microsoft Corporation.

All trademarks are the property of their respective owners.

11.5 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

11.6 Glossary

TI Glossary This glossary lists and explains terms, acronyms, and definitions.



12 Mechanical, Packaging, and Orderable Information

12.1 Packaging Information

The following pages include mechanical packaging and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.



PACKAGING INFORMATION

Orderable part number	Status	Material type	Package Pins	Package qty Carrier	RoHS	Lead finish/ Ball material	MSL rating/ Peak reflow	Op temp (°C)	Part marking
	(-)	(=)			(-)	(4)	(5)		(-)
CC1312R1F3RGZR	Active	Production	VQFN (RGZ) 48	2500 LARGE T&R	Yes	NIPDAU NIPDAUAG	Level-3-260C-168 HR	-40 to 105	CC1312 R1F3
CC1312R1F3RGZR.A	Active	Production	VQFN (RGZ) 48	2500 LARGE T&R	Yes	NIPDAU	Level-3-260C-168 HR	-40 to 105	CC1312 R1F3
CC1312R1F3RGZR.B	Active	Production	VQFN (RGZ) 48	2500 LARGE T&R	Yes	NIPDAU	Level-3-260C-168 HR	-40 to 105	CC1312 R1F3
CC1312R1F3RGZRG4	Active	Production	VQFN (RGZ) 48	2500 LARGE T&R	Yes	NIPDAU	Level-3-260C-168 HR	-40 to 105	CC1312 R1F3
CC1312R1F3RGZRG4.A	Active	Production	VQFN (RGZ) 48	2500 LARGE T&R	Yes	NIPDAU	Level-3-260C-168 HR	-40 to 105	CC1312 R1F3
CC1312R1F3RGZRG4.B	Active	Production	VQFN (RGZ) 48	2500 LARGE T&R	Yes	NIPDAU	Level-3-260C-168 HR	-40 to 105	CC1312 R1F3
CC1312R1F3RGZT	Active	Production	VQFN (RGZ) 48	250 SMALL T&R	Yes	NIPDAU NIPDAUAG	Level-3-260C-168 HR	-40 to 105	CC1312 R1F3
CC1312R1F3RGZT.A	Active	Production	VQFN (RGZ) 48	250 SMALL T&R	Yes	NIPDAU	Level-3-260C-168 HR	-40 to 105	CC1312 R1F3
CC1312R1F3RGZT.B	Active	Production	VQFN (RGZ) 48	250 SMALL T&R	Yes	NIPDAU	Level-3-260C-168 HR	-40 to 105	CC1312 R1F3

⁽¹⁾ **Status:** For more details on status, see our product life cycle.

⁽²⁾ Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

⁽⁴⁾ Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

⁽⁵⁾ MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.



www.ti.com

PACKAGE OPTION ADDENDUM

17-Jun-2025

⁽⁶⁾ Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


Texas

STRUMENTS

TAPE AND REEL INFORMATION





QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal												
Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
CC1312R1F3RGZR	VQFN	RGZ	48	2500	330.0	16.4	7.3	7.3	1.1	12.0	16.0	Q2
CC1312R1F3RGZRG4	VQFN	RGZ	48	2500	330.0	16.4	7.3	7.3	1.1	12.0	16.0	Q2
CC1312R1F3RGZT	VQFN	RGZ	48	250	180.0	16.4	7.3	7.3	1.1	12.0	16.0	Q2



www.ti.com

PACKAGE MATERIALS INFORMATION

23-Jul-2025



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
CC1312R1F3RGZR	VQFN	RGZ	48	2500	367.0	367.0	35.0
CC1312R1F3RGZRG4	VQFN	RGZ	48	2500	336.6	336.6	31.8
CC1312R1F3RGZT	VQFN	RGZ	48	250	210.0	185.0	35.0

RGZ 48

7 x 7, 0.5 mm pitch

GENERIC PACKAGE VIEW

VQFN - 1 mm max height

PLASTIC QUADFLAT PACK- NO LEAD



Images above are just a representation of the package family, actual package may vary. Refer to the product data sheet for package details.



RGZ0048A

PACKAGE OUTLINE VQFN - 1 mm max height

VQI II IIIIII IIIAX Holgiii

PLASTIC QUADFLAT PACK- NO LEAD



NOTES:

- 1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
- 2. This drawing is subject to change without notice.
- 3. The package thermal pad must be soldered to the printed circuit board for optimal thermal and mechanical performance.



EXAMPLE BOARD LAYOUT

VQFN - 1 mm max height

PLASTIC QUADFLAT PACK- NO LEAD



NOTES: (continued)

- 4. This package is designed to be soldered to a thermal pad on the board. For more information, see Texas Instruments literature number SLUA271 (www.ti.com/lit/slua271).
- 5. Vias are optional depending on application, refer to device data sheet. If any vias are implemented, refer to their locations shown on this view. It is recommended that vias under paste be filled, plugged or tented.



RGZ0048A

RGZ0048A

EXAMPLE STENCIL DESIGN

VQFN - 1 mm max height

PLASTIC QUADFLAT PACK- NO LEAD



6. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265 Copyright © 2025, Texas Instruments Incorporated