











CSD17507Q5A

SLPS243G -JULY 2010-REVISED JANUARY 2017

# CSD17507Q5A 30-V N-Channel NexFET™ Power MOSFET

#### **Features**


- Ultra-Low Qa and Qad
- Low-Thermal Resistance
- Avalanche Rated
- Lead-Free Terminal Plating
- **RoHS Compliant**
- Halogen Free
- SON 5-mm x 6-mm Plastic Package

# 2 Applications

- Point-of-Load Synchronous Buck in Networking, Telecom and Computing Systems
- Optimized for Control FET Applications

## 3 Description

This 30-V, 9-m $\Omega$ , SON 5-mm × 6-mm NexFET<sup>TM</sup> power MOSFET has been designed to minimize losses in power conversion applications.



# R<sub>DS(on)</sub> vs V<sub>GS</sub> 30 $T_C = 25^{\circ}C, I_D = 11 A$ $T_C = 125^{\circ}C, I_D = 11 A$ R<sub>DS(on)</sub> - On-State Resistance (mΩ) 20 0 8 10 12 14 16 V<sub>GS</sub> - Gate-to-Source Voltage (V)

#### **Product Summary**

$T_A = 25^\circ$	С	TYPICAL VA	UNIT	
$V_{DS}$	Drain-to-Source Voltage 30			٧
$Q_g$	Gate Charge Total (4.5 V)	2.8		nC
$Q_{gd}$	Gate Charge Gate-to-Drain	0.7	nC	
D	Drain-to-Source On Resistance	V <sub>GS</sub> = 4.5 V 11.8		mΩ
R <sub>DS(on)</sub>	Diam-to-Source Off Resistance	V <sub>GS</sub> = 10 V 9		11177
$V_{GS(th)}$	Threshold Voltage 1.6			

#### Device Information<sup>(1)</sup>

DEVICE	MEDIA	QTY	PACKAGE	SHIP
CSD17507Q5A	13-Inch Reel	2500	SON	Tape
CSD17507Q5AT	7-Inch Reel	250	5.00-mm x 6.00-mm Plastic Package	and Reel


(1) For all available packages, see the orderable addendum at the end of the data sheet.

#### **Absolute Maximum Ratings**

T <sub>A</sub> = 2	5°C (unless otherwise stated)	VALUE	UNIT	
V <sub>DS</sub>	Drain-to-Source Voltage	30	V	
$V_{GS}$	Gate-to-Source Voltage	±20	V	
	Continuous Drain Current	65		
$I_D$	Continuous Drain Current (Silicon Limited), $T_C = 25^{\circ}C$	61	Α	
	Continuous Drain Current <sup>(1)</sup>	14		
$I_{DM}$	Pulsed Drain Current, T <sub>C</sub> = 25°C <sup>(2)</sup>	163	Α	
n	Power Dissipation <sup>(1)</sup>	3.1	W	
$P_D$	Power Dissipation, T <sub>C</sub> = 25°C	39	VV	
T <sub>J</sub> , T <sub>STG</sub>	Operating Junction, Storage Temperature	-55 to 150	°C	
E <sub>AS</sub>	Avalanche Energy, Single Pulse $I_D = 30 \text{ A}, L = 0.1 \text{ mH}, R_G = 25 \Omega$	45	mJ	

- (1) Typical  $R_{\theta JA}=40^{\circ} C/W$  on a 1-in², 2-oz Cu pad on a 0.06-in thick FR4 PCB.
- (2) Max  $R_{\theta JC} = 2^{\circ}C/W$ , pulse duration  $\leq 100 \ \mu s$ , duty cycle  $\leq 1\%$ .

#### **Gate Charge**





<b>T</b> -	<b>I</b> _	-	_ £	<b>^</b> -	nte	4
19	n	10	$\Delta T$		nto	ntc
10	•	16	OI.	$\mathbf{v}$	IILE	111.3

1	Features 1	6.3	2 Community Resources	8
2	Applications 1	6.3		
3	Description 1	6.4	3	
4	Revision History2	6.	,	
5	Specifications4		echanical, Packaging, and Orderab	
	5.1 Electrical Characteristics4		formation	
	5.2 Thermal Information 4		Q5A Package Dimensions  Recommended PCB Pattern	
	5.3 Typical MOSFET Characteristics5		3 Recommended Stencil Opening	
6	Device and Documentation Support		4 Q5A Tape and Reel Information	
	Revision History E: Page numbers for previous revisions may differ from page	e numhere	in the current version	
NOI	E. Page numbers for previous revisions may unter from page	e numbers	in the current version.	
Cha	nges from Revision F (November 2016) to Revision G			Page
• (	Corrected package size in the Description section			1
Ch a	ngo from Povicion E ( July 2014) to Povicion E			Done
Cna	nges from Revision E (July 2011) to Revision F			Page
• (	Changed Description text			1
• /	Added silicon limited continuous drain current to Absolute Ma	aximum Ra	tings table	1
• (	Changed Note 2 in Absolute Maximum Ratings table			1
	Changed THERMAL CHARACTERISTICS table to Thermal I.			
	Changed R <sub>0JC</sub> from 1.9°C/W : to 2.1°C/W			
	Changed R <sub>0JA</sub> from 51°C/W : to 50°C/W			
	Added Device and Documentation Support section			
• (	Changed MECHANICAL DATA section to Mechanical, Packa	aging, and	Orderable Information section	<u> 9</u>
Cha	nges from Revision D (December 2010) to Revision E			Page
	, , , , , , , , , , , , , , , , , , , ,			

# Changes from Revision C (November 2010) to Revision D

# Changes from Revision B (September 2010) to Revision C

# Changes from Revision A (August 2010) to Revision B

Page

Product Folder Links: CSD17507Q5A





Cł	Changes from Original (July 2010) to Revision A			
•	Changed the Y axis scale for Figure 5.		5	

Product Folder Links: CSD17507Q5A



# 5 Specifications

#### 5.1 Electrical Characteristics

 $T_{A} = 25^{\circ}C$  (unless otherwise stated)

	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
STATIC	CHARACTERISTICS					
BV <sub>DSS</sub>	Drain-to-source voltage	$V_{GS} = 0 \text{ V}, I_{DS} = 250 \mu\text{A}$	30			V
I <sub>DSS</sub>	Drain-to-source leakage current	V <sub>GS</sub> = 0 V, V <sub>DS</sub> = 24 V			1	μΑ
I <sub>GSS</sub>	Gate-to-source leakage current	V <sub>DS</sub> = 0 V, V <sub>GS</sub> = 20 V			100	nA
V <sub>GS(th)</sub>	Gate-to-source threshold voltage	$V_{DS} = V_{GS}, I_{DS} = 250 \mu A$	1.1	1.6	2.1	V
Б	Dunin to anyone an uncirtaine	V <sub>GS</sub> = 4.5 V, I <sub>DS</sub> = 11 A		11.8	16.1	0
R <sub>DS(on)</sub>	Drain-to-source on resistance	V <sub>GS</sub> = 10 V, I <sub>DS</sub> = 11 A		9.0	10.8	mΩ
9 <sub>fs</sub>	Transconductance	V <sub>DS</sub> = 15 V, I <sub>DS</sub> = 11 A		44		S
DYNAMI	C CHARACTERISTICS					
C <sub>iss</sub>	Input capacitance			410	530	pF
C <sub>oss</sub>	Output capacitance	$V_{GS} = 0 \text{ V}, V_{DS} = 15 \text{ V},$ f = 1  MHz		270	350	pF
C <sub>rss</sub>	Reverse transfer capacitance	J = 1 1811 12		23	30	pF
R <sub>G</sub>	Series gate resistance			0.7	1.4	Ω
Qg	Gate charge total (4.5 V)			2.8	3.6	nC
$Q_{gd}$	Gate charge gate-to-drain	V 45 V 1 44 A		0.7		nC
Q <sub>gs</sub>	Gate charge gate-to-source	V <sub>DS</sub> = 15 V, I <sub>DS</sub> = 11 A		1.3		nC
Q <sub>g(th)</sub>	Gate charge at Vth			0.7		nC
Q <sub>oss</sub>	Output charge	V <sub>DS</sub> = 13 V, V <sub>GS</sub> = 0 V		7.2		nC
t <sub>d(on)</sub>	Turnon delay time			4.7		ns
t <sub>r</sub>	Rise time	$V_{DS} = 15 \text{ V}, V_{GS} = 4.5 \text{ V},$		5.2		ns
t <sub>d(off)</sub>	Turnoff delay time	$I_{DS} = 11 \text{ A}, R_G = 2 \Omega$		5.7		ns
t <sub>f</sub>	Fall time			2.3		ns
DIODE C	HARACTERISTICS				*	
V <sub>SD</sub>	Diode forward voltage	I <sub>SD</sub> = 11 A, V <sub>GS</sub> = 0 V		0.85	1	V
Q <sub>rr</sub>	Reverse recovery charge	V 42.V I 44.A 45/45 222.A/ -		11		nC
t <sub>rr</sub>	Reverse recovery time	$V_{DS}$ = 13 V, $I_F$ = 11 A, di/dt = 300 A/ $\mu$ s		16		ns

## 5.2 Thermal Information

 $T_A = 25$ °C (unless otherwise stated)


	PARAMETER	MIN	TYP	MAX	UNIT
$R_{\theta JC}$	Thermal resistance junction-to-case <sup>(1)</sup>			2.1	°C/W
$R_{\theta JA}$	Thermal resistance junction-to-ambient (1)(2)			50	°C/W

 <sup>(1)</sup> R<sub>θ,JC</sub> is determined with the device mounted on a 1-in² (6.45-cm²), 2-oz (0.071-mm) thick Cu pad on a 1.5-in x 1.5-in (3.81-cm x 3.81-cm), 0.06-in (1.52-mm) thick FR4 PCB. R<sub>θ,JC</sub> is specified by design, whereas R<sub>θ,JA</sub> is determined by the user's board design.
 (2) Device mounted on FR4 material with 1-in² (6.45-cm²), 2-oz (0.071-mm) thick Cu.


Submit Documentation Feedback

Copyright © 2010–2017, Texas Instruments Incorporated






Max  $R_{\theta JA} = 50^{\circ}\text{C/W}$  when mounted on 1 in<sup>2</sup> (6.45 cm<sup>2</sup>) of 2-oz (0.071-mm) thick Cu.



Max  $R_{\theta JA} = 125^{\circ} C/W$  when mounted on a minimum pad area of 2-oz (0.071-mm) thick Cu.

# 5.3 Typical MOSFET Characteristics

 $T_A = 25$ °C (unless otherwise stated)




Copyright © 2010–2017, Texas Instruments Incorporated

# TEXAS INSTRUMENTS

## **Typical MOSFET Characteristics (continued)**

 $T_A = 25$ °C (unless otherwise stated)







Figure 2. Saturation Characteristics

Figure 3. Transfer Characteristics







Figure 4. Gate Charge

Figure 5. Capacitance






Figure 7. On-State Resistance vs Gate-to-Source Voltage


Submit Documentation Feedback


Copyright © 2010–2017, Texas Instruments Incorporated




## **Typical MOSFET Characteristics (continued)**

 $T_A = 25$ °C (unless otherwise stated)












Figure 10. Maximum Safe Operating Area

Figure 11. Single Pulse Unclamped Inductive Switching




Figure 12. Maximum Drain Current vs Temperature



## 6 Device and Documentation Support

## 6.1 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. In the upper right corner, click on *Alert me* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

#### 6.2 Community Resources

The following links connect to TI community resources. Linked contents are provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's Terms of Use.

TI E2E™ Online Community TI's Engineer-to-Engineer (E2E) Community. Created to foster collaboration among engineers. At e2e.ti.com, you can ask questions, share knowledge, explore ideas and help solve problems with fellow engineers.

**Design Support** *TI's Design Support* Quickly find helpful E2E forums along with design support tools and contact information for technical support.

#### 6.3 Trademarks

NexFET, E2E are trademarks of Texas Instruments.

All other trademarks are the property of their respective owners.

#### 6.4 Electrostatic Discharge Caution



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

Product Folder Links: CSD17507Q5A

#### 6.5 Glossary

SLYZ022 — TI Glossary.


This glossary lists and explains terms, acronyms, and definitions.



# 7 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

#### 7.1 Q5A Package Dimensions




DIM		MILLIMETERS	
DIM	MIN	NOM	MAX
Α	0.90	1.00	1.10
b	0.33	0.41	0.51
С	0.20	0.25	0.34
D1	4.80	4.90	5.00
D2	3.61	3.81	4.02
Е	5.90	6.00	6.10
E1	5.70	5.75	5.80
E2	3.38	3.58	3.78
E3	3.03	3.13	3.23
е	1.17	1.27	1.37
e1	0.27	0.37	0.47
e2	0.15	0.25	0.35
Н	0.41	0.56	0.71
K	1.10	_	_
L	0.51	0.61	0.71
L1	0.06	0.13	0.20
θ	0°	_	12°

Copyright © 2010–2017, Texas Instruments Incorporated



# 7.2 Recommended PCB Pattern




DIM	MILLIMETER	RS	INCH	ES
DIIVI	MIN	MAX	MIN	MAX
F1	6.205	6.305	0.244	0.248
F2	4.46	4.56	0.176	0.18
F3	4.46	4.56	0.176	0.18
F4	0.65	0.7	0.026	0.028
F5	0.62	0.67	0.024	0.026
F6	0.63	0.68	0.025	0.027
F7	0.7	8.0	0.028	0.031
F8	0.65	0.7	0.026	0.028
F9	0.62	0.67	0.024	0.026
F10	4.9	5	0.193	0.197
F11	4.46	4.56	0.176	0.18


For recommended circuit layout for PCB designs, see *Reducing Ringing Through PCB Layout Techniques* (SLPA005).



## 7.3 Recommended Stencil Opening



#### 7.4 Q5A Tape and Reel Information



#### Notes:

- 1. 10-sprocket hole-pitch cumulative tolerance ±0.2.
- 2. Camber not to exceed 1 mm in 100 mm, noncumulative over 250 mm.
- 3. Material: black static-dissipative polystyrene.
- 4. All dimensions are in mm (unless otherwise specified).
- 5. A0 and B0 measured on a plane 0.3 mm above the bottom of the pocket.

Copyright © 2010–2017, Texas Instruments Incorporated

www.ti.com 10-Nov-2025

#### PACKAGING INFORMATION

Orderable part number	Status	Material type	Package   Pins	Package qty   Carrier	RoHS	Lead finish/	MSL rating/	Op temp (°C)	Part marking
	(1)	(2)			(3)	Ball material	Peak reflow		(6)
						(4)	(5)		
CSD17507Q5A	Active	Production	VSONP (DQJ)   8	2500   LARGE T&R	ROHS Exempt	SN	Level-1-260C-UNLIM	-55 to 150	CSD17507
CSD17507Q5A.B	Active	Production	VSONP (DQJ)   8	2500   LARGE T&R	ROHS Exempt	SN	Level-1-260C-UNLIM	-55 to 150	CSD17507
CSD17507Q5AT	Active	Production	VSONP (DQJ)   8	250   SMALL T&R	ROHS Exempt	SN	Level-1-260C-UNLIM	-55 to 150	CSD17507
CSD17507Q5AT.B	Active	Production	VSONP (DQJ)   8	250   SMALL T&R	ROHS Exempt	SN	Level-1-260C-UNLIM	-55 to 150	CSD17507

<sup>(1)</sup> Status: For more details on status, see our product life cycle.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

<sup>(2)</sup> Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

<sup>(4)</sup> Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

<sup>(5)</sup> MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

<sup>(6)</sup> Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

#### IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale, TI's General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025