







CSD18503KCS SLPS368B - SEPTEMBER 2012 - REVISED MARCH 2024

CSD18503KCS 40V N-Channel NexFET™ Power MOSFET

1 Features


- Ultra low Qg and Qgd
- Low thermal resistance
- Avalanche rated
- Logic level
- Pb free terminal plating
- RoHS compliant
- Halogen free
- TO-220 plastic package


2 Applications

- DC-DC Conversion
- Secondary Side Synchronous Rectifier
- **Motor Control**

3 Description

This 40V, 3.6mΩ, TO-220 NexFET[™] power MOSFET has been designed to minimize losses in power conversion applications.





Product Summary

T _A = 25°	С	TYPICAL VA	UNIT		
V _{DS}	Drain-to-Source Voltage 40				
Qg	Gate Charge Total (10V) 30				
Q _{gd}	Gate Charge Gate-to-Drain	4.6	nC		
_	Drain-to-Source On-Resistance	V _{GS} = 4.5V 5.4		mΩ	
R _{DS(on)}	Dialii-to-Source Off-Resistance	V _{GS} = 10V 3.6		mΩ	
V _{GS(th)}	Threshold Voltage	1.9		V	

Ordering Information (1)


	•			
Device	Package	Media	Qty	Ship
CSD18503KCS	TO-220 Plastic Package	Tube	50	Tube

For all available packages, see the orderable addendum at the end of the data sheet.

Absolute Maximum Ratings

	Absolute maximum nut	95	
$T_A = 2$	25°C	VALUE	UNIT
V_{DS}	Drain-to-Source Voltage	40	V
V_{GS}	Gate-to-Source Voltage	±20	V
	Continuous Drain Current (Package limited)	100	
I _D	Continuous Drain Current (Silicon limited), T _C = 25°C	142	A
	Continuous Drain Current (Silicon limited), T _C = 100°C	100	
I _{DM}	Pulsed Drain Current (1)	358	Α
P _D	Power Dissipation	188	W
T _J , T _{stg}	Operating Junction and Storage Temperature Range	-55 to 175	°C
E _{AS}	Avalanche Energy, single pulse I_D = 57A, L = 0.1mH, R_G = 25 Ω	162	mJ

(1) Max R_{θJC} = 0.8°C/W, pulse duration ≤100μs, duty cycle ≤1%



Gate Charge



Table of Contents

1 Features	5.1 Receiving Notification of Documentation Updates7
2 Applications1	5.2 Support Resources7
3 Description1	
4 Specifications3	
4.1 Electrical Characteristics3	
4.2 Thermal Information3	· ·
4.3 Typical MOSFET Characteristics4	7 Mechanical, Packaging, and Orderable Information8
5 Device and Documentation Support7	

4 Specifications

4.1 Electrical Characteristics

(T_A = 25°C unless otherwise stated)

	PARAMETER	TEST CONDITIONS	MIN TYP	MAX	UNIT
STATIC	CHARACTERISTICS				
BV _{DSS}	Drain-to-Source Voltage	V _{GS} = 0V, I _D = 250μA	40		V
I _{DSS}	Drain-to-Source Leakage Current	V _{GS} = 0V, V _{DS} = 32V		1	μA
I _{GSS}	Gate-to-Source Leakage Current	V _{DS} = 0V, V _{GS} = 20V		100	nA
V _{GS(th)}	Gate-to-Source Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250 \mu A$	1.5 1.9	2.3	V
	Dunin to Course On Bonistones	V _{GS} = 4.5V, I _D = 75A	5.4	6.8	mΩ
R _{DS(on)}	Drain-to-Source On-Resistance	V _{GS} = 10V, I _D = 75A	3.6	4.5	mΩ
9 _{fs}	Transconductance	V _{DS} = 20V, I _D = 75A	98		S
DYNAM	IC CHARACTERISTICS				
C _{iss}	Input Capacitance		2500	3150	pF
C _{oss}	Output Capacitance	$V_{GS} = 0V, V_{DS} = 20V, f = 1MHz$	480	600	pF
C _{rss}	Reverse Transfer Capacitance		12	16	pF
R _G	Series Gate Resistance		1.4	2.8	Ω
Qg	Gate Charge Total (4.5V)		15	18	nC
Qg	Gate Charge Total (10V)		30	36	nC
Q _{gd}	Gate Charge Gate-to-Drain	V _{DS} = 20V, I _D = 75A	4.6		nC
Q _{gs}	Gate Charge Gate-to-Source		7.7		nC
Q _{g(th)}	Gate Charge at Vth		4.7		nC
Q _{oss}	Output Charge	V _{DS} = 20V, V _{GS} = 0V	30		nC
t _{d(on)}	Turn On Delay Time		5.7		ns
t _r	Rise Time	V _{DS} = 20V, V _{GS} = 10V,	5.3		ns
t _{d(off)}	Turn Off Delay Time	$I_{DS} = 75A$, $R_G = 0\Omega$	14		ns
t _f	Fall Time		6.8		ns
DIODE (CHARACTERISTICS				
V _{SD}	Diode Forward Voltage	I _{SD} = 75A, V _{GS} = 0V	0.8	1	V
Q _{rr}	Reverse Recovery Charge	V _{DS} = 20V, I _F = 75A,	60		nC
t _{rr}	Reverse Recovery Time	di/dt = 300A/µs	37		ns

4.2 Thermal Information

(T_A = 25°C unless otherwise stated)


	THERMAL METRIC	MIN	TYP	MAX	UNIT
$R_{\theta JC}$	Junction-to-Case Thermal Resistance			0.8	°C/W
$R_{\theta JA}$	Junction-to-Ambient Thermal Resistance			62	C/VV


Copyright © 2024 Texas Instruments Incorporated



4.3 Typical MOSFET Characteristics

(T_A = 25°C unless otherwise stated)









Figure 4-3. Transfer Characteristics

Submit Document Feedback


Copyright © 2024 Texas Instruments Incorporated

www.ti.com



Product Folder Links: CSD18503KCS





5 Device and Documentation Support

5.1 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. Click on *Notifications* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

5.2 Support Resources

TI E2E[™] support forums are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's Terms of Use.

5.3 Trademarks

NexFET[™] is a trademark of Texas Instruments.

TI E2E™ is a trademark of Texas Instruments.

All trademarks are the property of their respective owners.

5.4 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

5.5 Glossary

TI Glossary

This glossary lists and explains terms, acronyms, and definitions.

6 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

Changes from Revision A (October 2023) to Revision B (March 2024)

Page

Updated the numbering format for tables, figures, and cross-references throughout the document.......



7 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

Submit Document Feedback

Copyright © 2024 Texas Instruments Incorporated

www.ti.com 8-Nov-2025

PACKAGING INFORMATION

Orderable part number	Status	Material type	Package Pins	Package qty Carrier	RoHS (3)	Lead finish/ Ball material	MSL rating/ Peak reflow	Op temp (°C)	Part marking (6)
CSD18503KCS	Active	Production	TO-220 (KCS) 3	50 TUBE	ROHS Exempt	SN	N/A for Pkg Type	-55 to 175	CSD18503KCS
CSD18503KCS.B	Active	Production	TO-220 (KCS) 3	50 TUBE	ROHS Exempt	SN	N/A for Pkg Type	-55 to 175	CSD18503KCS

⁽¹⁾ Status: For more details on status, see our product life cycle.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

⁽²⁾ Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

⁽⁴⁾ Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

⁽⁵⁾ MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

⁽⁶⁾ Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

PACKAGE MATERIALS INFORMATION

www.ti.com 5-Sep-2025

TUBE



*All dimensions are nominal

Device	Package Name	Package Type	Pins	SPQ	L (mm)	W (mm)	T (µm)	B (mm)
CSD18503KCS	KCS	TO-220	3	50	532	34.1	700	9.6
CSD18503KCS.B	KCS	TO-220	3	50	532	34.1	700	9.6



TO-220



NOTES:

- 1. Dimensions are in millimeters. Any dimension in brackets or parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.

 2. This drawing is subject to change without notice.

 3. Reference JEDEC registration TO-220.



TO-220



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale, TI's General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025