

# CSD19536KTT 100V N-Channel NexFET™ Power MOSFET

## 1 Features


- Ultra-low  $Q_g$  and  $Q_{gd}$
- Low thermal resistance
- Avalanche rated
- Lead-free terminal plating
- RoHS compliant
- Halogen free
- D<sup>2</sup>PAK plastic package

## 2 Applications


- Secondary side synchronous rectifier
- Hot swap
- Motor control

## 3 Description

This 100V, 2m $\Omega$ , D<sup>2</sup>PAK (TO-263) NexFET™ power MOSFET is designed to minimize losses in power conversion applications.



**Pin Out**



**$R_{DS(on)}$  vs  $V_{GS}$**

## Product Summary

$T_A = 25^\circ\text{C}$		TYPICAL VALUE	UNIT
$V_{DS}$	Drain-to-Source Voltage	100	V
$Q_g$	Gate Charge Total (10V)	118	nC
$Q_{gd}$	Gate Charge Gate-to-Drain	17	nC
$R_{DS(on)}$	Drain-to-Source On-Resistance	$V_{GS} = 6\text{V}$	2.2
		$V_{GS} = 10\text{V}$	2
$V_{GS(th)}$	Threshold Voltage	2.5	V

## Device Information


DEVICE <sup>(1)</sup>	QTY	MEDIA	PACKAGE	SHIP
CSD19536KTT	500	13-Inch Reel	D <sup>2</sup> PAK Plastic Package	Tape and Reel
CSD19536KTTT	50			

- (1) For all available packages, see the orderable addendum at the end of the data sheet.

## Absolute Maximum Ratings

$T_A = 25^\circ\text{C}$		VALUE	UNIT
$V_{DS}$	Drain-to-Source Voltage	100	V
$V_{GS}$	Gate-to-Source Voltage	$\pm 20$	V
$I_D$	Continuous Drain Current (Package Limited)	200	A
	Continuous Drain Current (Silicon Limited), $T_C = 25^\circ\text{C}$	272	
	Continuous Drain Current (Silicon Limited), $T_C = 100^\circ\text{C}$	192	
$I_{DM}$	Pulsed Drain Current <sup>(1)</sup>	400	A
$P_D$	Power Dissipation	375	W
$T_J, T_{stg}$	Operating Junction, Storage Temperature	$-55$ to $175$	$^\circ\text{C}$
$E_{AS}$	Avalanche Energy, Single Pulse $I_D = 127\text{A}$ , $L = 0.1\text{mH}$ , $R_G = 25\Omega$	806	mJ

- (1) Max  $R_{\theta JC} = 0.4^\circ\text{C/W}$ , Pulse duration  $\leq 100\mu\text{s}$ , Duty cycle  $\leq 1\%$ .



**Gate Charge**



## Table of Contents

<b>1 Features</b> .....	<b>1</b>	<b>5 Device and Documentation Support</b> .....	<b>7</b>
<b>2 Applications</b> .....	<b>1</b>	5.1 Receiving Notification of Documentation Updates.....	7
<b>3 Description</b> .....	<b>1</b>	5.2 Community Resources.....	7
<b>4 Specifications</b> .....	<b>3</b>	5.3 Trademarks.....	7
4.1 Electrical Characteristics.....	3	<b>6 Revision History</b> .....	<b>7</b>
4.2 Thermal Information.....	3	<b>7 Mechanical, Packaging, and Orderable Information</b> ....	<b>8</b>
4.3 Typical MOSFET Characteristics.....	4		

---

## 4 Specifications

### 4.1 Electrical Characteristics

$T_A = 25^\circ\text{C}$  (unless otherwise stated)

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT	
STATIC CHARACTERISTICS							
BV <sub>DSS</sub>	Drain-to-source voltage	V <sub>GS</sub> = 0V, I <sub>D</sub> = 250μA	100			V	
I <sub>DSS</sub>	Drain-to-source leakage current	V <sub>GS</sub> = 0V, V <sub>DS</sub> = 80V	1			μA	
I <sub>GSS</sub>	Gate-to-source leakage current	V <sub>DS</sub> = 0V, V <sub>GS</sub> = 20V	100			nA	
V <sub>GS(th)</sub>	Gate-to-source threshold voltage	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250μA	2.1	2.5	3.2	V	
R <sub>DS(on)</sub>	Drain-to-source on-resistance	V <sub>GS</sub> = 6V, I <sub>D</sub> = 100A	2.2			mΩ	
		V <sub>GS</sub> = 10V, I <sub>D</sub> = 100A	2				
g <sub>fs</sub>	Transconductance	V <sub>DS</sub> = 10V, I <sub>D</sub> = 100A	329			S	
DYNAMIC CHARACTERISTICS							
C <sub>iss</sub>	Input capacitance	V <sub>GS</sub> = 0V, V <sub>DS</sub> = 50V, f = 1MHz	9250			12000	pF
C <sub>oss</sub>	Output capacitance		1820			2370	pF
C <sub>rss</sub>	Reverse transfer capacitance		47			61	pF
R <sub>G</sub>	Series gate resistance		1.4			2.8	Ω
Q <sub>g</sub>	Gate charge total (10V)	V <sub>DS</sub> = 50V, I <sub>D</sub> = 100A	118			153	nC
Q <sub>gd</sub>	Gate charge gate-to-drain		17				nC
Q <sub>gs</sub>	Gate charge gate-to-source		37				nC
Q <sub>g(th)</sub>	Gate charge at V <sub>th</sub>		24				nC
Q <sub>oss</sub>	Output charge	V <sub>DS</sub> = 50V, V <sub>GS</sub> = 0V	335				nC
t <sub>d(on)</sub>	Turnon delay time	V <sub>DS</sub> = 50V, V <sub>GS</sub> = 10V, I <sub>DS</sub> = 100A, R <sub>G</sub> = 0Ω	13				ns
t <sub>r</sub>	Rise time		8				ns
t <sub>d(off)</sub>	Turnoff delay time		32				ns
t <sub>f</sub>	Fall time		6				ns
DIODE CHARACTERISTICS							
V <sub>SD</sub>	Diode forward voltage	I <sub>SD</sub> = 100A, V <sub>GS</sub> = 0V	0.9			1.1	V
Q <sub>rr</sub>	Reverse recovery charge	V <sub>DS</sub> = 50V, I <sub>F</sub> = 100A, di/dt = 300A/μs	548				nC
t <sub>rr</sub>	Reverse recovery time		103				ns




### 4.2 Thermal Information


$T_A = 25^\circ\text{C}$  (unless otherwise stated)

THERMAL METRIC		MIN	TYP	MAX	UNIT
$R_{\theta JC}$	Junction-to-case thermal resistance			0.4	$^\circ\text{C/W}$
$R_{\theta JA}$	Junction-to-ambient thermal resistance			62	$^\circ\text{C/W}$


### 4.3 Typical MOSFET Characteristics

$T_A = 25^\circ\text{C}$  (unless otherwise stated)







**Figure 4-4. Gate Charge**




**Figure 4-5. Capacitance**




**Figure 4-6. Threshold Voltage vs Temperature**



**Figure 4-7. On-State Resistance vs Gate-to-Source Voltage**



**Figure 4-8. Normalized On-State Resistance vs Temperature**



**Figure 4-9. Typical Diode Forward Voltage**




Figure 4-10. Maximum Safe Operating Area




Figure 4-11. Single Pulse Unclamped Inductive Switching




Figure 4-12. Maximum Drain Current vs Temperature

## 5 Device and Documentation Support

### 5.1 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. In the upper right corner, click on *Alert me* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

### 5.2 Community Resources

### 5.3 Trademarks

NexFET™ is a trademark of Texas Instruments.  
All trademarks are the property of their respective owners.

## 6 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

<b>Changes from Revision B (May 2015) to Revision C (May 2025)</b>	<b>Page</b>
• Updated the numbering format for tables, figures, and cross-references throughout the document.....	<b>1</b>

<b>Changes from Revision A (May 2015) to Revision B (August 2016)</b>	<b>Page</b>
• Added <a href="#">Section 5.1</a> section.....	<b>7</b>

<b>Changes from Revision * (March 2015) to Revision A (May 2015)</b>	<b>Page</b>
• Added <a href="#">Section 5.2</a> section.....	<b>7</b>
• Added PCB and stencil drawings in <a href="#">Section 7</a> .....	<b>8</b>

## 7 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.



## PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package   Pins	Package qty   Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
<a href="#">CSD19536KTT</a>	Active	Production	DDPAK/ TO-263 (KTT)   2	500   LARGE T&R	ROHS Exempt	SN	Level-2-260C-1 YEAR	-55 to 175	CSD19536KTT
CSD19536KTT.B	Active	Production	DDPAK/ TO-263 (KTT)   2	500   LARGE T&R	ROHS Exempt	SN	Level-2-260C-1 YEAR	-55 to 175	CSD19536KTT
<a href="#">CSD19536KTTT</a>	Active	Production	DDPAK/ TO-263 (KTT)   2	50   SMALL T&R	ROHS Exempt	SN	Level-2-260C-1 YEAR	-55 to 175	CSD19536KTT
CSD19536KTTT.B	Active	Production	DDPAK/ TO-263 (KTT)   2	50   SMALL T&R	ROHS Exempt	SN	Level-2-260C-1 YEAR	-55 to 175	CSD19536KTT

<sup>(1)</sup> **Status:** For more details on status, see our [product life cycle](#).

<sup>(2)</sup> **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

<sup>(4)</sup> **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

<sup>(5)</sup> **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

<sup>(6)</sup> **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.



## TAPE AND REEL INFORMATION



\*All dimensions are nominal


Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
CSD19536KTT	DDPAK/ TO-263	KTT	2	500	330.0	24.4	10.8	16.3	5.11	16.0	24.0	Q2
CSD19536KTTT	DDPAK/ TO-263	KTT	2	50	330.0	24.4	10.8	16.3	5.11	16.0	24.0	Q2

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
CSD19536KTT	DDPAK/TO-263	KTT	2	500	340.0	340.0	38.0
CSD19536KTTT	DDPAK/TO-263	KTT	2	50	340.0	340.0	38.0



4222117/C 02/2017

## NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. Features may not exist and shape may vary per different assembly sites.
4. Reference JEDEC registration TO-263.

# EXAMPLE BOARD LAYOUT


KTT0002A

TO-263 - 4.7 mm max height

TO-263



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:5X



SOLDER MASK DETAILS

4222117/C 02/2017


NOTES: (continued)

5. This package is designed to be soldered to a thermal pad on the board. For more information, see Texas Instruments literature numbers SLMA002 ([www.ti.com/lit/slm002](http://www.ti.com/lit/slm002)) and SLMA004 ([www.ti.com/lit/slma004](http://www.ti.com/lit/slma004)).
6. Vias are optional depending on application, refer to device data sheet. It is recommended that vias under paste be filled, plugged or tented.

**KT0002A**

**TO-263 - 4.7 mm max height**

TO-263



## SOLDER PASTE EXAMPLE BASED ON 0.125 mm THICK STENCIL

EXPOSED PAD  
60.5% PRINTED SOLDER COVERAGE BY AREA  
SCALE:6X

4222117/C 02/2017

NOTES: (continued)

7. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
8. Board assembly site may have different recommendations for stencil design.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2025, Texas Instruments Incorporated