









CSD83325L SLPS494C - NOVEMBER 2014 - REVISED NOVEMBER 2023

CSD83325L 12-V Dual N-Channel NexFET™ Power MOSFET

1 Features

- Common drain configuration
- Low-on resistance
- Small footprint of 2.2 mm × 1.15 mm
- Lead free
- RoHS compliant
- Halogen free
- Gate ESD protection

2 Applications


- Battery management
- **Battery protection**

3 Description


This 12-V, $9.9\text{-m}\Omega$, $2.2\text{-mm} \times 1.15\text{-mm}$ LGA Dual NexFET™ power MOSFET is designed to minimize resistance and gate charge in a small footprint. Its small footprint and common drain configuration make the device ideal for battery pack applications in small handheld devices.



Top View



Configuration



R_{DS(on)} vs V_{GS}

Product Summary

T _A = 25°C		TYPICAL V	UNIT	
V _{S1S2}	Source-to-Source Voltage	12	12	
Qg	Gate Charge Total (4.5 V)	8.4	8.4	
Q _{gd}	Gate Charge Gate-to-Drain	1.9	nC	
		V _{GS} = 2.5 V	17.5	mΩ
R _{S1S2(on)}	Source-to-Source On Resistance	V _{GS} = 3.8 V	10.9	mΩ
		V _{GS} = 4.5 V 9.9		mΩ
V _{GS(th)}	Threshold Voltage	1.0		V

Device Information⁽¹⁾


DEVICE	QTY	MEDIA	PACKAGE	SHIP
CSD83325L	3000		2.20-mm × 1.15-mm	Таре
CSD83325LT	250	7-Inch Reel	Land Grid Array (LGA) Package	and Reel

For all available packages, see the orderable addendum at the end of the data sheet.

Absolute Maximum Ratings

T _A = 25	s°C	VALUE	UNIT					
V _{S1S2}	Source-to-Source Voltage	12	V					
V _{GS}	Gate-to-Source Voltage	±10	V					
I _S	Continuous Source Current ⁽¹⁾	8	Α					
I _{SM}	Pulsed Source Current ⁽²⁾	52	Α					
P _D	Power Dissipation	2.3	W					
V _(ESD)	Human-Body Model (HBM)	2000	V					
T _J , T _{stg}	Operating Junction Temperature, Storage Temperature	-55 to 150	°C					

- Device operating at a temperature of 105°C. (1)
- Typical min Cu R_{θJA} = 150°C/W, pulse duration ≤ 100 μs, duty (2) cycle ≤ 1%.



Gate Charge



Table of Contents

1 Features1	5.1 Third-Party Products Disclaimer6
2 Applications1	5.2 Receiving Notification of Documentation Updates6
3 Description1	
4 Specifications3	
4.1 Electrical Characteristics3	
4.2 Thermal Information3	5.6 Glossary6
4.3 Typical MOSFET Characteristics4	6 Revision History6
5 Device and Documentation Support6	7 Mechanical, Packaging, and Orderable Information7

4 Specifications

4.1 Electrical Characteristics

 $T_A = 25^{\circ}C$ (unless otherwise stated)

	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
STATIC C	CHARACTERISTICS					
BV _{S1S2}	Source-to-source voltage	V _{GS} = 0 V, I _S = 250 μA	12			V
I _{S1S2}	Source-to-source leakage current	V _{GS} = 0 V, V _{S1S2} = 9.6 V			1.0	μA
I _{GSS}	Gate-to-source leakage current	V _{S1S2} = 0 V, V _{GS} = 10 V			10	μA
V _{GS(th)}	Gate-to-source threshold voltage	V _{S1S2} = V _{GS} , I _S = 250 μA	0.7	1.0	1.4	V
		V _{GS} = 2.5 V, I _S = 5 A	12.0	17.5	23.0	mΩ
R _{S1S2(on)}	Source-to-source on resistance	V _{GS} = 3.8 V, I _S = 5 A	8.8	10.9	13.0	mΩ
		V _{GS} = 4.5 V, I _S = 5 A	7.9	9.9	11.9	mΩ
9 _{fs}	Transconductance	V _{S1S2} = 1.2 V, I _S = 5 A		36		S
DYNAMI	C CHARACTERISTICS ⁽¹⁾					
C _{iss}	Input capacitance			902	1170	pF
C _{oss}	Output capacitance	$V_{GS} = 0 \text{ V}, V_{S1S2} = 6 \text{ V}, f = 1 \text{ MHz}$		187	243	pF
C _{rss}	Reverse transfer capacitance			111	144	pF
Qg	Gate charge total (4.5 V)			8.4	10.9	nC
Q _{gd}	Gate charge gate-to-drain	V -6VI -5A		1.9		nC
Q _{gs}	Gate charge gate-to-source	$V_{S1S2} = 6 \text{ V, } I_S = 5 \text{ A}$		2.2		nC
Q _{g(th)}	Gate charge at V _{th}			0.6		nC
Q _{oss}	Output charge	V _{S1S2} = 6 V, V _{GS} = 0 V		2.9		nC
t _{d(on)}	Turnon delay time			205		ns
t _r	Rise time	V _{S1S2} = 6 V, V _{GS} = 4.5 V,		353		ns
t _{d(off)}	Turnoff delay time	$I_{S1S2} = 5 \text{ A}, R_G = 0 \Omega$		711		ns
t _f	Fall time			589		ns
DIODE C	HARACTERISTICS		1			
V _{F(S-S)}	Source-to-source diode forward voltage	I _{SS} = 5 A, V _{G1S1} = 0 V, V _{G2S2} = 4.5 V		0.79	1.0	V

⁽¹⁾ Dynamic characteristics values specified are per single FET.

4.2 Thermal Information

T_A = 25°C (unless otherwise stated)

	THERMAL METRIC	MIN	TYP	MAX	UNIT
$R_{\theta JA}$	Junction-to-ambient thermal resistance ⁽¹⁾		150		°C/W
	Junction-to-ambient thermal resistance ⁽²⁾		55		C/VV


⁽¹⁾ Device mounted on FR4 material with minimum Cu mounting area.


⁽²⁾ Device mounted on FR4 material with 1-in² (6.45-cm²), 2-oz (0.071-mm) thick Cu.





4.3 Typical MOSFET Characteristics


 $T_A = 25$ °C (unless otherwise stated)













Submit Document Feedback

Copyright © 2023 Texas Instruments Incorporated






30

Figure 4-6. Threshold Voltage vs Temperature

Figure 4-7. On-State Source-to-Source Resistance vs Gate-to-Source Voltage







Figure 4-8. Normalized On-State Resistance vs
Temperature

Figure 4-9. Typical Diode Forward Voltage






Figure 4-11. Maximum Source Current vs
Temperature



5 Device and Documentation Support

5.1 Third-Party Products Disclaimer

TI'S PUBLICATION OF INFORMATION REGARDING THIRD-PARTY PRODUCTS OR SERVICES DOES NOT CONSTITUTE AN ENDORSEMENT REGARDING THE SUITABILITY OF SUCH PRODUCTS OR SERVICES OR A WARRANTY, REPRESENTATION OR ENDORSEMENT OF SUCH PRODUCTS OR SERVICES, EITHER ALONE OR IN COMBINATION WITH ANY TI PRODUCT OR SERVICE.

5.2 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. Click on *Notifications* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

5.3 Support Resources

TI E2E[™] support forums are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's Terms of Use.

5.4 Trademarks

NexFET[™] and TI E2E[™] are trademarks of Texas Instruments. All trademarks are the property of their respective owners.

5.5 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

5.6 Glossary

TI Glossary

This glossary lists and explains terms, acronyms, and definitions.

6 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

Changes from Revision B (February 2017) to Revision C (November 2023)	Page
Updated Threshold Voltage GS(th) from 0.95 V to 1.0 V	
 Updated the numbering format for tables, figures, and cross-references throughout the docume 	
 Updated Source-to-source on resistance VGS = 2.5 V from 14 mΩ to 12 mΩ 	
 Updated Gate-to-source threshold voltage from 0.75 V min, 0.95 V typ, 1.25 V max to 0.7 V min 	ı, 1.0 V typ,
1.4 V max	
Changes from Revision A (January 2016) to Revision B (February 2017)	Page
, , , , , , , , , , , , , , , , , , , ,	
 Added Diode Characteristics (V_{F(S-S)}) in the <i>Electrical Characteristics</i> table Added Figure 4-9 to <i>Typical MOSFET Characteristics</i> section 	
Changes from Revision * (November 2014) to Revision A (January 2016)	Page
Improved graph setup for readability	4

Submit Document Feedback

7 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

www.ti.com 9-Nov-2025

PACKAGING INFORMATION

Orderable part number	Status	Material type	Package Pins	Package qty Carrier	RoHS	Lead finish/	MSL rating/	Op temp (°C)	Part marking
	(1)	(2)			(3)	Ball material	Peak reflow		(6)
						(4)	(5)		
CSD83325L	Active	Production	PICOSTAR (YJE) 6	3000 LARGE T&R	Yes	NIAU	Level-1-260C-UNLIM	-55 to 150	83325L
CSD83325L.B	Active	Production	PICOSTAR (YJE) 6	3000 LARGE T&R	Yes	NIAU	Level-1-260C-UNLIM	-55 to 150	83325L
CSD83325LT	Active	Production	PICOSTAR (YJE) 6	250 SMALL T&R	Yes	NIAU	Level-1-260C-UNLIM	-55 to 150	83325L
CSD83325LT.B	Active	Production	PICOSTAR (YJE) 6	250 SMALL T&R	Yes	NIAU	Level-1-260C-UNLIM	-55 to 150	83325L

⁽¹⁾ Status: For more details on status, see our product life cycle.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

⁽²⁾ Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

⁽⁴⁾ Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

⁽⁵⁾ MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

⁽⁶⁾ Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

PACKAGE MATERIALS INFORMATION

www.ti.com 22-Nov-2024

TAPE AND REEL INFORMATION





A0	Dimension designed to accommodate the component width
В0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE




*All dimensions are nominal

Device		Package Drawing			Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
CSD83325L	ICOSTAF	YJE	6	3000	180.0	8.4	1.25	2.34	0.32	4.0	8.0	Q1
CSD83325LT	PICOSTAF	YJE	6	250	180.0	8.4	1.25	2.34	0.32	4.0	8.0	Q1



www.ti.com 22-Nov-2024




*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
CSD83325L	PICOSTAR	YJE	6	3000	182.0	182.0	20.0
CSD83325LT	PICOSTAR	YJE	6	250	182.0	182.0	20.0



PicoStar



NOTES:


PicoStar is a trademark of Texas Instruments.

- 1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.

 2. This drawing is subject to change without notice.



PicoStar




NOTES: (continued)

3. Final dimensions may vary due to manufacturing tolerance considerations and also routing constraints. For more information, see Texas Instruments literature number SLUA271 (www.ti.com/lit/slua271).



PicoStar



NOTES: (continued)

4. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release.



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale, TI's General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025