

## SNx4LS245 Octal Bus Transceivers With 3-State Outputs

## 1 Features

- 3-State Outputs Drive Bus Lines Directly
- PNP Inputs Reduce DC Loading on Bus Lines
- Hysteresis at Bus Inputs Improves Noise Margins
- Typical Propagation Delay Times Port to Port, 8 ns

## 2 Applications

- Building Automation
- Electronic Point of Sale
- Factory Automation and Control
- Test and Measurement

### 3 Description

These octal bus transceivers are designed for asynchronous two-way communication between data buses. The control-function implementation minimizes external timing requirements.


The SNx4LS245 devices allow data transmission from the A bus to the B bus or from the B bus to the A bus, depending on the logic level at the direction-control (DIR) input. The output-enable ( $\overline{\text{OE}}$ ) input can disable the device so that the buses are effectively isolated.

### Device Information<sup>(1)</sup>

| PART NUMBER | PACKAGE   | BODY SIZE (NOM)    |
|-------------|-----------|--------------------|
| SN54LS245J  | CDIP (20) | 24.20 mm x 6.92 mm |
| SN54LS245W  | CFP (20)  | 7.02 mm x 13.72 mm |
| SN54LS245FK | LCCC (20) | 8.89 mm x 8.89 mm  |
| SN74LS245DB | SSOP (20) | 7.20 mm x 5.30 mm  |
| SN74LS245DW | SOIC (20) | 12.80 mm x 7.50 mm |
| SN74LS245N  | PDIP (20) | 24.33 mm x 6.35 mm |
| SN74LS245NS | SO (20)   | 12.60 mm x 5.30 mm |

(1) For all available packages, see the orderable addendum at the end of the data sheet.

### Logic Diagram (Positive Logic)



## To Seven Other Channels

Copyright © 2016, Texas Instruments Incorporated



An IMPORTANT NOTICE at the end of this data sheet addresses availability, warranty, changes, use in safety-critical applications, intellectual property matters and other important disclaimers. PRODUCTION DATA.

On products compliant to MIL-PRF-38535, all parameters are tested unless otherwise noted. On all other products, production processing does not necessarily include testing of all parameters.

## Table of Contents

|  |          |  |           |
|--|----------|--|-----------|
| <b>1 Features</b> .....                          | <b>1</b> | 9.3 Feature Description .....                                    | <b>8</b>  |
| <b>2 Applications</b> .....                      | <b>1</b> | 9.4 Device Functional Modes .....                                | <b>8</b>  |
| <b>3 Description</b> .....                       | <b>1</b> | <b>10 Application and Implementation</b> .....                   | <b>10</b> |
| <b>4 Revision History</b> .....                  | <b>2</b> | 10.1 Application Information .....                               | <b>10</b> |
| <b>5 Device Comparison Table</b> .....           | <b>3</b> | 10.2 Typical Application .....                                   | <b>10</b> |
| <b>6 Pin Configuration and Functions</b> .....   | <b>3</b> | <b>11 Power Supply Recommendations</b> .....                     | <b>12</b> |
| <b>7 Specifications</b> .....                    | <b>4</b> | <b>12 Layout</b> .....   | <b>12</b> |
| 7.1 Absolute Maximum Ratings .....               | <b>4</b> | 12.1 Layout Guidelines .....                                     | <b>12</b> |
| 7.2 ESD Ratings .....                            | <b>4</b> | 12.2 Layout Example .....  | <b>12</b> |
| 7.3 Recommended Operating Conditions .....       | <b>4</b> | <b>13 Device and Documentation Support</b> .....                 | <b>13</b> |
| 7.4 Thermal Information .....                    | <b>4</b> | 13.1 Related Links .....   | <b>13</b> |
| 7.5 Electrical Characteristics .....             | <b>5</b> | 13.2 Receiving Notification of Documentation Updates .....       | <b>13</b> |
| 7.6 Switching Characteristics .....              | <b>5</b> | 13.3 Community Resource .....                                    | <b>13</b> |
| 7.7 Typical Characteristics .....                | <b>6</b> | 13.4 Trademarks .....  | <b>13</b> |
| <b>8 Parameter Measurement Information</b> ..... | <b>7</b> | 13.5 Electrostatic Discharge Caution .....                       | <b>13</b> |
| <b>9 Detailed Description</b> .....              | <b>8</b> | 13.6 Glossary .....  | <b>13</b> |
| 9.1 Overview .....                               | <b>8</b> | <b>14 Mechanical, Packaging, and Orderable Information</b> ..... | <b>13</b> |
| 9.2 Functional Block Diagram .....               | <b>8</b> |  |           |

## 4 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.


| Changes from Revision A (February 2002) to Revision B  | Page     |
|--|----------|
| • Added <i>ESD Ratings</i> table, <i>Feature Description</i> section, <i>Device Functional Modes</i> , <i>Application and Implementation</i> section, <i>Power Supply Recommendations</i> section, <i>Layout</i> section, <i>Device and Documentation Support</i> section, and <i>Mechanical, Packaging, and Orderable Information</i> section ..... | <b>1</b> |
| • Deleted <i>Ordering Information</i> table; see POA at the end of the data sheet .....  | <b>1</b> |
| • Changed $R_{\theta JA}$ values in <i>Thermal Information</i> table: 70 to 91.7 for DB package, 58 to 79 for DW package, 69 to 46.1 for N package, and 60 to 74.2 for NS package .....  | <b>4</b> |

## 5 Device Comparison Table


| TYPE      | $I_{OL}$<br>(SINK CURRENT) | $I_{OH}$<br>(SOURCE CURRENT) |
|-----------|----------------------------|------------------------------|
| SN54LS245 | 12 mA                      | –12 mA                       |
| SN74LS245 | 24 mA                      | –15 mA                       |

## 6 Pin Configuration and Functions

**J, W, DB, DW, N, or NS Package**  
20-Pin CDIP, CFP, SSOP, SOIC, PDIP, or SO  
Top View



**FK Package**  
20-Pin LCCC  
Top View



### Pin Functions

| PIN |                 | I/O | DESCRIPTION  |
|-----|-----------------|-----|--|
| NO. | NAME            |     |  |
| 1   | DIR             | I   | Controls signal direction; Low = Bx to Ax, High = Ax to Bx   |
| 2   | A1              | I/O | Channel 1, A side  |
| 3   | A2              | I/O | Channel 2, A side  |
| 4   | A3              | I/O | Channel 3, A side  |
| 5   | A4              | I/O | Channel 4, A side  |
| 6   | A5              | I/O | Channel 5, A side  |
| 7   | A6              | I/O | Channel 6, A side  |
| 8   | A7              | I/O | Channel 7, A side  |
| 9   | A8              | I/O | Channel 8, A side  |
| 10  | GND             | —   | Ground   |
| 11  | B8              | O/I | Channel 8, B side  |
| 12  | B7              | O/I | Channel 7, B side  |
| 13  | B6              | O/I | Channel 6, B side  |
| 14  | B5              | O/I | Channel 5, B side  |
| 15  | B4              | O/I | Channel 4, B side  |
| 16  | B3              | O/I | Channel 3, B side  |
| 17  | B2              | O/I | Channel 2, B side  |
| 18  | B1              | O/I | Channel 1, B side  |
| 19  | $\overline{OE}$ | I   | Active low output enable; Low = all channels active, High = all channels disabled (high impedance) |
| 20  | V <sub>CC</sub> | —   | Power supply   |

## 7 Specifications

### 7.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)

|           |  | MIN | MAX | UNIT |
|-----------|--|-----|-----|------|
| $V_{CC}$  | Supply voltage                         |     | 7   | V    |
| $V_I$     | Input voltage <sup>(1)</sup>           |     | 7   | V    |
| $T_J$     | Operating virtual junction temperature |     | 150 | °C   |
| $T_{stg}$ | Storage temperature                    | –65 | 150 | °C   |

(1) All voltage values are with respect to GND.

### 7.2 ESD Ratings

|             |                         | VALUE  | UNIT  |
|-------------|-------------------------|--|-------|
| $V_{(ESD)}$ | Electrostatic discharge | Human-body model (HBM), per ANSI/ESDA/JEDEC JS-001 <sup>(1)</sup>              | ±2500 |
|             |                         | Charged-device model (CDM), per JEDEC specification JESD22-C101 <sup>(2)</sup> | ±1500 |

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

### 7.3 Recommended Operating Conditions

|          |                                |           | MIN  | NOM | MAX  | UNIT |
|----------|--------------------------------|-----------|------|-----|------|------|
| $V_{CC}$ | Supply voltage                 | SN54LS245 | 4.5  | 5   | 5.5  | V    |
|          |                                | SN74LS245 | 4.75 | 5   | 5.25 |      |
| $I_{OH}$ | High-level output current      | SN54LS245 |      |     | –12  | mA   |
|          |                                | SN74LS245 |      |     | –15  |      |
| $I_{OL}$ | Low-level output current       | SN54LS245 |      |     | 12   | mA   |
|          |                                | SN74LS245 |      |     | 24   |      |
| $T_A$    | Operating free-air temperature | SN54LS245 | –55  |     | 125  | °C   |
|          |                                | SN74LS245 | 0    |     | 70   |      |

### 7.4 Thermal Information

| THERMAL METRIC <sup>(1)</sup> |  | SNx4LS245           |                      |                     |              |              |             |            | UNIT |
|-------------------------------|--|---------------------|----------------------|---------------------|--------------|--------------|-------------|------------|------|
|                               |  | J<br>(CDIP)         | W<br>(CFP)           | FK<br>(LCCC)        | DB<br>(SSOP) | DW<br>(SOIC) | N<br>(PDIP) | NS<br>(SO) |      |
|                               |  | 20 PINS             | 20 PINS              | 20 PINS             | 20 PINS      | 20 PINS      | 20 PINS     | 20 PINS    |      |
| $R_{\theta JA}$               | Junction-to-ambient thermal resistance       | N/A                 | N/A                  | N/A                 | 91.7         | 79.0         | 46.1        | 74.2       | °C/W |
| $R_{\theta JC(top)}$          | Junction-to-case (top) thermal resistance    | 42.3 <sup>(2)</sup> | 70.1 <sup>(2)</sup>  | 46.7 <sup>(2)</sup> | 53.1         | 44.4         | 32.1        | 40.4       | °C/W |
| $R_{\theta JB}$               | Junction-to-board thermal resistance         | 56.9 <sup>(2)</sup> | 109.5 <sup>(2)</sup> | 45.6 <sup>(2)</sup> | 46.8         | 46.9         | 27.0        | 41.7       | °C/W |
| $\Psi_{JT}$                   | Junction-to-top characterization parameter   | N/A                 | N/A                  | N/A                 | 18.9         | 18.0         | 17.6        | 16.9       | °C/W |
| $\Psi_{JB}$                   | Junction-to-board characterization parameter | N/A                 | N/A                  | N/A                 | 46.4         | 46.3         | 26.9        | 41.3       | °C/W |
| $R_{\theta JC(bot)}$          | Junction-to-case (bottom) thermal resistance | 15.9 <sup>(2)</sup> | 13.0 <sup>(2)</sup>  | 6.7 <sup>(2)</sup>  | N/A          | N/A          | N/A         | N/A        | °C/W |

(1) For more information about traditional and new thermal metrics, see the [Semiconductor and IC Package Thermal Metrics](#) application report.

(2) MIL-STD-883 for  $R_{th-JC}$  JEDEC JESD51 for  $R_{th-JB}$  (body not contact PCB)

## 7.5 Electrical Characteristics

over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER                                       |  |                     | TEST CONDITIONS <sup>(1)</sup>   |                         | MIN       | TYP <sup>(1)</sup> | MAX  | UNIT |
|---|--|---------------------|--|-------------------------|-----------|--------------------|------|------|
| V <sub>IH</sub>                                 | High-level input voltage                             |                     |  |                         | 2         |                    |      | V    |
| V <sub>IL</sub>                                 | Low-level input voltage                              |                     | SN54LS245  |                         |           |                    | 0.7  | V    |
|   |  |                     | SN74LS245  |                         |           |                    | 0.8  |      |
| V <sub>IK</sub>                                 | Input clamp voltage                                  |                     | V <sub>CC</sub> = MIN,   | I <sub>I</sub> = –18 mA |           |                    | –1.5 | V    |
| Hysteresis (V <sub>T+</sub> – V <sub>T–</sub> ) |  | A or B              | V <sub>CC</sub> = MIN  |                         | 0.2       | 0.4                |      | V    |
| V <sub>OH</sub>                                 | High-level output voltage                            |                     | V <sub>CC</sub> = MIN,<br>V <sub>IL</sub> = V <sub>IL(max)</sub><br>V <sub>IH</sub> = 2 V, | I <sub>OH</sub> = –3 mA | 2.4       | 3.4                |      | V    |
|   |  |                     |  | I <sub>OH</sub> = MAX   | 2         |                    |      |      |
| V <sub>OL</sub>                                 | Low-level output voltage                             |                     | V <sub>CC</sub> = MIN,<br>V <sub>IH</sub> = 2 V,<br>V <sub>IL</sub> = V <sub>IL(max)</sub> | I <sub>OL</sub> = 12 mA |           |                    | 0.4  | V    |
|   |  |                     |  | I <sub>OL</sub> = 24 mA | SN74LS245 |                    | 0.5  |      |
| I <sub>OZH</sub>                                | Off-state output current, high-level voltage applied |                     | V <sub>CC</sub> = MAX,<br>OE at 2 V  | V <sub>O</sub> = 2.7 V  |           |                    | 20   | μA   |
| I <sub>OZL</sub>                                | Off-state output current, low-level voltage applied  |                     | V <sub>CC</sub> = MAX,<br>OE at 2 V  | V <sub>O</sub> = 0.4 V  |           |                    | –200 | μA   |
| I <sub>I</sub>                                  | Input current at maximum input voltage               | A or B              | V <sub>CC</sub> = MAX  | V <sub>I</sub> = 5.5 V  |           |                    | 0.1  | mA   |
|   |  | DIR or OE           |  | V <sub>I</sub> = 7 V    |           |                    | 0.1  |      |
| I <sub>IH</sub>                                 | High-level input current                             |                     | V <sub>CC</sub> = MAX,   | V <sub>IH</sub> = 2.7 V |           |                    | 20   | μA   |
| I <sub>IL</sub>                                 | Low-level input current                              |                     | V <sub>CC</sub> = MAX,   | V <sub>IL</sub> = 0.4 V |           |                    | –0.2 | mA   |
| I <sub>OS</sub>                                 | Short-circuit output current <sup>(2)</sup>          |                     | V <sub>CC</sub> = MAX  |                         | –40       |                    | –225 | mA   |
| I <sub>CC</sub>                                 | Supply current                                       | Total, outputs high | V <sub>CC</sub> = MAX  | Outputs open            |           |                    | 48   | mA   |
|   |  | Total, outputs low  |  |                         |           |                    | 62   |      |
|   |  | Outputs at high Z   |  |                         |           |                    | 64   |      |

(1) All typical values are at V<sub>CC</sub> = 5 V, T<sub>A</sub> = 25°C.

(2) Not more than one output should be shorted at a time, and duration of the short circuit should not exceed one second.

## 7.6 Switching Characteristics

V<sub>CC</sub> = 5 V, T<sub>A</sub> = 25°C (see Figure 2)

| PARAMETER        |   | TEST CONDITIONS                                | MIN | TYP | MAX | UNIT |
|------------------|---|--|-----|-----|-----|------|
| t <sub>PLH</sub> | Propagation delay time, low- to high-level output | C <sub>L</sub> = 45 pF, R <sub>L</sub> = 667 Ω |     | 8   | 12  | ns   |
| t <sub>PHL</sub> | Propagation delay time, high- to low-level output |  |     | 8   | 12  |      |
| t <sub>PZL</sub> | Output enable time to low level                   | C <sub>L</sub> = 45 pF, R <sub>L</sub> = 667 Ω |     | 27  | 40  | ns   |
| t <sub>PZH</sub> | Output enable time to high level                  |  |     | 25  | 40  |      |
| t <sub>PLZ</sub> | Output disable time from low level                | C <sub>L</sub> = 5 pF, R <sub>L</sub> = 667 Ω  |     | 15  | 25  | ns   |
| t <sub>PHZ</sub> | Output disable time from high level               |  |     | 15  | 28  |      |


## SN54LS245, SN74LS245

SDLS146B – OCTOBER 1976 – REVISED SEPTEMBER 2016

[www.ti.com](http://www.ti.com)


### 7.7 Typical Characteristics

$V_{CC} = 5\text{ V}$ ,  $T_A = 25^\circ\text{C}$ ,  $C_L = 45\text{ pF}$ ,  $R_L = 667\ \Omega$



**Figure 1. Simulated Propagation Delay From Input to Output**

## 8 Parameter Measurement Information



- NOTES: A.  $C_L$  includes probe and jig capacitance.  
 B. All diodes are 1N3064 or equivalent.  
 C. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.  
 D. S1 and S2 are closed for  $t_{PLH}$ ,  $t_{PHL}$ ,  $t_{PHZ}$ , and  $t_{PLZ}$ ; S1 is open and S2 is closed for  $t_{pZH}$ ; S1 is closed and S2 is open for  $t_{pZL}$ .  
 E. Phase relationships between inputs and outputs have been chosen arbitrarily for these examples.  
 F. All input pulses are supplied by generators having the following characteristics:  $PRR \leq 1$  MHz,  $Z_O \approx 50 \Omega$ ,  $t_r \leq 1.5$  ns,  $t_f \leq 2.6$  ns.  
 G. The outputs are measured one at a time with one input transition per measurement.


**Figure 2. Load Circuits and Voltage Waveforms**

## 9 Detailed Description

### 9.1 Overview

The SNx4LS245 uses Schottky transistor logic to perform the standard '245 transceiver function. This standard logic function has a common pinout, direction select pin, and active-low output enable. When the outputs are disabled, the A and B sides of the device are effectively isolated.

### 9.2 Functional Block Diagram



Copyright © 2016, Texas Instruments Incorporated

**Figure 3. Logic Diagram (Positive Logic)**

### 9.3 Feature Description

#### 9.3.1 3-State outputs

The 3-state outputs can drive bus lines directly. All outputs can be put into high impedance mode through the  $\overline{OE}$  pin.

#### 9.3.2 PNP Inputs

This device has PNP inputs which reduce dc loading on bus lines.

#### 9.3.3 Hysteresis on Bus Inputs

The bus inputs have built-in hysteresis that improves noise margins.


### 9.4 Device Functional Modes

The SNx4LS245 performs the standard '245 logic function. Data can be transmitted from A to B or from B to A depending on the DIR pin value, or the A and B sides can be isolated from one another by setting the  $\overline{OE}$  pin HIGH.



**Table 1. Function Table**

| INPUTS          |     | OPERATION       |
|-----------------|-----|-----------------|
| $\overline{OE}$ | DIR |                 |
| L               | L   | B data to A bus |
| L               | H   | A data to B bus |
| H               | X   | Isolation       |



**Figure 4. Schematics of Inputs and Outputs**

## 10 Application and Implementation

### NOTE


Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

### 10.1 Application Information

The SNx4LS245 is commonly used to drive ribbon cables or back plane busses. It allows isolation from the bus when necessary, and increases drive strength on the bus.

### 10.2 Typical Application

Figure 5 shows the SNx4LS245 wired up as a permanently enabled data bus transceiver for both a master and slave device communicating over a ribbon cable or back plane.



Copyright © 2016, Texas Instruments Incorporated

**Figure 5. SNx4LS245 Being Used to Communicate Over a Ribbon Cable or Back Plane**

#### 10.2.1 Design Requirements

This device uses Schottky transistor logic technology. Take care to avoid bus contention because it can drive currents that would exceed maximum limits. The high drive creates fast edges into light loads, so routing and load conditions must be considered to prevent ringing.


#### 10.2.2 Detailed Design Procedure

- Power Supply
  - Each device must maintain a supply voltage between 4.5 V and 5.5 V
- Inputs
  - Input signals must meet the  $V_{IH}$  and  $V_{IL}$  specifications in [Electrical Characteristics](#)
  - Inputs leakage values ( $I_I$ ,  $I_{IH}$ ,  $I_{IL}$ ) from [Electrical Characteristics](#) must be considered
- Outputs
  - Output signals are specified to meet the  $V_{OH}$  and  $V_{OL}$  specifications in [Electrical Characteristics](#) as a minimum (the values could be closer to  $V_{CC}$  for high signals or GND for low signals)
  - TI recommends maintaining output currents as specified in [Recommended Operating Conditions](#)
  - The part can be damaged by sourcing or sinking too much current. See [Electrical Characteristics](#) for details.

## Typical Application (continued)

### 10.2.3 Application Curve

It is common to see significant losses in ribbon cables and back planes. [Figure 6](#) shows a simplified simulation of a ribbon cable from a 5-V, 10-MHz low-drive strength source. It shows the difference between an input signal from a weak driver like an MCU or FPGA compared to a strong driver like the SN74LS245 when measured at the distant end of the cable. By adding a high-current drive transceiver before the cable, the signal strength can be significantly improved, and subsequently the cable can be longer.



Unbuffered line is directly connected to low current source, SN74LS245 line is buffered through the transceiver. Both signals are measured at the distant end of the ribbon cable. **Input signal is not shown.**

**Figure 6. Simulated Outputs From Ribbon Cable With a 5-V, 10-MHz Source**

## 11 Power Supply Recommendations


The power supply can be any voltage between the minimum and maximum supply voltage rating located in [Recommended Operating Conditions](#). Each  $V_{CC}$  pin must have a good bypass capacitor to prevent power disturbance. For devices with a single supply, TI recommends a 0.1- $\mu$ F bypass capacitor. If there are multiple  $V_{CC}$  pins, TI recommends a 0.01- $\mu$ F or 0.022- $\mu$ F bypass capacitors for each power pin. It is acceptable to parallel multiple bypass capacitors to reject different frequencies of noise. Two bypass capacitors of value 0.1  $\mu$ F and 1  $\mu$ F are commonly used in parallel. For best results, install the bypass capacitor(s) as close to the power pin as possible.

## 12 Layout

### 12.1 Layout Guidelines

When using multiple bit logic devices, inputs must not be left floating. In many applications, some channels of the SNx4LS245 are unused, and thus must be terminated properly. Because each transceiver channel pin can be either an input or an output, they must be treated as both when being terminated. Ground or  $V_{CC}$  (whichever is more convenient) can be used to terminate unused inputs; however, each unused channel should be terminated to the same logic level on both the A and B side. For example, in [Figure 7](#) unused channels 4, 5, 6, and 7 are terminated correctly with both sides connected to the same voltage, while channel 8 is terminated incorrectly with each side being tied to a different voltage. The  $\overline{OE}$  input is also unused in this example, and is terminated directly to ground to permanently enable all outputs.

### 12.2 Layout Example



**Figure 7. Example Demonstrating How to Terminate Unused Inputs and Channels of a Transceiver**

## 13 Device and Documentation Support

### 13.1 Related Links

The table below lists quick access links. Categories include technical documents, support and community resources, tools and software, and quick access to sample or buy.

**Table 2. Related Links**

| PARTS     | PRODUCT FOLDER             | SAMPLE & BUY               | TECHNICAL DOCUMENTS        | TOOLS & SOFTWARE           | SUPPORT & COMMUNITY        |
|-----------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| SN54LS245 | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> |
| SN74LS245 | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> |

### 13.2 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. In the upper right corner, click on *Alert me* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

### 13.3 Community Resource

The following links connect to TI community resources. Linked contents are provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's [Terms of Use](#).

**TI E2E™ Online Community** *TI's Engineer-to-Engineer (E2E) Community*. Created to foster collaboration among engineers. At e2e.ti.com, you can ask questions, share knowledge, explore ideas and help solve problems with fellow engineers.

**Design Support** *TI's Design Support* Quickly find helpful E2E forums along with design support tools and contact information for technical support.

### 13.4 Trademarks

E2E is a trademark of Texas Instruments.  
All other trademarks are the property of their respective owners.

### 13.5 Electrostatic Discharge Caution



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

### 13.6 Glossary

[SLYZ022](#) — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

## 14 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

**PACKAGING INFORMATION**

| Orderable part number            | Status<br>(1) | Material type<br>(2) | Package   Pins | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6)                |
|----------------------------------|---------------|----------------------|----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|------------------------------------|
| <a href="#">5962-8002101VSA</a>  | Active        | Production           | CFP (W)   20   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-8002101VS<br>A<br>SNV54LS245W |
| 5962-8002101VSA.A                | Active        | Production           | CFP (W)   20   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-8002101VS<br>A<br>SNV54LS245W |
| <a href="#">80021012A</a>        | Active        | Production           | LCCC (FK)   20 | 55   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 80021012A<br>SNJ54LS<br>245FK      |
| <a href="#">8002101SA</a>        | Active        | Production           | CFP (W)   20   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 8002101SA<br>SNJ54LS245W           |
| <a href="#">JM38510/32803B2A</a> | Active        | Production           | LCCC (FK)   20 | 55   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>32803B2A               |
| JM38510/32803B2A.A               | Active        | Production           | LCCC (FK)   20 | 55   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>32803B2A               |
| <a href="#">JM38510/32803BRA</a> | Active        | Production           | CDIP (J)   20  | 20   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>32803BRA               |
| JM38510/32803BRA.A               | Active        | Production           | CDIP (J)   20  | 20   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>32803BRA               |
| <a href="#">JM38510/32803BSA</a> | Active        | Production           | CFP (W)   20   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>32803BSA               |
| JM38510/32803BSA.A               | Active        | Production           | CFP (W)   20   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>32803BSA               |
| <a href="#">M38510/32803B2A</a>  | Active        | Production           | LCCC (FK)   20 | 55   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>32803B2A               |
| <a href="#">M38510/32803BRA</a>  | Active        | Production           | CDIP (J)   20  | 20   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>32803BRA               |
| <a href="#">M38510/32803BSA</a>  | Active        | Production           | CFP (W)   20   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>32803BSA               |
| <a href="#">SN54LS245J</a>       | Active        | Production           | CDIP (J)   20  | 20   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | SN54LS245J                         |
| SN54LS245J.A                     | Active        | Production           | CDIP (J)   20  | 20   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | SN54LS245J                         |
| <a href="#">SN74LS245DBR</a>     | Active        | Production           | SSOP (DB)   20 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | LS245                              |
| SN74LS245DBR.A                   | Active        | Production           | SSOP (DB)   20 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | LS245                              |

| Orderable part number        | Status<br>(1) | Material type<br>(2) | Package   Pins | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6)           |
|------------------------------|---------------|----------------------|----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|-------------------------------|
| <a href="#">SN74LS245DW</a>  | Obsolete      | Production           | SOIC (DW)   20 | -                     | -           | Call TI                              | Call TI                           | 0 to 70      | LS245                         |
| <a href="#">SN74LS245DWR</a> | Active        | Production           | SOIC (DW)   20 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | LS245                         |
| SN74LS245DWR.A               | Active        | Production           | SOIC (DW)   20 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | LS245                         |
| <a href="#">SN74LS245N</a>   | Active        | Production           | PDIP (N)   20  | 20   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74LS245N                    |
| SN74LS245N.A                 | Active        | Production           | PDIP (N)   20  | 20   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74LS245N                    |
| SN74LS245NE4                 | Active        | Production           | PDIP (N)   20  | 20   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74LS245N                    |
| <a href="#">SN74LS245NSR</a> | Active        | Production           | SOP (NS)   20  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 74LS245                       |
| SN74LS245NSR.A               | Active        | Production           | SOP (NS)   20  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 74LS245                       |
| <a href="#">SNJ54LS245FK</a> | Active        | Production           | LCCC (FK)   20 | 55   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 80021012A<br>SNJ54LS<br>245FK |
| SNJ54LS245FK.A               | Active        | Production           | LCCC (FK)   20 | 55   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 80021012A<br>SNJ54LS<br>245FK |
| <a href="#">SNJ54LS245J</a>  | Active        | Production           | CDIP (J)   20  | 20   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | SNJ54LS245J                   |
| SNJ54LS245J.A                | Active        | Production           | CDIP (J)   20  | 20   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | SNJ54LS245J                   |
| <a href="#">SNJ54LS245W</a>  | Active        | Production           | CFP (W)   20   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 8002101SA<br>SNJ54LS245W      |
| SNJ54LS245W.A                | Active        | Production           | CFP (W)   20   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 8002101SA<br>SNJ54LS245W      |

<sup>(1)</sup> **Status:** For more details on status, see our [product life cycle](#).

<sup>(2)</sup> **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

<sup>(4)</sup> **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

<sup>(5)</sup> **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

**(6) Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF SN54LS245, SN54LS245-SP, SN74LS245 :**

- Catalog : [SN74LS245](#), [SN54LS245](#)
- Military : [SN54LS245](#)
- Space : [SN54LS245-SP](#)

**NOTE:** Qualified Version Definitions:

- Catalog - TI's standard catalog product
- Military - QML certified for Military and Defense Applications
- Space - Radiation tolerant, ceramic packaging and qualified for use in Space-based application



## TAPE AND REEL INFORMATION



\*All dimensions are nominal

| Device       | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|--------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| SN74LS245DBR | SSOP         | DB              | 20   | 2000 | 330.0              | 16.4               | 8.2     | 7.5     | 2.5     | 12.0    | 16.0   | Q1            |
| SN74LS245DWR | SOIC         | DW              | 20   | 2000 | 330.0              | 24.4               | 10.8    | 13.3    | 2.7     | 12.0    | 24.0   | Q1            |
| SN74LS245NSR | SOP          | NS              | 20   | 2000 | 330.0              | 24.4               | 8.4     | 13.0    | 2.5     | 12.0    | 24.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device       | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|--------------|--------------|-----------------|------|------|-------------|------------|-------------|
| SN74LS245DBR | SSOP         | DB              | 20   | 2000 | 356.0       | 356.0      | 35.0        |
| SN74LS245DWR | SOIC         | DW              | 20   | 2000 | 367.0       | 367.0      | 45.0        |
| SN74LS245NSR | SOP          | NS              | 20   | 2000 | 367.0       | 367.0      | 45.0        |

## TUBE




\*All dimensions are nominal

| Device             | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|--------------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| 5962-8002101VSA    | W            | CFP          | 20   | 25  | 506.98 | 26.16  | 6220   | NA     |
| 5962-8002101VSA.A  | W            | CFP          | 20   | 25  | 506.98 | 26.16  | 6220   | NA     |
| 80021012A          | FK           | LCCC         | 20   | 55  | 506.98 | 12.06  | 2030   | NA     |
| 8002101SA          | W            | CFP          | 20   | 25  | 506.98 | 26.16  | 6220   | NA     |
| JM38510/32803B2A   | FK           | LCCC         | 20   | 55  | 506.98 | 12.06  | 2030   | NA     |
| JM38510/32803B2A.A | FK           | LCCC         | 20   | 55  | 506.98 | 12.06  | 2030   | NA     |
| JM38510/32803BSA   | W            | CFP          | 20   | 25  | 506.98 | 26.16  | 6220   | NA     |
| JM38510/32803BSA.A | W            | CFP          | 20   | 25  | 506.98 | 26.16  | 6220   | NA     |
| M38510/32803B2A    | FK           | LCCC         | 20   | 55  | 506.98 | 12.06  | 2030   | NA     |
| M38510/32803BSA    | W            | CFP          | 20   | 25  | 506.98 | 26.16  | 6220   | NA     |
| SN74LS245N         | N            | PDIP         | 20   | 20  | 506    | 13.97  | 11230  | 4.32   |
| SN74LS245N.A       | N            | PDIP         | 20   | 20  | 506    | 13.97  | 11230  | 4.32   |
| SN74LS245NE4       | N            | PDIP         | 20   | 20  | 506    | 13.97  | 11230  | 4.32   |
| SNJ54LS245FK       | FK           | LCCC         | 20   | 55  | 506.98 | 12.06  | 2030   | NA     |
| SNJ54LS245FK.A     | FK           | LCCC         | 20   | 55  | 506.98 | 12.06  | 2030   | NA     |
| SNJ54LS245W        | W            | CFP          | 20   | 25  | 506.98 | 26.16  | 6220   | NA     |
| SNJ54LS245W.A      | W            | CFP          | 20   | 25  | 506.98 | 26.16  | 6220   | NA     |

W (R-GDFP-F20)

CERAMIC DUAL FLATPACK




- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. This package can be hermetically sealed with a ceramic lid using glass frit.
  - D. Index point is provided on cap for terminal identification only.
  - E. Falls within Mil-Std 1835 GDFP2-F20



## SSOP - 2 mm max height

## SMALL OUTLINE PACKAGE



4214851/B 08/2019

NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-150.

# EXAMPLE BOARD LAYOUT

DB0020A

SSOP - 2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE: 10X



SOLDER MASK DETAILS

4214851/B 08/2019

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DB0020A

SSOP - 2 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE: 10X

4214851/B 08/2019

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

# MECHANICAL DATA

NS (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE PACKAGE

14-PINS SHOWN



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15.



J (R-GDIP-T\*\*)

14 LEADS SHOWN

# CERAMIC DUAL IN-LINE PACKAGE



| PINS **<br>DIM | 14                     | 16                     | 18                     | 20                     |
|----------------|------------------------|------------------------|------------------------|------------------------|
| A              | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC |
| B MAX          | 0.785<br>(19,94)       | .840<br>(21,34)        | 0.960<br>(24,38)       | 1.060<br>(26,92)       |
| B MIN          | —                      | —                      | —                      | —                      |
| C MAX          | 0.300<br>(7,62)        | 0.300<br>(7,62)        | 0.310<br>(7,87)        | 0.300<br>(7,62)        |
| C MIN          | 0.245<br>(6,22)        | 0.245<br>(6,22)        | 0.220<br>(5,59)        | 0.245<br>(6,22)        |



4040083/F 03/03

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. This package is hermetically sealed with a ceramic lid using glass frit.
  - D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
  - E. Falls within MIL STD 1835 GDIP1-T14, GDIP1-T16, GDIP1-T18 and GDIP1-T20.

## GENERIC PACKAGE VIEW

**FK 20**

**LCCC - 2.03 mm max height**

8.89 x 8.89, 1.27 mm pitch

LEADLESS CERAMIC CHIP CARRIER

This image is a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.



4229370VA\

N (R-PDIP-T\*\*)

16 PINS SHOWN

## PLASTIC DUAL-IN-LINE PACKAGE



| PINS **<br>DIM      | 14               | 16               | 18               | 20               |
|---------------------|------------------|------------------|------------------|------------------|
| A MAX               | 0.775<br>(19,69) | 0.775<br>(19,69) | 0.920<br>(23,37) | 1.060<br>(26,92) |
| A MIN               | 0.745<br>(18,92) | 0.745<br>(18,92) | 0.850<br>(21,59) | 0.940<br>(23,88) |
| MS-001<br>VARIATION | AA               | BB               | AC               | AD               |



4040049/E 12/2002

NOTES:

- A. All linear dimensions are in inches (millimeters).  
B. This drawing is subject to change without notice.
-  Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).  
 The 20 pin end lead shoulder width is a vendor option, either half or full width.



## NOTES:

1. All linear dimensions are in millimeters. Dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.43 mm per side.
5. Reference JEDEC registration MS-013.

# EXAMPLE BOARD LAYOUT


DW0020A

SOIC - 2.65 mm max height

SOIC



LAND PATTERN EXAMPLE  
SCALE:6X



SOLDER MASK DETAILS

4220724/A 05/2016

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DW0020A

SOIC - 2.65 mm max height

SOIC



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:6X

4220724/A 05/2016

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2025, Texas Instruments Incorporated