











TPS62730, TPS62732, TPS62733

SLVSAC3D-MAY 2011-REVISED DECEMBER 2014

TPS6273x Step-Down Converter With Bypass Mode for Ultra Low-Power Wireless **Applications**


Features

- Input Voltage Range V_{IN} From 1.9 V to 3.9 V
- Typ. 30-nA Ultra Low-Power Bypass Mode
- Typ. 25-µA DC-DC Quiescent Current
- Internal Feedback Divider Disconnect
- Typical 2.1-Ω Bypass Switch Between V_{IN} and V_{OUT}
- Automatic Transition from DC-DC to Bypass Mode
- Up to 3-MHz Switch Frequency
- Up to 95% DC-DC Efficiency
- Open-Drain Status Output STAT
- Output Peak Current up to 100 mA
- Fixed Output Voltages 1.9 V, 2.05 V, 2.1 V, 2.3 V
- Small External Output Filter Components 2.2 µH and 2.2 µF
- Optimized For Low Output Ripple Voltage
- Small 1 x 1.5 x 0.6-mm³ USON Package
- 12-mm² Minimum Solution Size

2 Applications

- CC2540 Bluetooth™ Low-Energy System-On-Chip Solution
- **Low-Power Wireless Applications**
- RF4CE, Metering

Typical Application



3 Description

The TPS62730 is a high frequency synchronous stepdown DC-DC converter optimized for ultra low-power wireless applications. The device is optimized to supply TI's Low-Power Wireless sub 1-GHz and 2.4-GHz RF transceivers and System-On-Chip (SoC) solutions. The TPS62730 reduces the current consumption drawn from the battery during TX and RX mode by a high efficient step-down voltage conversion. The device provides an output current of up to 100 mA and allows the use of tiny and low-cost chip inductors and capacitors. With an input voltage range of 1.9 V to 3.9 V, the device supports Liprimary battery chemistries such as Li-SOCI2, Li-SO2, Li-MnO2, and also two cell alkaline batteries.

The TPS62730 features an Ultra Low-Power bypass mode with typical 30-nA current consumption to support sleep and low power modes of TI's CC2540 Bluetooth Low Energy and CC430 SoC solutions. In this bypass mode, the output capacitor of the DC-DC converter is connected through an integrated typical $2.1-\Omega$ bypass switch to the battery.

Device Information⁽¹⁾

PART NUMBER	PACKAGE	BODY SIZE (NOM)					
TPS62730							
TPS62732	USON (6)	1.45 mm x 1.00 mm					
TPS62733							

(1) For all available packages, see the orderable addendum at the end of the datasheet.

Battery Current Reduction Using TPS62730






Table of Contents

1	Features 1		9.3 Feature Description	8
2	Applications 1		9.4 Device Functional Modes	10
3	Description 1	10	Application and Implementation	11
4	Revision History2		10.1 Application Information	11
5	Description (Continued)3		10.2 Typical Application	11
6	Device Comparison Table3		10.3 System Examples	18
7	Pin Configuration and Functions	11	Power Supply Recommendations	19
8	Specifications	12	Layout	19
٠	8.1 Absolute Maximum Ratings		12.1 Layout Guidelines	19
	8.2 ESD Ratings		12.2 Layout Example	19
	8.3 Recommended Operating Conditions	13	Device and Documentation Support	20
	8.4 Thermal Information		13.1 Device Support	20
	8.5 Electrical Characteristics		13.2 Related Links	20
	8.6 Typical Characteristics		13.3 Trademarks	20
9	**		13.4 Electrostatic Discharge Caution	20
9	Detailed Description		13.5 Glossary	20
	9.1 Overview 8 9.2 Functional Block Diagram 8	14	Mechanical, Packaging, and Orderable Information	20

4 Revision History

Changes from Revision C (December 2012) to Revision D

Page

Added Pin Configuration and Functions section, ESD Ratings table, Feature Description section, Device Functional
Modes, Application and Implementation section, Power Supply Recommendations section, Layout section, Device
and Documentation Support section, and Mechanical, Packaging, and Orderable Information section

Submit Documentation Feedback

Copyright © 2011–2014, Texas Instruments Incorporated



5 Description (Continued)

In DC-DC operation mode the device provides a fixed output voltage to the system. With a switch frequency up to 3 MHz, the TPS62730 features low output ripple voltage and low noise even with a small 2.2-uF output capacitor. The automatic transition into bypass mode during DC-DC operation prevents an increase of output ripple voltage and noise once the DC-DC converter operates close to 100% duty cycle. The device automatically enters bypass mode once the battery voltage falls below the transition threshold $V_{\text{IT BYP}}$. The TPS62730 is available in a 1 x 1.5-mm² 6-pin USON package.

6 Device Comparison Table

	PART NUMBER OUTPUT VOLTAGE IVI		AUTOMATIC BYPASS MODE TRANSITION THRESHOLDS $V_{\mathrm{IT\;BYP}}$				
TA	PART NUMBER	R OUTPUT VOLTAGE [V]	V _{IT BYP} [V] RISING V _{IN}	V _{IT BYP} [V] FALLING V _{IN}	V _{IT BYP} [mV] HYSTERESIS		
	TPS62730	2.10	2.25	2.20	50		
	TPS62731 ⁽¹⁾	2.05	2.2	2.15	50		
-40°C to 85°C	TPS62732	1.90	2.10	2.05	50		
-40 C to 65 C	TPS62733	2.3	2.48	2.41	70		
	TPS62734 ⁽¹⁾	2.10	2.28	2.23	50		
	TPS62735 ⁽¹⁾	2.10	2.33	2.23	100		

⁽¹⁾ Device status is product preview. Contact TI for more details / samples.

7 Pin Configuration and Functions

DRY Package 6 Pins Top View



Pin Functions

PIN	1	1/0	DESCRIPTION
NAME	NO	1/0	DESCRIPTION
VIN	3	PWR	V_{IN} power supply pin. Connect this pin close to the VIN terminal of the input capacitor. A ceramic capacitor of 2.2 μF is required.
GND	4	PWR	GND supply pin. Connect this pin close to the GND terminal of the input and output capacitor.
ON/BYP	5	IN	This is the mode selection pin of the device. Pulling this pin to low forces the device into ultra low-power bypass mode. The output of the DC-DC converter is connected to VIN through an internal bypass switch. Pulling this pin to high enables the DC-DC converter operation. This pin must be terminated and is controlled by the system.
SW	2	OUT	This is the switch pin and is connected to the internal MOSFET switches. Connect the inductor to this terminal.
VOUT	6	IN	Feedback Pin for the internal feedback divider network and regulation loop. The internal bypass switch is connected between this pin and VIN. Connect this pin directly to the output capacitor with short trace.
STAT	1	OUT	This is the open-drain status output with active low level. An internal comparator drives this output. The pin is high impedance with ON/BYP = low. With ON/BYP set to high the device and the internal VOUT comparator becomes active. The active low STAT pin indicates if the DC-DC regulator is settled and the output voltage above the V_{TSTAT} threshold. If not used, this pin can be left open.

Product Folder Links: TPS62730 TPS62732 TPS62733



8 Specifications

8.1 Absolute Maximum Ratings

Over operating free-air temperature range (unless otherwise noted)⁽¹⁾

		MIN	MAX	UNIT
Voltage ⁽²⁾	VIN, SW, VOUT	-0.3	4.2	V
	ON/BYP, STAT	-0.3	V _{IN} + 0.3 ≤ 4.2	V
Operating junction temperature, T _J		-40	125	ô
Storage temperature, T _{stg}		-65	150	°C

⁽¹⁾ Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under Recommended Operating Conditions is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

8.2 ESD Ratings

			VALUE	UNIT
		Human body model (HBM), per ANSI/ESDA/JEDEC JS-001 (1)	±2000	
V _(ESD)	Electrostatic discharge	Charged-device model (CDM), per JEDEC specification JESD22-C101 (2)	±1000	V
		Machine model (MM), all pins	±150	

JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process. Manufacturing with less than 500-V HBM is possible with the necessary precautions.

8.3 Recommended Operating Conditions

Operating ambient temperature $T_A = -40$ to 85°C (unless otherwise noted)

	MIN	NOM	MAX	UNIT
Supply voltage V _{IN}	1.9		3.9	V
Effective inductance	1.5	2.2	3	μΗ
Effective output capacitance connected to V _{OUT}	1.0		10	μF
Operating junction temperature range, T _J			125	°C
T _A Operating free air temperature range	-40 85			

8.4 Thermal Information

		TPS6273x	
	THERMAL METRIC ⁽¹⁾	DRY	UNIT
		6 PINS	
θ_{JA}	Junction-to-ambient thermal resistance	293.8	
θ_{JCtop}	Junction-to-case (top) thermal resistance	165.1	
θ_{JB}	Junction-to-board thermal resistance	160.8	°C/W
ΨЈТ	Junction-to-top characterization parameter	27.3	*C/VV
ΨЈВ	Junction-to-board characterization parameter	159.6	
θ_{JCbot}	Junction-to-case (bottom) thermal resistance	65.8	

(1) For more information about traditional and new thermal metrics, see the IC Package Thermal Metrics application report, SPRA953.

Product Folder Links: TPS62730 TPS62732 TPS62733

⁽²⁾ All voltages are with respect to network ground pin.

⁽²⁾ JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process. Manufacturing with less than 250-V CDM is possible with the necessary precautions.



8.5 Electrical Characteristics

 $V_{IN}=3.0~V,~V_{OUT}=2.1~V,~ON/BYP=V_{IN},~T_A=-40^{\circ}C~to~85^{\circ}C~typical~values~are~at~T_A=25^{\circ}C~(unless~otherwise~noted),~C_{IN}=2.2~\mu F,~L=2.2~\mu H,~C_{OUT}=2.2~\mu F$

	PARAMETER		TEST CON	DITIONS	MIN	TYP	MAX	UNIT
SUPPLY	(
V _{IN}	Input voltage range				1.9		3.9	V
			ON/BYP = high, I _{OUT} = device not switching	0mA. V _{IN} = 3 V		25	40	
I_Q	Operating quiescent current		I _{OUT} = 0 mA. device sw V _{OUT} = 2.1 V	vitching, $V_{IN} = 3.0 \text{ V}$,		34		μΑ
			ON/BYP = high, Bypas = V _{OUT} = 2.1 V	s switch active, V _{IN}		23		Ī
I _{SD}	Shutdown current, Bypass Switch Acti	vated ⁽¹⁾	ON/BYP = GND, leaka	ge current into V _{IN}		30	550	
		ON/BYP = GND, leaka T _A = 60°C	ge current into V _{IN} ,		110		nA	
ON/BYP								
V _{IH} TH	Threshold for detecting high ON/BYP		1.9 V ≤ V _{IN} ≤ 3.9 V , ris	sing edge		0.8	1	V
V _{IL TH}	Threshold for detecting low ON/BYP		1.9 V ≤ V _{IN} ≤ 3.9 V , fa	lling edge	0.4	0.6		٧
I _{IN}	Input bias Current					0	50	nΑ
POWER	SWITCH							
Б	High side MOSFET on-resistance		V - 20 V			600		mΩ
R _{DS(ON)}	Low Side MOSFET on-resistance		$V_{IN} = 3.0 \text{ V}$			350		11152
-	Forward current limit MOSFET high side		V _{IN} = 3.0 V, open loop			410		mA
I _{LIMF}	Forward current limit MOSFET low side					410		mA
BYPASS	S SWITCH							
R _{DS(ON)}	Bypass Switch on-resistance		$V_{IN} = 2.1 \text{ V}, I_{OUT} = 20 \text{ mA}, T_{J} \text{max} = 85^{\circ} \text{C}$			2.9	3.8	
			V _{IN} = 3 V			2.1		Ω
V _{IT BYP}	Automatic Bypass Switch Transition	ON/BYP	TPS62730 (2.1 V)	ON / falling V _{IN}	2.14	2.20	2.3	
	Threshold (Activation / Deactivation)	= high		OFF/ rising V _{IN}	2.19	2.25	2.35	ı
			TPS62731 (2.05 V)	ON / falling V _{IN}		2.15		ı
				OFF / rising V _{IN}		2.20		ı
			TPS62732 (1.9 V)	ON / falling V _{IN}		2.05		ı
				OFF / rising V _{IN}		2.10		
			TPS62733 (2.3 V)	ON / falling V _{IN}		2.41		V
				OFF/ rising V _{IN}		2.48		1
			TPS62734 (2.1 V)	ON / falling V _{IN}		2.23		i
				OFF / rising V _{IN}		2.28		i
			TPS62735 (2.3 V)	ON / falling V _{IN}		2.23		i
				OFF / rising V _{IN}		2.33		ı

⁽¹⁾ Shutdown current into VIN pin, includes internal leakage



Electrical Characteristics (continued)

 $V_{IN}=3.0~V,~V_{OUT}=2.1~V,~ON/BYP=V_{IN},~T_A=-40^{\circ}C~to~85^{\circ}C~typical~values~are~at~T_A=25^{\circ}C~(unless~otherwise~noted),~C_{IN}=2.2~\mu F,~L=2.2~\mu H,~C_{OUT}=2.2~\mu F$

	PARAMETER	TEST CONDI	TIONS	MIN	TYP	MAX	UNIT
STAT S	TATUS OUTPUT (OPEN DRAIN)						
V _{TSTAT}	Threshold level for STAT OUTPUT in % from V_{OUT}	ON/BYP = high and regulator is ready, V _{IN} falling			95%		
		ON/BYP = high and regul rising (2)	ator is ready, V _{IN}		98%		
V _{OL}	Output Low Voltage	Current into STAT pin I = 500 μ A, V_{IN} = 2.3 V				0.4	V
V _{OH}	Output High Voltage	Open drain output, extern	al pull up resistor			V_{IN}	
I _{LKG}	Leakage into STAT pin	$ON/BYP = GND, V_{IN} = V_{O}$	_{TUC} = 3 V		0	50	nA
REGUL	ATOR						
t _{ONmin}	Minimum ON time	V _{IN} = 3.0 V, V _{OUT} = 2.1 V	, I _{OUT} = 0 mA		180		ns
t _{OFFmin}	Minimum OFF time	V _{IN} = 2.3 V		50			ns
t _{Start}	Regulator start up time from transition ON/BYP = high to STAT = low	$V_{IN} = 3.0 \text{ V}, V_{OUT} = 3.0 \text{ V}$			50		μs
OUTPU	Т						
V _{REF}	Internal Reference Voltage				0.70		V
	VOLIT Foodbook Veltere Commenter Throughold	V _{IN} = 3.0 V	T _A = 25°C	-1.5%	0%	1.5%	
V	VOUT Feedback Voltage Comparator Threshold Accuracy		$T_A = -40$ °C to 85°C	-2.5%	0%	2.5%	
V_{VOUT}	DC output voltage load regulation	I_{OUT} = 1 mA to 50 mA V_{IN} = 3.0 V, V_{OUT} = 2.1 V			-0.01		%/mA
	DC output voltage line regulation	$I_{OUT} = 20 \text{ mA}, 2.4 \text{ V} \le V_{IN} \le 3.9 \text{ V}$			0.01		%/V
I _{LK_SW}	Leakage current into SW pin	$V_{IN} = V_{OUT} = V_{SW} = 3.0 \text{ V}$, ON/Byp= GND		0.0	100	nA


The STAT output comparator is enabled once the rising input voltage exceeds the minimum input voltage V_{IN} min of 1.9 V. In case of the 1.9 V output voltage option, the STAT output is active once the rising input voltage V_{IN} exceeds 1.9 V. The internal resistor divider network is disconnected from VOUT pin.

Submit Documentation Feedback

Copyright © 2011–2014, Texas Instruments Incorporated



8.6 Typical Characteristics






9 Detailed Description

9.1 Overview

The TPS62730 combines a synchronous buck converter for high efficient voltage conversion and an integrated ultra low power bypass switch to support low power modes of modern micro controllers and RF ICs.

9.2 Functional Block Diagram



9.3 Feature Description

9.3.1 DCS-Control™

The TPS62730 includes TI's DCS-Control, an advanced regulation topology, that combines the advantages of hysteretic and voltage mode control architectures. While a comparator stage provides excellent load transient response, an additional voltage feedback loop ensures high DC accuracy as well. The DCS-Control enables switch frequencies up to 3 MHz, excellent transient and AC load regulation as well as operation with small and cost-competitive external components. The TPS6273x devices offer fixed output voltage options featuring smallest solution size by using only three external components. Furthermore this step-down converter provides excellent low output voltage ripple over the entire load range which makes this part ideal for RF applications. In the ultra low-power bypass mode, the output of the device VOUT is directly connected to the input VIN through the internal bypass switch. In this mode, the buck converter is shut down and consumes only 30 nA typical input current. Once the device is turned from ultra low-power bypass mode into buck converter operation for an RF transmission, all the internal circuits of the regulator are activated within a start up time t_{Start} of typical 50 µs. During this time the bypass switch is still turned on and maintains the output VOUT connected to the input VIN. Once the DC-DC converter is settled and ready to operate, the internal bypass switch is turned off and the system is supplied by the output capacitor and the other decoupling capacitors. The buck converter kicks in once the capacitors connected to VOUT are discharged to the level of the nominal buck converter output voltage. Once the output voltage falls below the threshold of the internal error comparator, a switch pulse is initiated, and the high side switch of the DC-DC converter is turned on. The high-side switch remains turned on until a minimum on time of toNmin expires and the output voltage trips the threshold of the error comparator or the inductor current reaches the high side switch current limit. Once the high side switch turns off, the low side switch

Submit Documentation Feedback

Copyright © 2011–2014, Texas Instruments Incorporated



Feature Description (continued)

rectifier is turned on and the inductor current ramps down until the high side switch turns on again or the inductor current reaches zero. The converter operates in the PFM (pulse frequency modulation) mode during light loads, which maintains high efficiency over a wide load current range. In PFM mode, the device starts to skip switch pulses and generates only single pulses with the on time t_{ONmin}. The PFM mode of TPS62730 is optimized for low output ripple voltage if small external components are used.

The on time t_{ONmin} can be estimated to:

$$t_{ONmin} = \frac{V_{OUT}}{V_{IN}} \times 260 \text{ ns}$$

where

t_{ONmin}: High side switch on time [ns]

V_{IN}: Input voltage [V]

• V_{OUT}: Output voltage [V]

• (1)

Therefore, the peak inductor current in PFM mode is approximately:

$$I_{LPFMpeak} = \frac{(V_{IN} - V_{OUT})}{L} \times t_{ONmin}$$

where

• V_{IN}: Input voltage [V]

• V_{OUT}: Output voltage [V]

L : Inductance [μH]

• I_{LPFMpeak}: PFM inductor peak current [mA] (2)

9.3.2 ON/BYP Mode Selection


The DC-DC converter is activated when ON/BYP is set high. For proper operation, the ON/BYP pin must be terminated and may not be left floating. This pin is controlled by the RF transceiver or micro controller for proper mode selection. Pulling the ON/BYP pin low activates the ultra low-power bypass mode with typical 30-nA current consumption. In this mode, the internal bypass switch is turned on and the output of the DC-DC converter is connected to the battery VIN. All other circuits like the entire internal-control circuitry, the High Side and Low Side MOSFETs of the DC-DC output stage are turned off as well the internal resistor feedback divider is disconnected. The ON/BYP must be controlled by a microcontroller for proper mode selection. In case of CC2540, connect this to the power down signal which is output on one of the P1.x ports (see CC2540 user guide).

9.3.3 STAT Open-Drain Output

The STAT output is active when the device is enabled (EN/BYP = high) and indicates the status of the output voltage. The STAT output is a open-drain output with active low level and needs a external pullup resistor to indicate a high level. It is driven by an internal comparator which monitors the output voltage V_{OUT} . The STAT pin is tied to low level, if the output voltage V_{OUT} is considered as valid and exceeding the threshold V_{TSTAT} (95% of V_{OUT} for falling V_{IN} and 98% of V_{OUT} for rising V_{IN}). The pin is high impedance with the ON/BYP pin set to low level or V_{OUT} is below the V_{TSTAT} threshold. If not used, the STAT pin can be left open. See Figure 6 and Figure 7.

Copyright © 2011–2014, Texas Instruments Incorporated

Feature Description (continued)



9.4 Device Functional Modes

9.4.1 Start-Up

Once the device is supplied with a battery voltage, the bypass switch is activated. If the ON/BYP pin is set to high, the device operates in bypass mode until the DC-DC converter has settled and can kick in. During start-up, high peak currents can flow over the bypass switch to charge up the output capacitor and the additional decoupling capacitors in the system.

9.4.2 Automatic Transition from DC-DC to Bypass Operation

With the ON/BYP pin set to high, the TPS62730 is active and features an automatic transition between DC-DC and bypass mode to reduce the output ripple voltage to zero. Once the input voltage comes close to the output voltage of the DC-DC converter, the DC-DC converters operates close to 100% duty cycle operation. At this operating condition, the switch frequency would start to drop and would lead to increased output ripple voltage. The internal bypass switch is turned on once the battery voltage at VIN trips the Automatic Bypass Transition Threshold VIT BYP for falling VIN. The DC-DC regulator is turned off and therefore it generates no output ripple voltage. Due to the output is connected through the bypass switch to the input, the output voltage follows the input voltage minus the voltage drop across the internal bypass switch. In this mode the current consumption of the DC-DC converter is reduced to typically 23 μ A. Once the input voltage increases and trips the bypass deactivation threshold VIT BYP for rising VIN, the DC-DC regulator turns on and the bypass switch is turned off. See Figure 7 and Figure 24.

9.4.3 Internal Current Limit

The TPS62730 integrates a High Side and Low Side MOSFET current limit to protect the device against heavy load or short circuit when the DC-DC converter is active. The current in the switches is monitored by current limit comparators. When the current in the High Side MOSFET reaches its current limit, the High Side MOSFET is turned off and the Low Side MOSFET is turned on to ramp down the current in the inductor. The High Side MOSFET switch can only turn on again, once the current in the Low Side MOSFET switch has fallen below the threshold of its current limit comparator. The bypass switch does not feature a current limit to support lowest current consumption.



10 Application and Implementation

NOTE

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

10.1 Application Information

The TPS62730 is a high-frequency synchronous step down DC-DC converter optimized for ultra low-power wireless applications. The device is optimized to supply TI's Low-Power Wireless sub 1-GHz and 2.4-GHz RF transceivers and system-on-chip (SoC) solutions.

10.2 Typical Application




Figure 8. Typical Application

10.2.1 Design Requirements

The TPS6273x is a highly integrated DC-DC converter. The output voltage is internally fixed and does not require and external feedback divider network. For proper operation only a input- and output capacitor and an inductor is required. Table 1 shows the components used for the application characteristic curves.

REFERENCE DESCRIPTION VALUE MANUFACTURER DIMENSIONS Step-down converter with bypass TPS62730 **Texas Instruments** 1.5 x 1.0 x 0.55 mm mode Ceramic capacitor 0402 X5R 6.3V CIN, COUT 2.2 µF Murata 1.0 x 0.5 x 0.5 mm GRM155R60J225 Inductor MIPSZ2012 2R2 **FDK** L 2.2 µH 2.0 x 1.2 x 1.0 mm

Table 1. List of Components

10.2.2 Detailed Design Procedure

10.2.2.1 Output Filter Design (Inductor and Output Capacitor)

The TPS62730 is optimized to operate with effective inductance values in the range of 1.5 μ H to 3 μ H and with effective output capacitance in the range of 1.0 μ F to 10 μ F. The internal compensation is optimized to operate with an output filter of L = 2.2 μ H and C_{OUT} = 2.2 μ F, which gives and LC output filter corner frequency of:

$$f_C = \frac{1}{2 \times \pi \times \sqrt{(2.2\mu H \times 2.2\mu F)}} = 72kHz \tag{3}$$

Copyright © 2011–2014, Texas Instruments Incorporated

(4)



10.2.2.2 Inductor Selection

The inductor value affects its peak-to-peak ripple current, the PWM-to-PFM transition point, the output voltage ripple and the efficiency. The selected inductor must be rated for its DC resistance and saturation current. The inductor ripple current (ΔI_L) decreases with higher inductance and increases with higher $V_{I,N}$ or $V_{O,UT}$. Equation 4 calculates the maximum inductor current under static load conditions. The saturation current of the inductor should be rated higher than the maximum inductor current as calculated with Equation 5.

$$\Delta I_L = Vout \times \frac{1 - \frac{Vout}{Vin}}{L \times f}$$

where

- f = Switching Frequency
- L = Inductor Value

$$I_{Lmax} = I_{outmax} + \frac{\Delta I_{L}}{2}$$

where

- ΔI_L= Peak-to-Peak inductor ripple current
- I_{Lmax} = Maximum Inductor current (5)

In high-frequency converter applications, the efficiency is essentially affected by the inductor AC resistance (that is, quality factor) and to a smaller extent by the inductor DCR value. To achieve high efficiency operation, care should be taken in selecting inductors featuring a quality factor above 25 at the switching frequency. Increasing the inductor value produces lower RMS currents, but degrades transient response. For a given physical inductor size, increased inductance usually results in an inductor with lower saturation current.

The total losses of the coil consist of both the losses in the DC resistance, $R_{(DC)}$, and the following frequency-dependent components:

- The losses in the core material (magnetic hysteresis loss, especially at high switching frequencies)
- Additional losses in the conductor from the skin effect (current displacement at high frequencies)
- Magnetic field losses of the neighboring windings (proximity effect)
- Radiation losses

The following inductor series from different suppliers have been used with the TPS62730 converters.

Table 2. List of Inductors

INDUCTANCE [µH]	DIMENSIONS [mm3]	INDUCTOR TYPE	SUPPLIER
2.2	$2.0 \times 1.2 \times 1.0$	LQM21PN2R2NGC	Murata
2.2	2.0 × 1.2 × 1.0	MIPSZ2012	FDK

10.2.2.3 DC-DC Output Capacitor Selection

The DCS-Control scheme of the TPS62730 allows the use of tiny ceramic capacitors. Ceramic capacitors with low ESR values have the lowest output voltage ripple and are recommended. The output capacitor requires either an X7R or X5R dielectric. Y5V and Z5U dielectric capacitors, aside from their wide variation in capacitance over temperature, become resistive at high frequencies. At light load currents the converter operate in power save mode and the output voltage ripple is dependent on the output capacitor value and the PFM peak inductor current.

10.2.2.4 Additional Decoupling Capacitors

In addition to the output capacitor there are further decoupling capacitors connected to the output of the TPS62730. These decoupling capacitor are placed closely at the RF transmitter or micro controller. The total capacitance of these decoupling capacitors should be kept to a minimum and should not exceed the values given in the reference designs, see Figure 31 and Figure 32. During mode transition from DC-DC operation to bypass mode the capacitors on the output VOUT are charged up to the battery voltage VIN through the internal bypass

Submit Documentation Feedback

Copyright © 2011–2014, Texas Instruments Incorporated



switch. During mode transition from bypass mode to DC-DC operation, these capacitors must be discharged by the system supply current to the nominal output voltage threshold until the DC-DC converter will kick in. The charge change in the output and decoupling capacitors can be calculated according to Equation 6. The energy loss due to charge and discharge of the output and decoupling capacitors can be calculated according to Equation 7.

$$dQ_{cout_cdec} = C_{cout_cdec} \times \left(V_{IN} - V_{out_dc_dc}\right)$$

where

- dQ_{COUT_CDEC} : Charge change needed to charge up and discharge the output and decoupling capacitors from VOUT_DC_DC to V_{IN} and vice versa
- C_{COUT CDEC}: Total capacitance on the VOUT pin of the device, includes output and decoupling capacitors
- V_{IN}: Input (battery) voltage

$$E_{Ch \arg e_Loss} = \frac{1}{2} \times C_{COUT_CDEC} \times \left(V_{IN}^2 - V_{OUT_DC_DC}^2\right)$$

where

- C_{COUT CDEC}: Total capacitance on the VOUT pin of the device, includes output and decoupling capacitors
- V_{IN}: Input (battery) voltage
- V_{OUT_DC_DC}: nominal DC-DC output voltage V_{OUT} (7)

10.2.2.5 Input Capacitor Selection

Because of the nature of the buck converter having a pulsating input current, a low ESR input capacitor is required for best input voltage filtering to ensure proper function of the device and to minimize input voltage spikes. For most applications a 2.2 μ F to 4.7 μ F ceramic capacitor is recommended. The input capacitor can be increased without any limit for better input voltage filtering.

Table 3 shows a list of tested input/output capacitors.

10.2.2.5.1 Input Buffer Capacitor Selection

In addition to the small ceramic input capacitor a larger buffer capacitor C_{Buf} is recommended to reduce voltage drops and ripple voltage. When using battery chemistries like Li-SOCI2, Li-SO2, Li-MnO2, the impedance of the battery must be considered. These battery types tend to increase their impedance depending on discharge status and often can support output currents of only a few mA. Therefore a buffer capacitor is recommended to stabilize the battery voltage during DC-DC operations (for example, for an RF transmission). A voltage drop on the input of the TPS62730 during DC-DC operation impacts the advantage of the step-down conversion for system power reduction. Furthermore the voltage drops can fall below the minimum recommended operating voltage of the device and leads to an early system cut off. Both impacts effects reduce the battery life time. To achieve best performance and to extract most energy out of the battery, a good procedure is to design the select the buffer capacitor value for an voltage drop below 50 mVpp during DC-DC operation. The capacitor value strongly depends on the used battery type, as well the current consumption during an RF transmission as well the duration of the transmission.

Table 3. List of Capacitor

CAPACITANCE [µF]	SIZE	CAPACITOR TYPE	SUPPLIER
2.2	0402	GRM155R60J225	Murata

10.2.2.6 Checking Loop Stability

The first step of circuit and stability evaluation is to look from a steady-state perspective at the following signals:

- Switching node, SW
- Inductor current, I_L
- Output ripple voltage, V_{OUT(AC)}

Basic signals must be measured when evaluating a switching converter. When the switching waveform shows large duty cycle jitter or the output voltage or inductor current shows oscillations, the regulation loop may be unstable. This is often a result of board layout and/or L-C combination.

Copyright © 2011–2014, Texas Instruments Incorporated




As a next step in the evaluation of the regulation loop, the load transient response is tested. The time between the application of the load transient and the turn on of the High Side MOSFET, the output capacitor must supply all of the current required by the load. V_{OUT} immediately shifts by an amount equal to $\Delta I_{(LOAD)}$ x ESR, where ESR is the effective series resistance of C_{OUT} . $\Delta I_{(LOAD)}$ begins to charge or discharge C_O generating a feedback error signal used by the regulator to return V_{OUT} to its steady-state value. The results are most easily interpreted when the device operates in PWM mode.

During this recovery time, V_{OUT} can be monitored for settling time, overshoot or ringing that helps judge the converter's stability. Without any ringing, the loop has usually more than 45° of phase margin.

Because the damping factor of the circuitry is directly related to several resistive parameters (for example, MOSFET $r_{DS(on)}$) that are temperature dependant, the loop stability analysis must be done over the input voltage range, load current range, and temperature range.


10.2.3 Application Curves




Submit Documentation Feedback

Copyright © 2011–2014, Texas Instruments Incorporated


















10.3 System Examples



CC2540 power supply decoupling capacitors

Figure 31. System Example CC2540



CC430 power supply decoupling capacitors

Figure 32. System Example CC430



11 Power Supply Recommendations

The power supply to the TPS62730 must have a current rating according to the supply voltage, output voltage and output current of the TPS62730.

12 Layout

12.1 Layout Guidelines

As for all switching power supplies, the layout is an important step in the design. Especially RF designs demand careful attention to the PCB layout. Care must be taken in board layout to get the specified performance. If the layout is not carefully done, the regulator could show poor line and/or load regulation, stability issues as well as EMI problems and interference with RF circuits. It is critical to provide a low inductance, impedance ground path. Therefore, use wide and short traces for the main current paths. The input capacitor should be placed as close as possible to the IC pins as well as the inductor and output capacitor. Use a common Power GND node and a different node for the Signal GND to minimize the effects of ground noise. Keep the common path to the GND PIN, which returns the small signal components and the high current of the output capacitors as short as possible to avoid ground noise. The VOUT line should be connected to the output capacitor and routed away from noisy components and traces (for example, SW line).

12.2 Layout Example




Figure 33. Recommended PCB Layout for TPS62730

Copyright © 2011–2014, Texas Instruments Incorporated



13 Device and Documentation Support

13.1 Device Support

13.1.1 Third-Party Products Disclaimer

TI'S PUBLICATION OF INFORMATION REGARDING THIRD-PARTY PRODUCTS OR SERVICES DOES NOT CONSTITUTE AN ENDORSEMENT REGARDING THE SUITABILITY OF SUCH PRODUCTS OR SERVICES OR A WARRANTY, REPRESENTATION OR ENDORSEMENT OF SUCH PRODUCTS OR SERVICES, EITHER ALONE OR IN COMBINATION WITH ANY TI PRODUCT OR SERVICE.

13.2 Related Links

The table below lists quick access links. Categories include technical documents, support and community resources, tools and software, and quick access to sample or buy.

Table 4. Related Links

PARTS	PRODUCT FOLDER	SAMPLE & BUY	TECHNICAL DOCUMENTS	TOOLS & SOFTWARE	SUPPORT & COMMUNITY
TPS62730	Click here	Click here	Click here	Click here	Click here
TPS62732	Click here	Click here	Click here	Click here	Click here
TPS62733	Click here	Click here	Click here	Click here	Click here

13.3 Trademarks

Bluetooth is a trademark of Bluetooth SIG.

All other trademarks are the property of their respective owners.

13.4 Electrostatic Discharge Caution



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

13.5 Glossary

SLYZ022 — TI Glossary.

This glossary lists and explains terms, acronyms, and definitions.

14 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

Product Folder Links: TPS62730 TPS62732 TPS62733

www.ti.com

10-Nov-2025

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type	Package Pins	Package qty Carrier	RoHS (3)	Lead finish/ Ball material	MSL rating/ Peak reflow	Op temp (°C)	Part marking (6)
TPS62730DRYR	Active	Production	SON (DRY) 6	5000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	RP
TPS62730DRYR.B	Active	Production	SON (DRY) 6	5000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	RP
TPS62730DRYRG4.B	Active	Production	SON (DRY) 6	5000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	RP
TPS62730DRYT	Active	Production	SON (DRY) 6	250 SMALL T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	RP
TPS62730DRYT.B	Active	Production	SON (DRY) 6	250 SMALL T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	RP
TPS62732DRYR	Active	Production	SON (DRY) 6	5000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	RR
TPS62732DRYR.B	Active	Production	SON (DRY) 6	5000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	RR
TPS62732DRYT	Active	Production	SON (DRY) 6	250 SMALL T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	RR
TPS62732DRYT.B	Active	Production	SON (DRY) 6	250 SMALL T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	RR
TPS62733DRYR	Active	Production	SON (DRY) 6	5000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	YA
TPS62733DRYR.B	Active	Production	SON (DRY) 6	5000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	YA
TPS62733DRYRG4.B	Active	Production	SON (DRY) 6	5000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	YA
TPS62733DRYT	Active	Production	SON (DRY) 6	250 SMALL T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	YA
TPS62733DRYT.B	Active	Production	SON (DRY) 6	250 SMALL T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	YA

⁽¹⁾ Status: For more details on status, see our product life cycle.

⁽²⁾ Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

⁽⁴⁾ Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

⁽⁵⁾ MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

⁽⁶⁾ Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.



PACKAGE OPTION ADDENDUM

www.ti.com 10-Nov-2025

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

www.ti.com 19-Jan-2024

TAPE AND REEL INFORMATION





A0	Dimension designed to accommodate the component width
В0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing		SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TPS62730DRYR	SON	DRY	6	5000	180.0	9.5	1.2	1.65	0.7	4.0	8.0	Q1
TPS62730DRYT	SON	DRY	6	250	180.0	9.5	1.2	1.65	0.7	4.0	8.0	Q1
TPS62732DRYR	SON	DRY	6	5000	180.0	9.5	1.2	1.65	0.7	4.0	8.0	Q1
TPS62732DRYT	SON	DRY	6	250	180.0	9.5	1.2	1.65	0.7	4.0	8.0	Q1
TPS62733DRYR	SON	DRY	6	5000	180.0	9.5	1.2	1.65	0.7	4.0	8.0	Q1
TPS62733DRYT	SON	DRY	6	250	180.0	9.5	1.2	1.65	0.7	4.0	8.0	Q1



www.ti.com 19-Jan-2024



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TPS62730DRYR	SON	DRY	6	5000	189.0	185.0	36.0
TPS62730DRYT	SON	DRY	6	250	189.0	185.0	36.0
TPS62732DRYR	SON	DRY	6	5000	189.0	185.0	36.0
TPS62732DRYT	SON	DRY	6	250	189.0	185.0	36.0
TPS62733DRYR	SON	DRY	6	5000	189.0	185.0	36.0
TPS62733DRYT	SON	DRY	6	250	189.0	185.0	36.0



Images above are just a representation of the package family, actual package may vary. Refer to the product data sheet for package details.







PLASTIC SMALL OUTLINE - NO LEAD



NOTES:

- 1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.

 2. This drawing is subject to change without notice.



PLASTIC SMALL OUTLINE - NO LEAD



NOTES: (continued)

3. For more information, see QFN/SON PCB application report in literature No. SLUA271 (www.ti.com/lit/slua271).



PLASTIC SMALL OUTLINE - NO LEAD



NOTES: (continued)

Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale, TI's General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025