

LM2941-SP Neutron Displacement Damage (NDD) Characterization



ABSTRACT

This report presents the effect of neutron displacement damage (NDD) on the LM2941QML-SP device. The devices were radiated up to 1×10^{13} n/cm² (1-MeV equivalent). A sample size of nine units was exposed to radiation testing per MIL-STD-883(Method 1017 for Neutron Irradiation) and an additional unirradiated sample device was used for correlation. Electrical testing was performed at Texas Instruments before and after neutron irradiation using the production test program for LM2941QML-SP.

Table of Contents

1 Overview.....	1
2 Test Procedures.....	3
3 Facility.....	4
4 Results.....	5
A Appendix: NDD Test Results.....	6

List of Figures

Figure 2-1. LM2941QML-SP Device.....	3
--------------------------------------	---

List of Tables

Table 1-1. Overview Information.....	2
Table 2-1. Neutron Irradiation Conditions.....	3
Table 4-1. LM2941QML-SP Specification Compliance Matrix.....	5

Trademarks

All trademarks are the property of their respective owners.

1 Overview

The LM2941-SP is a radiation-hardened QMLV, 6-V to 26-V input, 1-A adjustable output linear regulator. The LM2941 positive voltage regulator features the ability to source 1A of output current with a typical dropout voltage of 0.5V and a maximum of 1V over the entire temperature range. Furthermore, a which reduces the ground pin current when the differential between the input voltage and the output voltage exceeds approximately 3V.

General device information and testing conditions are listed in [Table 1-1](#).

Table 1-1. Overview Information

TI Part Number	LM2941QML-SP
Orderable Number	LM2941GWRLQMLV
Device Function	Linear Regulator
Die Name	RLM1940FAQSRY
Package	16-pin CFP (NAC)
Technology	SLM
A/T Lot Number / Date Code	9161157/1918A
Unbiased Quantity Tested	9 + control
Exposure Facility	VPT Rad
Neutron Fluence (1-MeV equivalent)	1.0×10^{12} , 5.0×10^{12} , 1.0×10^{13} n/cm ²
Irradiation Temperature	25°C

TI may provide technical, applications or design advice, quality characterization, and reliability data or service providing these items shall not expand or otherwise affect TI's warranties as set forth in the Texas Instruments Incorporated Standard Terms and Conditions of Sale for Semiconductor Products and no obligation or liability shall arise from Semiconductor Products and no obligation or liability shall arise from TI's provision of such items.

2 Test Procedures

The LM2941QML-SP was electrically pre-tested using the production automated test equipment (ATE) program. General test procedures were IAW MIL-STD-883, Method 1017 for Neutron Irradiation of LM2941QML-SP.

Table 2-1. Neutron Irradiation Conditions

Group	Sample Qty	Neutron Fluence (n/cm ²)	Bias
A	3	1.0×10^{12}	Unbiased
B	3	5.0×10^{12}	Unbiased
C	3	1.0×10^{13}	Unbiased




Figure 2-1. LM2941QML-SP Device

The LM2941QML-SP is packaged in a 16-pin ceramic flat pack package (NAC) as shown in [Figure 2-1](#).

3 Facility

VPT Rad performs all neutron displacement damage irradiations in a low-enriched, open-pool, water moderated, thermal neutron reactor. It utilizes flat-plate type fuel and has a maximum thermal energy output of up to 1 MW. The Fast Neutron Irradiator (FNI) faces one side of the reactor core. The FNI design produces a geometrical planar *beam* of fast neutrons that is approximately uniform over an area of 12 in \times 20 in. Lead and thermal neutron absorbing compounds are combined to filter out both fission gammas and thermal neutrons. The ratio of fast-to-thermal neutrons is approximately 400:1, with a gamma exposure of up to 1401 rad(Si) for a 1E13 n/cm² (1-MeV(Si) equivalent) exposure. The FNI can accommodate a sample or samples with size up to 30 cm in diameter and 15-cm thick including packaging materials. The minimum neutron fluence rate is 1E6 n/cm²-s. The maximum neutron fluence rate is approximately 1.0E11 n/cm²-s (both values are 1-MeV(Si) equivalent).

The neutron fluence rate is determined using the previously-measured neutron radiation field for the FNI, performed in accordance with ASTM standards (ASTM F1190), and correlated to the measured reactor power level. The neutron dose is timed to meet the customer-specified fluence for the irradiation. Neutron dosimetry meeting ASTM standards (ASTM E265) is utilized to track and ensure irradiations meet the required minimum. The facility retains *source-suitability* with the Defense Logistics Agency (DLA) Laboratory Suitability Program for ASTM Test Method 1017. The DUTS are typically irradiation in an unbiased condition as per TM1017. If bias conditions are required, they can be maintained via dry thimbles connected to the irradiation volume.

4 Results

There were failures at all tested neutron fluence levels. At the 1×10^{12} n/cm² level, there was a marginal failure for one test for all three devices. At the 5×10^{12} n/cm² fluence levels, failures were present in all three devices. At the 1×10^{13} n/cm² fluence levels, failures were present in all three devices. The full parameter list and graphs are found in [Appendix A](#).

Table 4-1 lists the LM2941QML-SP specification compliance matrix.

Table 4-1. LM2941QML-SP Specification Compliance Matrix

PARAMETER	TEST CONDITION	LM2941QML-SP DATA SHEET (SNVS390B)			ATE TEST #
		MIN	MAX	UNIT	
Reference Voltage	$5\text{mA} \leq I_O \leq 1\text{A}$	1.237	1.313	V	1.0, 7.0, 101.0, 106.0
Line Regulation	$V_O + 2\text{V} \leq V_{IN} \leq 26\text{V}, I_O = 5\text{mA}$		10	mV	2.0
Quiescent Current	$V_O + 2\text{V} \leq V_{IN} \leq 26\text{V}, I_O = 5\text{mA}$		15	mA	3.0, 4.0, 102.0, 103.0
	$V_{IN} = V_O + 5\text{V}, I_O = 1\text{A}$		45		5.0, 104.0
Load Regulation	$5\text{mA} \leq I_O \leq 1\text{A}, V_{IN} = 10\text{V}, V_{OUT} = 5\text{V}$		10	mV/V	6.0
	$5\text{mA} \leq I_O \leq 1\text{A}, V_{IN} = 25\text{V}, V_{OUT} = 20\text{V}$		10		105.0
ON/OFF Threshold Current	$V_{ON/OFF} = 2.0\text{V}, I_O \leq 1\text{A}$		100	µA	10.0
Dropout Voltage	$I_O = 100\text{mA}$		200	mV	11.0
	$I_O = 1\text{A}$		0.8	V	12.0, 110.0
Short Circuit Current	$V_{IN MAX} = 26\text{V}$	1.6	3.5	A	35.0


A Appendix: NDD Test Results

This appendix contains the detailed NDD test results.


NDD Report

LM2941GWRLQMLV

1.0 — 1				
Test Site		Tester		
Test Number			<th></th>	
Unit	V	V		
Max Limit	1.311	1.311		
Min Limit	1.239	1.239		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	1.288	1.284	-0.004
1E+12	2.1	1.288	1.285	-0.004
1E+12	3.1	1.290	1.286	-0.004
5E+12	4.1	1.288	1.265	-0.022
5E+12	5.1	1.289	1.268	-0.022
5E+12	6.1	1.274	1.252	-0.022
1E+13	7.1	1.288	1.240	-0.048
1E+13	8.1	1.289	1.245	-0.044
1E+13	9.1	1.275	1.232	-0.042
0	10.1	1.290	1.290	0.000
Max		1.290	1.290	0.000
Average		1.286	1.265	-0.021
Min		1.274	1.232	-0.048
Std Dev		0.006	0.021	0.018




1.0 — 1				
Test Site		Tester		
Test Number			<th></th>	
Unit	1.311	V		
Max Limit	1.239	V		
Min Limit	1.239	V		
n/cm ²	0	1E+12	5E+12	1E+13
LL	1.239	1.239	1.239	1.239
Min	1.290	1.284	1.252	1.232
Average	1.290	1.285	1.262	1.239
Max	1.290	1.286	1.268	1.245
UL	1.311	1.311	1.311	1.311




NDD Report

LM2941GWRLQMLV

2.0 — 2				
Test Site		Tester		
Test Number			<th></th>	
Unit	mV	mV		
Max Limit	48	48		
Min Limit	-48	-48		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	-3.100	2.600	5.700
1E+12	2.1	-3.100	3.000	6.100
1E+12	3.1	-3.300	-2.600	0.700
5E+12	4.1	-3.200	-1.400	1.800
5E+12	5.1	-3.400	-1.600	1.800
5E+12	6.1	-3.000	-1.400	1.600
1E+13	7.1	-3.300	-0.500	2.800
1E+13	8.1	-3.000	-0.300	2.700
1E+13	9.1	-3.000	-0.600	2.400
0	10.1	-3.100	4.300	7.400
Max		-3.000	4.300	7.400
Average		-3.150	0.150	3.300
Min		-3.400	-2.600	0.700
Std Dev		0.143	2.309	2.260




2.0 — 2				
Test Site		Tester		
Test Number			<th></th>	
Max Limit	48	mV		
Min Limit	-48	mV		
n/cm ²	0	1E+12	5E+12	1E+13
LL	-48.000	-48.000	-48.000	-48.000
Min	4.300	-2.600	-1.600	-0.600
Average	4.300	1.000	-1.467	-0.467
Max	4.300	3.000	-1.400	-0.300
UL	48.000	48.000	48.000	48.000




NDD Report

LM2941GWRLQMLV

3.0 — 3				
Test Site	3.0	3		
Tester				
Test Number				
Unit	mA	mA		
Max Limit	14.3	14.3		
Min Limit	0	0		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	5.140	7.000	1.860
1E+12	2.1	4.820	6.950	2.130
1E+12	3.1	4.930	6.950	2.020
5E+12	4.1	5.060	4.800	-0.260
5E+12	5.1	4.980	4.760	-0.220
5E+12	6.1	4.980	4.760	-0.220
1E+13	7.1	4.980	3.320	-1.660
1E+13	8.1	4.900	3.430	-1.470
1E+13	9.1	4.900	3.380	-1.520
0	10.1	4.980	7.750	2.770
Max		5.140	7.750	2.770
Average		4.967	5.310	0.343
Min		4.820	3.320	-1.660
Std Dev		0.089	1.709	1.699




3.0 — 3				
Test Site	3.0	3		
Tester				
Test Number				
Max Limit	14.3	mA		
Min Limit	0	mA		
n/cm ²	0	1E+12	5E+12	1E+13
LL	0.000	0.000	0.000	0.000
Min	7.750	6.950	4.760	3.320
Average	7.750	6.967	4.773	3.377
Max	7.750	7.000	4.800	3.430
UL	14.300	14.300	14.300	14.300




NDD Report

LM2941GWRLQMLV

4.0 — 4				
Test Site			<th></th>	
Tester				
Test Number				
Unit	mA	mA	mA	mA
Max Limit	14.1	14.1	14.1	14.1
Min Limit	0	0	0	0
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	5.590	7.810	2.220
1E+12	2.1	5.160	7.160	2.000
1E+12	3.1	5.430	7.280	1.850
5E+12	4.1	5.430	5.830	0.400
5E+12	5.1	5.380	4.820	-0.560
5E+12	6.1	5.430	4.710	-0.720
1E+13	7.1	5.300	3.170	-2.130
1E+13	8.1	5.300	3.250	-2.050
1E+13	9.1	5.250	3.300	-1.950
0	10.1	5.360	8.550	3.190
Max		5.590	8.550	3.190
Average		5.363	5.588	0.225
Min		5.160	3.170	-2.130
Std Dev		0.119	2.028	1.988




4.0 — 4				
Test Site			<th></th>	
Tester				
Test Number				
Max Limit	14.1	mA	mA	mA
Min Limit	0	mA	mA	mA
n/cm ²	0	1E+12	5E+12	1E+13
LL	0.000	0.000	0.000	0.000
Min	8.550	7.160	4.710	3.170
Average	8.550	7.417	5.120	3.240
Max	8.550	7.810	5.830	3.300
UL	14.100	14.100	14.100	14.100




NDD Report

LM2941GWRLQMLV

		5.0	5	
Test Site				
Tester				
Test Number				
Unit	mA	mA		
Max Limit	42.3	42.3		
Min Limit	0	0		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	21.480	24.670	3.190
1E+12	2.1	20.770	24.360	3.590
1E+12	3.1	21.230	24.770	3.540
5E+12	4.1	21.480	39.700	18.220
5E+12	5.1	21.660	40.590	18.930
5E+12	6.1	21.160	39.820	18.660
1E+13	7.1	21.290	36.860	15.570
1E+13	8.1	20.890	40.710	19.820
1E+13	9.1	20.970	40.540	19.570
0	10.1	21.610	23.690	2.080
		Max	21.660	40.710
		Average	21.254	33.571
		Min	20.770	23.690
		Std Dev	0.308	7.996
				8.025




		5.0	5	
Test Site				
Tester				
Test Number				
Max Limit	42.3	mA		
Min Limit	0	mA		
n/cm ²	0	1E+12	5E+12	1E+13
LL	0.000	0.000	0.000	0.000
Min	23.690	24.360	39.700	36.860
Average	23.690	24.600	40.037	39.370
Max	23.690	24.770	40.590	40.710
UL	42.300	42.300	42.300	42.300




NDD Report

LM2941GWRLQMLV

		6.0	6	
Test Site				
Tester				
Test Number				
Unit	mV	mV		
Max Limit	46.4	46.4		
Min Limit	-46.4	-46.4		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	-0.900	-1.900	-1.000
1E+12	2.1	-1.100	-1.000	0.100
1E+12	3.1	-0.700	-0.600	0.100
5E+12	4.1	-1.300	-6.500	-5.200
5E+12	5.1	-0.900	-3.400	-2.500
5E+12	6.1	-4.000	-6.700	-2.700
0	10.1	-0.900	-1.000	-0.100
Max		-0.700	-0.600	0.100
Average		-1.400	-3.014	-1.614
Min		-4.000	-6.700	-5.200
Std Dev		1.162	2.616	1.974




		6.0	6
Test Site			
Tester			
Test Number			
Max Limit	46.4	mV	
Min Limit	-46.4	mV	
n/cm ²	0	1E+12	5E+12
LL	-46.400	-46.400	-46.400
Min	-1.000	-1.900	-6.700
Average	-1.000	-1.167	-5.533
Max	-1.000	-0.600	-3.400
UL	46.400	46.400	46.400




NDD Report

LM2941GWRLQMLV

7.0 — 7				
Test Site		Tester		
Test Number			<th></th>	
Unit	V	V		
Max Limit	1.311	1.311		
Min Limit	1.239	1.239		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	1.286	1.282	-0.004
1E+12	2.1	1.287	1.283	-0.004
1E+12	3.1	1.288	1.284	-0.004
5E+12	4.1	1.286	1.262	-0.024
5E+12	5.1	1.288	1.265	-0.023
5E+12	6.1	1.271	1.247	-0.023
0	10.1	1.289	1.289	0.000
	Max	1.289	1.289	0.000
	Average	1.285	1.273	-0.012
	Min	1.271	1.247	-0.024
	Std Dev	0.006	0.015	0.011




7.0 — 7				
Test Site		Tester		
Test Number			<th></th>	
Max Limit	1.311	V		
Min Limit	1.239	V		
n/cm ²	0	1E+12	5E+12	
LL	1.239	1.282	1.239	
Min	1.289	1.283	1.247	
Average	1.289	1.284	1.258	
Max	1.289	1.284	1.265	
UL	1.311	1.311	1.311	




NDD Report

LM2941GWRLQMLV

8.0 — 8				
Test Site		Tester		
Test Number			<th></th>	
Unit	V	V		
Max Limit	0.0956	0.0956		
Min Limit	-0.05	-0.05		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	-0.001	-0.001	0.000
1E+12	2.1	-0.001	-0.001	0.000
1E+12	3.1	-0.001	-0.001	0.000
5E+12	4.1	-0.001	-0.001	0.000
5E+12	5.1	-0.001	-0.001	0.000
5E+12	6.1	-0.001	-0.001	0.000
1E+13	7.1	-0.001	0.000	0.001
1E+13	8.1	-0.001	0.000	0.001
1E+13	9.1	-0.001	0.000	0.001
0	10.1	-0.001	-0.001	0.000
Max		-0.001	0.000	0.001
Average		-0.001	-0.001	0.000
Min		-0.001	-0.001	0.000
Std Dev		0.000	0.000	0.000




8.0 — 8				
Test Site		Tester		
Test Number			<th></th>	
Unit	0.0956	V		
Max Limit	-0.05	V		
Min Limit				
n/cm ²	0	1E+12	5E+12	1E+13
LL	-0.050	-0.050	-0.050	-0.050
Min	-0.001	-0.001	-0.001	0.000
Average	-0.001	-0.001	-0.001	0.000
Max	-0.001	-0.001	-0.001	0.000
UL	0.096	0.096	0.096	0.096




NDD Report

LM2941GWRLQMLV

		9.0	9			
Test Site						
Tester						
Test Number						
Unit	V	V				
Max Limit	5.133	5.133				
Min Limit	4.867	4.867				
n/cm^2	Serial #	pre	post	Delta	Delta %	% of Limit Range
1E+12	1.1	5.100	5.085	-0.015	-0.28%	5.45%
1E+12	2.1	5.102	5.088	-0.014	-0.27%	5.26%
1E+12	3.1	5.109	5.094	-0.016	-0.31%	5.90%
5E+12	4.1	5.099	5.008	-0.092	-1.80%	34.44%
5E+12	5.1	5.107	5.020	-0.087	-1.71%	32.78%
5E+12	6.1	5.039	4.952	-0.087	-1.73%	32.78%
0	10.1	5.111	5.111	0.000	0.01%	0.11%
Max		5.111	5.111	0.000	0.01%	34.44%
Average		5.095	5.051	-0.044	-0.87%	16.68%
Min		5.039	4.952	-0.092	-1.80%	0.11%
Std Dev		0.025	0.059	0.042	0.82%	15.71%




		9.0	9
Test Site			
Tester			
Test Number			
Max Limit	5.133	V	
Min Limit	4.867	V	
n/cm^2	0	1E+12	5E+12
LL	4.867	4.867	4.867
Min	5.111	5.085	4.952
Average	5.111	5.089	4.993
Max	5.111	5.094	5.020
UL	5.133	5.133	5.133




NDD Report

LM2941GWRLQMLV

10.0 — 10				
Test Site		Tester		
Test Number			<th></th>	
Unit	μA	μA		
Max Limit	89.4	89.4		
Min Limit	0	0		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	43.400	41.700	-1.700
1E+12	2.1	41.900	39.900	-2.000
1E+12	3.1	44.100	41.900	-2.200
5E+12	4.1	43.400	35.900	-7.500
5E+12	5.1	45.400	37.700	-7.700
5E+12	6.1	42.900	35.400	-7.500
1E+13	7.1	41.900	30.700	-11.200
1E+13	8.1	40.100	28.900	-11.200
1E+13	9.1	40.400	29.400	-11.000
0	10.1	44.900	45.500	0.600
Max		45.400	45.500	0.600
Average		42.840	36.700	-6.140
Min		40.100	28.900	-11.200
Std Dev		1.772	5.708	4.457




10.0 — 10				
Test Site		Tester		
Test Number			<th></th>	
Unit	89.4	μA		
Max Limit	89.4	μA		
Min Limit	0	μA		
n/cm ²	0	1E+12	5E+12	1E+13
LL	0.000	0.000	0.000	0.000
Min	45.500	39.900	35.400	28.900
Average	45.500	41.167	36.333	29.667
Max	45.500	41.900	37.700	30.700
UL	89.400	89.400	89.400	89.400




NDD Report

LM2941GWRLQMLV

11.0 — 11				
Test Site		Tester		
Test Number			<th></th>	
Unit	V	V		
Max Limit	0.19	0.19		
Min Limit	0	0		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	0.112	0.118	0.006
1E+12	2.1	0.113	0.120	0.008
1E+12	3.1	0.113	0.120	0.008
5E+12	4.1	0.112	0.140	0.027
5E+12	5.1	0.113	0.140	0.026
5E+12	6.1	0.113	0.141	0.028
1E+13	7.1	0.113	0.171	0.058
1E+13	8.1	0.114	0.171	0.057
1E+13	9.1	0.114	0.171	0.057
0	10.1	0.113	0.115	0.002
Max		0.114	0.171	0.058
Average		0.113	0.141	0.028
Min		0.112	0.115	0.002
Std Dev		0.001	0.023	0.022




11.0 — 11				
Test Site		Tester		
Test Number			<th></th>	
Unit	0.19	V		
Max Limit	0.19	V		
Min Limit	0	V		
n/cm ²	0	1E+12	5E+12	1E+13
LL	0.000	0.000	0.000	0.000
Min	0.115	0.118	0.140	0.171
Average	0.115	0.120	0.140	0.171
Max	0.115	0.121	0.141	0.171
UL	0.190	0.190	0.190	0.190




NDD Report

LM2941GWRLQMLV

12.0 — 12				
Test Site			<th></th>	
Tester				
Test Number				
Unit	V	V		
Max Limit	0.7	0.7		
Min Limit	0	0		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	0.539	0.547	0.008
1E+12	2.1	0.525	0.566	0.041
1E+12	3.1	0.526	0.568	0.042
5E+12	4.1	0.518	2.054	1.535
5E+12	5.1	0.531	2.054	1.522
5E+12	6.1	0.527	2.054	1.526
1E+13	7.1	0.527	2.054	1.526
1E+13	8.1	0.530	2.054	1.524
1E+13	9.1	0.527	2.054	1.526
0	10.1	0.527	0.543	0.016
Max		0.539	2.054	1.535
Average		0.528	1.455	0.927
Min		0.518	0.543	0.008
Std Dev		0.005	0.773	0.775




12.0 — 12				
Test Site			<th></th>	
Tester				
Test Number				
Max Limit	0.7	V		
Min Limit	0	V		
n/cm ²	0	1E+12	5E+12	1E+13
LL	0.000	0.000	0.000	0.000
Min	0.543	0.547	2.054	2.054
Average	0.543	0.560	2.054	2.054
Max	0.543	0.568	2.054	2.054
UL	0.700	0.700	0.700	0.700




NDD Report

LM2941GWRLQMLV

101.0 — 101				
Test Site	101			
Tester				
Test Number				
Unit	V	V		
Max Limit	1.3112	1.3112		
Min Limit	1.2388	1.2388		
n/cm²	Serial #	pre	post	Delta
1E+12	1.1	1.274	1.270	-0.004
1E+12	2.1	1.275	1.270	-0.004
1E+12	3.1	1.276	1.272	-0.005
5E+12	4.1	1.274	1.248	-0.026
5E+12	5.1	1.276	1.250	-0.026
5E+12	6.1	1.260	1.233	-0.027
1E+13	7.1	1.275	1.220	-0.054
1E+13	8.1	1.275	1.225	-0.050
1E+13	9.1	1.260	1.211	-0.050
0	10.1	1.277	1.277	0.000
		Max	1.277	1.277
Average		1.272	1.248	-0.025
Min		1.260	1.211	-0.054
Std Dev		0.006	0.024	0.021




101.0 — 101				
Test Site	101			
Tester				
Test Number				
Max Limit	1.3112	V		
Min Limit	1.2388	V		
n/cm²	0	1E+12	5E+12	1E+13
LL	1.239	1.239	1.239	1.239
Min	1.277	1.270	1.233	1.211
Average	1.277	1.271	1.244	1.219
Max	1.277	1.272	1.250	1.225
UL	1.311	1.311	1.311	1.311




NDD Report

LM2941GWRLQMLV

		102.0	102	
Test Site				
Tester				
Test Number				
Unit	mA	mA		
Max Limit	14	14		
Min Limit	0	0		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	5.870	7.420	1.550
1E+12	2.1	5.400	7.340	1.940
1E+12	3.1	5.660	7.410	1.750
5E+12	4.1	5.660	5.030	-0.630
5E+12	5.1	5.540	5.000	-0.540
5E+12	6.1	5.540	4.950	-0.590
1E+13	7.1	5.680	3.430	-2.250
1E+13	8.1	5.630	3.560	-2.070
1E+13	9.1	5.360	3.560	-1.800
0	10.1	5.570	8.440	2.870
		Max	5.870	8.440
		Average	5.591	5.614
		Min	5.360	3.430
		Std Dev	0.146	1.880
				1.858




		102.0	102	
Test Site				
Tester				
Test Number				
Max Limit	14	mA		
Min Limit	0	mA		
n/cm ²	0	1E+12	5E+12	1E+13
LL	0.000	0.000	0.000	0.000
Min	8.440	7.340	4.950	3.430
Average	8.440	7.390	4.993	3.517
Max	8.440	7.420	5.030	3.560
UL	14.000	14.000	14.000	14.000




NDD Report

LM2941GWRLQMLV

103.0 — 103				
Test Site		Tester		
Test Number			<th></th>	
Unit	mA	mA		
Max Limit	14	14		
Min Limit	0	0		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	5.630	7.420	1.790
1E+12	2.1	5.350	7.390	2.040
1E+12	3.1	5.520	7.330	1.810
5E+12	4.1	5.540	4.960	-0.580
5E+12	5.1	5.540	4.950	-0.590
5E+12	6.1	5.520	4.920	-0.600
1E+13	7.1	5.490	3.320	-2.170
1E+13	8.1	5.490	3.510	-1.980
1E+13	9.1	5.470	3.510	-1.960
0	10.1	5.490	8.240	2.750
Max		5.630	8.240	2.750
Average		5.504	5.555	0.051
Min		5.350	3.320	-2.170
Std Dev		0.070	1.876	1.877




103.0 — 103				
Test Site		Tester		
Test Number			<th></th>	
Unit	14	mA		
Max Limit	14	mA		
Min Limit	0	mA		
n/cm ²	0	1E+12	5E+12	1E+13
LL	0.000	0.000	0.000	0.000
Min	8.240	7.330	4.920	3.320
Average	8.240	7.380	4.943	3.447
Max	8.240	7.420	4.960	3.510
UL	14.000	14.000	14.000	14.000




NDD Report

LM2941GWRLQMLV

104.0 — 104				
Test Site	104	Tester		
Test Number				
Unit	mA	mA		
Max Limit	37.2	37.2		
Min Limit	0	0		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	22.460	25.750	3.290
1E+12	2.1	21.830	25.600	3.770
1E+12	3.1	22.250	26.060	3.810
5E+12	4.1	22.500	41.670	19.170
5E+12	5.1	22.730	42.460	19.730
5E+12	6.1	22.140	41.160	19.020
1E+13	7.1	22.300	74.020	51.720
1E+13	8.1	22.010	78.030	56.020
1E+13	9.1	21.910	61.630	39.720
0	10.1	22.660	24.570	1.910
		Max	22.730	78.030
		Average	22.279	44.095
		Min	21.830	24.570
		Std Dev	0.309	20.431
				20.530




104.0 — 104				
Test Site	104	Tester		
Test Number				
Unit	mA	mA		
Max Limit	37.2	mA		
Min Limit	0	mA		
n/cm ²	0	1E+12	5E+12	1E+13
LL	0.000	0.000	0.000	0.000
Min	24.570	25.600	41.160	61.630
Average	24.570	25.803	41.763	71.227
Max	24.570	26.060	42.460	78.030
UL	37.200	37.200	37.200	37.200




NDD Report

LM2941GWRLQMLV

105.0 — 105				
Test Site	105.0	Tester	105	
Test Number			<th></th>	
Unit	mV	mA		
Max Limit	138	138		
Min Limit	-138	-138		
n/cm²	Serial #	pre	post	Delta
1E+12	1.1	-12.000	-16.000	-4.000
1E+12	2.1	-16.000	-13.000	3.000
1E+12	3.1	-11.000	-9.000	2.000
5E+12	4.1	-14.000	-81.000	-67.000
5E+12	5.1	-12.000	-75.000	-63.000
5E+12	6.1	-26.000	-83.000	-57.000
1E+13	7.1	-13.000	19.000	32.000
1E+13	8.1	-14.000	28.000	42.000
1E+13	9.1	-18.000	23.000	41.000
0	10.1	-11.000	-12.000	-1.000
Max		-11.000	28.000	42.000
Average		-14.700	-21.900	-7.200
Min		-26.000	-83.000	-67.000
Std Dev		4.547	42.951	41.750



105.0 — 105				
Test Site	105.0	Tester	105	
Test Number			<th></th>	
Unit	mA	138	mA	138
Max Limit	mA	-138	mA	-138
n/cm²	0	1E+12	5E+12	1E+13
LL	-138.000	-138.000	-138.000	-138.000
Min	-12.000	-16.000	-83.000	19.000
Average	-12.000	-12.667	-79.667	23.333
Max	-12.000	-9.000	-75.000	28.000
UL	138.000	138.000	138.000	138.000




NDD Report

LM2941GWRLQMLV


106.0 — 106				
Test Site		Tester		
Test Number			<th></th>	
Unit	V	V		
Max Limit	1.3112	1.3112		
Min Limit	1.2388	1.2388		

n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	1.272	1.268	-0.004
1E+12	2.1	1.273	1.269	-0.004
1E+12	3.1	1.275	1.270	-0.005
5E+12	4.1	1.272	1.246	-0.026
5E+12	5.1	1.274	1.249	-0.026
5E+12	6.1	1.257	1.231	-0.026
1E+13	7.1	1.273	1.273	0.000
1E+13	8.1	1.274	1.223	-0.050
1E+13	9.1	1.258	1.209	-0.050
0	10.1	1.275	1.276	0.000
Max		1.275	1.276	0.000
Average		1.270	1.251	-0.019
Min		1.257	1.209	-0.050
Std Dev		0.007	0.024	0.020



106.0 — 106				
Test Site		Tester		
Test Number			<th></th>	
Unit	1.3112	V		
Max Limit	1.3112	V		
Min Limit	1.2388	V		

n/cm ²	0	1E+12	5E+12	1E+13
LL	1.239	1.239	1.239	1.239
Min	1.276	1.268	1.231	1.209
Average	1.276	1.269	1.242	1.235
Max	1.276	1.270	1.249	1.273
UL	1.311	1.311	1.311	1.311




NDD Report

LM2941GWRLQMLV


107.0 — 107				
Test Site		Tester		
Test Number			<th></th>	
Unit	V	V		
Max Limit	0.097	0.097		
Min Limit	-0.05	-0.05		

n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	0.001	0.001	0.000
1E+12	2.1	0.001	0.001	-0.001
1E+12	3.1	0.001	0.001	0.000
5E+12	4.1	0.001	0.001	0.000
5E+12	5.1	0.001	0.001	0.000
5E+12	6.1	0.001	0.001	0.000
1E+13	7.1	0.001	0.001	0.000
1E+13	8.1	0.001	0.001	0.000
1E+13	9.1	0.001	0.001	0.000
0	10.1	0.001	0.001	0.000
		Max	0.001	0.000
		Average	0.001	0.000
		Min	0.001	0.001
		Std Dev	0.000	0.000



107.0 — 107				
Test Site		Tester		
Test Number			<th></th>	
Unit	0.097	V		
Max Limit	-0.05	V		

n/cm ²	0	1E+12	5E+12	1E+13
LL	-0.050	-0.050	-0.050	-0.050
Min	0.001	0.001	0.001	0.001
Average	0.001	0.001	0.001	0.001
Max	0.001	0.001	0.001	0.001
UL	0.097	0.097	0.097	0.097




NDD Report

LM2941GWRLQMLV


108.0 — 108				
Test Site		108	<th>108</th>	108
Tester				
Test Number				
Unit	V	V		
Max Limit	20.564	20.564		
Min Limit	19.436	19.436		

n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	19.961	19.894	-0.067
1E+12	2.1	19.970	19.903	-0.067
1E+12	3.1	20.003	19.929	-0.074
5E+12	4.1	19.959	19.533	-0.426
5E+12	5.1	19.993	19.578	-0.415
5E+12	6.1	19.713	19.295	-0.418
1E+13	7.1	19.969	19.137	-0.832
1E+13	8.1	19.982	19.218	-0.764
1E+13	9.1	19.731	18.979	-0.752
0	10.1	20.010	20.011	0.001
Max		20.010	20.011	0.001
Average		19.929	19.548	-0.381
Min		19.713	18.979	-0.832
Std Dev		0.111	0.376	0.321



108.0 — 108				
Test Site		108	<th>108</th>	108
Tester				
Test Number				
Max Limit	20.564	V		
Min Limit	19.436	V		


n/cm ²	0	1E+12	5E+12	1E+13
LL	19.436	19.436	19.436	19.436
Min	20.011	19.894	19.295	18.979
Average	20.011	19.909	19.469	19.111
Max	20.011	19.929	19.578	19.218
UL	20.564	20.564	20.564	20.564




NDD Report

LM2941GWRLQMLV

109.0 — 109				
Test Site	109.0	109		
Tester				
Test Number				
Unit	μA	μA		
Max Limit	89.6	89.6		
Min Limit	0	0		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	41.100	39.200	-1.900
1E+12	2.1	39.600	37.400	-2.200
1E+12	3.1	41.400	39.400	-2.000
5E+12	4.1	40.600	32.400	-8.200
5E+12	5.1	42.400	34.200	-8.200
5E+12	6.1	40.400	32.400	-8.000
1E+13	7.1	39.400	27.700	-11.700
1E+13	8.1	37.900	26.200	-11.700
1E+13	9.1	37.600	26.200	-11.400
0	10.1	42.100	42.400	0.300
Max		42.400	42.400	0.300
Average		40.250	33.750	-6.500
Min		37.600	26.200	-11.700
Std Dev		1.630	5.814	4.622




109.0 — 109				
Test Site	109.0	109		
Tester				
Test Number				
Unit	89.6	μA		
Max Limit	0	μA		
Min Limit	0	μA		
n/cm ²	0	1E+12	5E+12	1E+13
LL	0.000	0.000	0.000	0.000
Min	42.400	37.400	32.400	26.200
Average	42.400	38.667	33.000	26.700
Max	42.400	39.400	34.200	27.700
UL	89.600	89.600	89.600	89.600




NDD Report

LM2941GWRLQMLV

110.0 — 110				
Test Site		Tester		
Test Number			<th></th>	
Unit	V	V		
Max Limit	0.7	0.7		
Min Limit	0	0		
n/cm²	Serial #	pre	post	Delta
1E+12	1.1	0.665	0.711	0.046
1E+12	2.1	0.672	0.715	0.043
1E+12	3.1	0.666	0.716	0.050
5E+12	4.1	0.662	2.054	1.392
5E+12	5.1	0.673	2.054	1.381
5E+12	6.1	0.665	2.054	1.389
1E+13	7.1	0.672	2.054	1.382
1E+13	8.1	0.668	2.054	1.385
1E+13	9.1	0.660	2.054	1.393
0	10.1	0.670	0.688	0.018
Max		0.673	2.054	1.393
Average		0.667	1.515	0.848
Min		0.660	0.688	0.018
Std Dev		0.004	0.695	0.696




110.0 — 110				
Test Site		Tester		
Test Number			<th></th>	
Max Limit	0.7	V		
Min Limit	0	V		
n/cm²	0	1E+12	5E+12	1E+13
LL	0.000	0.000	0.000	0.000
Min	0.688	0.712	2.054	2.054
Average	0.688	0.714	2.054	2.054
Max	0.688	0.716	2.054	2.054
UL	0.700	0.700	0.700	0.700




NDD Report

LM2941GWRLQMLV

31.0 — 31				
Test Site			<th></th>	
Tester				
Test Number				
Unit		μV	μV	
Max Limit	448	448		
Min Limit	10	10		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	14.700	16.500	1.800
1E+12	2.1	14.600	14.900	0.300
1E+12	3.1	13.500	15.900	2.400
5E+12	4.1	13.400	16.500	3.100
5E+12	5.1	13.200	16.700	3.500
5E+12	6.1	13.000	18.100	5.100
1E+13	7.1	13.900	18.500	4.600
1E+13	8.1	13.800	18.900	5.100
1E+13	9.1	13.000	18.100	5.100
0	10.1	13.800	14.200	0.400
Max		14.700	18.900	5.100
Average		13.690	16.830	3.140
Min		13.000	14.200	0.300
Std Dev		0.599	1.565	1.877




31.0 — 31				
Test Site			<th></th>	
Tester				
Test Number				
Max Limit	448	μV		
Min Limit	10	μV		
n/cm ²	0	1E+12	5E+12	1E+13
LL	10.000	10.000	10.000	10.000
Min	14.200	14.900	16.500	18.100
Average	14.200	15.767	17.100	18.500
Max	14.200	16.500	18.100	18.900
UL	448.000	448.000	448.000	448.000




NDD Report

LM2941GWRLQMLV

32.0 — 32				
Test Site		Tester	<th></th>	
Test Number			<th></th>	
Unit	mΩ	mΩ	<th></th>	
Max Limit	296.4	296.4		
Min Limit	1.2	1.2		
n/cm²	Serial #	pre	post	Delta
1E+12	1.1	2.500	2.900	0.400
1E+12	2.1	2.500	3.300	0.800
1E+12	3.1	2.000	2.600	0.600
5E+12	4.1	1.900	5.500	3.600
5E+12	5.1	2.000	4.000	2.000
5E+12	6.1	1.900	6.700	4.800
1E+13	7.1	2.000	5.900	3.900
1E+13	8.1	1.900	6.000	4.100
1E+13	9.1	2.000	6.100	4.100
0	10.1	2.000	2.600	0.600
Max		2.500	6.700	4.800
Average		2.070	4.560	2.490
Min		1.900	2.600	0.400
Std Dev		0.231	1.634	1.775




32.0 — 32				
Test Site		Tester		
Test Number			<th></th>	
Unit	296.4	mΩ		
Max Limit	1.2	mΩ		
n/cm²	0	1E+12	5E+12	1E+13
LL	1.200	1.200	1.200	1.200
Min	2.600	2.600	4.000	5.900
Average	2.600	2.933	5.400	6.000
Max	2.600	3.300	6.700	6.100
UL	296.400	296.400	296.400	296.400




NDD Report

LM2941GWRLQMLV

33.0 — 33				
Test Site		Tester		
Test Number			<th></th>	
Unit	dB	dB		
Max Limit	114.6	114.6		
Min Limit	65.4	65.4		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	98.100	100.200	2.100
1E+12	2.1	98.300	104.000	5.700
1E+12	3.1	99.700	101.800	2.100
5E+12	4.1	100.500	89.700	-10.800
5E+12	5.1	98.800	79.000	-19.800
5E+12	6.1	99.700	82.800	-16.900
1E+13	7.1	100.200	68.400	-31.800
1E+13	8.1	100.000	68.300	-31.700
1E+13	9.1	100.200	67.900	-32.300
0	10.1	100.200	99.000	-1.200
Max		100.500	104.000	5.700
Average		99.570	86.110	-13.460
Min		98.100	67.900	-32.300
Std Dev		0.859	14.786	15.220




33.0 — 33				
Test Site		Tester		
Test Number			<th></th>	
Unit	114.6	dB		
Max Limit	114.6	dB		
Min Limit	65.4	dB		
n/cm ²	0	1E+12	5E+12	1E+13
LL	65.400	65.400	65.400	65.400
Min	99.000	100.200	79.000	67.900
Average	99.000	102.000	83.833	68.200
Max	99.000	104.000	89.700	68.400
UL	114.600	114.600	114.600	114.600




NDD Report

LM2941GWRLQMLV

34.0 — 34				
Test Site		Tester		
Test Number			<th></th>	
Unit	dB	dB		
Max Limit	114.6	114.6		
Min Limit	53.4	53.4		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	85.600	87.900	2.300
1E+12	2.1	85.100	90.100	5.000
1E+12	3.1	86.000	89.900	3.900
5E+12	4.1	86.000	82.200	-3.800
5E+12	5.1	86.000	82.500	-3.500
5E+12	6.1	85.800	81.000	-4.800
1E+13	7.1	86.200	77.200	-9.000
1E+13	8.1	86.400	77.400	-9.000
1E+13	9.1	85.900	76.700	-9.200
0	10.1	86.200	91.800	5.600
		Max	86.400	91.800
		Average	85.920	83.670
		Min	85.100	76.700
		Std Dev	0.365	5.817




34.0 — 34				
Test Site		Tester		
Test Number			<th></th>	
Unit	114.6	dB		
Max Limit	114.6	dB		
Min Limit	53.4	dB		
n/cm ²	0	1E+12	5E+12	1E+13
LL	53.400	53.400	53.400	53.400
Min	91.800	87.900	81.000	76.700
Average	91.800	89.300	81.900	77.100
Max	91.800	90.100	82.500	77.400
UL	114.600	114.600	114.600	114.600




NDD Report

LM2941GWRLQMLV

35.0 — 35				
Test Site		Tester		
Test Number			<th></th>	
Unit	A	A		
Max Limit	3.4	3.4		
Min Limit	1.86	1.86		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	2.653	2.519	-0.134
1E+12	2.1	2.624	2.547	-0.076
1E+12	3.1	2.670	2.523	-0.147
5E+12	4.1	2.674	2.018	-0.656
5E+12	5.1	2.649	2.005	-0.644
5E+12	6.1	2.670	2.006	-0.664
1E+13	7.1	2.681	1.517	-1.164
1E+13	8.1	2.680	1.527	-1.153
1E+13	9.1	2.658	1.514	-1.144
0	10.1	2.641	2.636	-0.005
Max		2.681	2.636	-0.005
Average		2.660	2.081	-0.578
Min		2.624	1.514	-1.164
Std Dev		0.018	0.457	0.469




35.0 — 35				
Test Site		Tester		
Test Number			<th></th>	
Unit	3.4	A		
Max Limit	3.4	A		
Min Limit	1.86	A		
n/cm ²	0	1E+12	5E+12	1E+13
LL	1.860	1.860	1.860	1.860
Min	2.636	2.519	2.005	1.514
Average	2.636	2.530	2.010	1.519
Max	2.636	2.547	2.018	1.527
UL	3.400	3.400	3.400	3.400




NDD Report

LM2941GWRLQMLV

36.0 — 36				
Test Site		Tester	<th></th>	
Test Number			<th></th>	
Unit	V	V		
Max Limit	5.133	5.133		
Min Limit	4.867	4.867		
n/cm ²	Serial #	pre	post	Delta
1E+12	1.1	5.090	5.071	-0.018
1E+12	2.1	5.101	5.080	-0.020
1E+12	3.1	5.103	5.084	-0.019
5E+12	4.1	5.092	4.986	-0.106
5E+12	5.1	5.101	5.002	-0.099
5E+12	6.1	5.030	4.926	-0.104
1E+13	7.1	5.096	4.896	-0.200
1E+13	8.1	5.101	4.911	-0.190
1E+13	9.1	5.032	4.851	-0.181
0	10.1	5.105	5.105	0.000
Max		5.105	5.105	0.000
Average		5.085	4.991	-0.094
Min		5.030	4.851	-0.200
Std Dev		0.029	0.091	0.077



36.0 — 36				
Test Site		Tester		
Test Number			<th></th>	
Unit	5.133	V		
Max Limit	5.133	V		
Min Limit	4.867	V		
n/cm ²	0	1E+12	5E+12	1E+13
LL	4.867	4.867	4.867	4.867
Min	5.105	5.071	4.926	4.851
Average	5.105	5.079	4.971	4.886
Max	5.105	5.084	5.002	4.912
UL	5.133	5.133	5.133	5.133



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](#) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2022, Texas Instruments Incorporated